

DCE 1.2.2 Problem Determination Guide

OSF[®] DCE Product Documentation

The Open Group

Copyright © The Open Group 1997

All Rights Reserved

The information contained within this document is subject to change without notice.

This documentation and the software to which it relates are derived in part from copyrighted materials supplied by Digital Equipment Corporation, Hewlett-Packard Company, Hitachi, Ltd., International Business Machines, Massachusetts Institute of Technology, Siemens Nixdorf Informationssysteme AG, Transarc Corporation, and The Regents of the University of California.

THE OPEN GROUP MAKES NO WARRANTY OF ANY KIND WITH REGARD TO THIS MATERIAL, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The Open Group shall not be liable for errors contained herein, or for any direct or indirect, incidental, special or consequential damages in connection with the furnishing, performance, or use of this material.

OSF® DCE Product Documentation:

DCE 1.2.2 Problem Determination Guide, (Volume 1)
ISBN 1-85912-143-8
Document Number F213A

DCE 1.2.2 Problem Determination Guide, (Volume 2)
ISBN 1-85912-148-9
Document Number F213B

Published in the U.K. by The Open Group, 1997.

Any comments relating to the material contained in this document may be submitted to:

The Open Group
Apex Plaza
Forbury Road
Reading
Berkshire, RG1 1AX
United Kingdom

or by Electronic Mail to:
OGPubs@opengroup.org

OTHER NOTICES

THIS DOCUMENT AND THE SOFTWARE DESCRIBED HEREIN ARE FURNISHED UNDER A LICENSE, AND MAY BE USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE COPYRIGHT NOTICE. TITLE TO AND OWNERSHIP OF THE DOCUMENT AND SOFTWARE REMAIN WITH THE OPEN GROUP OR ITS LICENSORS.

Security components of DCE may include code from M.I.T.'s Kerberos program. Export of this software from the United States of America is assumed to require a specific license from the United States Government. It is the responsibility of any person or organization contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both the copyright notice and this permission notice appear in supporting documentation, and that the name of M.I.T. not be used in advertising or publicity pertaining to distribution of the software without specific written permission. M.I.T. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

FOR U.S. GOVERNMENT CUSTOMERS REGARDING THIS DOCUMENTATION AND THE ASSOCIATED SOFTWARE

These notices shall be marked on any reproduction of this data, in whole or in part.

NOTICE: Notwithstanding any other lease or license that may pertain to, or accompany the delivery of, this computer software, the rights of the Government regarding its use, reproduction and disclosure are as set forth in Section 52.227-19 of the FARS Computer Software-Restricted Rights clause.

RESTRICTED RIGHTS NOTICE: Use, duplication, or disclosure by the Government is subject to the restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 52.227-7013.

RESTRICTED RIGHTS LEGEND: Use, duplication or disclosure by the Government is subject to restrictions as set forth in paragraph (b)(3)(B) of the rights in Technical Data and Computer Software clause in DAR 7-104.9(a). This computer software is submitted with "restricted rights." Use, duplication or disclosure is subject to the restrictions as set forth in NASA FAR SUP 18-52.227-79 (April 1985) "Commercial Computer Software-Restricted Rights (April 1985)." If the contract contains the Clause at 18-52.227-74 "Rights in Data General" then the "Alternate III" clause applies.

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract.

Unpublished - All rights reserved under the Copyright Laws of the United States.

This notice shall be marked on any reproduction of this data, in whole or in part.

Contents

- Preface iii
 - The Open Group iii
 - The Development of Product Standards iv
 - Open Group Publications v
 - Versions and Issues of Specifications vii
 - Corrigenda vii
 - Ordering Information vii
 - This Book viii
 - Audience viii
 - Applicability viii
 - Purpose viii
 - Document Usage viii
 - Related Documents ix
 - Problem Reporting x
 - Trademarks x

- Chapter 1. Introduction. 1
 - 1.1 Message Structure 2
 - 1.1.1 Severity Levels 3
 - 1.1.2 Subcomponents 4
 - 1.2 Message Routing With the Serviceability API 5
 - 1.2.1 Using Routing Files 5
 - 1.2.2 Using Environment Variables 6
 - 1.2.3 Using dce_svc_routing 6
 - 1.2.4 Using Attributes 6
 - 1.3 Administering the Routing State. 7

1.4	Using This Guide	7
Chapter 2.	Error Messages and Status Codes	9
Appendix A.	Message Numbers and Symbolic Names	1023
Appendix B.	Message Text and Symbolic Names	1179

Preface

The Open Group

The Open Group is the leading vendor-neutral, international consortium for buyers and suppliers of technology. Its mission is to cause the development of a viable global information infrastructure that is ubiquitous, trusted, reliable, and as easy-to-use as the telephone. The essential functionality embedded in this infrastructure is what we term the IT DialTone. The Open Group creates an environment where all elements involved in technology development can cooperate to deliver less costly and more flexible IT solutions.

Formed in 1996 by the merger of the X/Open Company Ltd. (founded in 1984) and the Open Software Foundation (founded in 1988), The Open Group is supported by most of the world's largest user organizations, information systems vendors, and software suppliers. By combining the strengths of open systems specifications and a proven branding scheme with collaborative technology development and advanced research, The Open Group is well positioned to meet its new mission, as well as to assist user organizations, vendors, and suppliers in the development and implementation of products supporting the adoption and proliferation of systems which conform to standard specifications.

With more than 200 member companies, The Open Group helps the IT industry to advance technologically while managing the change caused by innovation. It does this by:

- consolidating, prioritizing, and communicating customer requirements to vendors
- conducting research and development with industry, academia, and government agencies to deliver innovation and economy through projects associated with its Research Institute
- managing cost-effective development efforts that accelerate consistent multi-vendor deployment of technology in response to customer requirements
- adopting, integrating, and publishing industry standard specifications that provide an essential set of blueprints for building open information systems and integrating new technology as it becomes available
- licensing and promoting the Open Brand, represented by the “X” mark, that designates vendor products which conform to Open Group Product Standards
- promoting the benefits of IT DialTone to customers, vendors, and the public.

The Open Group operates in all phases of the open systems technology lifecycle including innovation, market adoption, product development, and proliferation. Presently, it focuses on seven strategic areas: open systems application platform development, architecture, distributed systems management, interoperability, distributed computing environment, security, and the information superhighway. The Open Group is also responsible for the management of the UNIX trademark on behalf of the industry.

The Development of Product Standards

This process includes the identification of requirements for open systems and, now, the IT DialTone, development of CAE and Preliminary Specifications through an industry consensus review and adoption procedure (in parallel with formal standards work), and the development of tests and conformance criteria.

This leads to the preparation of a Product Standard which is the name used for the documentation that records the conformance requirements (and other information) to which a vendor may register a product. There are currently two forms of Product

Standard, namely the Profile Definition and the Component Definition, although these will eventually be merged into one.

The “X” mark is used by vendors to demonstrate that their products conform to the relevant Product Standard. By use of the Open Brand they guarantee, through the X/Open Trade Mark License Agreement (TMLA), to maintain their products in conformance with the Product Standard so that the product works, will continue to work, and that any problems will be fixed by the vendor.

Open Group Publications

The Open Group publishes a wide range of technical documentation, the main part of which is focused on specification development and product documentation, but which also includes Guides, Snapshots, Technical Studies, Branding and Testing documentation, industry surveys, and business titles.

There are several types of specification:

CAE Specifications

CAE (Common Applications Environment) Specifications are the stable specifications that form the basis for our Product Standards, which are used to develop X/Open branded systems. These specifications are intended to be used widely within the industry for product development and procurement purposes.

Anyone developing products that implement a CAE Specification can enjoy the benefits of a single, widely supported industry standard. Where appropriate, they can demonstrate product compliance through the Open Brand. CAE Specifications are published as soon as they are developed, so enabling vendors to proceed with development of conformant products without delay.

Preliminary Specifications

Preliminary Specifications usually address an emerging area of technology and consequently are not yet supported by multiple sources of stable conformant implementations. They are published for the purpose of validation through implementation of products. A Preliminary Specification is not a draft specification; rather, it is as

stable as can be achieved, through applying The Open Group's rigorous development and review procedures.

Preliminary Specifications are analogous to the trial-use standards issued by formal standards organizations, and developers are encouraged to develop products on the basis of them. However, experience through implementation work may result in significant (possibly upwardly incompatible) changes before its progression to becoming a CAE Specification. While the intent is to progress Preliminary Specifications to corresponding CAE Specifications, the ability to do so depends on consensus among Open Group members.

Consortium and Technology Specifications

The Open Group publishes specifications on behalf of industry consortia. For example, it publishes the NMF SPIRIT procurement specifications on behalf of the Network Management Forum. It also publishes Technology Specifications relating to OSF/1, DCE, OSF/Motif, and CDE.

Technology Specifications (formerly AES Specifications) are often candidates for consensus review, and may be adopted as CAE Specifications, in which case the relevant Technology Specification is superseded by a CAE Specification.

In addition, The Open Group publishes:

Product Documentation

This includes product documentation—programmer's guides, user manuals, and so on—relating to the Prestructured Technology Projects (PSTs), such as DCE and CDE. It also includes the Single UNIX Documentation, designed for use as common product documentation for the whole industry.

Guides

These provide information that is useful in the evaluation, procurement, development, or management of open systems, particularly those that relate to the CAE Specifications. The Open Group Guides are advisory, not normative, and should not be referenced for purposes of specifying or claiming conformance to a Product Standard.

Technical Studies

Technical Studies present results of analyses performed on subjects of interest in areas relevant to The Open Group's Technical Program. They

are intended to communicate the findings to the outside world so as to stimulate discussion and activity in other bodies and the industry in general.

Versions and Issues of Specifications

As with all live documents, CAE Specifications require revision to align with new developments and associated international standards. To distinguish between revised specifications which are fully backwards compatible and those which are not:

- A new Version indicates there is no change to the definitive information contained in the previous publication of that title, but additions/extensions are included. As such, it replaces the previous publication.
- A new Issue indicates there is substantive change to the definitive information contained in the previous publication of that title, and there may also be additions/extensions. As such, both previous and new documents are maintained as current publications.

Corrigenda

Readers should note that Corrigenda may apply to any publication. Corrigenda information is published on the World-Wide Web at <http://www.opengroup.org/public/pubs>.

Ordering Information

Full catalogue and ordering information on all Open Group publications is available on the World-Wide Web at <http://www.opengroup.org/public/pubs>.

This Book

The *DCE 1.2.2 Problem Determination Guide* provides a compilation of all DCE error messages and status codes along with explanations and recovery actions.

Audience

This guide is written for DCE application programmers and system and network administrators.

Applicability

This document applies to the OSF DCE Version 1.2.2 offering and related updates. See your software license for details.

Purpose

The purpose of this guide is to help programmers and administrators to interpret and act upon error messages and status codes when received.

Document Usage

The *DCE 1.2.2 Problem Determination Guide* consists of a brief Introduction and one chapter containing a listing of all error messages and status codes. This listing is alphabetical by symbolic name. There are also two appendixes: One maps error numbers to symbolic names; the other maps symbolic names to message text.

Related Documents

For additional information about the Distributed Computing Environment, refer to the following documents:

- *DCE 1.2.2 Introduction to OSF DCE*
Document Number F201, ISBN 1-85912-182-9
- *DCE 1.2.2 Command Reference*
Document Number F212, ISBN 1-85912-138-1
- *DCE 1.2.2 Application Development Reference*
Document Number F205A, ISBN 1-85912-103-9 (Volume 1)
Document Number F205B, ISBN 1-85912-108-X (Volume 2)
Document Number F205C, ISBN 1-85912-159-4 (Volume 3)
- *DCE 1.2.2 Administration Guide—Introduction*
Document Number F207, ISBN 1-85912-113-6
- *DCE 1.2.2 Administration Guide—Core Components*
Document Number F208, ISBN 1-85912-118-7
- *DCE 1.2.2 DFS Administration Guide and Reference*
Document Number F209A, ISBN 1-85912-123-3 (Volume 1)
Document Number F209B, ISBN 1-85912-128-4 (Volume 2)
- *DCE 1.2.2 GDS Administration Guide and Reference*
Document Number F211, ISBN 1-85912-133-0
- *DCE 1.2.2 File-Access Administration Guide and Reference*
Document Number F216, ISBN 1-85912-158-6
- *DCE 1.2.2 File-Access User's Guide*
Document Number F217, ISBN 1-85912-163-3
- *DCE 1.2.2 Application Development—Introduction and Style Guide*
Document Number F202, ISBN 1-85912-187-X
- *DCE 1.2.2 Application Development Guide—Core Components*
Document Number F203A, ISBN 1-85912-192-6 (Volume 1)
Document Number F203B, ISBN 1-85912-154-3 (Volume 2)
- *DCE 1.2.2 Application Development Guide—Directory Services*
Document Number F204, ISBN 1-85912-197-7

- *DCE 1.2.2 Testing Guide*
Document Number F215, ISBN 1-85912-153-5
- *DCE 1.2.2 File-Access FVT User's Guide*
Document Number F210, ISBN 1-85912-189-6
- *DCE 1.2.2 Release Notes*
Document Number F218, ISBN 1-85912-168-3

Problem Reporting

If you have any problems with the software or vendor-supplied documentation, contact your software vendor's customer service department. Comments relating to this Open Group document, however, should be sent to the addresses provided on the copyright page.

Trademarks

Motif[®], OSF/1[®], and UNIX[®] are registered trademarks and the IT DialTone[™], The Open Group[™], and the "X Device"[™] are trademarks of The Open Group.

DEC, DIGITAL, and ULTRIX are registered trademarks of Digital Equipment Corporation.

DECstation 3100 and DECnet are trademarks of Digital Equipment Corporation.

HP, Hewlett-Packard, and LaserJet are trademarks of Hewlett-Packard Company.

Network Computing System and PasswdEtc are registered trademarks of Hewlett-Packard Company.

AFS, Episode, and Transarc are registered trademarks of the Transarc Corporation.

DFS is a trademark of the Transarc Corporation.

Episode is a registered trademark of the Transarc Corporation.

Ethernet is a registered trademark of Xerox Corporation.

AIX and RISC System/6000 are registered trademarks of International Business Machines Corporation.

IBM is a registered trademark of International Business Machines Corporation.

DIR-X is a trademark of Siemens Nixdorf Informationssysteme AG.

MX300i is a trademark of Siemens Nixdorf Informationssysteme AG.

NFS, Network File System, SunOS and Sun Microsystems are trademarks of Sun Microsystems, Inc.

PostScript is a trademark of Adobe Systems Incorporated.

Microsoft, MS-DOS, and Windows are registered trademarks of Microsoft Corp.

NetWare is a registered trademark of Novell, Inc.

———— **OM_FUNCTION_DECLINED**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: An attempt was made to apply a function to an object, but the function does not apply to the object.

Action: None required.

———— **OM_FUNCTION_INTERRUPTED**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The function was aborted by an external force; for example, a keystroke designated for this purpose at a user interface.

Action: If desired, retry the operation.

———— **OM_MEMORY_INSUFFICIENT**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The service could not allocate the main memory it needs to complete the function.

Action: Acquire more memory before retrying the operation.

———— **OM_NETWORK_ERROR**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The service attempted to employ the network upon which its implementation depends, but was unable to do so.

Action: Wait until the network is available and retry the operation.

———— **OM_NO_SUCH_CLASS**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: A purported class identifier was not defined.

Action: This error is returned for the following functions:

- **om_copy()**
- **om_create()**
- **om_delete()**
- **om_instance()**
- **om_put()**

Ensure that the class identifier is correctly defined in the header files.

----- **OM_NO_SUCH_EXCLUSION**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: A purported exclusion identifier was not defined.

Action: This error is returned by the **om_get()** function. Ensure that you have defined all exclusion identifiers.

----- **OM_NO_SUCH_MODIFICATION**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: A purported modification identifier was not defined.

Action: This error is returned by the **om_put()** function. Ensure that you have defined all modification identifiers.

----- **OM_NO_SUCH_OBJECT**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: A purported object is nonexistent, or the purported handle is invalid.

Action: Ensure that you have indicated the correct object or a valid handle for the desired object.

——— **OM_NO_SUCH_SYNTAX**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The purported syntax identifier is not defined.

Action: Ensure that the syntax identifier is defined.

——— **OM_NO_SUCH_TYPE**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The purported type identifier is not defined.

Action: Ensure that the type identifier is defined.

——— **OM_NO_SUCH_WORKSPACE**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: A purported workspace is nonexistent.

Action: This error is returned by the **om_copy()** and the **om_create()** functions. The original or specified class must be in a package associated with the workspace.

——— **OM_NOT_CONCRETE**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The class was abstract, not concrete.

Action: This error is returned by **om_create()** and **om_put()**. The specified class needs to be concrete.

——— **OM_NOT_PRESENT**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: An attribute value was missing.

Action: Ensure that all required attributes are included.

———— **OM_NOT_PRIVATE**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The object named is a public object.

Action: You must name a private object.

———— **OM_NOT_THE_SERVICES**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: An object was client-generated, rather than a service-generated or private object.

Action: This error is returned by **om_delete()** or **om_get()**. The **om_delete()** function operates on a service-generated public object or makes a private object inaccessible. The **om_get()** function makes an exact, but independent copy of an existing private object, thus you must name a private object.

———— **OM_PERMANENT_ERROR**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The service encountered a permanent difficulty other than those indicated by other return codes.

Action: Wait and retry the operation.

———— **OM_POINTER_INVALID**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: In the C interface, an invalid pointer was supplied as a function argument, or as the receptacle for a function result.

Action: Correct the pointer and retry the operation.

——— **OM_SYSTEM_ERROR**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The service could not successfully employ the operating system upon which its implementation depends.

Action: Wait until the operating system is available and retry the operation.

——— **OM_TEMPORARY_ERROR**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The service encountered a temporary difficulty other than those indicated by other return codes.

Action: Wait and retry the operation.

——— **OM_TOO_MANY_VALUES**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: An implementation limit prevents a further attribute value from being added to an object. This limit is undefined.

Action: Simplify the object, if possible, and retry.

——— **OM_VALUES_NOT_ADJACENT**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: The descriptors for the values of a particular attribute are not adjacent.

Action: This error is returned by **om_put()**. Ensure that the descriptors for the values of a particular attribute with two or more values are adjacent to one another in the sequence.

——— **OM_WRONG_VALUE_LENGTH**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: This error is returned by **om_copy_value()**, **om_put()**, and **om_write()**. An attribute has, or would have, a value that violates a constraint on the value syntax.

Action: Check the value length for the attribute and correct the length accordingly.

_____ **OM_WRONG_VALUE_MAKEUP**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: This error is returned by **om_put()** and **om_write()**. An attribute has, or would have, a value that violates a constraint on the value syntax.

Action: Ensure that the value and the the value syntax are acceptable.

_____ **OM_WRONG_VALUE_NUMBER**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: This error is returned by **om_put()**. An attribute has, or would have, a value that violates the value number constraints in force.

Action: Ensure that you have not included more values than acceptable for the attribute.

_____ **OM_WRONG_VALUE_POSITION**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: This error is returned by **om_put()** and **om_write()**. The use defined for the value position in the argument or arguments of a function is invalid.

Action: This error is returned by **om_put()** and **om_write()**. Correct the position of the value within the attribute to conform with the defined position for the value.

_____ **OM_WRONG_VALUE_SYNTAX**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: An attribute has, or would have, a value whose syntax is not permitted.

Action: Correct the syntax for the value.

———— **OM_WRONG_VALUE_TYPE**

Severity: Error **Component:** Directory Services

Text: _____

Explanation: This error is returned by **om_copy_value()**, **om_get()**, and **om_put()**.
An object has, or would have, an attribute whose type is not permitted.

Action: Correct the attribute type.

0x15f5202b pkc_s_alg_already_registered

Severity: Varies **Component:** pkc

Text: The algorithm has already been registered

Explanation: An implementation of the specified algorithm is already registered.

Action: Either use the existing implementation or over-ride it by specifying
PKC_REPLACE_ALL.

0x15f5202a pkc_s_alg_deleted

Severity: Varies **Component:** pkc

Text: The algorithm has been deleted

Explanation: The specified algorithm has been deleted.

Action: Use a different algorithm.

0x15f5200c pkc_s_asn_bad_indefinite

Severity: Varies **Component:** pkc

Text: Bad indefinite-length value.

Explanation: An indefinite-length value was invalid, or not allowed for the type..

Action: Check that the BER you are trying to read is correct.

0x15f52006 pkc_s_asn_bad_param

Severity: Varies **Component:** pkc

Text: Bad Parameter.

Explanation: A parameter value was invalid.

Action: Check the parameters you pass.

0x15f52001 pkc_s_asn_internal_error

Severity: Varies **Component:** pkc

Text: Internal error.

Explanation: An error handler was invoked due to an internal error.

Action: Submit a problem report.

0x15f5200e pkc_s_asn_invalid_value

Severity: Varies **Component:** pkc

Text: Invalid value.

Explanation: The encoding is not valid for the value type.

Action: Correct the BER.

0x15f5200a pkc_s_asn_inv_length

Severity: Varies **Component:** pkc

Text: Invalid length.

Explanation: A length indicator contained an invalid value.

Action: Check that the BER you are trying to read is correct.

0x15f52005 pkc_s_asn_inv_type

Severity: Varies **Component:** pkc

Text: Invalid type.

Explanation: A type indicator denoted the wrong type.

Action: Check that the value you are trying to read is correct.

0x15f5200b pkc_s_asn_inv_value

Severity: Varies **Component:** pkc

Text: Invalid value.

Explanation: A value field contained invalid data.

Action: Check that the BER you are trying to read is correct.

0x15f52002 pkc_s_asn_no_default_value

Severity: Varies **Component:** pkc

Text: No default available.

Explanation: A request was made for the default encoding of an object with no default value.

Action: Submit a problem report.

0x15f52009 pkc_s_asn_no_more_data

Severity: Varies **Component:** pkc

Text: No more data.

Explanation: There is no more data to read.

Action: Application-specific.

0x15f5200f pkc_s_asn_not_supported

Severity: Varies **Component:** pkc

Text: Construct not supported.

Explanation: The BER construct is not supported.

Action: Check that the BER you are trying to read is correct.

0x15f52003 pkc_s_asn_out_of_range

Severity: Varies **Component:** pkc

Text: A value was out of range.

Explanation: An attempt was made to read a value into an object that is too small to contain it.

Action: Submit a problem report.

0x15f52011 pkc_s_asn_unexpected_call

Severity: Varies **Component:** pkc

Text: Unexpected invocation.

Explanation: The routine was invoked unexpectedly.

Action: Submit a problem report.

0x15f52004 pkc_s_asn_unset

Severity: Varies **Component:** pkc

Text: Value unset.

Explanation: An attempt was made to encode an unset value.

Action: Ensure that all values are set before invoking the encode member.

0x15f52010 pkc_s_asn_value_already_set

Severity: Varies **Component:** pkc

Text: Value already set.

Explanation: The value is already set.

Action: A CHOICE value has already been defined.

0x15f5200d pkc_s_asn_value_overflow

Severity: Varies **Component:** pkc

Text: Value overflow.

Explanation: A value being parsed caused an overflow.

Action: Check the BER; Use an object with larger capacity.

0x15f52008 pkc_s_asn_wrong_type

Severity: Varies **Component:** pkc

Text: Invalid type.

Explanation: A type indicator denoted the wrong type.

Action: Check that the value you are trying to read is correct.

0x15f52026 pkc_s_bad_attribute

Severity: Varies **Component:** pkc

Text: Internal error - the wrong attribute was returned.

Explanation: An error occurred while trying to read a certificate

Action: Submit a problem report.

0x15f52028 pkc_s_bad_certificate_handle

Severity: Varies **Component:** pkc

Text: The certificate-handle was invalid

Explanation: The certificate-handle failed consistency checks

Action: Acquire a new certificate-handle, or submit a problem report.

0x15f52040 pkc_s_bad_param

Severity: Varies **Component:** pkc

Text: Bad Parameter.

Explanation: A parameter value was invalid.

Action: Check the parameters you pass.

0x15f52029 pkc_s_bad_time

Severity: Varies **Component:** pkc

Text: Bad time

Explanation: A time value was invalid

Action: Try a different value.

0x15f52025 pkc_s_bad_value

Severity: Varies **Component:** pkc

Text: The value was invalid.

Explanation: An error occurred while trying to parse a value

Action: Ensure the value syntax is correct.

0x15f52048 pkc_s_cant_create_mutex

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't create mutex

Explanation: An error occurred while trying to create a mutex.

Action: Increase process quotas and re-try the operation.

0x15f52049 pkc_s_cant_delete_mutex

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't delete mutex

Explanation: An error occurred while trying to delete a mutex. This is an internal error

Action: Attempt to delete a locked mutex. File a problem report.

0x15f5204a pkc_s_cant_lock_mutex

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't lock mutex

Explanation: An error occurred while trying to lock a mutex. This is an internal error

Action: Can't lock a mutex. File a problem report.

0x15f5204b pkc_s_cant_unlock_mutex

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't unlock mutex

Explanation: An error occurred while trying to unlock a mutex. This is an internal error

Action: Can't unlock a mutex. File a problem report.

0x15f5203c pkc_s_certificate_not_revoked

Severity: Varies **Component:** pkc

Text: The certificate has not been revoked.

Explanation: The certificate has not been revoked.

Action: None - this is an informational status.

0x15f5203d pkc_s_certificate_revoked

Severity: Varies **Component:** pkc

Text: The certificate has been revoked.

Explanation: The certificate has been revoked.

Action: None - this is an informational status.

0x15f5203a pkc_s_cert_invalid_algid

Severity: Varies **Component:** pkc

Text: The certificate is invalid - signature algorithm mismatch.

Explanation: The two signatureAlgorithm fields within the certificate differ.

Action: Retry with a valid certificate.

0x15f5203b pkc_s_cert_not_added

Severity: Varies **Component:** pkc

Text: The certificate was not added as it could not be verified.

Explanation: Trust could not be established in the certificate, so it will not be added.

Action: Application-dependent

0x15f52038 pkc_s_cert_not_verified_signature

Severity: Varies **Component:** pkc

Text: The certificate could not be verified. The signature was wrong.

Explanation: The provided public-key did not match the certificate signature.

Action: Either consider the certificate unverifiable or try another key.

0x15f52037 pkc_s_cert_not_verified_validity

Severity: Varies **Component:** pkc

Text: The certificate could not be verified. Key validity mismatch

Explanation: The validity period of the chosen key did not overlap that of the certificate.

Action: Either consider the certificate unverifiable or retry the operation, specifying a different key.

0x15f5202f pkc_s_conversion_error

Severity: Varies **Component:** pkc

Text: Conversion failed.

Explanation: An error was detected while converting between XDS and XDS++

Action: None.

0x15f5204c pkc_s_delete_not_pending

Severity: Error **Component:** pkc/pkc_s_locks

Text: Locking violation - Delete not pending

Explanation: An internal error occurred in the locking protocol.

Action: Internal error - delete not pending. File a problem report.

0x15f5201b pkc_s_delete_pending

Severity: Varies **Component:** pkc

Text: Delete pending

Explanation: Delete pending.

Action: None. This is an informational status.

0x15f52027 pkc_s_failure

Severity: Varies **Component:** pkc

Text: Non-specific failure.

Explanation: The operation failed

Action: Determine the cause of failure.

0x15f52021 pkc_s_forbidden

Severity: Varies **Component:** pkc

Text: Key not found; lookup forbidden.

Explanation: The requested key may not be retrieved.

Action: Try another key.

0x15f5203e pkc_s_index_out_of_range

Severity: Varies **Component:** pkc

Text: Index out of range

Explanation: The requested key with given index could not be retrieved.

Action: Try another key.

0x15f5204d pkc_s_init_cant_create_mutexattr

Severity: Error **Component:** pkc/pkc_s_locks

Text: Initialization error - Can't create mutex attributes

Explanation: An internal error occurred during module initialization.

Action: Internal error - can't create mutex attributes. File a problem report.

0x15f5204e pkc_s_init_cant_init_mutexattr

Severity: Error **Component:** pkc/pkc_s_locks

Text: Initialization error - Can't initialize mutex attributes

Explanation: An internal error occurred during module initialization.

Action: Internal error - can't initialize mutex attributes. File a problem report.

0x15f5202e pkc_s_init_error

Severity: Varies **Component:** pkc

Text: Initialization failed.

Explanation: The interface could not initialize itself

Action: Retry the operation.

0x15f52050 pkc_s_init_failure_asn

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't initialize ASN.1 subfacility. Code: %x

Explanation: An internal error occurred during ASN.1 initialization.

Action: Internal error - can't initialize ASN.1 subfacility. File a problem report.

0x15f5204f pkc_s_init_failure_locks

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't initialize locking subfacility. Code: %x

Explanation: An internal error occurred during lock initialization.

Action: Internal error - can't initialize locking subfacility. File a problem report.

0x15f52051 pkc_s_init_failure_pkc

Severity: Error **Component:** pkc/pkc_s_locks

Text: Can't initialize PKC subfacility. Code: %x

Explanation: An internal error occurred during PKC initialization.

Action: Internal error - can't initialize PKC subfacility. File a problem report.

0x15f5201d pkc_s_initialization_failure

Severity: Varies **Component:** pkc

Text: Initialization failure.

Explanation: An error occurred during module initialization.

Action: Submit a problem-report.

0x15f52031 pkc_s_insufficient_rdns

Severity: Varies **Component:** pkc

Text: The source name had insufficient components to complete the operation

Explanation: An attempt was made to remove more components than are present in the name

Action: Request the removal of fewer components.

0x15f5203f **pkc_s_internal_error**

Severity: Varies **Component:** pkc

Text: Internal error.

Explanation: An error handler was invoked due to an internal error.

Action: Submit a problem report.

0x15f52018 **pkc_s_invalid_handle**

Severity: Varies **Component:** pkc

Text: Invalid handle.

Explanation: The handle presented was invalid.

Action: Application-specific.

0x15f52039 **pkc_s_invalid_public_key**

Severity: Varies **Component:** pkc

Text: The provided public key is invalid.

Explanation: The public-key is corrupt.

Action: Retry with a valid key.

0x15f52015 **pkc_s_invalid_version**

Severity: Varies **Component:** pkc

Text: Invalid structure version.

Explanation: You passed an unsupported version of a data structure to a library routine.

Action: Re-compile your application against the installed library.

0x15f5201e **pkc_s_inv_lock_type**

Severity: Varies **Component:** pkc

Text: Invalid lock type.

Explanation: An invalid lock type was requested.

Action: Request lock types of either PKC_READ_LOCK or PKC_WRITE_LOCK.

0x15f52036 pkc_s_key_not_certified

Severity: Varies **Component:** pkc

Text: The key is not certified

Explanation: An attempt was made to retrieve information about the certifier of an uncertified key.

Action: None - this is an informational status.

0x15f52020 pkc_s_key_not_found

Severity: Varies **Component:** pkc

Text: Key not found.

Explanation: The requested key could not be retrieved.

Action: Try another key.

0x15f52035 pkc_s_key_not_trusted

Severity: Varies **Component:** pkc

Text: The key is not trusted

Explanation: An attempt was made to retrieve information about an untrusted key.

Action: Present certificate(s) to establish trust in the key before interrogating it.

0x15f5201a pkc_s_locking_violation

Severity: Varies **Component:** pkc

Text: Locking error.

Explanation: A locking operation unexpectedly failed.

Action: Submit a problem report.

0x15f52007 pkc_s_nomem

Severity: Varies **Component:** pkc

Text: Out of memory.

Explanation: An attempt to allocate heap memory failed.

Action: Check your process quotas.

0x15f52017 pkc_s_no_more_items

Severity: Varies **Component:** pkc

Text: No more items.

Explanation: There are no more items in the sequence.

Action: None. This is a success status.

0x15f5202d pkc_s_no_value

Severity: Varies **Component:** pkc

Text: The requested value does not exist

Explanation: There are no more values to retrieve

Action: None.

0x15f52034 pkc_s_plcy_already_registered

Severity: Varies **Component:** pkc

Text: The policy has already been registered

Explanation: An implementation of the specified policy is already registered.

Action: Either use the existing implementation or over-ride it in the re-registration call.

0x15f52033 pkc_s_plcy_deleted

Severity: Varies **Component:** pkc

Text: The policy has been deleted

Explanation: The specified policy has been deleted.

Action: Use a different policy.

0x15f52023 pkc_s_policy_close_failure

Severity: Varies **Component:** pkc

Text: The close operation failed.

Explanation: An error occurred while trying to close a policy

Action: Policy-specific.

0x15f52022 pkc_s_policy_open_failure

Severity: Varies **Component:** pkc

Text: The open operation failed.

Explanation: An error occurred while trying to open a policy

Action: Policy-specific.

0x15f52024 pkc_s_policy_retrieve_failure

Severity: Varies **Component:** pkc

Text: The retrieve operation failed.

Explanation: An error occurred while trying to retrieve a key from a policy

Action: Policy-specific.

0x15f5201f pkc_s_policy_unavailable

Severity: Varies **Component:** pkc

Text: No appropriate policy could be found.

Explanation: The requested key retrieval policy is unavailable.

Action: Request a registered policy.

0x15f52016 pkc_s_replaced

Severity: Varies **Component:** pkc

Text: Object replaced.

Explanation: The object just registered replaced a pre-existing object.

Action: None. This is a success status.

0x15f5201c pkc_s_unimplemented

Severity: Varies **Component:** pkc

Text: Unimplemented feature.

Explanation: The feature is unimplemented.

Action: Application-specific.

0x15f52030 pkc_s_unimplemented_syntax

Severity: Varies **Component:** pkc

Text: Unimplemented syntax.

Explanation: The presented object used a value syntax that is not supported

Action: Retry the operation using a different syntax.

0x15f5202c pkc_s_unsupported

Severity: Varies **Component:** pkc

Text: The operation is unsupported

Explanation: The specified operation is unsupported or unimplemented.

Action: Application-specific.

0x15f52019 pkc_s_unsupported_algorithm

Severity: Varies **Component:** pkc

Text: Unsupported algorithm.

Explanation: An implementation of the specified algorithm has not been registered.

Action: Either specify a supported algorithm, or register an implementation of the algorithm and retry the operation..

0x15f52032 pkc_s_unsupported_policy

Severity: Varies **Component:** pkc

Text: Unsupported policy.

Explanation: An implementation of the specified policy has not been registered

Action: Either specify a supported policy, or register a policy implementation

0x15f52014 pkc_s_x500_at_root

Severity: Varies **Component:** pkc

Text: Already at root.

Explanation: You attempted to find the parent of the namespace root.

Action: Application-specific.

0x15f52013 pkc_s_x500_unsupported_attribute

Severity: Varies **Component:** pkc

Text: Unsupported attribute.

Explanation: The X.500 attribute type is not supported.

Action: Use another attribute type.

0x15f52012 pkc_s_x500_unsupported_syntax

Severity: Varies **Component:** pkc

Text: Unsupported syntax.

Explanation: The X.500 value syntax is not supported.

Action: Use an alternate syntax.

0x15f62051 pks_s_acl_not_authorized

Severity: Error **Component:** pks/pks_s_acl

Text: Unauthorized add or modify attempt on user '%s'.

Explanation: Caller attempted add or modify operation without required privileges.

Action: none

0x15f62008 pks_s_already_initialized

Severity: Notice **Component:** pks/pks_s_server

Text: The PKSS has already initialized.

Explanation: An initialization routine was called more than once.

Action: None - this is an informational status.

0x15f6200b pks_s_bad_acl

Severity: Varies **Component:** pks

Text: An error was detected in a retrieved ACL.

Explanation: An ACL did not pass consistency checks.

Action: Check the integrity of the database.

0x15f6200c pks_s_bad_acl_type

Severity: Varies **Component:** pks

Text: The specified ACL type was not recognized.

Explanation: The specified ACL type was not recognized.

Action: Specify a recognized ACL type.

0x15f62024 pks_s_bad_msg_type

Severity: Varies **Component:** pks

Text: Unexpected message type returned from pipe helper.

Explanation: A protocol violation occurred.

Action: Internal error

0x15f62005 pks_s_cant_open_storage_file

Severity: Varies **Component:** pks

Text: Failed to open file associated with pks object

Explanation: When attempting to open a file associated with the pks object, a failure occurred.

Action: Ensure that the **storage_tag** field of the **id** parameter refers to an existing file, and that the file is accessible to the pks process.

0x15f62009 pks_s_cant_remove_storage_file

Severity: Varies **Component:** pks

Text: Failed to remove file belonging to pks object

Explanation: When attempting to remove a file referred to by the pks object, a failure occurred.

Action: Ensure that the **storage_tag** field of the **id** parameter refers to an existing file, and that the file and directory in which it resides is accessible to the pks process.

0x15f62018 pks_s_exec_e2big

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (E2BIG).

Explanation: Exec failed, errno = E2BIG.

Action: Submit a problem report

0x15f62019 pks_s_exec_eaccess

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (EACCESS).

Explanation: Exec failed, errno = EACCESS.

Action: Submit a problem report

0x15f6201a pks_s_exec_eloop

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (ELOOP).

Explanation: Exec failed, errno = ELOOP.

Action: Submit a problem report

0x15f6201b pks_s_exec_enametoolong

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (ENAMETOOLONG).

Explanation: Exec failed, errno = ENAMETOOLONG.

Action: Submit a problem report

0x15f6201c pks_s_exec_enoent

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (ENOENT).

Explanation: Exec failed, errno = ENOENT.

Action: Submit a problem report

0x15f6201f pks_s_exec_enoexec

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (ENOEXEC).

Explanation: Exec failed, errno = ENOEXEC.

Action: Submit a problem report

0x15f6201d pks_s_exec_enomem

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (ENOMEM).

Explanation: Exec failed, errno = ENOMEM.

Action: Submit a problem report

0x15f6201e pks_s_exec_enotdir

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (ENOTDIR).

Explanation: Exec failed, errno = ENOTDIR.

Action: Submit a problem report

0x15f62020 pks_s_exec_fail

Severity: Error **Component:** pks/pks_s_pipe

Text: Exec failed (%d).

Explanation: Exec failed.

Action: Submit a problem report

0x15f62014 pks_s_fork_error

Severity: Error **Component:** pks/pks_s_pipe

Text: Can't create child process.

Explanation: The PKSS split-client can't fork a child

Action: Check process resources

0x15f62016 pks_s_int_length_error

Severity: Varies **Component:** pks

Text: Pipe length error.

Explanation: Error calculating pipe data length.

Action: Submit a problem report

0x15f62017 pks_s_int_length_errorp

Severity: Error **Component:** pks/pks_s_pipe

Text: Pipe length error (%d).

Explanation: Error calculating pipe data length.

Action: Submit a problem report

0x15f62003 pks_s_invalid_arg

Severity: Error **Component:** pks/pks_s_general

Text: Bad or wrong arguments

Explanation: Bad or wrong arguments were supplied.

Action: Reinvoke the command with the correct arguments.

0x15f62004 pks_s_invalid_arg_1_parm

Severity: Error **Component:** pks/pks_s_general

Text: Bad or wrong argument: %d

Explanation: Bad or wrong argument were supplied.

Action: Reinvoke the command with the correct arguments.

0x15f6200d pks_s_invalid_op

Severity: Varies **Component:** pks

Text: The specified authorization operation was unrecognized.

Explanation: Internal error - the specified authorization operation was unre cognized.

Action: Submit a problem report.

0x15f6200a pks_s_no_acl

Severity: Varies **Component:** pks

Text: The ACL was not found.

Explanation: The ACL did not exist within the database.

Action: Application-specific

0x15f62006 pks_s_no_config_file

Severity: Error **Component:** pks/pks_s_server

Text: Inaccessible or absent configuration file.

Explanation: The PKSS configuration file could not be opened.

Action: Check that a valid configuration exists and can be read.

0x15f62002 pks_s_no_gen_reply

Severity: Error **Component:** pks/pks_s_general

Text: Cannot generate a reply message, %x

Explanation: Could not generate ASN.1-encoded reply message

Action: none

0x15f62007 pks_s_no_group_name

Severity: Error **Component:** pks/pks_s_server

Text: Cannot read server group name from config info

Explanation: Cannot read server group name from config info

Action: Check that a valid configuration exists and can be read.

0x15f62001 pks_s_no_memory

Severity: Error **Component:** pks/pks_s_general

Text: Cannot allocate memory

Explanation: Memory allocation operation failed

Action: Check memory limits on your machine, and increase available memory, if possible.

0x15f62023 pks_s_pipclt_bad_msg

Severity: Error **Component:** pks/pks_s_pipe

Text: Unexpected message type returned from pipe helper (%d).

Explanation: A protocol violation occurred.

Action: Internal error

0x15f62022 pks_s_pipclt_nomem

Severity: Fatal **Component:** pks/pks_s_pipe

Text: Pipe client can't allocate memory (%d).

Explanation: The client can't allocate memory.

Action: Check process resources

0x15f62015 pks_s_pipe_data_error

Severity: Error **Component:** pks/pks_s_pipe

Text: Pipe data error.

Explanation: Error communicating with child process.

Action: Check process resources

0x15f6200f pks_s_pipe_error

Severity: Error **Component:** pks/pks_s_pipe

Text: Can't create pipe.

Explanation: The PKSS split-client can't create a pipe

Action: Check process resources

0x15f62013 pks_s_pipe_svr_decrypt_fail

Severity: Error **Component:** pks/pks_s_pipe

Text: Error decrypting data in server from pipe (%x).

Explanation: Error returned from crypto routine

Action: submit a problem report

0x15f62012 pks_s_pipe_svr_encrypt_fail

Severity: Error **Component:** pks/pks_s_pipe

Text: Error encrypting data in server for pipe (%x).

Explanation: Error returned from crypto routine

Action: Submit a problem report

0x15f62025 pks_s_pipsvr_decode_error

Severity: Error **Component:** pks/pks_s_pipe

Text: Error decoding pipe data.

Explanation: Error decoding pipe data.

Action: Submit a problem report

0x15f62026 pks_s_pipsvr_decode_errorp

Severity: Error **Component:** pks/pks_s_pipe

Text: Error decoding pipe data (%d).

Explanation: Error decoding pipe data.

Action: Submit a problem report

0x15f62021 pks_s_pipsvr_nomem

Severity: Fatal **Component:** pks/pks_s_pipe

Text: Pipe server can't allocate memory (%d).

Explanation: The client-side helper can't allocate memory.

Action: Check process resources

0x15f6202a pks_s_ready_to_listen

Severity: Notice **Component:** pks/pks_s_server

Text: Ready to listen on interfaces...

Explanation: The daemon has started.

Action: None required.

0x15f62027 pks_s_unexpected_termination

Severity: Fatal **Component:** pks/pks_s_pipe

Text: Unexpected child termination, status=**code**.

Explanation: The child process unexpectedly terminated. The status code **code** specifies additional information.

Action: Correct the indicated error and retry the operation.

0x170830df pwd_exp_cl_bad_arg

Severity: Varies **Component:** sad

Text: %s: Unknown command line option %s\n

Explanation: User entered an invalid option

Action: Check passwd_export manual for correct option.

0x170830e2 pwd_exp_cl_bad_entries

Severity: Varies **Component:** sad

Text: %s: User entered an illegal number of requested entries,\n Using the internal maximum (%d entries)for reporting.

Explanation: User entered an invalid value for requested entries, default is used

Action: None required

0x170830e1 pwd_exp_cl_bad_opt_d

Severity: Varies **Component:** sad

Text: %s: Option -d requires argument\n

Explanation: User needs to specify a directory with -d option

Action: Check passwd_export manual for correct argument for -d option.

0x170830e0 pwd_exp_cl_bad_opt_m

Severity: Varies **Component:** sad

Text: %s: Option -m requires argument\n

Explanation: Number of maximum entries should be specified after -m option

Action: Check passwd_export manual for correct command argument.

0x170830de pwd_exp_cl_usage

Severity: Varies **Component:** sad

Text: Usage: %s [-d dirname][-m maxentries][--s][-n][-x][-v] | [-h]\n\n

Explanation: passwd_export started with incorrect arguments

Action: Run passwd_export with correct options and arguments. \n Consult the passwd_export manual page for details.

0x170830eb pwd_exp_env_fail_change_dir

Severity: Varies **Component:** sad

Text: Could not change to directory %s (%s).

Explanation: chdir() system call failed.

Action: Check your permission mode for the directory or the directory exists.

0x170830ec pwd_exp_env_fail_getcwd

Severity: Varies **Component:** sad

Text: Could not get pathname of current directory (%s).

Explanation: getcwd() system call failed.

Action:

0x1708310c pwd_exp_err_no_memory

Severity: Varies **Component:** sad

Text: Cannot allocate requested amount of memory.\n

Explanation: Cannot allocate memory for requested operation.

Action: Check available system swap space and increase if necessary.

0x170830e8 pwd_exp_f_cannot_open_prime_group

Severity: Varies **Component:** sad

Text: Warning: error opening %s for priming group file (%s).

Explanation: When priming the group file to a temporary file, error occurred open the group file.

Action: Check your permission mode for the file.

0x170830e9 pwd_exp_f_cannot_open_temp_group

Severity: Varies **Component:** sad

Text: Could not open temporary group file %s for writing (%s).

Explanation: When priming group file to a temporary file, error occurred open the temporary file.

Action: Check your permission mode for the file.

0x170830ea pwd_exp_f_cannot_open_temp_passwd

Severity: Varies **Component:** sad

Text: Could not %s temporary passwd file %s for writing (%s).

Explanation: Temporary passwd file is used as a lock to ensure there is only one passwd_export process running. If the error indicates the file exists, it may imply that either another passwd_export process is up running or the temporary passwd file was not deleted from last run. For the later case, DCE administrator should delete this file manually.

Action: Check your permission mode for the file.

0x1708310b pwd_exp_no_space

Severity: Varies **Component:** sad

Text: Unable to save passwd database to disk, not enough space.\n

Explanation: Unable to save passwd database to disk.

Action: Ensure that there is adequate disk space.

0x170830e7 pwd_exp_rgy_cannot_close

Severity: Varies **Component:** sad

Text: Can't close connection to registry.

Explanation: Cannot close connection to registry server

Action:

0x170830e6 pwd_exp_rgy_cannot_open

Severity: Varies **Component:** sad

Text: Can't open connection to registry.

Explanation: Cannot connect to registry server

Action:

0x170830e3 pwd_exp_rgy_connect_rejected

Severity: Varies **Component:** sad

Text: Cannot get override information due to server connection rejected.

Explanation: Possible sec_clientd is not available.

Action: Check if sec_clientd is not started, restart it.

0x170830e5 pwd_exp_rgy_error_group

Severity: Varies **Component:** sad

Text: Error occurred while acquiring group entries.

Explanation:

Action:

0x170830e4 pwd_exp_rgy_error_passwd

Severity: Varies **Component:** sad

Text: Error occurred while acquiring passwd entries.

Explanation:

Action:

0x170830ed pwd_imp_cl_usage

Severity: Varies **Component:** sad

Text: Usage: %s [-h] | [-i][-c][-v][-o org][-d dir][-u username] [-p password]\n\n

Explanation: passwd_import started with incorrect arguments

Action: Run passwd_import with correct options and arguments. \n Consult the passwd_import manual page for details.

0x170830f3 pwd_imp_err_add_group_member

Severity: Varies **Component:** sad

Text: Cannot add member: Member \"%s\", Group UNIX id \"%d\" - %s\n

Explanation:

Action:

0x170830f6 pwd_imp_err_add_org_member

Severity: Varies **Component:** sad

Text: Error when adding principal to org \"%s\" - %s\n

Explanation:

Action:

0x170830f2 pwd_imp_err_add_pgo

Severity: Varies **Component:** sad

Text: Error when adding \"%s\" - %s\n

Explanation: Input exceeds internal data storage.

Action:

0x170830f4 pwd_imp_err_add_princ_group

Severity: Varies **Component:** sad

Text: Principal \"%s\", Group \"%d\" - %s\n

Explanation:

Action:

0x170830ef pwd_imp_err_auth

Severity: Varies **Component:** sad

Text: - Authentication failure

Explanation: Calls to check authentication failed.

Action:

0x17083108 pwd_imp_err_bad_ask_y_n

Severity: Varies **Component:** sad

Text: Invalid answer - \"%s\", please answer [yes|no].

Explanation: User typed an invalid answer.

Action:

0x170830f0 pwd_imp_err_bad_name

Severity: Varies **Component:** sad

Text: (Name in question - %s.)\n

Explanation: More information for previous error message

Action:

0x170830c4 pwd_imp_err_cache_e_not_found

Severity: Varies **Component:** sad

Text: Cache entry not found.\n

Explanation: Data not found in cache database.

Action:

0x170830c3 pwd_imp_err_data_too_long

Severity: Varies **Component:** sad

Text: Data is too long for buffer - \"%s\"\n

Explanation: Data length exceeds rgy data storage size.

Action:

0x170830b8 pwd_imp_err_DEL0

Severity: Varies **Component:** sad

Text:

Explanation: MESSAGE NOT REFERENCED, THEREFORE DELETED.

Action: None required

0x170830b9 pwd_imp_err_DEL1

Severity: Varies **Component:** sad

Text:

Explanation: MESSAGE NOT REFERENCED, THEREFORE DELETED.

Action: None required

0x170830c5 pwd_imp_err_dup_name

Severity: Varies **Component:** sad

Text: Name already present in cache, cannot add duplicate entry.\n

Explanation:

Action:

0x170830c6 pwd_imp_err_dup_num

Severity: Varies **Component:** sad

Text: UNIX id already present in cache and entry is not an alias.\n

Explanation: ?

Action: None required

0x170830b3 pwd_imp_err_fatal

Severity: Varies **Component:** sad

Text: Cannot continue after previous error - import operation terminated.

Explanation: Previous error is fatal, has to exit

Action:

0x170830bd pwd_imp_err_gname_exist_match

Severity: Varies **Component:** sad

Text: Group name exists in registry and UNIX ids match.\n

Explanation:

Action:

0x170830be pwd_imp_err_gname_exist_nmatch

Severity: Varies **Component:** sad

Text: Group name exists in registry but UNIX ids don't match.\n

Explanation:

Action:

0x170830b5 pwd_imp_err_gname_too_long

Severity: Varies **Component:** sad

Text: Group name too long.\n

Explanation: Group name length exceeds maximum rgy name length.

Action:

0x170830f7 pwd_imp_err_group_conflict

Severity: Varies **Component:** sad

Text: >>>> The group (%s)exists in the registry with this id.\n

Explanation:

Action:

0x170830c0 pwd_imp_err_guid_exists

Severity: Varies **Component:** sad

Text: Import Group's UNIX id exists in registry.\n

Explanation:

Action:

0x170830f1 pwd_imp_err_input_too_long

Severity: Varies **Component:** sad

Text: Input is too long.\n

Explanation: Input exceeds internal data storage.

Action:

0x170830f5 pwd_imp_err_internal_cache

Severity: Varies **Component:** sad

Text: Internal cache error -

Explanation:

Action:

0x170830ba pwd_imp_err_internal_error

Severity: Varies **Component:** sad

Text: Internal error.\n

Explanation: Unexpected internal error occurs.

Action:

0x170830c1 pwd_imp_err_invalid_option

Severity: Varies **Component:** sad

Text: Invalid option - %s.

Explanation:

Action: Check manual for correct command syntax.

0x170830c2 pwd_imp_err_invalid_uid

Severity: Varies **Component:** sad

Text: Not a valid UNIX id.\n

Explanation:

Action:

0x170830b2 pwd_imp_err_no_grp_access

Severity: Varies **Component:** sad

Text: Unable to access group file %s (%s).

Explanation: This error may be caused by invalid file name or bad permission mode

Action: Validate the file name.

0x170830c7 pwd_imp_err_no_memory

Severity: Varies **Component:** sad

Text: Cannot allocate requested amount of memory.\n

Explanation:

Action:

0x170830b1 pwd_imp_err_no_pwd_access

Severity: Varies **Component:** sad

Text: Unable to access passwd file %s (%s).

Explanation: This error may be caused by invalid file name or bad permission mode

Action: Validate the file name.

0x170830b6 pwd_imp_err_ongame_too_long

Severity: Varies **Component:** sad

Text: Organization name too long.\n

Explanation: Organization name length exceeds maximum rgy name length.

Action:

0x170830ca pwd_imp_err_PAD0

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830cb pwd_imp_err_PAD1

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830cc pwd_imp_err_PAD2

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830cd pwd_imp_err_PAD3

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830b0 pwd_imp_err_path_too_long

Severity: Varies **Component:** sad

Text: Specified directory name too long (%s).

Explanation: Path name length exceeds implementation limit.

Action: Use a shorter pathname or directory name.

0x170830b7 pwd_imp_err_pname_bad_char

Severity: Varies **Component:** sad

Text: Illegal character encountered in principal name.\n

Explanation: ?

Action: None required

0x170830bb **pwd_imp_err_pname_exist_match**

Severity: Varies **Component:** sad

Text: Principal name exists in registry and UNIX ids match.\n

Explanation:

Action:

0x170830bc **pwd_imp_err_pname_exist_nmatch**

Severity: Varies **Component:** sad

Text: Principal name exists in registry but UNIX ids don't match.\n

Explanation:

Action:

0x170830b4 **pwd_imp_err_pname_too_long**

Severity: Varies **Component:** sad

Text: Principal name too long.\n

Explanation: Principal name length exceeds maximum rgy name length.

Action:

0x170830bf **pwd_imp_err_puid_exists**

Severity: Varies **Component:** sad

Text: Import Principal's UNIX id exists in registry.\n

Explanation:

Action:

0x170830c9 pwd_imp_err_unknown_group

Severity: Varies **Component:** sad

Text: Attempted to add membership to unknown group.\n

Explanation: A group with UNIX id was specified in a membership relationship\n in the import files, but no group with this id was added to the\n registry.

Action:

0x170830c8 pwd_imp_err_unknown_princ

Severity: Varies **Component:** sad

Text: Attempted to add membership with unknown principal.\n

Explanation:

Action:

0x170830d9 pwd_imp_inf_add_members

Severity: Varies **Component:** sad

Text: Add memberships from imported group file.\n

Explanation: For debug tracing.

Action:

0x170830d7 pwd_imp_inf_check_org

Severity: Varies **Component:** sad

Text: Verifying that the necessary Organization exists.\n

Explanation: For debug tracing.

Action:

0x170830d6 pwd_imp_inf_choices

Severity: Varies **Component:** sad

Text: (a)lias to existing entry, (g)enerate id automatically\n (e)nter new id, (s)kip this entry and go on to the next one\n

Explanation:

Action:

0x170830d0 pwd_imp_inf_close_import

Severity: Varies **Component:** sad

Text: Closing import files.\n

Explanation: For debug tracing.

Action:

0x170830d2 pwd_imp_inf_close_rgy

Severity: Varies **Component:** sad

Text: Closing connection to registry.\n

Explanation: For debug tracing.

Action:

0x170830d8 pwd_imp_inf_create_accounts

Severity: Varies **Component:** sad

Text: Creating principal entries and accounts from passwd file.\n

Explanation: For debug tracing.

Action:

0x170830ce pwd_imp_inf_create_groups

Severity: Varies **Component:** sad

Text: Creating group objects from group file.\n

Explanation: For debug tracing.

Action:

0x170830d3 pwd_imp_inf_ignore_conflict

Severity: Varies **Component:** sad

Text: Ignoring name conflict, as instructed\n

Explanation:

Action:

0x170830d4 pwd_imp_inf_need_new_name

Severity: Varies **Component:** sad

Text: Would need a new name to resolve conflict.\n

Explanation: Name existed in rgy database.

Action:

0x170830d5 pwd_imp_inf_need_new_uid

Severity: Varies **Component:** sad

Text: Would need new UNIX id to resolve conflict.\n

Explanation: Unix id is used in rgy database.

Action:

0x170830da pwd_imp_inf_PAD0

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830db pwd_imp_inf_PAD1

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830dc pwd_imp_inf_PAD2

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830dd **pwd_imp_inf_PAD3**

Severity: Varies **Component:** sad

Text: UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS\n

Explanation: ?

Action: None required

0x170830cf **pwd_imp_inf_prepare_import**

Severity: Varies **Component:** sad

Text: Preparing import files.\n

Explanation: For debug tracing.

Action:

0x170830d1 **pwd_imp_inf_prepare_rgy**

Severity: Varies **Component:** sad

Text: Setting up registry information.\n

Explanation: For debug tracing.

Action:

0x170830f9 **pwd_imp_msg_add_acct_fail**

Severity: Varies **Component:** sad

Text: ACCOUNT NOT ADDED: (%s %s %s)\n

Explanation:

Action:

0x17083105 **pwd_imp_msg_add_entry**

Severity: Varies **Component:** sad

Text: >> Adding %s entry for: %s %d\n

Explanation:

Action:

0x17083106 pwd_imp_msg_add_entry_gen_unix_id

Severity: Varies **Component:** sad

Text: >> Adding %s entry for: %s (generate-UNIX-id)\n

Explanation:

Action:

0x170830f8 pwd_imp_msg_conflict

Severity: Varies **Component:** sad

Text: CONFLICT: (%s %d) -

Explanation:

Action:

0x170830fb pwd_imp_msg_conflict_entry

Severity: Varies **Component:** sad

Text: (%s %d) is the conflicting entry from the registry.\n

Explanation:

Action:

0x170830fa pwd_imp_msg_conflict_rgy_st

Severity: Varies **Component:** sad

Text: %s\n

Explanation:

Action:

0x170830fc pwd_imp_msg_enter_group_name

Severity: Varies **Component:** sad

Text: Please enter a name for imported group (%d):

Explanation:

Action:

0x170830fe **pwd_imp_msg_enter_new_name**

Severity: Varies **Component:** sad

Text: Enter new name for %s \"%s\" \"%d\":

Explanation:

Action:

0x17083107 **pwd_imp_msg_import**

Severity: Varies **Component:** sad

Text: >> Import %s: \n

Explanation:

Action:

0x170830fd **pwd_imp_msg_temp_group_name**

Severity: Varies **Component:** sad

Text: group_%lu\n

Explanation: Used to generate temporary group name.

Action:

0x17083103 **pwd_imp_prompt_enter_unix_id**

Severity: Varies **Component:** sad

Text: Enter new UNIX id:

Explanation:

Action:

0x17083102 **pwd_imp_prompt_enter_user_name**

Severity: Varies **Component:** sad

Text: Enter your username:

Explanation:

Action:

0x17083101 pwd_imp_prompt_print

Severity: Varies **Component:** sad

Text: %s

Explanation: Print out a prompt.

Action:

0x17083104 pwd_imp_prompt_select_conflict_action

Severity: Varies **Component:** sad

Text: Select one of: (a)lias, (g)enerate, (e)nter, (s)kip entry, (h)elp:

Explanation:

Action:

0x170830ff pwd_imp_qus_enter_conflict_action

Severity: Varies **Component:** sad

Text: Do you wish to resolve the conflict (y) or skip this entry (n):

Explanation:

Action:

0x17083100 pwd_imp_qus_group_conflict

Severity: Varies **Component:** sad

Text: Do you wish to associate the existing group name with this id?

Explanation:

Action:

0x170830ee pwd_imp_rgy_bad_org

Severity: Varies **Component:** sad
Text: Invalid org name - %s
Explanation: <org> enter from -o option is invalid
Action: Make sure <org> specify is a valid name.

0x16c9a167 rpc_m_alloc_fail

Severity: Varies **Component:** rpc
Text: (%s) Memory allocation failed
Explanation: A call to malloc failed to return memory.
Action: Increase available memory and/or swap space.

0x16c9a14a rpc_m_bad_pkt_type

Severity: Varies **Component:** rpc
Text: (%s) Illegal or unknown packet type: %x
Explanation: An internal error occurred.
Action: Report the error to your vendor.

0x16c9a14f rpc_m_call_failed

Severity: Varies **Component:** rpc
Text: %s failed: %s
Explanation: A call to some internal routine or macro failed.
Action: Report the error to your vendor.

0x16c9a153 rpc_m_call_failed_c

Severity: Varies **Component:** rpc
Text: %s on client failed: %s
Explanation: A call to some internal routine or macro on a client failed.
Action: Report the error to your vendor.

0x16c9a151 rpc_m_call_failed_errno

Severity: Varies **Component:** rpc

Text: %s failed, errno = %d

Explanation: A call to some internal routine or macro failed.

Action: Report the error to your vendor.

0x16c9a150 rpc_m_call_failed_no_status

Severity: Varies **Component:** rpc

Text: %s: call failed

Explanation: A call to some internal routine or macro failed.

Action: Report the error to your vendor.

0x16c9a152 rpc_m_call_failed_s

Severity: Varies **Component:** rpc

Text: %s on server failed: %s

Explanation: A call to some internal routine or macro on a server failed.

Action: Report the error to your vendor.

0x16c9a162 rpc_m_cant_create_uuid

Severity: Varies **Component:** rpc

Text: (%s) Can't create UUID

Explanation: A UUID could not be created, probably because the RPC runtime's UUID generator was unable to get the local system's IEEE 802 address.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a169 rpc_m_cant_open_file

Severity: Varies **Component:** rpc

Text: (%s) Can't open file %s.

Explanation: A file couldn't be opened.

Action: Check the existence and permissions of the named file.

0x16c9a145 `rpc_m_cn_ill_state_trans_ca`

Severity: Varies **Component:** rpc

Text: Illegal state transition detected in CN client association state machine [cur_state: %s, cur_event: %s, assoc: %x]

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a147 `rpc_m_cn_ill_state_trans_cg`

Severity: Varies **Component:** rpc

Text: Illegal state transition detected in CN client association group state machine [cur_state: %d, cur_event: %d, grp: %x]

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a149 `rpc_m_cn_ill_state_trans_cr`

Severity: Varies **Component:** rpc

Text: Illegal state transition detected in CN client call state machine [cur_state: %d, cur_event: %d, call_rep: %x]

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a144 `rpc_m_cn_ill_state_trans_sa`

Severity: Varies **Component:** rpc

Text: Illegal state transition detected in CN server association state machine [cur_state: %s, cur_event: %s, assoc: %x]

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a146 rpc_m_cn_ill_state_trans_sg

Severity: Varies **Component:** rpc

Text: Illegal state transition detected in CN server association group state machine [cur_state: %d, cur_event: %d, grp: %x]

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a148 rpc_m_cn_ill_state_trans_sr

Severity: Varies **Component:** rpc

Text: Illegal state transition detected in CN server call state machine [cur_state: %d, cur_event: %d, call_rep: %x]

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a16d rpc_m_ctxrundown_exc

Severity: Varies **Component:** rpc

Text: Exception in routine at %x, running down context %x of client %x

Explanation: An exception was caught by the runtime while trying to rundown client context.

Action: Fix the context rundown routine to avoid raising the exception, or to **CATCH** it.

0x16c9a16c rpc_m_ctxrundown_nomem

Severity: Varies **Component:** rpc

Text: Out of memory while trying to run down contexts of client %x

Explanation: No memory was available from the operating system.

Action: Increase available memory and/or swap space.

0x16c9a165 rpc_m_dgpkt_bad_free

Severity: Varies **Component:** rpc

Text: (%s) Attempt to free already-freed DG packet

Explanation: An attempt was made to free a DG packet already on the packet pool's free list.

Action: Report the error to your vendor.

0x16c9a164 rpc_m_dgpkt_pool_corrupt

Severity: Varies **Component:** rpc

Text: (%s) DG packet free pool is corrupted

Explanation: The DG protocol's packet free pool is corrupted.

Action: Report the error to your vendor.

0x16c9a154 rpc_m_errmsg_toobig

Severity: Varies **Component:** rpc

Text: (%s) Error message will not fit in packet

Explanation: The sec_krb_cn_build_err_message routine failed.

Action: Report the error to your vendor.

0x16c9a15e rpc_m_eventlist_full

Severity: Varies **Component:** rpc

Text: (%s) Event list full

Explanation: A state machine's event list was full when someone tried to put an event on it.

Action: Report the error to your vendor.

0x16c9a14c rpc_m_frag_toobig

Severity: Varies **Component:** rpc

Text: (receive_packet) assoc->%x frag_length %d in header > fragbuf data size %d

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a157 rpc_m_invalid_acbytcnt

Severity: Varies **Component:** rpc

Text: (%s) Inconsistency in ACC_BYTCNT field

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a161 rpc_m_invalid_seqnum

Severity: Varies **Component:** rpc

Text: (%s) Invalid call sequence number

Explanation: An RPC call structure with an invalid sequence number was allocated/initialized.

Action: Report the error to your vendor.

0x16c9a155 rpc_m_invalid_srchattr

Severity: Varies **Component:** rpc

Text: (%s) Unexpected search attribute seen

Explanation: An unexpected search attribute was seen while looking through a name space entry.

Action: Report the error to your vendor.

0x16c9a166 rpc_m_lookaside_corrupt

Severity: Varies **Component:** rpc

Text: (%s) Lookaside list is corrupted

Explanation: A lookaside buffer (internal data structure) was corrupted.

Action: Report the error to your vendor.

0x16c9a15d rpc_m_no_stub_data

Severity: Varies **Component:** rpc

Text: (%s) No stub data to send

Explanation: No stub data was given to a routine to be sent.

Action: Report the error to your vendor.

0x16c9a156 rpc_m_nts_not_found

Severity: Varies **Component:** rpc

Text: (%s) Negotiated transfer syntax not found in presentation context element

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a158 rpc_m_pre_v2_ifspec

Severity: Varies **Component:** rpc

Text: (%s) Pre-v2 interface spec

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a163 rpc_m_pre_v2_ss

Severity: Varies **Component:** rpc

Text: (%s) Can't handle pre-v2 server stubs

Explanation: A Network Computing System (NCS) client tried to make an RPC to a server that did not link in the NCS compatibility library.

Action: Rebuild the server with the NCS compatibility library, or don't use the old NCS client to access the server.

0x16c9a14b rpc_m_prot_mismatch

Severity: Varies **Component:** rpc

Text: (receive_packet) assoc->%x %s: Protocol version mismatch - major->%x minor->%x

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a168 rpc_m_realloc_fail

Severity: Varies **Component:** rpc

Text: (%s) Memory reallocation failed

Explanation: A call to realloc failed to return memory.

Action: Increase available memory and/or swap space.

0x16c9a15a rpc_m_recvbuf_toosmall

Severity: Varies **Component:** rpc

Text: (%s) Socket's maximum receive buffering is less than NCA Connection Protocol minimum requirement

Explanation: Socket buffering available from the operating system is insufficient to support RPC.

Action: Increase the operating system's maximum socket buffer size.

0x16c9a15b rpc_m_unalign_authtrl

Severity: Varies **Component:** rpc

Text: (%s) Unaligned RPC_CN_PKT_AUTH_TRL

Explanation: Authorization trailer on CN protocol packet was not properly aligned.

Action: Report the error to your vendor.

0x16c9a15c rpc_m_unexpected_exc

Severity: Varies **Component:** rpc

Text: (%s) Unexpected exception was raised

Explanation: An unexpected exception was caught by the RPC runtime.

Action: Report the error to your vendor.

0x16c9a14e rpc_m_unhandled_callstate

Severity: Varies **Component:** rpc

Text: (%s) Unhandled call state: %s

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a160 rpc_m_unimp_call

Severity: Varies **Component:** rpc

Text: (%s) Call not implemented

Explanation: A call to an unimplemented routine was made by the RPC runtime.

Action: Report the error to your vendor.

0x16c9a159 rpc_m_unk_ifspec

Severity: Varies **Component:** rpc

Text: (%s) Unknown interface spec version

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a15f rpc_m_unk_sock_type

Severity: Varies **Component:** rpc

Text: (%s) Unknown socket type

Explanation: The socket corresponding to a file descriptor is of an unknown type.

Action: Report the error to your vendor.

0x16c9a14d rpc_m_unsupp_stub_rtl_if

Severity: Varies **Component:** rpc

Text: (%s) Unsupported stub/RTL IF version

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a04a rpc_s_access_control_info_inv

Severity: Varies **Component:** rpc

Text: Access control information invalid at remote host

Explanation: The client may have attempted to connect to a server at a protected address for which the client lacks the required permissions. If the client is attempting to connect to a server using the **ncacn_dnet_nsp** protocol sequence using a well known endpoint or a fully specified string binding, there are three possible reasons for this status: The server is not running The server is not listening for client connects

over the **ncacn_dnet_nsp** protocol sequence. The server is not listening for client connects on the endpoint specified by the client.

Action: In general, you should modify the access controls on the specified address to allow the client access. If the client is attempting to communicate with a server using the **ncacn_dnet_nsp** protocol sequence with a well-known or explicitly specified endpoint, do the following: Verify at the server node that the server application has been started and is listening over the **ncacn_dnet_nsp** protocol sequence. Verify that the client has specified the correct server endpoint. Verify that both client and server have specified a named server endpoint in upper-case characters. For protocol sequences that allow alphanumeric endpoints, specify endpoints in upper-case characters, not mixed lower-case characters.

0x16c9a022 rpc_s_already_listening

Severity: Varies **Component:** rpc

Text: Already listening

Explanation: A server application called **rpc_server_listen**, but another thread within the process is currently blocked inside a call to this procedure.

Action: Fix the application so that only one thread at a time calls **rpc_server_listen**.

0x16c9a01e rpc_s_already_registered

Severity: Varies **Component:** rpc

Text: Already registered

Explanation: An application tried to set the type of an object to a value that was already set for that object.

Action: Remove the redundant object type setting.

0x16c9a052 rpc_s_assoc_grp_max_exceeded

Severity: Varies **Component:** rpc

Text: Association group maximum exceeded

Explanation: An internal error occurred. The maximum number of associations per association group was exceeded.

Action: Report the error to your vendor.

0x16c9a038 rpc_s_assoc_grp_not_found

Severity: Varies **Component:** rpc

Text: Association group not found

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a056 rpc_s_assoc_shutdown

Severity: Varies **Component:** rpc

Text: Association shutdown

Explanation: An internal error occurred. The client runtime has received a shutdown request from the server runtime.

Action: Report the error to your vendor.

0x16c9a0ed rpc_s_auth_badaddr

Severity: Varies **Component:** rpc

Text: Incorrect network address in authentication request

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a0f5 rpc_s_auth_baddirection

Severity: Varies **Component:** rpc

Text: Incorrect authentication message direction

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a0e6 rpc_s_auth_bad_integrity

Severity: Varies **Component:** rpc

Text: Decrypt integrity check failed

Explanation: A received packet failed integrity check.

Action: This may indicate an attempt to circumvent security.

0x16c9a0f2 rpc_s_auth_badkeyver

Severity: Varies **Component:** rpc
Text: Authentication key version not available
Explanation: Authentication between the client and server failed.
Action: This may be an attempt to violate system security.

0x16c9a0eb rpc_s_auth_badmatch

Severity: Varies **Component:** rpc
Text: Authentication ticket/authenticator do not match
Explanation: Authentication between the client and server failed.
Action: This may indicate an attempt to violate system security.

0x16c9a0f1 rpc_s_auth_badorder

Severity: Varies **Component:** rpc
Text: Authentication message out of order
Explanation: An authentication service message was received out of order.
Action: This may be an attempt to violate system security.

0x16c9a0f7 rpc_s_auth_badseq

Severity: Varies **Component:** rpc
Text: Incorrect sequence number in authentication message
Explanation: Authentication between the client and server failed.
Action: This may be an attempt to violate system security.

0x16c9a0ee rpc_s_auth_badversion

Severity: Varies **Component:** rpc
Text: Authentication protocol version mismatch
Explanation: Authentication between the client and server failed.
Action: This may be an attempt to violate system security.

0x16c9a0f9 **rpc_s_auth_field_toolong**

Severity: Varies **Component:** rpc

Text: Authentication field too long for implementation

Explanation: An authentication packet with an authentication field exceeding implementation limits was received. This packet is part of the authentication exchange between the RPC runtime and the security server.

Action: This may be an attempt to violate system security.

0x16c9a0f8 **rpc_s_auth_inapp_cksum**

Severity: Varies **Component:** rpc

Text: Inappropriate authentication checksum type

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a0f6 **rpc_s_auth_method**

Severity: Varies **Component:** rpc

Text: Alternative authentication method required

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a0f0 **rpc_s_auth_modified**

Severity: Varies **Component:** rpc

Text: Authentication message stream modified

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a0ef **rpc_s_auth_msg_type**

Severity: Varies **Component:** rpc

Text: Invalid authentication message type

Explanation: An invalid message was received during the authentication exchange.

Action: This may be an attempt to violate system security.

0x16c9a0f4 rpc_s_auth_mut_fail

Severity: Varies **Component:** rpc

Text: Mutual authentication failed

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a066 rpc_s_authn_authz_mismatch

Severity: Varies **Component:** rpc

Text: Authentication authorization mismatch

Explanation: In a call to **rpc_binding_set_auth_info**, the requested authorization service is not supported by the requested authentication service.

Action: Choose a compatible pair of authentication and authorization services.

0x16c9a100 rpc_s_authn_challenge_malformed

Severity: Varies **Component:** rpc

Text: Authentication challenge malformed

Explanation: The client-side runtime detected that the authentication challenge it was given by the server was incorrectly formed.

Action: This usually does not happen. Check for version skew between client and server, or bugs in the client or server runtime.

0x16c9a0f3 rpc_s_auth_nokey

Severity: Varies **Component:** rpc

Text: Authentication service key not available

Explanation: Authentication between the client and server failed.

Action: This may be an attempt to violate system security.

0x16c9a0ea rpc_s_auth_not_us

Severity: Varies **Component:** rpc

Text: Authentication ticket is not for destination

Explanation: Authentication failed at the server because the ticket was not valid for this server.

Action: This may indicate an attempt to violate system security.

0x16c9a0e9 **rpc_s_auth_repeat**

Severity: Varies **Component:** rpc

Text: Authentication request is a replay

Explanation: A retransmission of an old request has been detected.

Action: This may indicate an attempt to violate system security.

0x16c9a0ec **rpc_s_auth_skew**

Severity: Varies **Component:** rpc

Text: Clock skew too great to authenticate

Explanation: Authentication failed because the timestamp in the message indicates that the systems' clocks are too far apart.

Action: The client and server systems' clocks may be skewed, or this may be an attempt to violate system security.

0x16c9a0e7 **rpc_s_auth_tkt_expired**

Severity: Varies **Component:** rpc

Text: Authentication ticket expired

Explanation: Some security credentials which you've acquired during login have expired.

Action: Acquire or renew your credentials by either logging in again or running **kinit** if available.

0x16c9a0e8 **rpc_s_auth_tkt_nyv**

Severity: Varies **Component:** rpc

Text: Authentication ticket not yet valid

Explanation: The authentication ticket passed to the server is not yet valid.

Action: This may indicate an attempt to violate system security.

0x16c9a010 rpc_s_binding_has_no_auth

Severity: Varies **Component:** rpc

Text: Not authenticated

Explanation: An application manager routine tried to inquire about authentication information from a client binding handle but the client did not establish any authentication on the call.

Action: The manager routine can either ignore the error or refuse to execute the call. The application writer can change the client to use authentication.

0x16c9a0fb rpc_s_binding_incomplete

Severity: Varies **Component:** rpc

Text: Binding incomplete (no object ID and no endpoint)

Explanation: The specified server binding information was insufficient. In a local or remote management call to the RPC runtime, the client-supplied binding information lacked an endpoint and an associated object UUID.

Action: Supply complete binding information and an object UUID to local or remote management calls.

0x16c9a0b9 rpc_s_binding_vector_full

Severity: Varies **Component:** rpc

Text: Binding vector full

Explanation: An internal status code.

Action: None required.

0x16c9a031 rpc_s_call_cancelled

Severity: Varies **Component:** rpc

Text: Call canceled

Explanation: A cancel was posted to a thread making a remote call. This error condition occurs at the server but is usually not seen by the server application.

Action: None required.

0x16c9a014 rpc_s_call_faulted

Severity: Varies **Component:** rpc

Text: Call faulted

Explanation: The execution of an application manager routine raised a fault (exception), for example, division by zero. Applications usually do not see this error as it is intercepted by the client stub and transformed into the specific error condition that occurs in the application manager routine.

Action: None required.

0x16c9a0e4 rpc_s_call_id_not_found

Severity: Varies **Component:** rpc

Text: Call ID in packet unknown

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a05e rpc_s_call_orphaned

Severity: Varies **Component:** rpc

Text: Call orphaned

Explanation: A client application has given up waiting for a manager routine to return. This error occurs at the server but is usually not seen by the server application.

Action: None required.

0x16c9a067 rpc_s_call_queued

Severity: Varies **Component:** rpc

Text: Call queued

Explanation: An internal status code.

Action: None required.

0x16c9a06f rpc_s_calls_too_large_for_wk_ep

Severity: Varies **Component:** rpc

Text: Calls too large for well known endpoint

Explanation: The specified value of argument **max_call_requests** exceeds the maximum allowed when using a well-known endpoint.

Action: Specify a **max_call_requests** value of **rpc_c_protseq_max_reqs_default** to obtain the maximum value allowed for the specified protocol sequence.

0x16c9a06c rpc_s_call_timeout

Severity: Varies **Component:** rpc

Text: Call timed out

Explanation: A remote call did not return before the timeout set by **rpc_mgmt_set_call_timeout** expired.

Action: None required.

0x16c9a030 rpc_s_cancel_timeout

Severity: Varies **Component:** rpc

Text: Cancel timeout

Explanation: A cancel was posted to a thread making a remote call, a non-infinite cancel timeout was previously specified (by **rpc_mgmt_set_cancel_timeout**), and the manager routine did not respond to the cancel within the cancel timeout period.

Action: None required.

0x16c9a037 rpc_s_cannot_accept

Severity: Varies **Component:** rpc

Text: Cannot accept

Explanation: An internal error occurred. The network listener thread cannot accept the connection on which a network event was detected.

Action: Report the error to your vendor.

0x16c9a034 rpc_s_cannot_connect

Severity: Varies **Component:** rpc

Text: Cannot connect

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a068 `rpc_s_cannot_set_nodelay`

Severity: Varies **Component:** rpc

Text: Cannot set nodelay

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a003 `rpc_s_cant_bind_socket`

Severity: Varies **Component:** rpc

Text: Cannot bind socket

Explanation: An underlying problem with the local system's network transport service prevented the RPC runtime from assigning an endpoint to a communications socket.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login). Verify that another executing server is not already using the specified endpoint.

0x16c9a002 `rpc_s_cant_create_socket`

Severity: Varies **Component:** rpc

Text: Cannot create socket

Explanation: An underlying problem with the local system's network transport service prevented the RPC runtime from creating a communications socket needed to make or receive remote calls.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a05c `rpc_s_cant_get_if_id`

Severity: Varies **Component:** rpc

Text: Cannot get interface ID

Explanation: The RPC runtime tried to get information about a communications socket but failed due to an underlying network transport service problem.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a05b `rpc_s_cant_getpeername`

Severity: Varies **Component:** rpc

Text: Cannot get peer name

Explanation: There was a failed attempt to get the network address of the other end of the connection. If the client-server connection is closed, an executing manager routine that calls either `rpc_binding_to_string_binding` or `rpc_binding_server_from_client` may receive this status. Both routines require connection information that is no longer available. This status can occur if the executing remote procedure was specified with the IDL `maybe` attribute, or if the remote procedure call has been orphaned.

Action: The `getpeername` routine returns the name of the peer connected to a particular socket. See the `getpeername(2)` for more information. In the case of an orphaned call the client can try to reissue the call.

0x16c9a029 `rpc_s_cant_inq_socket`

Severity: Varies **Component:** rpc

Text: Cannot inquire socket

Explanation: The RPC runtime tried to get information about a communications socket but failed due to an underlying network transport service problem.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a104 `rpc_s_class_version_mismatch`

Severity: Varies **Component:** rpc

Text: RPC class version mismatch

Explanation: The application attempted to read or modify a name service entry with an incompatible RPC class version. For example, a V1.0 client tried to read a name service entry with a V2.0 version. Only major version incompatibilities are flagged.

Action: Upgrade either the name service entry or client to the appropriate version.

0x16c9a01a rpc_s_coding_error

Severity: Varies **Component:** rpc

Text: RPC coding error

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a016 rpc_s_comm_failure

Severity: Varies **Component:** rpc

Text: Communications failure

Explanation: The RPC runtime that was attempting to implement a call to a remote procedure gave up waiting for the execution of the procedure to start or complete because the RPC runtime determined that it was not communicating with the remote server. .sp The RPC runtime may also return this status when a client makes a remote procedure call using a partially bound binding (no endpoint) and the RPC runtime is unable to communicate with the endpoint map service, which is provided by the RPC daemon.

Action: In the first case, try another server. In the second case, make sure the RPC daemon is running.

0x16c9a04c rpc_s_connect_closed_by_rem

Severity: Varies **Component:** rpc

Text: Connection closed by remote host

Explanation: The network connection was closed by the remote host.

Action: Check the remote process and network. Retry the operation.

0x16c9a035 rpc_s_connection_aborted

Severity: Varies **Component:** rpc

Text: Connection aborted

Explanation: An internal error occurred. The connection has been aborted by either the client or server RPC runtime.

Action: Report the error to your vendor.

0x16c9a036 rpc_s_connection_closed

Severity: Varies **Component:** rpc

Text: Connection closed

Explanation: The underlying session or transport connection has failed. If the client-server connection is closed, an executing manager routine that calls either **rpc_binding_to_string_binding** or **rpc_binding_server_from_client** may see this status. Both routines require connection information that is no longer available. This can occur if the executing remote procedure was specified to be an operation with the IDL **maybe** attribute, or if the remote procedure call has been orphaned.

Action: Verify the underlying connection and retry the operation. In the case of the orphaned call, the client can try to reissue the call.

0x16c9a044 rpc_s_connect_no_resources

Severity: Varies **Component:** rpc

Text: Not enough resources for connection at local or remote host

Explanation: There are insufficient system resources at either the local or remote host to establish the connection.

Action: Check the applicable system resources and retry the operation.

0x16c9a042 rpc_s_connect_rejected

Severity: Varies **Component:** rpc

Text: Connection request rejected

Explanation: The server rejected the connection request from the client. This can be because the server has reached its maximum allowable connect requests.

Action: Check the network connection and then retry the operation. If the network connection is ok, the server may be receiving too many simultaneous client requests. The client can retry the server or try contacting a different server.

0x16c9a041 rpc_s_connect_timed_out

Severity: Varies **Component:** rpc

Text: Connection request timed out

Explanation: The client cannot establish a connection to the server. The operation timed out.

Action: Check the network connection and then retry the operation.

0x16c9a058 rpc_s_context_id_not_found

Severity: Varies **Component:** rpc

Text: Context id not found

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0e3 rpc_s_credentials_too_large

Severity: Varies **Component:** rpc

Text: Credentials too large for packet

Explanation: The security credentials are too large to fit into an RPC message.

Action: The size of the security credentials is related to the number of groups to which a principal belongs. Reducing the group membership count can reduce the size of the credentials.

0x16c9a0c9 rpc_s_cthread_create_failed

Severity: Varies **Component:** rpc

Text: cthread create failed

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0cc rpc_s_cthread_invoke_disabled

Severity: Varies **Component:** rpc

Text: cthread invoke disabled

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0cb rpc_s_ctype_no_such_pool

Severity: Varies **Component:** rpc

Text: No such ctype pool

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a01c rpc_s_ctype_not_found

Severity: Varies **Component:** rpc

Text: Call ctype not found

Explanation: An internal error occurred. You'll see this error when the call queue is full. Client requests are coming in faster than they can be executed and eventually the call queue fills up. This status is translated and returned to the calling client as **rpc_s_server_too_busy**.

Action: Report the error to your vendor.

0x16c9a0ca rpc_s_ctype_pool_exists

Severity: Varies **Component:** rpc

Text: ctype pool exists

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0ba rpc_s_cycle_detected

Severity: Varies **Component:** rpc

Text: Cycle detected

Explanation: A cycle was detected in the course of traversing groups and profiles in the binding import operation.

Action: Modify the structure of groups and profiles in the name service database to eliminate the cycle.

0x16c9a021 rpc_s_desc_not_registered

Severity: Varies **Component:** rpc

Text: Descriptor not registered

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a10c rpc_s_dg_need_way_auth

Severity: Varies **Component:** rpc

Text: DG protocol needs reauthentication.

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a01f rpc_s_endpoint_not_found

Severity: Varies **Component:** rpc

Text: Endpoint not found

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0a4 rpc_s_entry_already_exists

Severity: Varies **Component:** rpc

Text: Entry already exists

Explanation: The name service entry to which the server or management application is exporting the binding already exists. This is not a problem.

Action: None required.

0x16c9a0a0 rpc_s_entry_not_found

Severity: Varies **Component:** rpc

Text: Entry not found

Explanation: The specified name service object (profile, group, or entry) does not exist in the name service database.

Action: Verify that the object or directory name supplied to the name service (NSI) operation exists and repeat the operation.

0x16c9a074 `rpc_s_fault_addr_error`

Severity: Varies **Component:** rpc

Text: Fault address error

Explanation: An application manager routine running in the server raised a hardware addressing exception.

Action: Fix the manager routine.

0x16c9a16e `rpc_s_fault_codeset_conv_error`

Severity: Varies **Component:** rpc

Text: Fault codeset conversion error

Explanation: A server stub or application manager routine received an error status back from a codeset conversion routine.

Action: There is invalid data being converted or the user supplied conversion routine needs to be fixed.

0x16c9a075 `rpc_s_fault_context_mismatch`

Severity: Varies **Component:** rpc

Text: Fault context mismatch

Explanation: A client application passed a context handle into a remote call, but the server detected that the server does not hold the specified context. This error can happen if a server stops and restarts in between remote calls from the client holding the context handle and the client calls the restarted server. .sp An application sees this status if **rpcd** restarts during a sequence of application calls to **rpc_mgmt_ep_elt_inq_next**. The new instance of **rpcd** does not inherit the context that was maintained by the previous **rpcd**.

Action: If returned from **rpc_mgmt_ep_elt_inq_next**, free the current inquiry context by calling **rpc_mgmt_ep_elt_inq_done** and restart the inquiry by calling **rpc_mgmt_ep_elt_inq_begin**.

0x16c9a076 `rpc_s_fault_fp_div_by_zero`

Severity: Varies **Component:** rpc

Text: Fault floating point divide by zero

Explanation: An application manager routine attempted to do a floating point division with a denominator of zero.

Action: Fix the manager routine.

0x16c9a077 rpc_s_fault_fp_error

Severity: Varies **Component:** rpc

Text: Fault floating point error

Explanation: An application manager routine failed in the execution of a floating point operation.

Action: Fix the manager routine.

0x16c9a078 rpc_s_fault_fp_overflow

Severity: Varies **Component:** rpc

Text: Fault floating point overflow

Explanation: A floating point calculation in an application manager routine resulted in an arithmetic overflow.

Action: Fix the manager routine.

0x16c9a079 rpc_s_fault_fp_underflow

Severity: Varies **Component:** rpc

Text: Fault floating point underflow

Explanation: A floating point calculation in an application manager routine resulted in an arithmetic underflow.

Action: Fix the manager routine.

0x16c9a07a rpc_s_fault_ill_inst

Severity: Varies **Component:** rpc

Text: Fault illegal instruction

Explanation: An application manager routine attempted to execute an illegal machine instruction.

Action: Fix the manager routine.

0x16c9a07b `rpc_s_fault_int_div_by_zero`

Severity: Varies **Component:** rpc

Text: Fault integer divide by zero

Explanation: An application manager routine attempted to do an integer division with a denominator of zero.

Action: Fix the manager routine.

0x16c9a07c `rpc_s_fault_int_overflow`

Severity: Varies **Component:** rpc

Text: Fault integer overflow

Explanation: An integer calculation in an application manager routine resulted in an arithmetic overflow.

Action: Fix the manager routine.

0x16c9a07d `rpc_s_fault_invalid_bound`

Severity: Varies **Component:** rpc

Text: Fault invalid bound

Explanation: An application made a remote call that attempted to pass or return an array with a dynamically specified bound that is not appropriate to the declared dimensions of the array.

Action: Fix the application.

0x16c9a07e `rpc_s_fault_invalid_tag`

Severity: Varies **Component:** rpc

Text: Fault invalid tag

Explanation: An application made a remote call that attempted to pass or return a discriminated union with an invalid tag.

Action: Fix the application.

0x16c9a170 `rpc_s_fault_no_client_stub`

Severity: Varies **Component:** rpc

Text: Fault client stub not linked into application

Explanation: A server stub or application manager routine attempted to make a remote procedure call, but the client stub module for the corresponding IDL interface was not linked into the application.

Action: Relink the application, including the relevant client stub module.

0x16c9a07f rpc_s_fault_pipe_closed

Severity: Varies **Component:** rpc

Text: Fault pipe closed

Explanation: An application manager routine attempted to write data to a pipe that was already closed by writing a terminator to it.

Action: Fix the application.

0x16c9a080 rpc_s_fault_pipe_comm_error

Severity: Varies **Component:** rpc

Text: Fault pipe communication error

Explanation: A communications error occurred while an application manager routine was reading from or writing to a pipe.

Action: The client code must recover from an unsuccessful remote call.

0x16c9a081 rpc_s_fault_pipe_discipline

Severity: Varies **Component:** rpc

Text: Fault pipe discipline

Explanation: An application manager routine returned control to the server stub while there was still pipe data to be read or written.

Action: Fix the application.

0x16c9a082 rpc_s_fault_pipe_empty

Severity: Varies **Component:** rpc

Text: Fault pipe empty

Explanation: An application manager routine attempted to read data from a pipe from which a terminator had already been received.

Action: Fix the application.

0x16c9a083 rpc_s_fault_pipe_memory

Severity: Varies **Component:** rpc

Text: Fault pipe memory

Explanation: The application code provided insufficient memory to allow the marshaling or unmarshaling of an element of a pipe.

Action: Fix the application.

0x16c9a084 rpc_s_fault_pipe_order

Severity: Varies **Component:** rpc

Text: Fault pipe order

Explanation: An application manager routine attempted to use the pipes in an operation in an order other than that required by the IDL language definition.

Action: Fix the application.

0x16c9a085 rpc_s_fault_remote_comm_failure

Severity: Varies **Component:** rpc

Text: Fault remote communication failure

Explanation: A server stub encountered a communications error.

Action: The client code must recover from an unsuccessful remote call.

0x16c9a086 rpc_s_fault_remote_no_memory

Severity: Varies **Component:** rpc

Text: Fault remote no memory

Explanation: A server stub or application manager routine was unable to allocate heap storage.

Action: If the failure is caused by overuse of underlying system resources (for example, address space or swap space), reduce the application's direct use of these resources if possible.

0x16c9a087 rpc_s_fault_unspec

Severity: Varies **Component:** rpc

Text: Fault unspecified

Explanation: A server stub or application manager routine raised an exception of an unknown kind.

Action: Fix the application.

0x16c9a113 rpc_s_fault_user_defined

Severity: Varies **Component:** rpc

Text: User defined exception received

Explanation: This status is given to a *[fault_status]* parameter if the server returned a user exception.

Action: Application dependent.

0x16c9a0a3 rpc_s_group_member_not_found

Severity: Varies **Component:** rpc

Text: Group member not found

Explanation: The server or management application attempted to remove a group member that does not exist in the name service database.

Action: Use the RPC control program to see if the group member exists. If it does not, correct the application. If the group member does exist in the name service database, report the problem to your vendor.

0x16c9a108 rpc_s_helper_aborted

Severity: Varies **Component:** rpc

Text: Helper process aborted

Explanation: The user-space helper process exited before responding to a request. This indicates that either someone stopped the helper process or that a bug in the helper process caused it to crash.

Action: Restart the helper process or fix the bug in the helper process.

0x16c9a107 rpc_s_helper_catatonic

Severity: Varies **Component:** rpc

Text: Helper process catatonic

Explanation: The user-space helper took longer than two to three minutes to respond to a request from the kernel. This indicates that the helper process or the services it depends on are malfunctioning or overloaded.

Action: Ease network congestion, fix bugs, or increase the hard-coded timeout in the kernel.

0x16c9a105 rpc_s_helper_not_running

Severity: Varies **Component:** rpc

Text: Helper process not running

Explanation: The kernel attempted to issue a request to the user space helper process, but discovered that it was not running.

Action: Start a helper process and try again.

0x16c9a10b rpc_s_helper_overflow

Severity: Varies **Component:** rpc

Text: Helper process too busy

Explanation: There were too many outstanding requests in the helper process.

Action: Increase the table size in the helper process and rebuild.

0x16c9a106 rpc_s_helper_short_read

Severity: Varies **Component:** rpc

Text: Short read from kernel helper

Explanation: The kernel attempted to read a request from the user-space DCE helper process, but not enough data was available to satisfy the request. This indicates a bug

in the user-space DCE helper process or version skew between the kernel and the helper process.

Action: Fix the bug or upgrade the helper process to match the kernel.

0x16c9a10a **rpc_s_helper_wrong_user**

Severity: Varies **Component:** rpc

Text: Attempting to use credentials belonging to another user

Explanation: Requests from the kernel to the helper process include the user ID and the credentials to use to authenticate a remote operation. The helper process detected that the user ID attached to a request from the kernel was different from the owner of the request.

Action: This indicates either a kernel bug or an attempt to violate security.

0x16c9a049 **rpc_s_host_unreachable**

Severity: Varies **Component:** rpc

Text: Remote host is unreachable

Explanation: The specified host is unreachable.

Action: Check the network connectivity. Retry the operation.

0x16c9a00d **rpc_s_in_args_too_big**

Severity: Varies **Component:** rpc

Text: Input arguments too big

Explanation: The size of the input arguments to a remote call was larger than is allowed in the current context. For example, in broadcast calls the input arguments must fit into a single transport-level packet.

Action: Reduce the size of input arguments.

0x16c9a094 **rpc_s_incomplete_name**

Severity: Varies **Component:** rpc

Text: Incomplete name

Explanation: An incomplete object or directory name was supplied to some name service (NSI) operation. The operation failed because the name cannot be expanded.

Action: Supply a complete name and retry the operation.

0x16c9a0a2 rpc_s_interface_not_found

Severity: Varies **Component:** rpc

Text: Interface not found

Explanation: The unexport operation did not find any binding information for the specified interface. No binding information was unexported.

Action: Use the RPC control program to find out whether the server entry contains binding information for the specified interface identifier. If the entry contains the binding information, report the problem to your vendor.

0x16c9a063 rpc_s_invalid_arg

Severity: Varies **Component:** rpc

Text: Invalid argument

Explanation: An aspect of the arguments supplied as input to the RPC runtime is inappropriate. In the case of **rpc_mgmt_set_server_stack_size**, the underlying thread package does not support the specified value of argument **thread_stack_size**.

Action: Check the supplied arguments against documentation for the call.

0x16c9a01d rpc_s_invalid_binding

Severity: Varies **Component:** rpc

Text: Invalid binding

Explanation: An application passed a binding handle to the RPC runtime that is invalid (for example, because it specifies an unsupported protocol).

Action: This error is frequently caused by an application passing a bad pointer (for example, to random memory or to a binding that was freed) to an RPC runtime routine that takes a binding handle input parameter. If this is the case, the application should be fixed.

0x16c9a02e rpc_s_invalid_call_opt

Severity: Varies **Component:** rpc

Text: Invalid call option

Explanation: A call was attempted that is not supported by the underlying RPC protocol. For example, calls to procedures marked [**broadcast**] are not supported by all RPC protocols.

Action: Change the application to make only supported calls.

0x16c9a0e1 rpc_s_invalid_checksum

Severity: Varies **Component:** rpc

Text: Received packet has an invalid checksum

Explanation: The checksum on the received packet was invalid. This indicates that a packet was modified in transit.

Action: This may indicate an attempt to violate security.

0x16c9a0fa rpc_s_invalid_crc

Severity: Varies **Component:** rpc

Text: Received packet has an invalid CRC

Explanation: A packet with an invalid cyclic redundancy check was received.

Action: This may be an attempt to violate system security.

0x16c9a0e2 rpc_s_invalid_credentials

Severity: Varies **Component:** rpc

Text: Credentials invalid

Explanation: The security credentials are not valid. Some security exchange has failed.

Action: Check your security server and also make sure that you have logged in properly.

0x16c9a04e rpc_s_invalid_endpoint_format

Severity: Varies **Component:** rpc

Text: Invalid endpoint format for remote host

Explanation: An endpoint string with invalid syntax was supplied as input to the RPC runtime.

Action: Use valid endpoint string syntax.

0x16c9a0a1 **rpc_s_invalid_inquiry_context**

Severity: Varies **Component:** rpc

Text: Invalid inquiry context

Explanation: An invalid inquiry context was passed to a begin, next, or done operation.

Action: Verify that the inquiry context is non-null and was successfully created in a begin operation.

0x16c9a0a9 **rpc_s_invalid_inquiry_type**

Severity: Varies **Component:** rpc

Text: Invalid inquiry type

Explanation: The application program attempted to perform a lookup in either a profile or an endpoint map using an unsupported lookup key.

Action: Make sure that the **inquiry_type** argument passed to **rpc_ns_profile_elt_inq_begin** or **rpc_mgmt_ep_elt_inq_begin** is within the set of supported values.

0x16c9a02a **rpc_s_invalid_naf_id**

Severity: Varies **Component:** rpc

Text: Invalid network address family ID

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a096 **rpc_s_invalid_name_syntax**

Severity: Varies **Component:** rpc

Text: Invalid name syntax

Explanation: An invalid value was specified for the entry name syntax.

Action: Check the value provided and use one of the API defined constants **rpc_c_ns_syntax_***.

0x16c9a0d9 **rpc_s_invalid_ns_handle**

Severity: Varies **Component:** rpc

Text: Invalid name service handle

Explanation: An invalid name service handle was passed to a begin, next, or done operation.

Action: Verify that the name service handle is non-null and was successfully created in a begin operation.

0x16c9a03a **rpc_s_invalid_object**

Severity: Varies **Component:** rpc

Text: Invalid object

Explanation: An application specified an illegal UUID value or specified a value that was not a valid UUID.

Action: Verify that the provided value is a UUID and that the called routine allows that value. Some routines do not allow a nil UUID.

0x16c9a0b6 **rpc_s_invalid_priority**

Severity: Varies **Component:** rpc

Text: Invalid priority

Explanation: The server or management application attempted to add a profile element at an invalid priority.

Action: Modify the application code to use a valid priority value.

0x16c9a020 **rpc_s_invalid_rpc_protseq**

Severity: Varies **Component:** rpc

Text: Invalid RPC protocol sequence

Explanation: An application specified an RPC protocol sequence that is not recognized by the RPC runtime.

Action: Specify only valid RPC protocol sequences.

0x16c9a040 **rpc_s_invalid_string_binding**

Severity: Varies **Component:** rpc

Text: Invalid string binding

Explanation: An application presented a string binding as input to the RPC runtime and the string binding has invalid syntax.

Action: Use the correct string binding syntax.

0x16c9a028 **rpc_s_invalid_timeout**

Severity: Varies **Component:** rpc

Text: Invalid timeout

Explanation: An application specified an invalid timeout value to **rpc_mgmt_set_com_timeout**.

Action: Supply a valid timeout value.

0x16c9a0bd **rpc_s_invalid_vers_option**

Severity: Varies **Component:** rpc

Text: Invalid interface version option

Explanation: The specified **vers_option** argument value was invalid.

Action: Check the value provided and use one of the API defined constants **rpc_c_vers_***.

0x16c9a02b **rpc_s_inval_net_addr**

Severity: Varies **Component:** rpc

Text: Invalid network address

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0fc **rpc_s_key_func_not_allowed**

Severity: Varies **Component:** rpc

Text: Key function not allowed when default authentication service specified

Explanation: A server application called **rpc_server_register_auth_info** with the default authentication service as input but also supplied a non-null key acquisition function as input.

Action: Specify either a nondefault authentication function or a **NULL** key function.

0x16c9a0e5 rpc_s_key_id_not_found

Severity: Varies **Component:** rpc

Text: Key ID in packet unknown

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a04b rpc_s_loc_connect_aborted

Severity: Varies **Component:** rpc

Text: Connection aborted by local host

Explanation: The client's attempt to connect to the server was aborted by the local system.

Action: Check network and system resource availability. Retry operation.

0x16c9a06e rpc_s_manager_not_entered

Severity: Varies **Component:** rpc

Text: Manager not entered

Explanation: An internal status code.

Action: None required.

0x16c9a0c8 rpc_s_max_calls_too_small

Severity: Varies **Component:** rpc

Text: Max calls (threads) too small

Explanation: A server application passed too small a value as the **max_calls_exec** input parameter to **rpc_server_listen**.

Action: Pass a large enough value for parameter **max_calls_exec**.

0x16c9a026 rpc_s_max_descs_exceeded

Severity: Varies **Component:** rpc

Text: Max descriptors exceeded

Explanation: An application caused the RPC runtime to use more file descriptors (for communications sockets) than the runtime is able to store internally.

Action: The RPC runtime's use of file descriptors can be reduced by making fewer remote calls in parallel, or by calling **rpc_server_use_protseq**, or one of its variants, fewer times.

0x16c9a0bf rpc_s_mbr_picked

Severity: Varies **Component:** rpc

Text: Member picked

Explanation: An internal status code.

Action: Report the error to your vendor.

0x16c9a119 rpc_s_mgmt_bad_type

Severity: Varies **Component:** rpc

Text: Unsupported attribute type was given to NSI

Explanation: One of the **rpc_ns_mgmt_*** routines was given an invalid name service (NSI) attribute type. The attribute should be one of the pre-architected types.

Action: Fix the program to pass a valid NSI attribute type.

0x16c9a06d rpc_s_mgmt_op_disallowed

Severity: Varies **Component:** rpc

Text: Management operation disallowed

Explanation: A client application called one of the local or remote management RPC runtime functions and the remote server refused to execute it.

Action: None required.

0x16c9a093 rpc_s_name_service_unavailable

Severity: Varies **Component:** rpc

Text: Name service unavailable

Explanation: A name service (NSI) operation was unable to communicate with the name service server, for example, the CDS server.

Action: Verify that the name service server is running.

0x16c9a043 rpc_s_network_unreachable

Severity: Varies **Component:** rpc

Text: Network is unreachable

Explanation: The server is not reachable from the client.

Action: Check the network connection between the server and client systems. Then retry the operation.

0x16c9a05a rpc_s_no_addrs

Severity: Varies **Component:** rpc

Text: No addresses

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a025 rpc_s_no_bindings

Severity: Varies **Component:** rpc

Text: No bindings

Explanation: An application passed an empty or null binding vector as input to the RPC runtime or requested a binding vector to be returned by the RPC runtime, but no bindings exist.

Action: In the first case, change the application to pass a valid binding vector. The second case may not indicate an error condition.

0x16c9a0c1 rpc_s_no_entry_name

Severity: Varies **Component:** rpc

Text: No entry name

Explanation: The binding handle does not refer to a name service entry name. Binding handles returned from the import and lookup operations refer to the name of the name service entry where the binding information was found. Binding handles obtained from other sources (for example, from a string binding), do not refer to an entry name.

Action: If a binding handle returned by the import or lookup operation does not refer to an entry name, report to your vendor.

0x16c9a0c4 rpc_s_no_env_setup

Severity: Varies **Component:** rpc

Text: Name service environment variable not defined

Explanation: A **NULL** entry name was specified in the import or lookup begin operations and the **RPC_DEFAULT_ENTRY** environment variable was not defined.

Action: Either define the **RPC_DEFAULT_ENTRY** environment variable or specify a non-null entry name in import or lookup begin.

0x16c9a02f rpc_s_no_fault

Severity: Varies **Component:** rpc

Text: No fault

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a027 rpc_s_no_interfaces

Severity: Varies **Component:** rpc

Text: No interfaces

Explanation: An application requested a list of the network interfaces registered by a server but no interfaces were registered.

Action: Check that a server instance exporting the desired interfaces is running.

0x16c9a0b1 rpc_s_no_interfaces_exported

Severity: Varies **Component:** rpc

Text: No interfaces exported

Explanation: No interfaces were exported to the specified name service entry. This status code is returned by `rpc_ns_mgmt_entry_inq_if_ids`.

Action: None required.

0x16c9a012 `rpc_s_no_memory`

Severity: Varies **Component:** rpc

Text: No memory for RPC runtime

Explanation: The RPC runtime was unable to allocate heap storage, or a fixed buffer supplied to IDL Encoding Services was not large enough.

Action: If the failure is caused by overuse of the underlying system resources (for example, address space or swap space), reduce the application's direct use of these resources if possible, or use a larger buffer when calling IDL Encoding Services.

0x16c9a102 `rpc_s_no_mepv`

Severity: Varies **Component:** rpc

Text: No manager EPV available

Explanation: The `rpc_server_register_if` routine was called specifying the default manager entry point vector (EPV), but no manager EPV exists (the server stub was generated using `-no_mepv`).

Action: Regenerate the server stub without specifying `-no_mepv` or provide a manager EPV.

0x16c9a0b5 `rpc_s_no_more_bindings`

Severity: Varies **Component:** rpc

Text: No more bindings

Explanation: A client or management application performing a lookup operation on a name service entry exhausted the list of compatible bindings that were exported.

Action: None required.

0x16c9a0a7 `rpc_s_no_more_elements`

Severity: Varies **Component:** rpc

Text: No more profile elements

Explanation: No more profile elements are found in the profile lookup. This is usually not reported through the API.

Action: Report the error to your vendor.

0x16c9a097 rpc_s_no_more_members

Severity: Varies **Component:** rpc

Text: No more members

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0a8 rpc_s_no_ns_permission

Severity: Varies **Component:** rpc

Text: No permission for name service operation

Explanation: The application program attempted to perform a name service operation that required permissions which the process did not possess.

Action: Make sure that the application has the requisite name service permission and retry the operation.

0x16c9a023 rpc_s_no_protseqs

Severity: Varies **Component:** rpc

Text: No protocol sequences

Explanation: An application requested a list of the protocol sequences supported by the RPC runtime, but none are supported.

Action: This may be an internal error. Report the error to your vendor.

0x16c9a024 rpc_s_no_protseqs_registered

Severity: Varies **Component:** rpc

Text: No protocol sequences registered

Explanation: A server application called **rpc_server_listen** but did not previously call **rpc_server_use_protseq** or one of its variants.

Action: Fix the application to call **rpc_server_use_protseq** or one of its variants.

0x16c9a047 rpc_s_no_rem_endpoint

Severity: Varies **Component:** rpc

Text: Endpoint does not exist at remote host

Explanation: No process was found at the specified endpoint.

Action: Check the network connection and then retry the operation.

0x16c9a171 rpc_s_no_server_stub

Severity: Varies **Component:** rpc

Text: Server stub not linked into application

Explanation: A client stub or client application routine invoked a function which causes the client to be set up as a server of a particular IDL interface, but the server stub module for the IDL interface was not linked into the application.

Action: Relink the application, including the relevant server stub module.

0x16c9a0c0 rpc_s_not_all_objs_unexported

Severity: Varies **Component:** rpc

Text: Not all objects unexported

Explanation: One or more of the object UUIDs specified for unexport were not found in the specified name service entry and therefore could not be removed.

Action: Verify that your application is unexporting the object UUIDs that were previously exported.

0x16c9a09c rpc_s_not_found

Severity: Varies **Component:** rpc

Text: Not found

Explanation: The specified name service entry was not found in the name service database. This entry could have been specified directly or indirectly through a profile or group.

Action: Report the error to your vendor.

0x16c9a0bb rpc_s_nothing_to_export

Severity: Varies **Component:** rpc

Text: Nothing to export

Explanation: The exporting application failed to provide an interface specification or a binding vector, and the object UUID vector is **NULL** (or empty).

Action: To export binding information, provide an interface specification and a binding vector. To export objects, provide an object UUID vector. To export binding information and objects, provide an interface specification, binding vector, and object UUID vector.

0x16c9a0bc rpc_s_nothing_to_unexport

Severity: Varies **Component:** rpc

Text: Nothing to unexport

Explanation: The server or management application attempted to unexport binding information for an interface ID that is not present in the target entry or to unexport object UUIDs that are not present.

Action: None required.

0x16c9a109 rpc_s_not_in_kernel

Severity: Varies **Component:** rpc

Text: Feature not supported in kernel

Explanation: A kernel application attempted to use a feature that is not supported in the kernel.

Action: Modify your application to avoid using that feature.

0x16c9a10f rpc_s_not_listening

Severity: Varies **Component:** rpc

Text: Listener thread is not running

Explanation: A request has been made through the **rpc_mgmt_stop_server_listening** call to stop the listener thread but the listener thread is not running.

Action: Depending upon what the caller of **rpc_mgmt_stop_server_listening** expected, this may be expected behavior or it may indicate an application program logic error. Recheck the program logic.

0x16c9a0b7 rpc_s_not_rpc_entry

Severity: Varies **Component:** rpc

Text: Not an RPC entry

Explanation: An internal status code.

Action: None required.

0x16c9a069 rpc_s_not_rpc_tower

Severity: Varies **Component:** rpc

Text: Not an RPC tower

Explanation: An internal status code. The protocol tower from the name service is not an RPC tower.

Action: Report the error to your vendor.

0x16c9a064 rpc_s_not_supported

Severity: Varies **Component:** rpc

Text: Not supported

Explanation: The requested operation is not supported by the RPC runtime. In the case of **rpc_mgmt_set_server_stack_size**, the underlying thread package does not support setting the stack size.

Action: Do not use the operation.

0x16c9a01b rpc_s_object_not_found

Severity: Varies **Component:** rpc

Text: Object not found

Explanation: Information was requested (for example, through **rpc_object_inq_type**) about an object that is unknown to the RPC runtime.

Action: Call **rpc_object_set_type** or **rpc_object_set_inq_fn** if appropriate.

0x16c9a001 rpc_s_op_rng_error

Severity: Varies **Component:** rpc

Text: Operation out of range

Explanation: A client called the n'th (zero-based) operation in an interface but the server supports fewer than n-1 operations from the interface.

Action: Modify the server to support the addition operations or arrange for the client to find a server that supports the requested operation.

0x16c9a117 rpc_s_partial_credentials

Severity: Varies **Component:** rpc

Text: Credentials have been fragmented

Explanation: The client's credentials were too large to fit in a single datagram packet. The client fragments them, and is returning only one fragment at this time.

Action: The server must use the **conv_who_are_you_auth_more** call to retrieve the remaining fragments of the client's credentials.

0x16c9a0c3 rpc_s_partial_results

Severity: Varies **Component:** rpc

Text: Partial results

Explanation: A name service entry was found to exist for a portion of the specified entry name. This status indicates that the resolved and unresolved portions of the name are returned as output arguments.

Action: If the name should be fully resolved, use the RPC control program to verify that a name service entry of the full name exists. If the entry exists, report the problem to your vendor.

0x16c9a0c2 rpc_s_priority_group_done

Severity: Varies **Component:** rpc

Text: Priority group done

Explanation: An internal status code.

Action: Report the error to your vendor.

0x16c9a0aa rpc_s_profile_element_not_found

Severity: Varies **Component:** rpc

Text: Profile element not found

Explanation: The server or management application called **rpc_ns_profile_elt_remove** specifying a profile member name that was not found in the name service database.

Action: Use the RPC control program to see if the profile element exists. If it does not, correct the application. If the profile element does exist in the name service database, report the problem to the vendor.

0x16c9a0ab rpc_s_profile_element_replaced

Severity: Varies **Component:** rpc

Text: Profile element replaced

Explanation: The profile element that the server or management application is adding already exists in the name service database. The old element was replaced.

Action: None required.

0x16c9a101 rpc_s_protect_level_mismatch

Severity: Varies **Component:** rpc

Text: Protection level changed unexpectedly

Explanation: The runtime detected an unexpected change to the protection level.

Action: This usually does not happen. Check for version skew between client and server, bugs in the client or server runtime, or modifications to packets sent over the network.

0x16c9a03e rpc_s_protocol_error

Severity: Varies **Component:** rpc

Text: Protocol error

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0ff rpc_s_proto_unsupp_by_auth

Severity: Varies **Component:** rpc

Text: RPC protocol not supported by this authentication protocol

Explanation: An application attempted to use a combination of authentication and RPC protocols that do not work together.

Action: Use RPC and authentication protocols that do work together.

0x16c9a05d rpc_s_protseq_not_supported

Severity: Varies **Component:** rpc

Text: Protocol sequence not supported

Explanation: An application specified an RPC protocol sequence that is recognized but is not supported by the RPC runtime.

Action: Specify only RPC protocol sequences supported by your vendor.

0x16c9a04d rpc_s_rem_host_crashed

Severity: Varies **Component:** rpc

Text: Remote host crashed

Explanation: The remote system crashed.

Action: Restart the remote host system and retry the operation.

0x16c9a048 rpc_s_rem_host_down

Severity: Varies **Component:** rpc

Text: Remote host is down

Explanation: The remote system is down.

Action: Retry the operation when the remote system is available or select a different system.

0x16c9a045 rpc_s_rem_network_shutdown

Severity: Varies **Component:** rpc

Text: Network is down

Explanation: The network connection has been shutdown. This could have been initiated by the client, server, or management application.

Action: Check the network connection and then restart the server or client.

0x16c9a017 rpc_s_rpcd_comm_failure

Severity: Varies **Component:** rpc

Text: RPC daemon communications failure

Explanation: The RPC runtime detected a failure while trying to communicate with the RPC daemon.

Action: Use the RPC control program to verify that the RPC daemon is running.

0x16c9a072 rpc_s_rpc_prot_version_mismatch

Severity: Varies **Component:** rpc

Text: RPC protocol version mismatch

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a070 rpc_s_server_too_busy

Severity: Varies **Component:** rpc

Text: Server too busy

Explanation: Client requests are coming in faster than they can be executed by the server and the server's call queue reached the maximum allowed.

Action: A client can retry the operation with a different server or wait a period of time and retry when the current sever is less busy. Otherwise, the server can be modified to increase the number of concurrent calls that can be executed by providing a larger **max_calls_exec** argument value when calling **rpc_server_listen**.

0x16c9a054 rpc_s_sm_invalid_state

Severity: Varies **Component:** rpc

Text: Invalid state machine state

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0df rpc_s_socket_failure

Severity: Varies **Component:** rpc

Text: Persistent errors on socket

Explanation: The RPC runtime encountered repeated errors using a communication socket.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a110 rpc_s_ss_bad_buffer

Severity: Varies **Component:** rpc

Text: Buffer not usable by IDL Encoding Services

Explanation: A buffer handed to the IDL Encoding Services was not 8-byte aligned or was not a multiple of 8 bytes.

Action: Modify the application code so that the buffer is aligned on an 8-byte boundary and is a multiple of 8 bytes long.

0x16c9a111 rpc_s_ss_bad_es_action

Severity: Varies **Component:** rpc

Text: Action cannot be performed by IDL Encoding Services

Explanation: Either the action requested in the handle being used was inconsistent with what was specified in the attribute configuration file (ACF), or **idl_es_inq_encoding_id** was called with an encoding handle that has not yet been used for any operation.

Action: In the first case, recompile the stubs using a modified ACF. In the second case modify the application code so that it does not make this call.

0x16c9a0db rpc_s_ss_char_trans_open_fail

Severity: Varies **Component:** rpc

Text: Could not open file containing ASCII/EBCDIC translation tables

Explanation: The file named in the environment variable **DCERPCCHARTRANS** is not accessible or does not exist.

Action: Either make the named file available, or unset **DCERPCCHARTRANS** and use the default ASCII/EBCDIC translation tables.

0x16c9a0dc rpc_s_ss_char_trans_short_file

Severity: Varies **Component:** rpc

Text: File containing ASCII/EBCDIC translation tables is damaged

Explanation: The file named in the environment variable **DCERPCCHARTRANS** contains less than 512 bytes.

Action: Either make a valid file available, or unset **DCERPCCHARTRANS** and use the default ASCII/EBCDIC translation tables.

0x16c9a125 rpc_s_ss_cleanup_failed

Severity: Varies **Component:** rpc

Text: Cleanup failed within an evaluation routine.

Explanation: A cleanup function was called from **rpc_ns_binding_lookup_done**, and its return status was other than **rpc_s_ok**.

Action: Application dependent.

0x16c9a16f rpc_s_ss_codeset_conv_error

Severity: Varies **Component:** rpc

Text: codeset conversion error

Explanation: A server stub or application manager routine received an error status back from a codeset conversion routine.

Action: There is invalid data being converted or the user supplied conversion routine needs to be fixed.

0x16c9a0dd rpc_s_ss_context_damaged

Severity: Varies **Component:** rpc

Text: A client side context handle has been incorrectly modified

Explanation: The client-side representation of a context handle was changed while a remote procedure call was in progress.

Action: Make sure there is no client-side thread, running concurrently with the remote procedure call, that modifies the context handle during the remote call's execution.

0x16c9a11c rpc_s_ss_iconv_error

Severity: Varies **Component:** rpc

Text: iconv failed other than conversion operation

Explanation: An **iconv** conversion routine failed when **conv_close** was called, or when **iconvsize** (HP specific) was called.

Action: Report the error to your vendor.

0x16c9a114 rpc_s_ss_incompatible_codesets

Severity: Varies **Component:** rpc

Text: Conversion between codesets not possible

Explanation: This status is used by International Character codeset conversion routines to indicate that conversion between the network and local codesets is not possible.

Action: Application dependent.

0x16c9a0de rpc_s_ss_in_null_context

Severity: Varies **Component:** rpc

Text: Null value of [in] context handle or all [in,out] context handles

Explanation: If an operation has [**in**] or [**in,out**] context handle parameters, the binding for that operation is determined using those parameters. A null context handle does not refer to valid binding information.

Action: Make sure that all [**in**] context handles are non-null. If the operation has [**in,out**] context handle parameters but no [**in**] context handles, make sure that at least one of the [**in,out**] context handles is non-null.

0x16c9a11a rpc_s_ss_invalid_char_input

Severity: Varies **Component:** rpc

Text: Invalid character input for conversion

Explanation: `iconv` or an XPG4 multibyte conversion routine detected invalid character input, for example, multibyte input or lock-shift sequence that spans the input buffer boundary, or an input character not in the set of characters being converted from.

Action: Application dependent.

0x16c9a118 `rpc_s_ss_invalid_codeset_tag`

Severity: Varies **Component:** `rpc`

Text: I18N tags structure is not valid

Explanation: The `rpc_cs_get_tags` routine found that the extended binding handle for I18N operation was broken.

Action: If the `rpc_cs_get_tags` routine is called directly from a user program, the user program probably modified the binding handle incorrectly. In this case, the user must write his own `get_tags` routine. If the user program uses the default RPC runtime I18N functionality, report the error to your vendor.

0x16c9a11e `rpc_s_ss_no_compat_charsets`

Severity: Varies **Component:** `rpc`

Text: Character sets are not compatible

Explanation: The code set evaluation routine examines character set compatibility before it checks code set compatibility, because connecting different languages, English and Chinese, for example, could result in massive data loss. The evaluation routine detected that the server and client do not share the same language.

Action: Application dependent.

0x16c9a11d `rpc_s_ss_no_compat_codeset`

Severity: Varies **Component:** `rpc`

Text: No compatible code set found

Explanation: Code set compatibility evaluation does not fall back to the universal encoding when `rpc_cs_eval_without_universal` is called. This status code indicates that `rpc_cs_eval_without_universal` was called when the server and client did not have a common encoding that both could recognize and convert.

Action: Application dependent.

0x16c9a073 rpc_s_ss_no_import_cursor

Severity: Varies **Component:** rpc

Text: No import cursor

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a11b rpc_s_ss_short_conv_buffer

Severity: Varies **Component:** rpc

Text: No room to place the converted characters

Explanation: An **iconv** conversion routine detected that there was no room left in the output buffer to place the converted characters.

Action: Application dependent.

0x16c9a112 rpc_s_ss_wrong_es_version

Severity: Varies **Component:** rpc

Text: Wrong version of IDL Encoding Services

Explanation: The decoding operation was inconsistent with the version of software used to create the encoding.

Action: Upgrade the installed version of DCE to one that supports the version of IDL Encoding Services specified in the encoded data.

0x16c9a103 rpc_s_stub_protocol_error

Severity: Varies **Component:** rpc

Text: Stub or runtime protocol error

Explanation: An internal stub or runtime error occurred.

Action: Report the error to your vendor.

0x16c9a046 rpc_s_too_many_rem_connects

Severity: Varies **Component:** rpc

Text: Too many connections at remote host

Explanation: The client could not establish a connection with the server because there are too many open connections at the remote server system.

Action: Retry the operation at a different server or when the current server's load decreases.

0x16c9a057 rpc_s_tsyntaxes_unsupported

Severity: Varies **Component:** rpc

Text: Transfer syntaxes unsupported

Explanation: An internal error occurred. The proposed transfer syntax is not supported by the server.

Action: Report the error to your vendor.

0x16c9a115 rpc_s_tx_not_in_transaction

Severity: Varies **Component:** rpc

Text: Transaction not started before operation

Explanation: A transactional RPC call was attempted on an operation that specified the [**transaction_mandatory**] attribute and the application program was not in a transaction.

Action: Either start a transaction prior to making the call, or remove the [**transaction_mandatory**] attribute associated with the operation. The [**transaction_optional**] attribute can be specified for the operation.

0x16c9a116 rpc_s_tx_open_failed

Severity: Varies **Component:** rpc

Text: Transaction open failed at server

Explanation: A transactional RPC operation was called and the server had either not previously called **tx_open()** or the call to **tx_open()** by the transaction manager failed.

Action: In the case where resource managers are used that require the operating system process as the thread of control, the application program must call **tx_open()** at the RPC server prior to receiving an RPC call. In the case where all resource managers used support the DCE thread of control, the transaction manager will call **tx_open()**; the user must make sure that the call to **tx_open()** succeeds.

0x16c9a061 rpc_s_type_already_registered

Severity: Varies **Component:** rpc

Text: Type already registered

Explanation: A server application tried to register an interface and type (by means of **rpc_server_register_if**) that was previously registered.

Action: Remove the redundant registration or unregister before registering.

0x16c9a0d8 rpc_s_underspecified_name

Severity: Varies **Component:** rpc

Text: Name is underspecified

Explanation: The syntax of a specified entry name indicated a global name. However, the cell name portion does not resolve to a cell. For example, this status code would be returned if the cell name is **./././c=us/o=osf/ou=dce**, but the cell name portion of the specified entry name is **./././c=us** or **./././c=us/o=osf**.

Action: Provide the full cell name portion in the specified entry name.

0x16c9a011 rpc_s_unknown_authn_service

Severity: Varies **Component:** rpc

Text: Unknown authentication service

Explanation: A client specified an authentication service that is not supported by the RPC runtime.

Action: Change the client to use no authentication or one of the supported authentication services.

0x16c9a0da rpc_s_unknown_error

Severity: Varies **Component:** rpc

Text: Unidentified communications error in client stub

Explanation: A communications error detected by the client stub could not be mapped to an exception. Note that this status is only used as the status value of the **rpc_x_unknown_error** exception.

Action: This error should be reported to your vendor. All client communication errors should result in identifiable exceptions. However, as a workaround, the **rpc_x_unknown_error** exception can be handled as a client communications error.

0x16c9a02c **rpc_s_unknown_if**

Severity: Varies **Component:** rpc

Text: Unknown interface

Explanation: A client application tried to make a remote call using an interface that the server being called does not support. This condition also includes the binding specifying a server that does not support the RPC management service (the **rpc_mgmt_*** routines). This situation can occur if a DCE client is trying to make a **rpc_mgmt_*** call to a NCS V1.5.1 server, or the decoding operation specified to IDL Encoding Services is not in the interface specified in encoded data.

Action: The client may have bound to an inappropriate server. Rebind the client to another server, or modify the application code to use the correct decoding call.

0x16c9a0fe **rpc_s_unknown_ifspec_vers**

Severity: Varies **Component:** rpc

Text: Interface's version is unknown

Explanation: An application supplied an interface handle that referred to an interface that specified an unknown interface format version. (The interface format version specifies how the interface specification is laid out internally. Do not confuse it with the contents of the IDL version field in an interface definition.) Either the handle is invalid (it does not point to a interface) or there is a version skew between the IDL compiler and RPC runtime used by the application developer.

Action: Make sure the handle is valid and that correct versions of the IDL compiler and the RPC runtime are used.

0x16c9a050 **rpc_s_unknown_mgr_type**

Severity: Varies **Component:** rpc

Text: Unknown or unsupported manager type

Explanation: A client application tried to make a remote call using a binding handle whose associated object UUID has a type that is unsupported for the interface being used.

Action: Either the client bound to an inappropriate server (in which case it should rebind to another server) or there is an application error.

0x16c9a060 **rpc_s_unknown_reject**

Severity: Varies **Component:** rpc

Text: Unknown reject

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0fd **rpc_s_unknown_stub_rtl_if_vers**

Severity: Varies **Component:** rpc

Text: Interface's stub/runtime version is unknown

Explanation: An application supplied an interface handle that referred to an interface that specified an unknown stub or runtime interface version. Either the handle is invalid (did not point to an interface) or there is a version skew between the IDL compiler and the RPC runtime used by the application developer.

Action: Make sure the handle is valid and that correct versions of the IDL compiler and RPC runtime are used.

0x16c9a10d **rpc_s_unsupported_auth_subtype**

Severity: Varies **Component:** rpc

Text: Receiver cannot support authentication subtype

Explanation: The receiver cannot support the authentication subtype. The connection-oriented protocol supports more than one algorithm for computations performed during security processing. In this case the sender of a remote procedure call requested the receiver to use an algorithm that the receiver (the server system) does not support.

Action: This may be an attempt to violate system security.

0x16c9a0a6 **rpc_s_unsupported_name_syntax**

Severity: Varies **Component:** rpc

Text: Unsupported name syntax

Explanation: The value specified for the entry name syntax was valid, but not supported.

Action: Check the value provided and use one of the supported API defined constants `rpc_c_ns_syntax_*`.

0x16c9a0e0 rpc_s_unsupported_protect_level

Severity: Varies **Component:** rpc

Text: Requested protection level is not supported

Explanation: The value for the protection level supplied to `rpc_binding_set_auth_info` is unsupported.

Action: Change the application to use a supported value.

0x16c9a02d rpc_s_unsupported_type

Severity: Varies **Component:** rpc

Text: Unsupported type

Explanation: A client application tried to make a remote call using a binding handle whose associated object UUID has a type that is unsupported for the interface being used.

Action: Either the client established a binding with an inappropriate server (and the client should rebind to another server), or an application error exists.

0x16c9a05f rpc_s_who_are_you_failed

Severity: Varies **Component:** rpc

Text: Who are you failed

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a006 rpc_s_wrong_boot_time

Severity: Varies **Component:** rpc

Text: Wrong boot time

Explanation: A binding handle that is successfully used to make a remote procedure call using the `ncadg` RPC protocol will be bound to that server instance (identified

by remembering the server's boot (startup) time in the binding handle). An **ncadg** remote procedure call made to a different server instance than the one originally associated with the binding handle results in the remote procedure call failing with this status code. .sp An application may also see this status code returned from the **rpc_mgmt_ep_elt_inq_begin** routine. In this case, the endpoint map service rebooted during the lifetime of the inquiry context.

Action: For the case of a failed remote procedure call, the client can call **rpc_binding_reset** for communications with the new server instance to succeed. .sp For inquiring endpoint map elements, call **rpc_mgmt_ep_elt_inq_done** to delete the failed inquiry context. Next, restart the inquiry by calling **rpc_mgmt_ep_elt_inq_begin**.

0x16c9a065 rpc_s_wrong_kind_of_binding

Severity: Varies **Component:** rpc

Text: Wrong kind of binding

Explanation: An application specified a client (server) binding handle as input to an RPC runtime routine that expects a server (client) binding handle.

Action: Change the application to use the correct kind of binding handle.

0x16c9a10e rpc_s_wrong_pickle_type

Severity: Varies **Component:** rpc

Text: Wrong type of pickle passed to unpickling routine

Explanation: Pickles are typed with a UUID. Unpickling routines are specific to a single type of pickle. If an unpickling routine is passed a pickle containing the wrong type UUID it will return this status code.

Action: Use the correct pickling routine or the correct type of pickle.

0x17122eea rsdb_cell_mismatch

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Database cell name %s is not local cell name or alias

Explanation: The cell name found in the security database does not match the name of the local cell configured in dce_cf.db

Action: ensure that local dce_cf.db matches security database and that security database is well formed

0x17122ee9 rsdb_check_cell_failure

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to check local cell name

Explanation: Unable to verify local cell name vs. database cell name

Action: ensure that local dce_cf.db matches security database and that security database is well formed

0x17122ee3 rsdb_journal_cant_init_list

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Could not initialize journal list

Explanation: ?

Action: ?

0x17122ee4 rsdb_journal_cant_open

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to open registry journal file

Explanation: ?

Action: ?

0x17122ee1 rsdb_journal_create_fail

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Cannot create registry journal file

Explanation: ?

Action: ?

0x17122ee2 rsdb_journal_hdr_write_failed

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Cannot create to registry journal header

Explanation: ?

Action: ?

0x17122ee0 rsdb_journal_open

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Journal file already open

Explanation: ?

Action: ?

0x17122ee5 rsdb_login_cant_init_list

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Could not initialize login list

Explanation: ?

Action: ?

0x17122026 sec_acl_bad_acl_syntax

Severity: Varies **Component:** sec

Text: bad acl syntax

Explanation: Specified ACL is not valid at this ACL manager. This error can be returned if less than 1 ACL is specified on a replace operation, or if more than 1 is specified on a replace and the controlling ACL manager was only expecting 1.

Action: Fix application, or notify support personnel if you have no access to the application source.

0x17122021 sec_acl_bad_key

Severity: Varies **Component:** sec

Text: bad information in sec_acl_key

Explanation: Internal error.

Action: Notify support personnel.

0x17122032 sec_acl_bad_parameter

Severity: Varies **Component:** sec
Text: bad parameter for acl operation
Explanation: Internal error, should never occur.
Action: Notify support personnel.

0x17122037 sec_acl_bad_permset

Severity: Varies **Component:** sec
Text: permission set is not valid for this acl manager type
Explanation: One or more permissions not valid for this type of ACL.
Action: Ensure that permissions are specified correctly.

0x1712202c sec_acl_bind_error

Severity: Varies **Component:** sec
Text: binding error on acl operation
Explanation: A binding error occurred during the requested ACL operation.
Action: Ensure that the object was specified correctly and retry.

0x17122017 sec_acl_cant_allocate_memory

Severity: Varies **Component:** sec
Text: acl operation unable to allocate memory
Explanation: Cannot allocate memory for requested operation.
Action: Check available system swap space and increase if necessary.

0x17122031 sec_acl_duplicate_entry

Severity: Varies **Component:** sec
Text: duplicate acl entry
Explanation: Duplicate ACL entries are not allowed.
Action: Remove duplicate entry and retry the operation.

0x170830a1 SEC_ACL_EDIT_PAD1

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD1

Explanation: ?

Action: None required

0x170830a2 SEC_ACL_EDIT_PAD2

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD2

Explanation: ?

Action: None required

0x170830a3 SEC_ACL_EDIT_PAD3

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD3

Explanation: ?

Action: None required

0x170830a4 SEC_ACL_EDIT_PAD4

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD4

Explanation: ?

Action: None required

0x170830a5 SEC_ACL_EDIT_PAD5

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD5

Explanation: ?

Action: None required

0x170830a6 SEC_ACL_EDIT_PAD6

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD6

Explanation: ?

Action: None required

0x170830a7 SEC_ACL_EDIT_PAD7

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD7

Explanation: ?

Action: None required

0x170830a8 SEC_ACL_EDIT_PAD8

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD8

Explanation: ?

Action: None required

0x170830a9 SEC_ACL_EDIT_PAD9

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PAD9

Explanation: ?

Action: None required

0x170830aa SEC_ACL_EDIT_PADa

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PADa

Explanation: ?

Action: None required

0x170830ab SEC_ACL_EDIT_PADb

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PADb

Explanation: ?

Action: None required

0x170830ac SEC_ACL_EDIT_PADc

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PADc

Explanation: ?

Action: None required

0x170830ad SEC_ACL_EDIT_PADd

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PADd

Explanation: ?

Action: None required

0x170830ae SEC_ACL_EDIT_PADe

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PADe

Explanation: ?

Action: None required

0x170830af SEC_ACL_EDIT_PADf

Severity: Varies **Component:** sad

Text: SEC_ACL_EDIT_PADf

Explanation: ?

Action: None required

0x1712201e sec_acl_expected_group_obj

Severity: Varies **Component:** sec

Text: acl operation expected group_obj

Explanation: Object has an owning group but no group_obj entry in its ACL.

Action: Add a group_obj entry to the ACL, then retry the operation.

0x1712201d sec_acl_expected_user_obj

Severity: Varies **Component:** sec

Text: acl operation expected user_obj

Explanation: Object has an owner but no user_obj entry contained in its ACL.

Action: Add a user_obj entry to the ACL, then retry the operation.

0x1712202d sec_acl_invalid_acl_handle

Severity: Varies **Component:** sec

Text: invalid acl handle

Explanation: Internal error, should never occur.

Action: Notify DCE support personnel.

0x17122020 sec_acl_invalid_acl_type

Severity: Varies **Component:** sec

Text: acl type not valid

Explanation: Specified ACL type is out of the valid range for this type.

Action: Ensure that the specified ACL entry type is valid. If this error is encountered within the DCE base components, notify support personnel.

0x17122035 sec_acl_invalid_dfs_acl

Severity: Varies **Component:** sec

Text: not a valid DFS acl

Explanation: DFS ACL manager does not understand the specified ACL.

Action: Ensure that ACL is specified correctly and retry the operation.

0x17122028 sec_acl_invalid_entry_class

Severity: Varies **Component:** sec

Text: invalid acl entry class

Explanation: Obsolete.

Action: None required.

0x1712201c sec_acl_invalid_entry_name

Severity: Varies **Component:** sec

Text: invalid acl object name

Explanation: NULL or invalid entry name passed to sec_acl_bind() API.

Action: Ensure that client is specifying a valid name to sec_acl_bind(). If this error is encountered within the base DCE components, then notify support personnel.

0x1712201f sec_acl_invalid_entry_type

Severity: Varies **Component:** sec

Text: acl entry type not valid

Explanation: An ACL entry type was specified that the server does not understand. It is possible for this to occur if a client is attempting to pass new ACL entry types to an older server that cannot interpret them (eg: delegation ACL entry types).

Action: Ensure that ACL entries are of a type that the server can understand.

0x17122022 sec_acl_invalid_manager_type

Severity: Varies **Component:** sec

Text: acl manager type invalid

Explanation: Invalid ACL manager type specified.

Action: If this error is encountered in an application, then that app needs to be fixed to obtain the correct ACL manager type and specify that type. If this error is encountered within the DCE base components, then notify support personnel.

0x17122025 sec_acl_invalid_permission

Severity: Varies **Component:** sec

Text: permission not valid for this acl

Explanation: One or more specified permissions not valid for this ACL.

Action: Determine correct permissions and retry the operation.

0x17122018 sec_acl_invalid_site_name

Severity: Varies **Component:** sec

Text: invalid site name for acl operation

Explanation: The ACL operation specified an invalid site name.

Action: Retry operation with a valid site name.

0x1712202f sec_acl_mgr_file_open_error

Severity: Varies **Component:** sec

Text: acl manager file open error

Explanation: ACL manager unable to open database file on startup.

Action: Ensure that this software is installed correctly.

0x17122036 sec_acl_mgr_no_space

Severity: Varies **Component:** sec

Text: not enough space for this ACL at specified ACL manager

Explanation: ACL manager was not able to store the specified ACL.

Action: Ensure that there is adequate disk and swap space on the server system.

0x17122030 sec_acl_missing_required_entry

Severity: Varies **Component:** sec

Text: missing required acl entry

Explanation: ACL is missing an entry required by this ACL manager.

Action: Determine what entries are required for this type of object.

0x1712202a sec_acl_name_resolution_failed

Severity: Varies **Component:** sec

Text: name resolution failed on acl operation

Explanation: Name resolution failed on the requested ACL operation.

Action: Ensure that a valid object name was specified.

0x1712201b sec_acl_no_acl_found

Severity: Varies **Component:** sec

Text: no acl found

Explanation: Object found, but object has no ACL associated with it.

Action: Retry operation with object that has an ACL, or notify support personnel for the server in question if object should have an ACL.

0x17122027 sec_acl_no_owner

Severity: Varies **Component:** sec

Text: at least one control permission bit required on acl

Explanation: There must be at least one entry in the ACL that grants control over the ACL.

Action: Grant the control permission to at least one entry.

0x17122033 sec_acl_not_authorized

Severity: Varies **Component:** sec

Text: operation on acl not authorized

Explanation: Not authorized to perform the requested operation on this object.

Action: Identity with control rights to ACL should perform the operation.

0x17122016 sec_acl_not_implemented

Severity: Varies **Component:** sec

Text: acl operation not implemented

Explanation: Requested operation is not implemented in this version of DCE.

Action: Do not attempt this operation with this version of DCE.

0x1712202e sec_acl_no_update_sites

Severity: Varies **Component:** sec

Text: no update sites for this acl operation

Explanation: No update sites available for this ACL operation.

Action: Try again later, the update site may be currently unavailable.

0x1712201a sec_acl_object_not_found

Severity: Varies **Component:** sec

Text: acl object not found

Explanation: Specified ACL object was not found.

Action: Check to make sure the object was specified correctly.

0x17122023 sec_acl_read_only

Severity: Varies **Component:** sec

Text: acl operation is read only

Explanation: Unable to perform update operation on read only ACL data

Action: None required.

0x1712202b sec_acl_rpc_error

Severity: Varies **Component:** sec

Text: rpc error on acl operation

Explanation: An RPC error was returned during the ACL operation.

Action: Retry the operation.

0x17122034 sec_acl_server_bad_state

Severity: Varies **Component:** sec

Text: acl server state doesn't support operation

Explanation: Server is not in a state capable of performing the requested operation.

Action: Retry the operation. Notify system administrator if problem persists.

0x17122024 sec_acl_site_read_only

Severity: Varies **Component:** sec

Text: update acl operation not valid on a read only site

Explanation: Requested operation attempted at a read only site. This error should be trapped by the security ACL API and the operation should be resent to an update site automatically if one can be located.

Action: None required.

0x17122029 sec_acl_unable_to_authenticate

Severity: Varies **Component:** sec

Text: unable to authenticate on acl operation

Explanation: Attempt to authenticate to server controlling the object failed.

Action: Ensure that the client has valid DCE credentials.

0x17122019 sec_acl_unknown_manager_type

Severity: Varies **Component:** sec

Text: acl manager type not recognized

Explanation: Programming error, should not happen.

Action: Notify support personnel of the problem.

0x17122151 sec_attr_bad_acl_mgr_set

Severity: Varies **Component:** sec

Text: invalid acl_mgr_set specified

Explanation: Application specified an invalid acl manager set for this operation.

Action: Determine the correct acl manager set and retry the operation.

0x17122152 sec_attr_bad_acl_mgr_type

Severity: Varies **Component:** sec

Text: invalid acl manager type

Explanation: Application specified an invalid acl manager.

Action: Retry the operation with the appropriate acl manager type specified.

0x17122161 sec_attr_bad_bind_authn_svc

Severity: Varies **Component:** sec

Text: invalid authentication service specified in binding auth_info

Explanation: Application specified an invalid authentication service in the binding auth info for this operation.

Action: Retry the operation with correct authentication server specified.

0x17122162 sec_attr_bad_bind_authz_svc

Severity: Varies **Component:** sec

Text: invalid authorization service specified in binding auth_info

Explanation: Application specified an invalid authz_svc parameter in a request to the privilege server.

Action: Retry operation with correct authorization service specified.

0x17122153 sec_attr_bad_bind_info

Severity: Varies **Component:** sec

Text: invalid binding information

Explanation: Application specified invalid binding information in an attribute update operation.

Action: Determine correct binding information and retry operation.

0x17122160 sec_attr_bad_bind_prot_level

Severity: Varies **Component:** sec

Text: invalid protection level specified in binding auth_info

Explanation: Application specified an invalid protection level in the binding auth info.

Action: Retry operation with the correct protection level specified.

0x1712215f sec_attr_bad_bind_svr_name

Severity: Varies **Component:** sec

Text: invalid server name specified in binding auth_info

Explanation: Application specified an invalid server name in the binding auth info.

Action: Retry operation with correct binding auth info specified.

0x1712215a sec_attr_bad_comment

Severity: Varies **Component:** sec

Text: invalid comment text specified

Explanation: Attribute comment specified exceeds 1024 characters.

Action: Make comment conform to size restrictions and retry the operation.

0x17122163 sec_attr_bad_cursor

Severity: Varies **Component:** sec

Text: invalid cursor

Explanation: Application specified an invalid cursor.

Action: Specify a valid cursor and retry operation.

0x17122158 sec_attr_bad_encoding_type

Severity: Varies **Component:** sec

Text: invalid encoding type specified

Explanation: Attribute encoding type specified is invalid.

Action: Select a valid encoding type and retry operation.

0x1712215b sec_attr_bad_intercell_action

Severity: Varies **Component:** sec

Text: invalid intercell action specified

Explanation: Intercell action specified for an attribute must be one of: accept, reject or evaluate.

Action: Select the appropriate intercell action and retry the operation.

0x17122157 sec_attr_bad_name

Severity: Varies **Component:** sec

Text: invalid attribute name specified

Explanation: Attribute name specified is NULL or exceeds 1024 characters.

Action: Select an appropriate attribute name and retry the operation.

0x17122166 sec_attr_bad_object_type

Severity: Varies **Component:** sec

Text: operation not supported on this object type

Explanation: Application specified an acl manager type for this object that is not contained in the schema entry for this attribute.

Action: Retry operation with an acl manager type that is contained in the schema entry.

0x1712216d sec_attr_bad_param

Severity: Varies **Component:** sec

Text: bad parameter for schema or attribute operation

Explanation: Application specified a bad parameter for a schema or attribute operation.

Action: Verify the specified parameters and retry the operation.

0x17122154 sec_attr_bad_permset

Severity: Varies **Component:** sec

Text: invalid permission set

Explanation: Application specified one or more invalid permissions for this type of ACL.

Action: Ensure that permissions are specified correctly and retry the operation.

0x17122159 sec_attr_bad_scope

Severity: Varies **Component:** sec

Text: invalid scope specified

Explanation: Attribute scope specified exceeds 1024 characters.

Action: Select appropriate scope and retry the operation.

0x1712215c sec_attr_bad_trig_type

Severity: Varies **Component:** sec

Text: invalid trigger type specified

Explanation: Application specified a trigger type other than query in this operation. Only query triggers are supported in this release.

Action: If a query trigger can be used, retry the operation with the query trigger specified.

0x17122150 sec_attr_bad_type

Severity: Varies **Component:** sec

Text: invalid or unsupported attribute type

Explanation: Application performing a lookup using the specified attribute type was unsuccessful.

Action: Determine the correct attribute type and retry the operation.

0x1712215e sec_attr_bad_uniq_query_accept

Severity: Varies **Component:** sec

Text: invalid combination of unique_flag=true, query trigger, and intercell_action=accept

Explanation: If the unique flag is set to true, and a query trigger is used, the intercell action can not be set to accept.

Action: Retry the operation with the intercell action set to either reject or evaluate.

0x17122ebc sec_attr_cant_get_attrinst

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: failed to get next attr instance in seq list

Explanation: ?

Action: Log a defect.

0x17122eb9 sec_attr_cant_get_attrlist

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: unable to retrieve attr_list

Explanation: ?

Action: Log a defect.

0x17122ebb sec_attr_cant_get_instance

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: failed to get last attr in seq list

Explanation: ?

Action: Log a defect.

0x1712214f sec_attr_field_no_update

Severity: Varies **Component:** sec

Text: field not modifiable

Explanation: Application attempted to update a field that does not allow modification.

Action: Verify that the correct field was specified. If not, retry the operation with the correct field specified. If so, the update operation should not be attempted on this field.

0x17122148 sec_attr_inst_exists

Severity: Varies **Component:** sec

Text: attribute instance already exists

Explanation: Application specified a registry object that does not exist.

Action: Ensure that the object is specified correctly and that the caller is granted read access to the object.

0x17122144 sec_attr_inst_not_found

Severity: Varies **Component:** sec

Text: attribute instance not found

Explanation: Application specified an attribute instance that was not found.

Action: Specify the correct attribute, or make sure the attribute has been placed on the specified object and retry the operation.

0x17122173 sec_attr_multi_inst_disallowed

Severity: Varies **Component:** sec

Text: multi_instanced void attributes are disallowed.

Explanation: It is meaningless to have multi_instanced void attributes.

Action: None required.

0x17122170 sec_attr_multi_inst_no_update

Severity: Varies **Component:** sec

Text: can't update the multi_instanced flag from unset to set

Explanation: Schema multi instance flag cannot be unset.

Action: Add a new schema entry if multi instanced attributes are required.

0x1712214d sec_attr_name_exists

Severity: Varies **Component:** sec

Text: attribute name already exists

Explanation: Application attempted to add an attribute with a duplicate name to the registry.

Action: Retry operation with a unique attribute name.

0x17122155 sec_attr_no_memory

Severity: Varies **Component:** sec

Text: unable to allocate memory

Explanation: Unable to allocate memory.

Action: Check available system swap space and increase if necessary.

0x1712216c sec_attr_no_more_entries

Severity: Varies **Component:** sec

Text: no more entries (attribute instances or schema entries) found

Explanation: Application has exhausted the available attribute instance or schema entries.

Action: Application should handle this condition appropriately.

0x17122145 sec_attr_not_all_avail

Severity: Varies **Component:** sec

Text: warning: some of the requested attributes do not exist on the object

Explanation: Application requested attributes that do not exist on the specified object.

Action: This is a warning message - it is for informational purposes only.

0x17122164 sec_attr_not_implemented

Severity: Varies **Component:** sec

Text: this operation not implemented

Explanation: Application specified an operation that has not yet been implemented.

Action: The application must not make use of this operation.

0x17122167 sec_attr_not_multi_valued

Severity: Varies **Component:** sec

Text: this attribute type does not support multi-valued updates

Explanation: Application specified more than one attribute instance for a type that is not multi valued.

Action: Specify a single attribute instance for this type and retry the operation.

0x17122156 sec_attr_not_unique

Severity: Varies **Component:** sec

Text: attribute value is not unique

Explanation: Application specified a non-unique value for an attribute.

Action: Ensure that the attribute value is unique and retry the operation.

0x17122eba sec_attr_num_attr_Itzero

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: tried to decrement num_attrs below zero

Explanation: ?

Action: Log a defect.

0x17122172 sec_attr_qry_trig_bad_enc_type

Severity: Varies **Component:** sec

Text: updates of query trigger attributes must have encoding type void

Explanation: Attribute encoding type specified is invalid.

Action: Select a valid encoding type and retry operation.

0x17122147 sec_attr_rgy_obj_not_found

Severity: Varies **Component:** sec

Text: registry object not found

Explanation: Specified registry object was not found.

Action: Ensure that the object is specified correctly and that the caller is granted read access to the object.

0x17122edd sec_attr_schema_cant_lookup

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to lookup schema entry

Explanation: ?

Action: Log a defect.

0x17122edc sec_attr_schema_cant_reset

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to reset schema entry info

Explanation: ?

Action: Log a defect.

0x17122143 sec_attr_sch_entry_not_found

Severity: Varies **Component:** sec

Text: schema entry not found

Explanation: Application specified a schema entry that does not exist.

Action: Specify a valid schema entry and retry the operation.

0x1712216e sec_attr_sch_reserved

Severity: Varies **Component:** sec

Text: can't delete schema entry with reserved flag set

Explanation: Cannot delete schema entry with reserved flag set.

Action: None required

0x17122146 sec_attr_set_member_missing

Severity: Varies **Component:** sec

Text: warning: one or more members of the attribute set do not exist on the object

Explanation: Application requested an attribute set where one or more of the members do not exist on the object.

Action: This is a warning message - it is for informational purposes only.

0x1712214a sec_attr_svr_read_only

Severity: Varies **Component:** sec

Text: server is read only

Explanation: Application requested an update operation on a read only server.

Action: Retry update operation on the master server.

0x1712214b sec_attr_svr_unavailable

Severity: Varies **Component:** sec

Text: server is unavailable

Explanation: Application attempted to contact a server that is unavailable.

Action: Retry operation with another server or contact your DCE administrator to determine why the server is unavailable.

0x1712215d sec_attr_trig_bind_info_missing

Severity: Varies **Component:** sec

Text: trigger binding info must be specified

Explanation: Application specified a trigger without supplying binding info.

Action: Retry operation with trigger binding info specified.

0x17122165 sec_attr_trig_query_not_sup

Severity: Varies **Component:** sec

Text: query trigger not supported for this operation

Explanation: Application specified a query trigger for an operation that does not support query triggers.

Action: Retry operation without a query trigger specified.

0x1712214c sec_attr_trig_svr_unavailable

Severity: Varies **Component:** sec

Text: trigger server is unavailable

Explanation: Application specified a trigger server in this operation that is unavailable.

Action: Retry operation with another trigger server or contact your DCE administrator to determine why the trigger server is unavailable.

0x17122171 sec_attr_trig_types_no_update

Severity: Varies **Component:** sec

Text: can't update the trig_types flag

Explanation: Schema trigger types cannot be updated.

Action: None required.

0x1712214e sec_attr_type_id_exists

Severity: Varies **Component:** sec

Text: attribute type id already exists

Explanation: Application attempted to add an attribute with a duplicate id to the registry.

Action: Retry operation with a unique attribute id.

0x17122149 sec_attr_unauthorized

Severity: Varies **Component:** sec

Text: unauthorized to perform this operation

Explanation: The object's ACL denied the attempted operation.

Action: An identity that is granted the right to perform the requested operation must be used.

0x1712216f sec_attr_unique_no_update

Severity: Varies **Component:** sec

Text: can't update the unique flag from set to unset

Explanation: Schema unique flag cannot be unset.

Action: Add a new schema entry if non-unique attributes are required.

0x1712216b sec_attr_val_attr_set_bad

Severity: Varies **Component:** sec

Text: attribute value attr_set has bad format

Explanation: Application specified an improperly formatted attribute value set.

Action: Correct the format of the attribute value set and retry the operation.

0x1712216a sec_attr_val_bytes_bad

Severity: Varies **Component:** sec

Text: attribute value bytes/confidential_bytes/i18n_data has bad format

Explanation: Application specified improperly formatted bytes string.

Action: Correct the format of the bytes string and retry the operation.

0x17122168 sec_attr_val_printstring_bad

Severity: Varies **Component:** sec

Text: attribute value printstring has bad format

Explanation: Application specified a printstring value that exceeds 1024 characters.

Action: Retry operation with a printstring value that is 1024 or less.

0x17122169 sec_attr_val_string_array_bad

Severity: Varies **Component:** sec

Text: attribute value string array has bad format

Explanation: Application either specified an improperly formatted attribute value string array or one or more of the attribute value strings in the array exceed 1024 characters.

Action: Ensure that the string array is properly formed and that each of the attribute value strings are less than 1024 and retry the operation.

0x17122180 sec_authn_bad_cell_name

Severity: Varies **Component:** sec

Text: Cell name does not start with /.../

Explanation: All DCE cell names must start with /.../

Action: Correct the cell name found in dce_cf.db

0x1712217d sec_authn_s_bad_seal

Severity: Varies **Component:** sec

Text: integrity error: EPAC seal mismatch.

Explanation: Data corruption, or an attacker asserting credentials that don't match the credentials that were actually granted. If error is reproducible, then it's most likely a defect in DCE.

Action: Notify support personnel, if reproducible.

0x1712217b sec_authn_s_missing_epac

Severity: Varies **Component:** sec

Text: EPAC missing after authenticator

Explanation: Improperly formed RPC authentication protocol message, probably due to a defect in DCE.

Action: Notify support personnel.

0x1712217c sec_authn_s_no_seal

Severity: Varies **Component:** sec

Text: can't find appropriate seal for EPAC

Explanation: Improperly formed RPC authentication protocol message, probably due to a defect in DCE.

Action: Notify support personnel.

0x17122f60 sec_buf_too_small

Severity: Varies **Component:** sec

Text: Buffer too small

Explanation: The buffer size is smaller than the amount of data which needs to be copied into the buffer. This is an internal error.

Action: Log a defect.

0x17122dc8 sec_crdb_at_char_in_cellname

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cell name %s cannot contain the @ character

Explanation: ?

Action: ?

0x17122dd8 sec_crdb_cant_add_replica

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot add new replica to master registry\n%s

Explanation: ?

Action: ?

0x17122ddc sec_crdb_cant_bind_updsite

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot locate and bind to master registry\n%s

Explanation: ?

Action: ?

0x17122ddd sec_crdb_cant_com_master

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot communicate with master registry\n%s

Explanation: ?

Action: ?

0x17122dd3 sec_crdb_cant_create_celluid

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Problem creating cell uuid\n%s

Explanation: ?

Action: ?

0x17122dd2 sec_crdb_cant_get_hostname

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Unable to retrieve host name\n%s

Explanation: ?

Action: ?

0x17122dd5 sec_crdb_cant_get_host_prname

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Unable to retrieve host principal name\n%s

Explanation: ?

Action: ?

0x17122dd7 sec_crdb_cant_register_ns

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot register with nameservice\n%s

Explanation: ?

Action: ?

0x17122dd4 sec_crdb_cant_setup_rgycreator

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Problem setting up rgy_creator\n%s

Explanation: ?

Action: ?

0x17122dd9 sec_crdb_cant_upd_rgyst_file

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot update rgy_state file\n%s

Explanation: ?

Action: ?

0x17122dd1 sec_crdb_cl_alt_dir_no_arg

Severity: Warning **Component:** sec/sec_s_rs_create_db

Text: No argument for alt_dir option. Using default path : %s

Explanation: No argument was specified for alt_dir . Hence a default path was used.

Action: None required.

0x17122dc9 sec_crdb_cl_bad_name

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Illegal name %s

Explanation: The specified name is not a legal CDS name.

Action: Provide the correct name

0x17122dca sec_crdb_cl_dup_option

Severity: Error **Component:** sec/sec_s_rs_create_db

Text: Both the options %s and %s specified.

Explanation: Only one of the two options may be used.

Action: Specify only one but not both options for sec_create_db.

0x17122dcd sec_crdb_cl_long_passwd

Severity: Error **Component:** sec/sec_s_rs_create_db

Text: default_passwd too long.

Explanation: Password longer than the permitted maximum.

Action: ?

0x17122dcc sec_crdb_cl_long_rgyname

Severity: Error **Component:** sec/sec_s_rs_create_db

Text: Name specified with option %s longer than %d

Explanation: Registry name is longer than the permitted maximum.

Action: ?

0x17122dcb sec_crdb_cl_missing_arg

Severity: Error **Component:** sec/sec_s_rs_create_db

Text: Missing argument for %s option

Explanation: The specified option requires an argument which was not specified.

Action: Specify the missing argument for the given option.

0x17122dcf sec_crdb_cl_null_myname

Severity: Error **Component:** sec/sec_s_rs_create_db

Text: Missing myname

Explanation: The specified name is either NULL or a null string.

Action: Specify a non-NULL string for the option.

0x17122dce sec_crdb_cl_unknown_option

Severity: Error **Component:** sec/sec_s_rs_create_db

Text: Unknown command line option %s

Explanation: The specified option is not valid. Consult the manual page for the correct set of options.

Action: Run the command again with correct options.

0x17122dd0 sec_crdb_cl_usage

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: Usage: sec_create_db -master|-slave -my[name] my_server_name\n [-k[eyseed] keyseed] [-v[erbose]]\n [-cr[erator] creator_name -cu[nix_id] creator_unix_id\n -u[uid] cell_uuid -pe[rson_low_unix_id] p_unix_id\n -g[roup_low_unix_id] g_unix_id\n -o[rg_low_unix_id] o_unix_id -ma[x_unix_id] max_unix_id\n -k[eyseed] keyseed -pa[ssword] default_password -v[erbose]]

Explanation: ?

Action: ?

0x17122dc6 sec_crdb_cr_db_succ

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: Successfully created registry database

Explanation: This is an informational message

Action: None required.

0x17122dc4 sec_crdb_cr_master_db

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: Attempting to create master registry database for cell %s

Explanation: This is an informational message

Action: None required.

0x17122dc5 sec_crdb_cr_rep_db

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: Attempting to create a replica of registry database for cell %s

Explanation: This is an informational message

Action: None required.

0x17122dc7 sec_crdb_db_exists

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Registry database already exists

Explanation: Registry database could not be created because one exists already.

Action: Delete the registry database and run sec_create_db.

0x17122dd6 sec_crdb_db_not_created

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Failed to create new database\n%s

Explanation: ?

Action: ?

0x17122ddb sec_crdb_inherit_hostident_err

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot inherit local host identity\n%s

Explanation: ?

Action: ?

0x17122dda sec_crdb_rep_not_registered

Severity: Warning **Component:** sec/sec_s_rs_create_db

Text: Replica not registered with nameservice

Explanation: The security replica has not successfully registered with the nameservice

Action: ?

0x17122dc0 sec_crdb_site_file_create_fail

Severity: Warning **Component:** sec/sec_s_rs_create_db

Text: pe_site file not created

Explanation: The pe_site file could not be created or updated because of an error. The error is logged prior to this message.

Action: ?

0x17122dc1 sec_crdb_site_file_create_succ

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: pe_site file created

Explanation: The pe_site file has been successfully created. This is an informational message.

Action: None required.

0x17122dc3 sec_crdb_site_file_upd_fail

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: RPC string bindings not appended to pe_site file

Explanation: RPC bindings could not be appended to the pe_site file. The messages logged prior to this indicate why this might have happened.

Action: None required.

0x17122dc2 sec_crdb_site_file_upd_succ

Severity: Notice **Component:** sec/sec_s_rs_create_db

Text: RPC String bindings appended to pe_site file

Explanation: RPC bindings have been successfully appended to the pe_site file. This is an informational message.

Action: None required.

0x17122132 sec_cred_s_authz_cannot_comply

Severity: Varies **Component:** sec

Text: authz service cannot supply the requested credentials

Explanation: Application programming error. The server is asking for information that the authorization service used for the call cannot supply (eg, calling `sec_cred_get_initiator()` when the call had used `authz_name`).

Action: Fix application code. Check the authorization service used before attempting to extract credentials.

0x1712212f sec_cred_s_invalid_auth_handle

Severity: Varies **Component:** sec

Text: invalid credential handle

Explanation: Specified credential handle is invalid.

Action: This is most likely a programming error that needs to be fixed.

0x17122131 sec_cred_s_invalid_cursor

Severity: Varies **Component:** sec

Text: invalid credential cursor

Explanation: Specified credential cursor is invalid.

Action: This is most likely a programming error that needs to be fixed.

0x17122133 sec_cred_s_invalid_key

Severity: Varies **Component:** sec

Text: rock key is not valid

Explanation: rock key may not be initialized.

Action: None required.

0x17122130 sec_cred_s_invalid_pa_handle

Severity: Varies **Component:** sec

Text: invalid privilege attribute handle

Explanation: Specified privilege attribute handle is invalid.

Action: This is most likely a programming error that needs to be fixed.

0x17122134 sec_cred_s_key_not_found

Severity: Varies **Component:** sec

Text: rock key not found

Explanation: ?

Action: None required.

0x1712212e sec_cred_s_no_more_entries

Severity: Varies **Component:** sec

Text: no more entries available

Explanation: No more entries available (informational status code).

Action: Don't try to obtain any more entries.

0x17122135 sec_cred_s_no_more_key

Severity: Varies **Component:** sec

Text: the only allowed rock key has been used

Explanation: ?

Action: None required.

0x171220d5 sec_id_e_bad_cell_uuid

Severity: Varies **Component:** sec

Text: Cell UUID does not correspond to a valid cell name

Explanation: Specified cell UUID does not match any known cell names.

Action: Ensure that a known cell UUID is specified.

0x171220d6 sec_id_e_foreign_cell_referral

Severity: Varies **Component:** sec

Text: Global name yields a principal in foreign cell, use referral

Explanation: Global name yields a principal in foreign cell, use referral

Action: None required.

0x171220d4 sec_id_e_name_too_long

Severity: Varies **Component:** sec

Text: Name is too long for current implementation

Explanation: The specified name is too long for the current implementation.

Action: Ensure that a valid name is specified.

0x171220d7 sec_id_e_no_at_hack

Severity: Varies **Component:** sec

Text: cannot obtain uuids of name in princ@cell form.

Explanation: ?

Action: None required.

0x17122044 sec_key_mgmt_e_authn_invalid

Severity: Varies **Component:** sec

Text: The authentication service is invalid

Explanation: The specified authentication service is invalid for this operation.

Action: Ensure that a valid authentication service is specified.

0x17122045 sec_key_mgmt_e_auth_unavailable

Severity: Varies **Component:** sec

Text: The authentication service is unavailable

Explanation: Unable to contact the authentication service.

Action: Notify a system administrator.

0x1712204a sec_key_mgmt_e_keytab_not_found

Severity: Varies **Component:** sec

Text: Specified key table not found

Explanation: Unable to locate or open specified key table.

Action: Ensure that a valid key table is specified.

0x17122043 sec_key_mgmt_e_key_unavailable

Severity: Varies **Component:** sec

Text: Requested key is unavailable

Explanation: No key matching specified principal and key version found in keytable.

Action: Ensure that the specified keytable is set up correctly.

0x17122047 sec_key_mgmt_e_key_unsupported

Severity: Varies **Component:** sec

Text: A requested key type is not supported

Explanation: A key with a type unknown to this version of DCE was specified.

Action: Ensure that operation was specified correctly.

0x17122048 sec_key_mgmt_e_key_version_ex

Severity: Varies **Component:** sec

Text: Specified key already exists in key store

Explanation: Specified key already exists in the specified key table.

Action: None required.

0x1712204b sec_key_mgmt_e_ktfile_err

Severity: Varies **Component:** sec

Text: Specified file is not a valid key table

Explanation: File found, but format does not conform to that of a key table.

Action: Ensure that a valid key table is specified.

0x17122049 sec_key_mgmt_e_not_implemented

Severity: Varies **Component:** sec

Text: Operation Not Implemented

Explanation: Specified operation not implemented in this version of DCE.

Action: Do not attempt this operation with this version of DCE.

0x17122046 sec_key_mgmt_e_unauthorized

Severity: Varies **Component:** sec

Text: The caller is unauthorized to perform operation

Explanation: The caller is unauthorized to perform the requested operation.

Action: Determine which identities have rights to perform the operation.

0x17122cc4 sec_lksm_bad_input

Severity: Varies **Component:** sec

Text: Bad input. Try again

Explanation: The user supplied response to the question of whether a locksmith account should be created is not correct.

Action: None required.

0x17122cc5 sec_lksm_create_acct

Severity: Varies **Component:** sec

Text: Account for %s doesn't exist. Should this be created ?

Explanation: This will be followed by the message in sec_lksm_def_yes_prompt.

Action: None required.

0x17122cc3 sec_lksm_def_no_prompt

Severity: Varies **Component:** sec

Text: [y/n]? (n)

Explanation: If security server is started in the locksmith mode and no locksmith account exists, then the user is prompted asking whether the account should be created. This prompt is used when the default is to not to create the the locksmith account.

Action: None required.

0x17122cc2 sec_lksm_def_yes_prompt

Severity: Varies **Component:** sec

Text: [y/n]? (y)

Explanation: If security server is started in the locksmith mode and no locksmith account exists, then the user is prompted asking whether the account should be created. This prompt is used when the desired default is to create the locksmith account.

Action: None required.

0x17122ccf sec_lksm_passwd_prompt

Severity: Varies **Component:** sec

Text: Enter password for locksmith account:

Explanation: ?

Action: None required.

0x17122cd0 sec_lksm_passwd_verify

Severity: Varies **Component:** sec

Text: Reenter password to verify:

Explanation: ?

Action: None required.

0x17122ccb sec_lksm_set_acct_span

Severity: Varies **Component:** sec

Text: Setting policy account lifespan to %d minutes (or %d hours or %d days)\n

Explanation: ?

Action: None required.

0x17122cc9 sec_lksm_set_acct_valid

Severity: Varies **Component:** sec

Text: Setting account valid flag for %s account\n

Explanation: ?

Action: None required.

0x17122cc7 sec_lksm_set_client_valid

Severity: Varies **Component:** sec

Text: Setting account admin flag to allow %s account to be a client\n

Explanation: ?

Action: None required.

0x17122cca sec_lksm_set_date_now

Severity: Varies **Component:** sec

Text: Setting %s account good_since_date to now\n

Explanation: ?

Action: None required.

0x17122ccc sec_lksm_set_expire

Severity: Varies **Component:** sec

Text: Setting %s account to expire in %d minutes\n

Explanation: ?

Action: None required.

0x17122cce sec_lksm_set_polpwd_expire

Severity: Varies **Component:** sec

Text: Setting policy password lifetime to %d minutes\n

Explanation: ?

Action: None required.

0x17122ccd sec_lksm_set_polpwd_expire_now

Severity: Varies **Component:** sec

Text: Setting policy password expiration time to %d minutes from now\n

Explanation: ?

Action: None required.

0x17122cc6 sec_lksm_set_pwd_valid

Severity: Varies **Component:** sec

Text: Setting password valid flag for %s account\n

Explanation: Setting password valid flag for the specified account.

Action: None required.

0x17122cc8 sec_lksm_set_server_valid

Severity: Varies **Component:** sec

Text: Setting account admin flag to allow %s account to be a server\n

Explanation: ?

Action: None required.

0x17122ea3 sec_logent_out_of_bounds

Severity: Warning **Component:** sec/sec_s_rs_rsd

Text: Log entry out of bounds and so skipped

Explanation: ?

Action: None required.

0x171220f6 sec_login_s_acct_invalid

Severity: Varies **Component:** sec

Text: account not valid for login

Explanation: Attempted to login to an account that is currently disabled.

Action: Have an administrator enable the account for login.

0x171220ef sec_login_s_already_valid

Severity: Varies **Component:** sec

Text: login context has already been validated

Explanation: Attempted to validate an already valid login context.

Action: Don't attempt to validate an already valid login context.

0x171220e9 sec_login_s_auth_local

Severity: Varies **Component:** sec

Text: Operation not valid on local context

Explanation: ?

Action: None required.

0x17122100 sec_login_s_compound_delegate

Severity: Varies **Component:** sec

Text: Login context already specifies a delegation chain.

Explanation: Attempted to call become_initiator with a login context that already contained a delegation chain.

Action: Do not attempt to become an initiator if already a delegate.

0x171220f3 sec_login_s_config

Severity: Varies **Component:** sec

Text: host configuration info not available

Explanation: ?

Action: None required.

0x171220eb sec_login_s_context_invalid

Severity: Varies **Component:** sec

Text: Context has not been validated

Explanation: Attempted to use a not-yet-validated login context for an operation that requires a validated context.

Action: This is most likely a programming error that needs to be fixed.

0x171220f0 sec_login_s_default_use

Severity: Varies **Component:** sec

Text: illegal use of default sec login handle

Explanation: ?

Action: None required.

0x17122102 sec_login_s_deleg_not_enabled

Severity: Varies **Component:** sec

Text: Delegation has not been enabled.

Explanation: Delegation/impersonation attempted, but initiator did not enable it.

Action: Server must not use delegation/impersonation, or initiator must enable it.

0x171220ed sec_login_s_groupset_invalid

Severity: Varies **Component:** sec

Text: Groupset not valid

Explanation: ?

Action: None required.

0x171220ea sec_login_s_handle_invalid

Severity: Varies **Component:** sec

Text: Context handle not valid

Explanation: Specified login handle does not correspond to a login context.

Action: This is most likely a programming error that needs to be fixed.

0x171220fe sec_login_s_incomplete_ovrd_ent

Severity: Varies **Component:** sec

Text: Incomplete override entry, cannot proceed.

Explanation: Override entry for this entry encountered, with password field specified, but other necessary field(s) missing.

Action: Have an administrator fix the override entry for this account.

0x171220ee sec_login_s_info_not_avail

Severity: Varies **Component:** sec

Text: Information not available

Explanation: ?

Action: None required.

0x171220f4 sec_login_s_internal_error

Severity: Varies **Component:** sec
Text: internal error in sec_login
Explanation: Internal error, should not occur.
Action: Notify support personnel.

0x17122101 sec_login_s_invalid_compat_mode

Severity: Varies **Component:** sec
Text: Invalid compatibility mode selection.
Explanation: Specified compatibility mode is not supported.
Action: Specify a valid compatibility mode.

0x171220ff sec_login_s_invalid_deleg_type

Severity: Varies **Component:** sec
Text: Invalid delegation type selection.
Explanation: Specified delegation type is not supported.
Action: Specify a valid delegation type.

0x171220fd sec_login_s_invalid_password

Severity: Varies **Component:** sec
Text: Invalid password.
Explanation: The specified password is invalid.
Action: Specify a valid password.

0x171220ec sec_login_s_no_current_context

Severity: Varies **Component:** sec
Text: No currently established network identity for which context exists
Explanation: Login context is no longer completely accessible.
Action: Ensure that credential files for the specified login context have not been deleted.

0x171220f9 sec_login_s_no_identity

Severity: Varies **Component:** sec

Text: no identity supplied

Explanation: ?

Action: None required.

0x171220e8 sec_login_s_no_memory

Severity: Varies **Component:** sec

Text: No memory available

Explanation: Unable to allocate memory.

Action: Check available system swap space and increase if necessary.

0x171220f5 sec_login_s_no_override_info

Severity: Varies **Component:** sec

Text: no override information available

Explanation: No override information is currently available.

Action: None required.

0x171220f2 sec_login_s_not_certified

Severity: Varies **Component:** sec

Text: login context has not been certified

Explanation: Warning only. Information was obtained from a login context that has been validated but not certified.

Action: None required if certification is not desired for this data.

0x171220e7 sec_login_s_not_implemented

Severity: Varies **Component:** sec

Text: Operation not yet implemented

Explanation: Specified operation is not yet implemented in this version of DCE.

Action: Do not attempt the specified operation with this version of DCE.

0x171220f7 sec_login_s_null_password

Severity: Varies **Component:** sec

Text: cannot log in with zero-length password

Explanation: Cannot log in with a zero length password.

Action: Specify a valid password for login.

0x171220fb sec_login_s_override_failure

Severity: Varies **Component:** sec

Text: Unable to determine if override exists

Explanation: Unable to determine if any override information exists, so operation must be denied.

Action: Ensure that password override information is accessible to sec_clientd or dced/secval.

0x171220fc sec_login_s_ovrd_ent_not_found

Severity: Varies **Component:** sec

Text: No matching override entry found.

Explanation: No matching override entry found (informational status code).

Action: None required.

0x17122103 sec_login_s_preauth_failed

Severity: Varies **Component:** sec

Text: Preauthentication failure.

Explanation: The client is unable to compose the necessary preauthentication data for this principal.

Action: Contact a system administrator.

0x171220f1 sec_login_s_privileged

Severity: Varies **Component:** sec

Text: privileged operation invoked in unprivileged process

Explanation: Privilege operation was attempted in an unprivileged (non-root) process.

Action: Only attempt this operation in a privileged (root, uid 0) process.

0x171220fa sec_login_s_refresh_ident_bad

Severity: Varies **Component:** sec

Text: identity to be refreshed is no longer valid

Explanation: Attempted to refresh credentials for an account that is no longer valid.

Action: Cannot perform this operation.

0x17122105 sec_login_s_unix_id_overflow

Severity: Varies **Component:** sec

Text: The UNIX ID obtained from DCE is larger than supported by this OS.

Explanation: The UNIX ID obtained from DCE is larger than supported by this OS.

Action: Contact a system administrator.

0x171220f8 sec_login_s_unsupp_passwd_type

Severity: Varies **Component:** sec

Text: unsupported password type.

Explanation: Attempted to login using an unsupported password type.

Action: Specify a valid password and password type for login.

0x17122119 sec_lrgy_s_cannot_create

Severity: Varies **Component:** sec

Text: cannot create local registry

Explanation: Unable to create local registry files.

Action: Administrator should ensure that local registry files can be created by the login programs.

0x1712211b sec_lrgy_s_internal_error

Severity: Varies **Component:** sec

Text: internal local registry error

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x17122117 sec_lrgy_s_max_lt_num_entries

Severity: Varies **Component:** sec

Text: max_entries must be at least as large as num_entries

Explanation: User specified a max entry value smaller than current number of entries.

Action: Specify a maximum number of entries that is at least as large as the current number of local registry entries.

0x1712211a sec_lrgy_s_no_access

Severity: Varies **Component:** sec

Text: cannot access local registry

Explanation: Local registry exists, but cannot be accessed.

Action: Administrator should ensure that login programs are able to access the local registry files.

0x1712211c sec_lrgy_s_no_matching_entry

Severity: Varies **Component:** sec

Text: no matching local registry account entry

Explanation: No matching local registry account entry (informational status code).

Action: None required.

0x1712211d sec_lrgy_s_no_matching_tgt

Severity: Varies **Component:** sec

Text: no matching local registry TGT entry

Explanation: No matching local registry TGT entry (informational status code).

Action: None required.

0x1712211e sec_lrgy_s_no_more_entries

Severity: Varies **Component:** sec

Text: no more entries available

Explanation: End of local registry entries.

Action: None required. Don't try to read any more entries.

0x17122118 sec_lrgy_s_not_found

Severity: Varies **Component:** sec

Text: cannot find local registry

Explanation: No local registry files found.

Action: Administrator should ensure that local registry files can be created by the login programs.

0x17122f2c sec_ns_import_begin

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Attempting to import RPC bindings from %s

Explanation: ?

Action: None required.

0x17122f2e sec_ns_import_done

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Completed importing of RPC bindings from %s

Explanation: ?

Action: None required.

0x17122f2d sec_ns_import_next

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Attempting to import next RPC binding from %s

Explanation: ?

Action: None required.

0x17122189 sec_pk_e_cell_too_long

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: target cell name too long for cache file

Explanation: Attempting to retrieve the public key for the KDC of a cell whose cell name is too long to create a cache file name.

Action: Configure and use a shorter cell name alias.

0x17122183 sec_pk_e_domain_unsupported

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Public key domain not supported for this operation.

Explanation: The specified public key domain is not supported for this operation.

Action: Login from another node with support for the DCE Login domain; or use a valid public key domain; or use a valid operation for the specified domain.

0x17122187 sec_pk_e_key_attr_read_failed

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Public key attribute read failed.

Explanation: The value of at least one public key was not read successfully.

Action: Make sure the principal has a public key (DCEPKAuthentication ERA or DCEPKKeyEncipherment ERA) attached; make sure sec.1.2.2 has been enabled in the principal's cell; make sure the DCEPK ERA schema entries have not been modified.

0x17122186 sec_pk_e_key_vers_unavailable

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Key version requested not found.

Explanation: Specified key version was not found.

Action: Request available key using version 0, or request version of key that exists.

0x17122185 sec_pk_e_key_vers_unsupported

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Key version not supported.

Explanation: For `sec_pubkey_store`, the key version must be between 1 and 255; for `sec_pubkey_retrieve`, the version number must be between 0 and 255.

Action: Call `sec_pubkey` interfaces with `kvno` set to valid value.

0x1712218f `sec_pk_e_kf_format_err`

Severity: Fatal **Component:** `sec/sec_s_pubkey`

Text: Keyfile not recognized.

Explanation: The keyfile is not a valid public or private key keyfile.

Action: Check file pathname; be sure file is created with correct format (header, version).

0x1712218c `sec_pk_e_kf_open_err`

Severity: Fatal **Component:** `sec/sec_s_pubkey`

Text: Error opening the keyfile.

Explanation: Specified keyfile could not be opened.

Action: Create keyfile or supply correct keyfile pathname.

0x1712218b `sec_pk_e_kf_param_not_alloc`

Severity: Fatal **Component:** `sec/sec_s_pubkey`

Text: Return parameters NULL

Explanation: The value of a return parameter was null. Return parameters must point to pre-allocated structures.

Action: Allocate the structure for the return value and pass its address to the function.

0x1712218d `sec_pk_e_kf_read_err`

Severity: Fatal **Component:** `sec/sec_s_pubkey`

Text: Error reading the keyfile.

Explanation: Specified keyfile could not be read.

Action: Re-create keyfile or supply correct keyfile pathname; verify permissions on keyfile.

0x17122190 sec_pk_e_kf_version_err

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Keyfile version not supported.

Explanation: The keyfile version is not supported.

Action: Create keyfile with current software.

0x1712218e sec_pk_e_kf_write_err

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Error writing the keyfile.

Explanation: Specified keyfile could not be written.

Action: Supply correct keyfile pathname; create path leading to keyfile; verify permissions on keyfile.

0x1712218a sec_pk_e_no_key_value

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: the public key value is NULL

Explanation: Attempting to store a public key whose value is NULL.

Action: Use a valid public key value.

0x17122188 sec_pk_e_no_memory

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Insufficient memory for public key operation.

Explanation: Insufficient memory for public key operation.

Action: Install more memory.

0x17122191 sec_pk_e_rsdb_keystore_err

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Failed to register the rsdb keystore.

Explanation: Error registering the private key keystore mechanism for the krbtgt key.

Action: Ensure libdce is compatible with secd.

0x17122184 sec_pk_e_usage_unsupported

Severity: Fatal **Component:** sec/sec_s_pubkey

Text: Public key usage type not supported.

Explanation: The specified public key usage type is not supported.

Action: Login from another node with support for the user's public key login keys, or use a supported public key usage type.

0x17122193 sec_pk_login_client_fail

Severity: Notice **Component:** sec/sec_s_pubkey

Text: Could not acquire public key credentials: %s in %s

Explanation: A failure was detected while the client was attempting to obtain credentials using public key login protocols

Action: Make a public key available to the client and known to the KDC

0x15f62011 sec_pkss_pipe_decrypt_fail

Severity: Error **Component:** pks/pks_s_pipe

Text: Error decrypting data from pipe (%x).

Explanation: Error returned from crypto routine

Action: Submit a problem report

0x15f62010 sec_pkss_pipe_encrypt_fail

Severity: Error **Component:** pks/pks_s_pipe

Text: Error encrypting for pipe (%x)

Explanation: Error returned from crypto routine

Action: Submit a problem report

0x17122063 sec_priv_s_bad_compat_mode

Severity: Varies **Component:** sec

Text: invalid compatibility mode

Explanation: An out of range compat mode parameter was passed to the privilege server.

Action: Notify support personnel.

0x17122064 sec_priv_s_bad_deleg_type

Severity: Varies **Component:** sec

Text: invalid delegation type

Explanation: Specified delegation type is not valid.

Action: Ensure that a valid delegation type is specified.

0x1712206c sec_priv_s_cmode_not_enabled

Severity: Varies **Component:** sec

Text: Requested compatibility mode has not been enabled

Explanation: Delegate attempted to specify a compatibility mode not allowed by initiator.

Action: Server should not attempt to specify this compatibility mode unless the initiator allows it.

0x17122067 sec_priv_s_corrupt_deleg_chain

Severity: Varies **Component:** sec

Text: delegation chain is corrupt

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x17122065 sec_priv_s_deleg_not_enabled

Severity: Varies **Component:** sec

Text: delegation not enabled

Explanation: Delegation attempted, but not enabled by initiator of operation.

Action: Don't attempt to become a delegate, or set up initiator correctly.

0x17122066 sec_priv_s_deleg_token_exp

Severity: Varies **Component:** sec

Text: delegation token has expired

Explanation: Delegation operation attempted, but delegation token has expired.

Action: Initiator or previous delegate(s) must refresh credentials before the operation can be performed.

0x17122069 sec_priv_s_intercell_deleg_req

Severity: Varies **Component:** sec

Text: privilege service delegation requests cannot cross cell boundaries

Explanation: Intercell delegation requests are not yet supported.

Action: Do not attempt to perform this delegation request across cell boundaries.

0x1712205e sec_priv_s_invalid_authn_svc

Severity: Varies **Component:** sec

Text: authentication service invalid

Explanation: Invalid authn_svc parameter in request to privilege server.

Action: Notify support personnel.

0x1712205f sec_priv_s_invalid_authz_svc

Severity: Varies **Component:** sec

Text: authorization service invalid

Explanation: Invalid authz_svc parameter in request to privilege server.

Action: Notify support personnel.

0x17122068 sec_priv_s_invalid_dlg_token

Severity: Varies **Component:** sec

Text: malformed delegation token

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x1712205b sec_priv_s_invalid_principal

Severity: Varies **Component:** sec

Text: invalid principal

Explanation: The principal requesting privileges is not valid. Could be caused by a race condition where the principal was just deleted, or could be caused by a defect in DCE.

Action: Ensure that the requesting principal exists. If so, and the error still occurs, notify support personnel.

0x1712206b sec_priv_s_invalid_protect_lvl

Severity: Varies **Component:** sec

Text: protocol level invalid

Explanation: Privilege client code passed in an invalid protection level.

Action: Notify support personnel.

0x17122061 sec_priv_s_invalid_request

Severity: Varies **Component:** sec

Text: malformed request

Explanation: Invalid request probably caused by defect in DCE, or corrupted data passed in.

Action: Notify support personnel.

0x1712206a sec_priv_s_invalid_server_name

Severity: Varies **Component:** sec

Text: Wrong priv server name

Explanation: Privilege client code passed in an invalid server name.

Action: Notify support personnel.

0x17122060 sec_priv_s_invalid_trust_path

Severity: Varies **Component:** sec

Text: trust path invalid

Explanation: The intercell authentication path traversed to authenticate to the DCE privilege server does not conform to the requirements for hierarchical trust in DCE.

Action: May need to reorganize the hierarchy of cells to conform to trust requirements.

0x1712205d sec_priv_s_no_mem

Severity: Varies **Component:** sec

Text: can't allocate memory

Explanation: Unable to allocate memory for specified operation.

Action: Check available system swap space and increase if necessary.

0x1712205c sec_priv_s_not_member_any_group

Severity: Varies **Component:** sec

Text: not member of any group

Explanation: Principal isn't a member of any of the groups it requested for its groupset. Most likely caused by a principal's group membership being changed since they logged in.

Action: Log out and log back in, or use kinit to refresh credentials.

0x1712205a sec_priv_s_server_unavailable

Severity: Varies **Component:** sec

Text: priv server unavailable

Explanation: Unable to locate an accessible privilege server.

Action: Retry the operation.

0x17122e43 sec_prop_bad_type

Severity: Error **Component:** sec/sec_s_rs_prop

Text: Bad propagation type.

Explanation: Internal error.

Action: Log a defect.

0x17122e47 sec_prop_chk_prop_slave_init

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Attempting to check slave initialization

Explanation: Check how slave initialization is going

Action: None required.

0x17122e45 sec_prop_fail

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Propagation failed : %s

Explanation: The update did not propagate successfully.

Action: Security server attempts to recover from this error. ??? It is not clear what the action should be. Or if eventually an ERROR message will be logged.

0x17122e42 sec_prop_no_master_info

Severity: Error **Component:** sec/sec_s_rs_prop

Text: Unable to get information about master

Explanation: Propagation thread tried but could not obtain information about the current master security server in the cell. This is an internal error.

Action: Log a defect.

0x17122e40 sec_prop_no_prop_thrs

Severity: Error **Component:** sec/sec_s_rs_prop

Text: Propagation threads not created

Explanation: The security server creates several propagation threads to manage the propagation of updates between the master and slave security servers. This error indicates that one or more such threads have not been created.

Action: Log a defect.

0x17122e41 sec_prop_not_master

Severity: Error **Component:** sec/sec_s_rs_prop

Text: Attempting to start propagation threads in a slave

Explanation: Propagation threads can only be created in a master security server not in a slave security server. This is an internal error.

Action: Log a defect.

0x17122e4c sec_prop_propq_clean_fail

Severity: Error **Component:** sec/sec_s_rs_prop

Text: Cleanup of propagation queue failed.\n%s

Explanation: An attempt to clean old entries from the prop queue failed.

Action: ?

0x17122e4a sec_prop_send_delete_rep

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Attempt to propagate delete replica %s

Explanation: ?

Action: None required.

0x17122e46 sec_prop_send_init_slave

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Attempt to initialize slave

Explanation: ?

Action: None required.

0x17122e48 sec_prop_slave_init_done

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Slave initialization done

Explanation: ?

Action: None required.

0x17122e44 sec_prop_succ

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Propagation succeeded

Explanation: The propagation has completed successfully.

Action: None required.

0x17122e49 sec_prop_updates_to_slaves

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: propagate updates to slaves

Explanation: ?

Action: None required.

0x1609c04a sec_psm_i_bad_domain

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) failed - Bad domain

Explanation: Debugging message

Action: None - Debugging message

0x1609c056 sec_psm_i_bad_keystore_id

Severity: Error **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Bad UUID in keystore %d (%.32s)

Explanation: Internal error - The specified entry in the registered keystore list is invalid

Action: Submit a problem report

0x1609c057 sec_psm_i_bad_keystore_id1

Severity: Error **Component:** psm/psm_s_psm

Text: sec_pvtkey__register_keystore - Bad UUID in keystore %d (%.32s)

Explanation: Internal error - The specified entry in the registered keystore list is invalid

Action: Submit a problem report

0x1609c04d sec_psm_i_bad_keystore_list

Severity: Error **Component:** psm/psm_s_psm

Text: Keystore entry %d is corrupt

Explanation: Internal error - The specified entry in the registered keystore list is invalid

Action: Submit a problem report

0x1609c051 sec_psm_i_chosen_keystore

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Returning keystore %d (%.32s)

Explanation: Debugging message

Action: None - Debugging message

0x1609c04e sec_psm_i_def_keystore

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Using default keystore %d (%.32s)

Explanation: Debugging message

Action: None - Debugging message

0x1609c055 sec_psm_i_discarded_keystore

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Discarded keystore %d (%.32s, uuid %s)

Explanation: Debugging message

Action: None - Debugging message

0x1609c050 sec_psm_i_era_lookup_failure

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) failed - Bad ERA lookup (0x%x)

Explanation: Debugging message

Action: None - Debugging message

0x1609c049 sec_psm_i_lookup_keystore

Severity: Unknown **Component:** psm/psm_s_psm

Text: Entering sec_pvtkey__lookup_keystore(%s)

Explanation: Debugging message

Action: None - Debugging message

0x1609c052 sec_psm_i_matchall_keystore

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Returning matchall keystore %d (%.32s)

Explanation: Debugging message

Action: None - Debugging message

0x1609c04c sec_psm_i_no_def_keystore_era

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - No default keystore ERA

Explanation: Debugging message

Action: None - Debugging message

0x1609c04f sec_psm_i_no_keystore

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) failed - No appropriate keystore

Explanation: Debugging message

Action: None - Debugging message

0x1609c04b sec_psm_i_no_prin_keystore_era

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - No principal keystore ERA

Explanation: Debugging message

Action: None - Debugging message

0x1609c041 sec_psm_internal_error

Severity: Error **Component:** psm/psm_s_psm

Text: psm internal error

Explanation: psm internal error

Action: Please inform engineer

0x1609c03e sec_psm_invalid_handle

Severity: Error **Component:** psm/psm_s_psm

Text: Invalid psm handle

Explanation: psm handle was corrupted

Action: Check the memory corruption

0x1609c045 sec_psm_invalid_keystore_handle

Severity: Error **Component:** psm/psm_s_psm

Text: Invalid keystore handle

Explanation: The sec_pvtkey__mechanism_handle_t was corrupt

Action: Check for an error in the calling program

0x1609c053 sec_psm_i_searching_explicit

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Searching for ERA-match keystore %s

Explanation: Debugging message

Action: None - Debugging message

0x1609c054 sec_psm_i_searching_matchall

Severity: Unknown **Component:** psm/psm_s_psm

Text: sec_pvtkey__lookup_keystore(%s) - Searching for matchall keystore

Explanation: Debugging message

Action: None - Debugging message

0x1609c047 sec_psm_keystore_already_registered

Severity: Error **Component:** psm/psm_s_psm

Text: Keystore already registered.

Explanation: The specified keystore is already registered

Action: To change an existing keystore, set the replace flag

0x1609c046 sec_psm_keystore_attr_read_failed

Severity: Error **Component:** psm/psm_s_psm

Text: Keystore ERA retrieval failed

Explanation: An attempt to retrieve a principal's keystore ERA failed

Action: Register a keystore for the principal

0x1609c044 sec_psm_keystore_list_corrupt

Severity: Error **Component:** psm/psm_s_psm

Text: Keystore list corrupt

Explanation: Internal error - the list of registered keystores is corrupt

Action: Submit a problem report

0x1609c048 sec_psm_keystore_list_full

Severity: Error **Component:** psm/psm_s_psm

Text: No space for a new keystore

Explanation: There is no space left in the keystore list

Action: None.

0x1609c043 sec_psm_keystore_not_found

Severity: Error **Component:** psm/psm_s_psm

Text: Keystore not found

Explanation: A keystore could not be found for the specified principal

Action: Register a keystore for the principal

0x1609c03f sec_psm_no_more_memory

Severity: Error **Component:** psm/psm_s_psm
Text: system ran out of memory
Explanation: system ran our of memory during malloc
Action: Increase the swap space or memory

0x1609c03d sec_psm_not_init

Severity: Error **Component:** psm/psm_s_psm
Text: PSM was not initialized
Explanation: PSM need to be initialized before calling any psm operations
Action: Please call sec_psm_open before any other psm operation

0x1609c03c sec_psm_unable_to_open_pvtkey

Severity: Error **Component:** psm/psm_s_psm
Text: Unable to access private key storage mechanism
Explanation: open a file or make a connection to private key mechanism failed.
Action: ?

0x1609c042 sec_psm_unsupported_algorithm_id

Severity: Error **Component:** psm/psm_s_psm
Text: unsupported crypto algorithm
Explanation: unsupported crypto algorithm
Action: Please choose supported one

0x1609c040 sec_psm_wrong_pub_key_type

Severity: Error **Component:** psm/psm_s_psm
Text: wrong public key type. The only supported public key type is RSA_PKCS
Explanation: The only supported public key type is RSA_PKCS
Action: Use the right public key type

0x1609c035 sec_pvtkey_capability_not_supported

Severity: Error **Component:** psm/psm_s_pvtkey

Text: specified capability not supported

Explanation: specified capability not supported in this private key storage mechanism

Action: ?

0x1609c033 sec_pvtkey_file_cannot_open_key_file

Severity: Error **Component:** psm/psm_s_pvtkey

Text: pvtkey file cannot be opened.

Explanation: pvtkey file cannot be opened.

Action: Check the permission of the file

0x1609c032 sec_pvtkey_file_locked

Severity: Error **Component:** psm/psm_s_pvtkey

Text: pvtkey file is locked by other process.

Explanation: Only one process, one thread can do a write access to the pvtkey file at a time

Action: Wait a while and try it later

0x1609c031 sec_pvtkey_internal_error

Severity: Error **Component:** psm/psm_s_pvtkey

Text: sec_pvtkey module internal error. Please inform the developer.

Explanation: This is a developer coding error.

Action: ?

0x1609c027 sec_pvtkey_invalid_handle

Severity: Error **Component:** psm/psm_s_pvtkey

Text: invalid sec_pvtkey_handle

Explanation: Pvtkey handle is invalid, could be caused by memory corruption.

Action: ?

0x1609c02c sec_pvtkey_invalid_pwd

Severity: Error **Component:** psm/psm_s_pvtkey

Text: invalid password

Explanation: illegal password for fetching private key.

Action: ?

0x1609c02e sec_pvtkey_key_deletion_not_supported

Severity: Error **Component:** psm/psm_s_pvtkey

Text: private key deletion functionality is not supported.

Explanation: private key deletion functionality is not supported.

Action: ?

0x1609c02b sec_pvtkey_key_generation_not_supported

Severity: Error **Component:** psm/psm_s_pvtkey

Text: key generation is not supported

Explanation: private key generation is done in psm level for file based key storage

Action: ?

0x1609c026 sec_pvtkey_mechanism_not_init

Severity: Error **Component:** psm/psm_s_pvtkey

Text: private key storage mechanism hasn't been initialized

Explanation: sec_pvtkey_open was not called before this operation.

Action: ?

0x1609c037 sec_pvtkey_multiple_key_usages

Severity: Error **Component:** psm/psm_s_pvtkey

Text: too many key usages supplied

Explanation: Multiple key usages supplied while only one key usage allowed

Action: ?

0x1609c030 sec_pvtkey_new_password_required

Severity: Error **Component:** psm/psm_s_pvtkey

Text: new password is required for updating the password

Explanation: New password is required for updating the password of th private key

Action: ?

0x1609c02a sec_pvtkey_no_matched_private_key

Severity: Error **Component:** psm/psm_s_pvtkey

Text: couldn't find a matched private key in the file

Explanation: No private key is matched to the requested name, domain, and key usage

Action: ?

0x1609c038 sec_pvtkey_no_more_data

Severity: Warning **Component:** psm/psm_s_pvtkey

Text: read reach the end of file

Explanation: No more data in the file

Action: ?

0x1609c02d sec_pvtkey_no_more_memory

Severity: Error **Component:** psm/psm_s_pvtkey

Text: ran out of memory

Explanation: Malloc failed because of no more memory

Action: ?

0x1609c03b sec_pvtkey_old_pass_required

Severity: Warning **Component:** psm/psm_s_pvtkey

Text: Old passphrase required for this update

Explanation: This is owner updating his key pair. Old passphrase is required to verify the passphrase

Action: Supply the correct old passphrase

0x1609c02f sec_pvtkey_private_key_is_not_supplied

Severity: Error **Component:** psm/psm_s_pvtkey

Text: private key is required fro admin to update user's private key

Explanation: For admin to update user's private key record, private key has to supplied.

Action: ?

0x1609c034 sec_pvtkey_privileged

Severity: Error **Component:** psm/psm_s_pvtkey

Text: Not file owner or root

Explanation: Must be the file owner or root account to access pvtkey file

Action: ?

0x1609c028 sec_pvtkey_same_domain_and_usage_key_already_exist

Severity: Error **Component:** psm/psm_s_pvtkey

Text: same domain and usage key already exist

Explanation: There is a private key with same domain, usage existent in the key storage mechanism

Action: ?

0x1609c029 sec_pvtkey_same_domain_and_usage_key_exist_with_diff_pwd

Severity: Error **Component:** psm/psm_s_pvtkey

Text: Unable to update same_domain_and_usage_key_already_exist key because of different pwd

Explanation: Either recreate the user account or use the right password.

Action: ?

0x1609c036 sec_pvtkey_unsupported_capability_name

Severity: Error **Component:** psm/psm_s_pvtkey

Text: specified capability name not supported

Explanation: specified capability name not supported in this private key storage mechanism

Action: ?

0x1609c03a sec_pvtkey_version_not_exist

Severity: Warning **Component:** psm/psm_s_pvtkey

Text: The correct private key version not found

Explanation: The correct private key version not found

Action: Use version 0 to indicate using the most recent one, or use the correct key version number

0x1609c039 sec_pvtkey_wrong_passwd

Severity: Warning **Component:** psm/psm_s_pvtkey

Text: New passphrase doesn't match other key pairs' passphrase

Explanation: The passphrases for all key pairs must be the same

Action: Change to the same passphrase and try it again

0x17122177 sec_pwd_mgmt_not_authorized

Severity: Varies **Component:** sec

Text: unauthorized to call password management server

Explanation: Caller is not authorized to communicate with the password management server.

Action: None required.

0x1712217a sec_pwd_mgmt_proxy_req

Severity: Varies **Component:** sec

Text: a proxy agent is required for secure transmission of data

Explanation: ?

Action: None required.

0x17122176 sec_pwd_mgmt_str_check_failed

Severity: Varies **Component:** sec

Text: password failed password strength server checking policy

Explanation: Specified password failed password strength server checking policy.

Action: Specify a stronger password.

0x17122178 sec_pwd_mgmt_svr_error

Severity: Varies **Component:** sec

Text: password management server generic error

Explanation: The password management server has failed to complete the requested operation due to an error.

Action: Contact the system administrator.

0x17122179 sec_pwd_mgmt_svr_unavail

Severity: Varies **Component:** sec

Text: password management server is unavailable

Explanation: Unable to contact password management server.

Action: An administrator should ensure proper configuration of the password management server.

0x17122f2f sec_rca_op_status

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Registry operation failed (%s): %s

Explanation: ?

Action: None required

0x17122f30 sec_rca_site_rebind

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Attempting to rebind to an alternate registry site and retrying operation

Explanation: ?

Action: None required

0x17122f32 sec_rca_site_rebind_fail

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Failed to rebind to an alternate registry to retry operation

Explanation: ?

Action: None required

0x17122f31 sec_rca_site_rebind_succ

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Rebound to site %s

Explanation: ?

Action: None required

0x17122e83 sec_rep_adopt_sw_rev_fatal

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Fatal error adopting new software version (%d)\nCurrent sw version = (%d):
status = %s

Explanation: An attempt to adopt a new software version failed due to an internal error condition that cannot be corrected dynamically. The most common causes of such a failure are an inability to register (or unregister) the remote interfaces needed (or no longer needed) to support the new software version. Examine the error status included in the output to determine the exact cause of failure.

Action: Ensure that the endpoint map service is running on the server host and reboot the security server. If the replica in question is the master, issue the administrative command to set the new software version. If the replica is a slave, there is no need to issue the administrative command—the master will force the slave to adopt the new software version as soon as the slave comes back on line.

0x17122e82 sec_rep_cant_get_sw_rev_fatal

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Error retrieving current software version \n%s

Explanation: An internal attempt to retrieve the current software version from a replica's master info failed in a context in which such a failure is fatal.

Action: Save the serviceability log and core file and notify DCE support personnel of the problem.

0x17122e6e sec_rep_cant_start_prop_tasks

Severity: Error **Component:** sec/sec_s_rs_rep

Text: Cannot start propagation tasks

Explanation: ?

Action: ?

0x17122e62 sec_rep_corrupt_auth_handle

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Corrupted replica auth handle detected

Explanation: ?

Action: Log a defect.

0x17122e6a sec_rep_dupe_cant_start

Severity: Error **Component:** sec/sec_s_rs_rep

Text: Replica is in dupe master state and cannot be started

Explanation: ?

Action: ?

0x17122e69 sec_rep_dupe_not_master

Severity: Error **Component:** sec/sec_s_rs_rep

Text: Replica is in dupe master state but is not the master

Explanation: ?

Action: ?

0x17122e74 sec_rep_init_slave_fail

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Initialization failed : %s

Explanation: ?

Action: None required.

0x17122e73 sec_rep_init_slave_succ

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Initialization completed successfully

Explanation: ?

Action: None required.

0x17122e63 sec_rep_invalid_auth_handle

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Invalid replica auth handle

Explanation: ?

Action: Log a defect.

0x17122e68 sec_rep_maint_not_master

Severity: Error **Component:** sec/sec_s_rs_rep

Text: Replica is in maintenance state but is not the master

Explanation: Only a master security server can be in the maintenance mode not a slave.

Action: ?

0x17122e67 sec_rep_mseq_not_dup_master

Severity: Error **Component:** sec/sec_s_rs_rep

Text: master_seqno specified but not duplicate master

Explanation: master_seqno flag can only be applied to a duplicate master

Action: ?

0x17122e6d sec_rep_msrepl_not_initd

Severity: Error **Component:** sec/sec_s_rs_rep

Text: Cannot initialize master replist

Explanation: ?

Action: ?

0x17122e6b sec_rep_nm_not_deleted

Severity: Warning **Component:** sec/sec_s_rs_rep

Text: Unable to remove server's name (%s)from namespace

Explanation: ?

Action: ?

0x17122e6c sec_rep_not_on_replst

Severity: Error **Component:** sec/sec_s_rs_rep

Text: This replica not on replica list

Explanation: ?

Action: ?

0x17122e6f sec_rep_prop_in_progress

Severity: Error **Component:** sec/sec_s_rs_rep

Text: a replica has a propagation in progress

Explanation: Propagation was in progress to a replica when an attempting to free the master's volatile copy of the replica list.

Action: ?

0x17122e70 sec_rep_prop_type_not_init

Severity: Warning **Component:** sec/sec_s_rs_rep

Text: propagation type not init or initing

Explanation: ?

Action: ?

0x17122e76 sec_rep_recv_become_master

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Slave received become master message

Explanation: ?

Action: None required.

0x17122e75 sec_rep_recv_i_am_master

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Slave received i_am_master message

Explanation: ?

Action: None required.

0x17122e72 sec_rep_recv_init_slave

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Slave received initialization request

Explanation: On receipt of this request, the slave will attempt to initialize or reinitialize (?) itself.

Action: None required.

0x17122e77 sec_rep_recv_stop_sw_compat

Severity: Notice **Component:** sec/sec_s_rs_prop

Text: Slave received stop until software compatible request

Explanation: ?

Action: None required.

0x17122e66 sec_rep_rm_not_in_service

Severity: Error **Component:** sec/sec_s_rs_rep

Text: restore_master specified but master not in service

Explanation: restore_master flag can only be specified to an in service master

Action: ?

0x17122cd8 sec_res_acct_add_err

Severity: Error **Component:** sec/sec_s_rs

Text: Error adding an account

Explanation: ?

Action: ?

0x17122cd9 sec_res_attr_sch_add_err

Severity: Error **Component:** sec/sec_s_rs

Text: Error adding an entry to the attribute schema

Explanation: ?

Action: ?

0x17122cd3 sec_res_host_key_set_err

Severity: Error **Component:** sec/sec_s_rs

Text: Error setting local host's key

Explanation: ?

Action: Try deleting old entry (this was hardcoded in the text)

0x17122cd7 sec_res_mem_add_err

Severity: Error **Component:** sec/sec_s_rs

Text: Error adding a member

Explanation: ?

Action: ?

0x17122cd6 sec_res_pgo_add_err

Severity: Error **Component:** sec/sec_s_rs

Text: Error adding a person/group/org entry

Explanation: ?

Action: ?

0x17122cda sec_res_pk_attr_sch_add_err

Severity: Error **Component:** sec/sec_s_rs
Text: Error adding an entry to the PK attribute schema
Explanation: ?
Action: ?

0x17122cd4 sec_res_princ_cvt_err

Severity: Error **Component:** sec/sec_s_rs
Text: Error converting cell name to local realm principal
Explanation: ?
Action: ?

0x17122cd5 sec_res_uuid_cvt_err

Severity: Error **Component:** sec/sec_s_rs
Text: Error converting cell uuid to string
Explanation: ?
Action: ?

0x17122d14 sec_rgy_acl_init

Severity: Fatal **Component:** sec/sec_s_rs_main
Text: Cannot initialize ACL manager\n%s
Explanation: Initializing for sec_acl wire interface failed.
Action: ?

0x17122096 sec_rgy_alias_not_allowed

Severity: Varies **Component:** sec
Text: Cant add alias for this name or principal (e.g. krbtgt)
Explanation: Attempted to add an alias to a principal which prohibits that operation.
Action: Do not attempt to add an alias for this principal.

0x17122d0d sec_rgy_aud_open

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot open audit trail\n%s

Explanation: Fail to open dce audit file

Action: Check auditing setup, e.g. ENV or audit tail file

0x17122d18 sec_rgy_auth_init

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot register auth info\n%s

Explanation: Cannot register server's authentication information with RPC runtime

Action: ?

0x17122083 sec_rgy_bad_alias_owner

Severity: Varies **Component:** sec

Text: PGO alias entry has an invalid owner

Explanation: PGO alias entry has an invalid owner

Action: None required.

0x17122097 sec_rgy_bad_chksum_type

Severity: Varies **Component:** sec

Text: Checksum type not supported

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x17122084 sec_rgy_bad_data

Severity: Varies **Component:** sec

Text: Invalid data record

Explanation: Invalid data encountered during specified registry operation.

Action: Ensure proper data is being passed by the client.

0x17122074 sec_rgy_bad_domain

Severity: Varies **Component:** sec

Text: Operation not supported on specified domain

Explanation: Attempted an operation that is not supported by the specified domain.

Action: Ensure that the correct domain is used for the operation.

0x1712209d sec_rgy_bad_handle

Severity: Varies **Component:** sec

Text: bad security context handle

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x17122098 sec_rgy_bad_integrity

Severity: Varies **Component:** sec

Text: Data integrity error

Explanation: Data integrity error. Could be caused by specifying invalid password.

Action: Ensure correct password is specified.

0x17122088 sec_rgy_bad_name

Severity: Varies **Component:** sec

Text: Illegal PGO or directory name

Explanation: Illegal name (possibly illegal character(s)) passed to the sec_rgy API.

Action: Ensure application is passing a valid name to the sec_rgy API. If this error is encountered within the DCE base components, then notify support personnel.

0x171220a3 sec_rgy_bad_nameservice_name

Severity: Varies **Component:** sec

Text: Invalid nameservice name

Explanation: Internal error.

Action: Notify support personnel.

0x17122eab sec_rgy_bad_rgy_db

Severity: Error **Component:** sec/sec_s_rs_rsdB

Text: Bad rgy database state.

Explanation: ?

Action: sec_create_db probably failed. Try rerunning it

0x17122093 sec_rgy_bad_scope

Severity: Varies **Component:** sec

Text: scope doesn't name existing directory or pgo

Explanation: Attempted to set scope to a name that does not exist in the registry.

Action: Ensure that a valid name is used for scope operation.

0x17122085 sec_rgy_cant_allocate_memory

Severity: Varies **Component:** sec

Text: Unable to allocate memory

Explanation: Unable to allocate memory for the specified operation.

Action: Check available system swap space and increase if necessary.

0x17122095 sec_rgy_cant_authenticate

Severity: Varies **Component:** sec

Text: Cant establish authentication to security server

Explanation: Can't establish authentication to security server.

Action: Ensure that caller has valid DCE credentials.

0x17122eaf sec_rgy_checkpoint

Severity: Notice **Component:** sec/sec_s_rs_rsdB

Text: Attempting to checkpoint registry database

Explanation: ?

Action: None required.

0x17122eb0 sec_rgy_checkpoint_succ

Severity: Notice **Component:** sec/sec_s_rs_rsdB

Text: Successfully checkpointed registry database

Explanation: ?

Action: None required.

0x17122eeb sec_rgy_checkpt_bad_at_time_str

Severity: Varies **Component:** sec

Text: The time string syntax for -at is incorrect.

Explanation: ?

Action: ?

0x17122eac sec_rgy_checkpt_log_file

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: Cannot checkpoint on log file\n%s

Explanation: ?

Action: ?

0x17122ead sec_rgy_checkpt_rename_files

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: Cannot rename files during checkpoint\n%s

Explanation: ?

Action: ?

0x17122eae sec_rgy_checkpt_save_rep_state

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: Cannot save replica state during checkpoint\n%s

Explanation: ?

Action: ?

0x17122d1c sec_rgy_checkpoint_start_task

Severity: Fatal **Component:** sec/sec_s_rs_main
Text: Cannot start checkpoint task\n%s
Explanation: Error when trying to start a thread to do checkpoint task
Action: ?

0x17122ee6 sec_rgy_chkpt_save_file

Severity: Notice **Component:** sec/sec_s_rs_rsdB
Text: Saving file %s
Explanation: ?
Action: None required.

0x17122ee7 sec_rgy_chkpt_save_relation

Severity: Notice **Component:** sec/sec_s_rs_rsdB
Text: Saving relation %s
Explanation: ?
Action: None required.

0x17122ee8 sec_rgy_compat_log_replay

Severity: Notice **Component:** sec/sec_s_rs_rsdB
Text: Compatibility log replay entered
Explanation: ?
Action: None required.

0x17122092 sec_rgy_crypt_bad_type

Severity: Varies **Component:** sec
Text: (de)encryption type not supported
Explanation: Specified encryption type is not supported.
Action: None required.

0x17122f66 sec_rgy_db_create

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Failed to create database\n%s

Explanation: ?

Action: ?

0x17122d01 sec_rgy_db_init

Severity: Notice **Component:** sec/sec_s_rs_main

Text: Attempting to initialize server database

Explanation: The security server is going to attempt to read the registry database into its virtual address space.

Action: None required.

0x17122d12 sec_rgy_db_init_err

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot initialize server database\n%s

Explanation: Loading or initializing rgy database has error.

Action: ?

0x17122d1a sec_rgy_dce_rgy_identity

Severity: Fatal **Component:** sec/sec_s_general

Text: Cannot setup dce_rgy identity\n%s

Explanation: Cannot set process identity (dce-rgy) and context.

Action: ?

0x17122089 sec_rgy_dir_could_not_create

Severity: Varies **Component:** sec

Text: Unable to create directory

Explanation: Unable to create a directory necessary for the specified operation.

Action: Ensure you have privileges to invoke the specified operation.

0x1712208a sec_rgy_dir_move_illegal

Severity: Varies **Component:** sec

Text: Directory move not allowed

Explanation: Attempted to make a parent directory the child of one of its descendents

Action: Don't do that.

0x17122087 sec_rgy_dir_not_empty

Severity: Varies **Component:** sec

Text: Directory not empty

Explanation: Attempted to delete a nonempty directory. Not passed to clients.

Action: None required.

0x17122086 sec_rgy_dir_not_found

Severity: Varies **Component:** sec

Text: Directory not found

Explanation: Internal sec status code used to tell caller to build dirs

Action: None required.

0x171220a5 sec_rgy_era_pwd_mgmt_auth_type

Severity: Varies **Component:** sec

Text: pwd_mgmt_binding ERA binding auth type cannot be none

Explanation: Principal's pwd_mgmt_binding ERA authentication cannot be 'none'.

Action: Reattach the principal's pwd_mgmt_binding ERA with an authentication type of 'dce'.

0x1712208c sec_rgy_foreign_quota_exhausted

Severity: Varies **Component:** sec

Text: Foreign quota for realm exhausted

Explanation: Attempt by a foreign principal to add a registry object, but quota is exhausted.

Action: Notify system administrator.

0x17122f65 sec_rgy_get_cellname

Severity: Fatal **Component:** sec/sec_s_rs_create_db

Text: Cannot retrieve cell name\n%s

Explanation: ?

Action: ?

0x17122d26 sec_rgy_get_local_host_princ

Severity: Fatal **Component:** sec/sec_s_rs_login

Text: Cannot get local host principal name\n%s

Explanation: ?

Action: ?

0x1712217f sec_rgy_homedir_too_long

Severity: Varies **Component:** sec

Text: Home directory pathname is too long after canonicalization

Explanation: The supplied home directory pathname is longer than 256 characters after expanded from local name to global name.

Action: Shortern the local name of the home directory pathname.

0x1712209f sec_rgy_host_context_not_avail

Severity: Varies **Component:** sec

Text: Login context of local host principal not available

Explanation: Login context of local host principal not available.

Action: None required.

0x17122d17 sec_rgy_host_identity

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot get host identity\n%s

Explanation: Cannot inherit host machine context and identity

Action: ?

0x1712207f sec_rgy_incomplete_login_name

Severity: Varies **Component:** sec

Text: Incomplete login name specification

Explanation: Specified login name structure was not completely specified.

Action: Ensure proper usage of the sec_rgy_login_name_t structure.

0x17122d10 sec_rgy_init_rpc_bind

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot initialize RPC services\n%s

Explanation: Trying to initialize rpc binding failed.

Action: ?

0x17122078 sec_rgy_is_an_alias

Severity: Varies **Component:** sec

Text: Query returned an alias and allow_aliases was not set

Explanation: Query returned an alias and allow_aliases was not set

Action: None required.

0x17122099 sec_rgy_key_bad_size

Severity: Varies **Component:** sec

Text: Invalid size for key data

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x17122091 sec_rgy_key_bad_type

Severity: Varies **Component:** sec

Text: key type not supported

Explanation: The key type specified was not a valid for the specified operation.

Action: Ensure proper key type is being used. If this error is encountered within the DCE base components, notify support personnel.

0x1712208f sec_rgy_key_bad_version

Severity: Varies **Component:** sec

Text: key version number out of range

Explanation: Specified key version number is out of the valid range.

Action: None required.

0x17122090 sec_rgy_key_version_in_use

Severity: Varies **Component:** sec

Text: key version number currently in use

Explanation: Specified key version number is already in use.

Action: None required.

0x17122d15 sec_rgy_locksmith_init

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot setup locksmith account\n%s

Explanation: ?

Action: ?

0x171220a4 sec_rgy_log_entry_out_of_range

Severity: Varies **Component:** sec

Text: Invalid log entry module or operation

Explanation: Internal error.

Action: Notify support personnel.

0x17122d11 sec_rgy_log_init_mgr

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot initialize server log managers\n%s

Explanation: ?

Action: ?

0x1712209c sec_rgy_mkey_bad

Severity: Varies **Component:** sec

Text: Supplied master key is bad

Explanation: Registry master key retrieved from .mkey file doesn't match master key stored in the database.

Action: Restore registry database and .mkey file from backup.

0x1712209b sec_rgy_mkey_bad_stored

Severity: Varies **Component:** sec

Text: Stored master key is bad

Explanation: Registry master key stored in .mkey file has been corrupted.

Action: Restore registry database and .mkey file from backup.

0x1712209a sec_rgy_mkey_cant_read_stored

Severity: Varies **Component:** sec

Text: Can't read stored master key

Explanation: Unable to retrieve stored master key from .mkey file.

Action: Restore registry database and .mkey file from backup.

0x171220a0 sec_rgy_mkey_file_io_failed

Severity: Varies **Component:** sec

Text: Master_key file I/O operation failed

Explanation: Master key file operation (create/read/write) failed.

Action: Security server must be started by root. Check permissions on registry database directory and .mkey file.

0x17122e20 sec_rgy_mky_bad_cellname

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Illegal cell name : %s

Explanation: The cell name must begin with /.../ but it does not.

Action: ?

0x17122e29 sec_rgy_mky_gen_random

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key: Error generating random master_key\n%s

Explanation: ?

Action: ?

0x17122e24 sec_rgy_mky_get_realm_name

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key: Error converting cell name to realm name\n%s

Explanation: The cell name to be converted is not a legal cell name.

Action: ?

0x17122e26 sec_rgy_mky_init_keyseed

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key. Error generating initial keyseed\n%s

Explanation: Problem generating a DES key from user-entered keyseed and timeofday.

Action: ?

0x17122e28 sec_rgy_mky_init_random

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key: Error initializing random key generator\n%s

Explanation: ?

Action: ?

0x17122e2d sec_rgy_mky_not_match

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Master_key in memory doesn't match master_key stored in database\n%s

Explanation: ?

Action: ?

0x17122e27 sec_rgy_mky_process_keyseed

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key. Error processing keyseed\n%s

Explanation: ?

Action: ?

0x17122e2a sec_rgy_mky_process_master_key

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key: Error processing master_key\n%s

Explanation: ?

Action: ?

0x17122e25 sec_rgy_mky_setup_mkey_name

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Cannot create master_key Error setting up master_key

Explanation: Possibly caused by not enough memory to be allocated.

Action: ?

0x17122e2c sec_rgy_mky_store_db

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Error storing master_key in database\n%s

Explanation: ?

Action: ?

0x17122e2b sec_rgy_mky_store_disk

Severity: Fatal **Component:** sec/sec_s_rs_mkey
Text: Cannot create master_key: Error storing master_key on disk\n%s
Explanation: ?
Action: ?

0x17122076 sec_rgy_name_exists

Severity: Varies **Component:** sec
Text: Name already exists
Explanation: Attempted to add a registry object that already exists.
Action: None required.

0x17122079 sec_rgy_no_more_entries

Severity: Varies **Component:** sec
Text: No more matching entries
Explanation: End of list encountered while performing registry lookup.
Action: Stop performing lookup operation when this code is returned.

0x1712208d sec_rgy_no_more_unix_ids

Severity: Varies **Component:** sec
Text: Unix id space for domain has been exhausted
Explanation: No more available Unix IDs within allowable range.
Action: Increase maximum Unix ID limit, or clean up registry.

0x17122081 sec_rgy_not_authorized

Severity: Varies **Component:** sec
Text: User is not authorized to update record
Explanation: The object's ACL denied the attempted operation.
Action: An identity that is granted the right to perform the requested operation must be used.

0x17122073 sec_rgy_not_implemented

Severity: Varies **Component:** sec

Text: Operation not yet implemented

Explanation: Operation is not implemented in this version of DCE.

Action: Do not specify the operation in question with this version of DCE.

0x1712207c sec_rgy_not_member_group

Severity: Varies **Component:** sec

Text: User is not member of specified group

Explanation: The principal specified in the account operation is not a member of the specified primary group.

Action: The principal should be added to the group before this account operation is attempted.

0x1712207e sec_rgy_not_member_group_org

Severity: Varies **Component:** sec

Text: User is not member of specified group and org

Explanation: The principal specified in the account operation is not a member of the specified group or organization.

Action: The principal should be added to the specified group and organization before this operation is attempted.

0x1712207d sec_rgy_not_member_org

Severity: Varies **Component:** sec

Text: User is not member of specified org

Explanation: The principal specified in the account operation is not a member of the specified organization.

Action: The principal should be added to the organization before this account operation is attempted.

0x17122d00 sec_rgy_not_root

Severity: Varies **Component:** sec

Text: Not a privileged user

Explanation: The attempted operation requires root privileges.

Action: Retry the operation after logging in as a privileged user.

0x17122d1b sec_rgy_ns_register

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot start nameservice registration task\n%s

Explanation: ?

Action: ?

0x17122d53 sec_rgy_ns_svr_get_binding

Severity: Fatal **Component:** sec/sec_s_rs_ns

Text: Cannot get server's bindings\n%s

Explanation: Cannot get server's rpc binding from its repository.

Action: ?

0x17122075 sec_rgy_object_exists

Severity: Varies **Component:** sec

Text: Object already exists

Explanation: Attempted to add a registry object that already exists.

Action: None required.

0x1712207a sec_rgy_object_not_found

Severity: Varies **Component:** sec

Text: Registry object not found

Explanation: Specified registry object was not found.

Action: Ensure that object is specified correctly and that caller is granted read access to the object.

0x17122094 sec_rgy_object_not_in_scope

Severity: Varies **Component:** sec

Text: object found was not in scope

Explanation: Attempted to lookup object that doesn't exist within the current scope.

Action: Ensure object is specified correctly and that scope is set to desired value.

0x17122080 sec_rgy_passwd_invalid

Severity: Varies **Component:** sec

Text: Invalid password

Explanation: Specified password is invalid.

Action: Ensure that the correct password is specified.

0x171220a7 sec_rgy_passwd_non_alpha

Severity: Varies **Component:** sec

Text: Passwords must contain at least one non-alphanumeric character

Explanation: Specified password contains all alphanumeric characters, which is not allowed by current policy.

Action: Specify a password that contains at least one non-alphanumeric character.

0x171220a8 sec_rgy_passwd_spaces

Severity: Varies **Component:** sec

Text: Passwords must contain at least one non-blank character

Explanation: Specified password contains no non-blank character, which is not allowed by current policy.

Action: Specify a password that contains at least one non-blank character.

0x171220a6 sec_rgy_passwd_too_short

Severity: Varies **Component:** sec

Text: Password is too short

Explanation: Specified password is shorter than the current minimum limit.

Action: Specify a longer password.

0x1712208b sec_rgy_quota_exhausted

Severity: Varies **Component:** sec

Text: Principal quota exhausted

Explanation: Principal's registry quota is exhausted and an update operation was attempted.

Action: Ensure that correct identity is used to perform operation. Increase quota if necessary.

0x17122082 sec_rgy_read_only

Severity: Varies **Component:** sec

Text: Registry is read only - updates are not allowed

Explanation: Registry is in a read only state and an update was attempted.

Action: Wait until registry is no longer in a read only state, then retry.

0x17122e80 sec_rgy_rep_add_master_replica

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Error adding master replica to an uninitialized database\n%s

Explanation: When a slave database is re-initializing, in-memory data is cleared and re-created. Problem occurred when trying to add master replica to its database.

Action: ?

0x17122e7f sec_rgy_rep_add_my_replica

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Error adding my replica to an uninitialized database\n%s

Explanation: When a slave database is re-initializing, in-memory data is cleared and re-created. Problem occurred when trying to add this slave replica to its database.

Action: ?

0x171220c9 sec_rgy_rep_already_inited

Severity: Varies **Component:** sec

Text: slave already initialized

Explanation: Attempt to initialize a replica that has already been initialized.

Action: None required.

0x171220bd sec_rgy_rep_babel

Severity: Varies **Component:** sec

Text: Cannot communicate with all slaves

Explanation: Obsolete?

Action: None required.

0x171220c2 sec_rgy_rep_bad_arg

Severity: Varies **Component:** sec

Text: bad argument

Explanation: Invalid operation.

Action: None required.

0x171220b6 sec_rgy_rep_bad_binding

Severity: Varies **Component:** sec

Text: bad binding

Explanation: Bad binding encountered by the registry server.

Action: Notify support personnel.

0x171220aa sec_rgy_rep_bad_db_version

Severity: Varies **Component:** sec

Text: bad database version

Explanation: Version stored with registry database is not that expected by the registry software executed.

Action: Ensure correct version of the DCE registry software is being used.

0x171220c8 sec_rgy_rep_bad_init_id

Severity: Varies **Component:** sec

Text: init_id from slave doesn't match master's init_id for the replica

Explanation: Internal error, should not occur

Action: Notify support personnel.

0x171220cf sec_rgy_rep_bad_master_seqno

Severity: Varies **Component:** sec

Text: Master sequence number is invalid

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x171220ca sec_rgy_rep_bad_prop_type

Severity: Varies **Component:** sec

Text: bad propagation type after prop operation

Explanation: Internal error, should not occur

Action: Notify support personnel.

0x171220b4 sec_rgy_rep_bad_state

Severity: Varies **Component:** sec

Text: bad state

Explanation: Operation attempted while registry was in a state unable to perform that type of operation.

Action: None required.

0x171220c6 sec_rgy_rep_bad_sw_vers

Severity: Varies **Component:** sec

Text: bad software version

Explanation: Attempted to start registry server with software that is at a version incompatible with that which is stored in the registry database.

Action: Ensure that you are using a version of DCE that is compatible with the existing configuration.

0x171220ab sec_rgy_rep_cannot_create_db

Severity: Varies **Component:** sec

Text: cannot create database

Explanation: Unable to create database.

Action: Ensure that replica is being configured correctly and that caller has rights to create the database files.

0x171220ac sec_rgy_rep_cannot_open_db

Severity: Varies **Component:** sec

Text: cannot open database

Explanation: Unable to open registry database file that should already exist.

Action: Ensure that replica has been configured correctly.

0x171220ad sec_rgy_rep_cannot_read_db

Severity: Varies **Component:** sec

Text: cannot read database

Explanation: Registry server is unable to read the registry database.

Action: The registry server must be run as root. If the registry database has been inadvertently deleted, restore it from backup.

0x171220af sec_rgy_rep_cannot_rename_db

Severity: Varies **Component:** sec

Text: cannot rename database

Explanation: The registry server was unable to rename the database files during conversion to the current database format.

Action: The registry server must be run as root. Ensure adequate disk space exists and that the registry database directory is accessible.

0x171220ae sec_rgy_rep_cannot_save_db

Severity: Varies **Component:** sec

Text: cannot save database

Explanation: Unable to save registry database to disk.

Action: Verify that registry database is still on disk and that sufficient disk space is available.

0x171220b9 sec_rgy_rep_clock_skew

Severity: Varies **Component:** sec

Text: clock skewed

Explanation: Clock value between registry server machines is out of tolerance.

Action: Synchronize the clocks on all registry server machines.

0x171220b8 sec_rgy_rep_db_locked

Severity: Varies **Component:** sec

Text: database locked

Explanation: Database is already locked by another process.

Action: Ensure that no other registry server is already running on this system.

0x171220b7 sec_rgy_rep_deleted

Severity: Varies **Component:** sec

Text: replica deleted

Explanation: Obsolete?

Action: None required.

0x171220bc sec_rgy_rep_doppelganger

Severity: Varies **Component:** sec

Text: Another replica with the same name or id exists

Explanation: Another replica with the same name or id exists.

Action: Determine why an identical replica already exists.

0x17122e71 sec_rgy_rep_entry_not_found

Severity: Fatal **Component:** sec/sec_s_rs_rep
Text: Cannot find in-memory replot entry in stable replot\n%s
Explanation: ?
Action: ?

0x17122d19 sec_rgy_rep_host_identity

Severity: Fatal **Component:** sec/sec_s_rs_main
Text: Replica cannot get local host identity\n%s
Explanation: Cannot get local host principal's context and identity
Action: ?

0x171220c5 sec_rgy_rep_init_ekey_invalid

Severity: Varies **Component:** sec
Text: initialization encryption key not valid
Explanation: Initialization encryption key is not valid.
Action: Notify support personnel.

0x17122d13 sec_rgy_rep_init_replica

Severity: Fatal **Component:** sec/sec_s_rs_main
Text: Cannot initialize server replica\n%s
Explanation: ?
Action: ?

0x171220c4 sec_rgy_rep_invalid_entry

Severity: Varies **Component:** sec
Text: invalid replica entry
Explanation: Invalid replica entry encountered.
Action: Notify support personnel.

0x171220c7 sec_rgy_rep_marked_for_init

Severity: Varies **Component:** sec

Text: replica already marked for initialization

Explanation: Attempted to mark a replica for initialization, that has already been marked for initialization.

Action: None required.

0x171220b1 sec_rgy_rep_master

Severity: Varies **Component:** sec

Text: Replica is the master

Explanation: Specified operation may only be performed at a non-master registry replica site.

Action: None required.

0x171220cb sec_rgy_rep_master_bad_sw_vers

Severity: Varies **Component:** sec

Text: master is running a bad software version

Explanation: Master registry is running a version of software that is not compatible with the replica registry servers.

Action: Ensure that the correct version of sw is being used.

0x171220cd sec_rgy_rep_master_dup

Severity: Varies **Component:** sec

Text: duplicate masters

Explanation: Duplicate master registry servers found.

Action: Ensure that only one master registry server exists for this cell.

0x171220b0 sec_rgy_rep_master_not_found

Severity: Varies **Component:** sec

Text: cannot find master

Explanation: A registry replica was unable to locate the master registry.

Action: Ensure the master registry is up and accessible.

0x17122e4b sec_rgy_rep_master_obsolete

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Master's database is probably obsolete\n%s

Explanation: A slave has a higher update sequence number than this master, which implies this master has an obsolete database; so exit itself.

Action: ?

0x17122e79 sec_rgy_rep_mst_restart_prop

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Master cannot restart prop tasks when change_master failed\n%s

Explanation: After change_master operation failed, the old master try to resume its master role but fail to restart its propagation task threads.

Action: ?

0x171220ce sec_rgy_rep_must_init_slave

Severity: Varies **Component:** sec

Text: Slave wants init to re-sync with master

Explanation: Internal usage only?

Action: None required.

0x171220b5 sec_rgy_rep_name_unavailable

Severity: Varies **Component:** sec

Text: name unavailable

Explanation: Obsolete?

Action: None required.

0x171220c3 sec_rgy_rep_no_default_replica

Severity: Varies **Component:** sec

Text: no default replica

Explanation: Obsolete?

Action: None required.

0x171220b3 sec_rgy_rep_not_from_master

Severity: Varies **Component:** sec

Text: not from master

Explanation: Internal error, should not happen.

Action: Notify support personnel.

0x171220b2 sec_rgy_rep_not_master

Severity: Varies **Component:** sec

Text: Replica is not the master

Explanation: Specified operation may only be performed by the master registry server.

Action: None required.

0x171220be sec_rgy_rep_not_on_replist

Severity: Varies **Component:** sec

Text: The server that greeted the master is not on the replica list

Explanation: Obsolete?

Action: None required.

0x17122e09 sec_rgy_rep_pack_entry

Severity: Fatal **Component:** sec/sec_s_rs_log

Text: Cannot pack replica entry\n%s

Explanation: When trying to log replication for add or replace, error occurs.

Action: ?

0x171220a9 sec_rgy_rep_pgmerr

Severity: Varies **Component:** sec

Text: replication program error

Explanation: Internal error, should not occur.

Action: Notify support personnel.

0x171220c0 sec_rgy_rep_prop_busy

Severity: Varies **Component:** sec

Text: All non-zombie replicas are either busy or have received the specified update

Explanation: Obsolete?

Action: None required.

0x171220bf sec_rgy_rep_prop_complete

Severity: Varies **Component:** sec

Text: All non-zombie replicas have received the specified update

Explanation: Obsolete?

Action: None required.

0x171220c1 sec_rgy_rep_prop_from_rep

Severity: Varies **Component:** sec

Text: Server will not accept propagations now because it is serving as initializer ('from_rep') to a new slave

Explanation: Obsolete?

Action: None required.

0x17122e7e sec_rgy_rep_recover_db

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Cannot recover database\n%s

Explanation: After an attempt to initialize a replica failed, this operation tried to clear data in memory and reload pre-initialization database from disk, also failed.

Action: ?

0x17122e7c sec_rgy_rep_set_init_id

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Cannot save state init_id\n%s

Explanation: This code won't be executed; we may as well take it out :-) or replaced with same fatal message

Action: ?

0x17122e7b sec_rgy_rep_set_state

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Cannot set replica state\n%s

Explanation: This code won't be executed; we may as well take it out :-) or replaced with same fatal message

Action: ?

0x17122e7d sec_rgy_rep_set_volatile_state

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Cannot save volatile replica state\n%s

Explanation: This code won't be executed; we may as well take it out :-) or replaced with same fatal message

Action: ?

0x171220cc sec_rgy_rep_slave_bad_sw_vers

Severity: Varies **Component:** sec

Text: slave is running a bad software version

Explanation: Replica registry server is running a version of software that is not compatible with the master registry server.

Action: Ensure that the correct version of sw is being used.

0x17122e7a sec_rgy_rep_slv_restart_prop

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Master cannot restart prop tasks when become_slave failed\n%s

Explanation: After become_slave operation failed, the old master try to resume its master role but fail to restart its propagation task threads.

Action: ?

0x17122181 sec_rgy_rep_sw_rev_multi

Severity: Varies **Component:** sec

Text: Security server software version must be set forward one version at a time

Explanation: Admin user attempted to set the security service software version forward multiple versions beyond the current software version

Action: Determine the current security software version and migrate forward one version at a time by issuing successive set version commands

0x171220d1 sec_rgy_rep_sw_rev_no_setback

Severity: Varies **Component:** sec

Text: Security server software version cannot be rolled back dynamically

Explanation: Admin user attempted to set the security service software version back to an earlier version than is currently running

Action: If an earlier version of the software is wanted, restore an earlier version from backup, make sure the security server binary can support the version that was in effect when the backup was performed, and restart the server.

0x171220d0 sec_rgy_rep_sw_rev_nosup

Severity: Varies **Component:** sec

Text: replica cannot support the specified software version

Explanation: An attempt was made to create a replica that cannot support the software version currently in effect at the master, or an admin operation to set the software version failed at the master because the master does not support the specified version.

Action: Find out what versions the security master can support and specify a correct version, or install a new binaries that can support the desired software version.

0x17122182 sec_rgy_rep_sw_rev_outstanding

Severity: Varies **Component:** sec

Text: A previous security server software version change is still underway

Explanation: Admin user attempted to set the security service software version before a previous version change had completed.

Action: Wait for the outstanding version change to complete before issuing another

0x171220ba sec_rgy_rep_update_seqno_high

Severity: Varies **Component:** sec

Text: slave must have missed/lost some update from master

Explanation: Slave must have missed/lost some update from the master.

Action: If problem does not correct itself with propagations from the master, then the replica may need to be initialized with a security administration tool.

0x171220bb sec_rgy_rep_update_seqno_low

Severity: Varies **Component:** sec

Text: slave received an old update from master

Explanation: Registry replica received an update from a master registry that is older than updates already received by the replica. Either the replica is accepting the new master and should automatically reinitialize itself from this master, or it believes that the master has an obsolete database and it will shut down.

Action: Ensure that an obsolete master registry server has not been started on the network.

0x17122ebf sec_rgy_rsdb_attr_delete

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Can't delete attribute instance\n%s

Explanation: ?

Action: ?

0x17122ec0 sec_rgy_rsdb_attr_export

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Cannot export attribute instance\n%s

Explanation: When exporting attribute values from database to sec_attr, error occurs.

Action: ?

0x17122ebe sec_rgy_rsdb_attr_import

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Can't import attribute\n%s

Explanation: When importing attribute values in sec_attr to internal buffer area, error occurs.

Action: ?

0x17122ebd sec_rgy_rsdb_attr_set_id

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Cannot set object's attr_list_id\n%s

Explanation: ?

Action: ?

0x17122e78 sec_rgy_rsdb_checkpoint

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Cannot do database checkpoint\n%s

Explanation: ?

Action: ?

0x17122e81 sec_rgy_rsdb_checkpoint_uninit

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Error checkpointing an uninitialized database\n%s

Explanation: When a slave database is re-initializing, in-memory data is cleared and re-created. Problem occurred when trying to do checkpoint on this database.

Action: ?

0x1712207b sec_rgy_server_unavailable

Severity: Varies **Component:** sec

Text: Registry server unavailable

Explanation: Unable to contact a registry server.

Action: Verify that at least one registry server exists and retry the operation.

0x17122d0f sec_rgy_set_stack_size

Severity: Fatal **Component:** sec/sec_s_general

Text: Cannot set stack size for listener threads

Explanation: Cannot set rpc listener thread stack size to be 64*1024.

Action: possible out of memory/swap space?

0x17122d06 sec_rgy_shutdown_done

Severity: Notice **Component:** sec/sec_s_rs_main

Text: Shutdown completed

Explanation: Security server shutdown has been completed.

Action: None required.

0x17122d1d sec_rgy_sigcatch_start_task

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot start signal catch task\n%s

Explanation: Error when trying to start a thread to do signal catch task

Action: ?

0x171220a2 sec_rgy_site_not_absolute

Severity: Varies **Component:** sec

Text: Registry site name must be absolute

Explanation: A non-absolute name specified as the registry site.

Action: Specify an absolute pathname for the registry site.

0x1712209e sec_rgy_s_pgo_is_required

Severity: Varies **Component:** sec

Text: PGO/account is required and can't be deleted

Explanation: Attempted to delete a required PGO or account.

Action: Do not attempt to delete this object.

0x17122d05 sec_rgy_startup_done

Severity: Notice **Component:** sec/sec_s_rs_main

Text: Startup completed

Explanation: Security server initialization has been completed.

Action: None required.

0x17122d16 sec_rgy_svr_register

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot register server\n%s

Explanation: Failed when registering with the rpc runtime and with the endpoint mapper.

Action: ?

0x17122d54 sec_rgy_svr_register_ns

Severity: Fatal **Component:** sec/sec_s_rs_ns

Text: Can't register with name service\n%s

Explanation: ?

Action: ?

0x17122d03 sec_rgy_thr_exit_alert

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Thread is exiting with alert exception

Explanation: ?

Action: ?

0x17122d04 sec_rgy_thr_exit_exc

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Thread is exiting with an exception

Explanation: ?

Action: ?

0x17122d02 sec_rgy_thr_join

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot join with listener task

Explanation: Cannot join pthread tasks

Action: ?

0x17122d1e sec_rgy_thr_set_pool

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot set default thread pool queue length\n%s

Explanation: Prior to setting maximum number of rpc listener threads, a call to set rpc listener threads pool queue length failed,

Action: ?

0x171220a1 sec_rgy_tower_rebind_failed

Severity: Varies **Component:** sec

Text: No usable tower entries

Explanation: ?

Action: None required.

0x17122d0e sec_rgy_unauth_cred_handle_init

Severity: Fatal **Component:** sec/sec_s_rs_main

Text: Cannot create global unauth cred handle

Explanation: Fail to create the global unauth cred handle

Action: possible out of memory/swap space?

0x17122077 sec_rgy_unix_id_changed

Severity: Varies **Component:** sec

Text: Unix id changed on an alias add

Explanation: The specified unix id doesn't match unix id extracted from the specified UUID.

Action: Pass a nil uuid (see uuid_create_nil()) and let the security service create a uuid from the specified unix id.

0x1712208e sec_rgy_uuid_bad_version

Severity: Varies **Component:** sec

Text: Uuid version invalid

Explanation: Version of UUID does not match that expected for this operation. Could occur if the registry server expected a UUID containing an embedded Unix ID, but was passed a generic UUID.

Action: Pass the proper UUID type specified by the particular API in use.

0x17122cc0 sec_rrs_cant_get_next_key

Severity: Fatal **Component:** sec/sec_s_rs_rrs

Text: Could not get current key version

Explanation: ?

Action: ?

0x17122eb7 sec_rsdb_acct_add_curkey

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Attempt to add current key version detected

Explanation: ?

Action: Log a defect.

0x17122192 sec_rsdb_acct_bad_keytype

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Only DES keys allowed for this account

Explanation: An attempt was made to set a non-default keytype for a principal where only DES keys are allowed. Only the krbtgt principal is allowed to have non-default keytypes.

Action: Use a DES keytype.

0x17122eb5 sec_rsdb_acct_cant_getid

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to get account by id

Explanation: ?

Action: Log a defect.

0x17122eb8 sec_rsdb_acct_end_list

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: unexpected end of member list

Explanation: ?

Action: Log a defect.

0x17122eb6 sec_rsdb_acct_noaliases

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Ran out of aliases

Explanation: ?

Action: Log a defect.

0x17122eb4 sec_rsdb_acct_reset

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to reset previous acct info

Explanation: ?

Action: ?

0x17122ecb sec_rsdb_bad_policy_data

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Bad size for policy data

Explanation: ?

Action: Log a defect.

0x17122ecc sec_rsdb_bad_policy_key

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Illegal key for policy data

Explanation: ?

Action: Log a defect.

0x17122ecd sec_rsdb_cant_ctr_item_name

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to construct item name

Explanation: ?

Action: Log a defect.

0x17122ed4 sec_rsdb_cant_get_group_creds

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to obtain credentials for group

Explanation: ?

Action: Log a defect.

0x17122ec9 sec_rsdb_cant_get_item

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to lookup item

Explanation: ?

Action: Log a defect.

0x17122ed2 sec_rsdb_cant_get_item_seqid

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to get item record for sequential id

Explanation: ?

Action: Log a defect.

0x17122ed7 sec_rsdb_cant_get_key

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to get key for sequential id

Explanation: ?

Action: Log a defect.

0x17122ed6 sec_rsdb_cant_get_member_data

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to get membership data

Explanation: ?

Action: Log a defect.

0x17122edb sec_rsdb_cant_get_mgr_typuuid

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Could not get manager type uuid

Explanation: ?

Action: Log a defect.

0x17122ed5 sec_rsdb_cant_get_org_creds

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to obtain credentials for org

Explanation: ?

Action: Log a defect.

0x17122ed3 sec_rsdb_cant_get_person_creds

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to obtain credentials for person

Explanation: ?

Action: Log a defect.

0x17122ec8 sec_rsd_b_cant_get_pgo_creds

Severity: Fatal **Component:** sec/sec_s_rs_rsd_b

Text: Unable to obtain credentials for pgo

Explanation: ?

Action: Log a defect.

0x17122ed9 sec_rsd_b_cant_init_acl

Severity: Fatal **Component:** sec/sec_s_rs_rsd_b

Text: Could not initialize acl list

Explanation: ?

Action: Log a defect.

0x17122ec6 sec_rsd_b_cant_set_auth_policy

Severity: Fatal **Component:** sec/sec_s_rs_rsd_b

Text: Unable to set auth policy

Explanation: ?

Action: Log a defect.

0x17122ec5 sec_rsd_b_cant_set_policy

Severity: Fatal **Component:** sec/sec_s_rs_rsd_b

Text: Unable to set policy

Explanation: ?

Action: Log a defect.

0x17122ec3 sec_rsd_b_cant_set_properties

Severity: Fatal **Component:** sec/sec_s_rs_rsd_b

Text: Unable to set properties

Explanation: ?

Action: Log a defect.

0x17122ec4 sec_rsdb_cant_set_realm

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to set realm

Explanation: ?

Action: Log a defect.

0x17122ed1 sec_rsdb_cant_store_new_item

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Could not store new item

Explanation: ?

Action: Log a defect.

0x17122eca sec_rsdb_cant_walk_alias_chain

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to walk alias chain

Explanation: ?

Action: Log a defect.

0x17122ece sec_rsdb_corrupt_alias_chain

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Database alias chain corrupt

Explanation: ?

Action: Log a defect.

0x17122ea5 sec_rsdb_db_chkpt_err

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Cannot checkpoint database

Explanation: ?

Action: ?

0x17122ed0 sec_rsdb_db_inconsistent

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Database inconsistent

Explanation: ?

Action: Log a defect.

0x17122ea9 sec_rsdb_dbstore_fail

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Database store failed.

Explanation: ?

Action: Log a defect.

0x17122ea1 sec_rsdb_db_unrecog_state

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Database in unrecognized state

Explanation: ?

Action: Use sec_create_db to create a new database.

0x17122eb3 sec_rsdb_db_write_fail

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Write to database failed

Explanation: ?

Action: ?

0x17122ecf sec_rsdb_end_memb_list

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: End of membership list

Explanation: ?

Action: Log a defect.

0x17122ea2 sec_rsdb_ent_not_xlated

Severity: Warning **Component:** sec/sec_s_rs_rsdb

Text: Log entry not translated and so skipped

Explanation: ?

Action: ?

0x17122ed8 sec_rsdb_fetch_error

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Error occurred while fetching data

Explanation: ?

Action: Log a defect.

0x17122ea7 sec_rsdb_file_rename_err

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Cannot rename files during checkpoint

Explanation: ?

Action: ?

0x17122eb1 sec_rsdb_file_stat_fail

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to stat file (file descriptor = %d)

Explanation: ?

Action: Log a defect.

0x17122ec7 sec_rsdb_inconsistent_creds

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Database inconsistent, credentials item length incorrect

Explanation: ?

Action: Log a defect.

0x17122ec1 sec_rsdb_list_not_terminated

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: List was not properly terminated

Explanation: ?

Action: Log a defect.

0x17122ea6 sec_rsdb_log_chkpt_err

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Cannot checkpoint log file

Explanation: ?

Action: ?

0x17122ea4 sec_rsdb_logent_replay_err

Severity: Warning **Component:** sec/sec_s_rs_rsdb

Text: Error occurred replaying log entry and so skipped

Explanation: ?

Action: ?

0x17122ea0 sec_rsdb_log_file_open

Severity: Warning **Component:** sec/sec_s_rs_rsdb

Text: Log file is already open

Explanation: ?

Action: ?

0x17122ec2 sec_rsdb_no_open_slot

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: No open slot in list

Explanation: ?

Action: Log a defect.

0x17122eb2 sec_rsdb_readver_fail

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unable to read version (%d) file

Explanation: ?

Action: Log a defect.

0x17122eaa sec_rsdb_repl_fail

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Database replace failed.

Explanation: ?

Action: Log a defect.

0x17122ea8 sec_rsdb_rep_state_not_saved

Severity: Error **Component:** sec/sec_s_rs_rsdb

Text: Cannot save replica state

Explanation: ?

Action: ?

0x17122eda sec_rsdb_unknown_aclmgr_type

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Unknown ACL manager type

Explanation: ?

Action: Log a defect.

0x17122edf sec_rs_global_lock_fatal_exc

Severity: Fatal **Component:** sec/sec_s_rs_rsdb

Text: Fatal exception while holding global %s lock

Explanation: An exception occurred while a global lock was held.

Action: Log a defect.

0x17122ede sec_rs_lock_fatal_exc

Severity: Fatal **Component:** sec/sec_s_rs_rsdB

Text: Fatal exception while holding %s %s lock

Explanation: An exception occurred while a lock was held. The first %s is the mode string which can be read, write or read-intend-to-write . The second parameter is the type of lock and indicates on what the lock was held - database, replica list, log etc.

Action: Log a defect.

0x17122e00 sec_rs_log_bad_version

Severity: Error **Component:** sec/sec_s_rs_log

Text: Bad version of log file

Explanation: ?

Action: ?

0x17122e06 sec_rs_log_base_prop_seq

Severity: Notice **Component:** sec/sec_s_rs_log

Text: Base propagation sequence in the log header : %s

Explanation: Logged during replay

Action: None required.

0x17122e02 sec_rs_log_file_closed

Severity: Error **Component:** sec/sec_s_rs_log

Text: Cannot write to closed log file

Explanation: The log file was not open.

Action: Internal error. Log a defect.

0x17122d27 sec_rs_login_bad_name

Severity: Error **Component:** sec/sec_s_rs_login

Text: Bad name . %s

Explanation: ?

Action: ?

0x17122d25 sec_rs_login_cant_refresh

Severity: Warning **Component:** sec/sec_s_rs_login

Text: Unable to refresh %s identity . Will idle and retry

Explanation: ?

Action: ?

0x17122d21 sec_rs_login_null_handle

Severity: Error **Component:** sec/sec_s_rs_login

Text: Null registry login handle.

Explanation: ?

Action: Internal error. Log a defect.

0x17122d22 sec_rs_login_null_name

Severity: Error **Component:** sec/sec_s_rs_login

Text: Name is either a NULL pointer or a null string.

Explanation: ?

Action: Internal error. Log a defect.

0x17122d24 sec_rs_login_refresh

Severity: Notice **Component:** sec/sec_s_rs_login

Text: Attempting to refresh context (%s)

Explanation: The thread will attempt to refresh to the login context using the call sec_login_refresh_identity()

Action: ?

0x17122d23 sec_rs_login_refresh_wait

Severity: Notice **Component:** sec/sec_s_rs_login

Text: Context (%s)- wait %d seconds before refreshing

Explanation: The thread will wait for the specified number of seconds before attempting to refresh the login context.

Action: ?

0x17122d20 sec_rs_login_wrong_call

Severity: Fatal **Component:** sec/sec_s_rs_login

Text: rs_login_inherit_host_identity must be called before rs_login_become_rgy

Explanation: Internal error.

Action: Log a defect.

0x17122e01 sec_rs_log_open_fail

Severity: Fatal **Component:** sec/sec_s_rs_log

Text: Failed to open log file

Explanation: ?

Action: ?

0x17122e03 sec_rs_log_propq_add_fail

Severity: Varies **Component:** sec

Text: Add to propagation queue failed.

Explanation: ?

Action: ?

0x17122e04 sec_rs_log_replay

Severity: Notice **Component:** sec/sec_s_rs_log

Text: Attempting to replay the log file

Explanation: Replay the log file.

Action: None required.

0x17122e07 sec_rs_log_replay_entry

Severity: Notice **Component:** sec/sec_s_rs_log

Text: \tReplay: Module=[%s] Op=[%s] Seqno=[%s]

Explanation: Logged during replay

Action: None required.

0x17122e08 sec_rs_log_replay_err

Severity: Error **Component:** sec/sec_s_rs_log

Text: Error replaying log

Explanation: ?

Action: ?

0x17122e05 sec_rs_log_replay_succ

Severity: Notice **Component:** sec/sec_s_rs_log

Text: Successfully replayed the log file

Explanation: Replayed the log file

Action: None required.

0x17122e21 sec_rs_mkey_actver_mismatch

Severity: Fatal **Component:** sec/sec_s_rs_mkey

Text: Account's master_key version doesn't match old or new

Explanation: ?

Action: ?

0x17122e23 sec_rs_mkey_long_keyseed

Severity: Error **Component:** sec/sec_s_rs_mkey

Text: Keyseed too long

Explanation: ?

Action: ?

0x17122e22 sec_rs_mkey_unknown

Severity: Fatal **Component:** sec/sec_s_rs_mkey
Text: Unrecognized master key version decrypting account key
Explanation: ?
Action: ?

0x17122d4c sec_rs_ns_bind_export

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Attempting to export bindings to %s
Explanation: The security server is attempting to export the interfaces to the name space.
Action: None required.

0x17122d4d sec_rs_ns_bind_export_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Successfully exported bindings to %s
Explanation: The bindings have been exported to name space.
Action: None required.

0x17122d4e sec_rs_ns_bind_remove_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Successfully removed bindings from %s
Explanation: The bindings have been exported to name space.
Action: None required.

0x17122d52 sec_rs_ns_cant_rm_member

Severity: Warning **Component:** sec/sec_s_rs_ns
Text: Unable to remove old name (%s)from group (%s)
Explanation: ?
Action: None required.

0x17122d51 sec_rs_ns_cant_rm_name

Severity: Warning **Component:** sec/sec_s_rs_ns
Text: Old name (%s)not removed from nameservice
Explanation: ?
Action: None required.

0x17122d42 sec_rs_ns_grp_ent_create_fail

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Group (%s) entry not created
Explanation: Informational event.
Action: None required.

0x17122d43 sec_rs_ns_grp_ent_create_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Group (%s) entry created
Explanation: Informational event
Action: None required.

0x17122d44 sec_rs_ns_grp_mbr_add_fail

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Member (%s) not added to group (%s)
Explanation: Informational event.
Action: None required.

0x17122d45 sec_rs_ns_grp_mbr_add_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Member (%s) added to group (%s)
Explanation: The member was added to the group.
Action: None required.

0x17122d4f sec_rs_ns_name_del_succ

Severity: Notice **Component:** sec/sec_s_rs_ns

Text: %s removed NSI and from group entry %s

Explanation: The name entry has been deleted successfully from the name space.
The name entry is also no longer a member of the group entry.

Action: None required.

0x17122d50 sec_rs_ns_name_not_removed

Severity: Warning **Component:** sec/sec_s_rs_ns

Text: Old name not removed from nameservice, it may not belong to this server

Explanation: ?

Action: None required.

0x17122d40 sec_rs_ns_null_profile

Severity: Error **Component:** sec/sec_s_rs_ns

Text: Profile name is NULL

Explanation: This is an internal error.

Action: Log a defect

0x17122d41 sec_rs_ns_null_v1_group

Severity: Error **Component:** sec/sec_s_rs_ns

Text: rs_ns_sec_group_name_v1 is NULL.

Explanation: This is an internal error.

Action: Log a defect.

0x17122d46 sec_rs_ns_prof_elt_add_fail

Severity: Notice **Component:** sec/sec_s_rs_ns

Text: Profile element (%s) not added

Explanation: The profile element was not added to cell-profile.

Action: None required.

0x17122d47 sec_rs_ns_prof_elt_add_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Profile element (%s) added
Explanation: The profile element was added to cell-profile.
Action: None required.

0x17122d4a sec_rs_ns_prof_elt_inq_fail

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Profile element inquire failed
Explanation: ?
Action: None required.

0x17122d4b sec_rs_ns_prof_elt_inq_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: Read catalog point: %s from profile: %s
Explanation: ?
Action: None required.

0x17122d48 sec_rs_ns_prof_elt_rm_fail

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: %s Profile element not removed
Explanation: The secidmap to sec mapping could not be removed from cell-profile
Action: None required.

0x17122d49 sec_rs_ns_prof_elt_rm_succ

Severity: Notice **Component:** sec/sec_s_rs_ns
Text: %s Profile element removed
Explanation: The secidmap to sec mapping was removed from cell-profile
Action: None required.

0x17122cd2 sec_rs_pipe_not_created

Severity: Error **Component:** sec/sec_s_rs

Text: Unable to establish parent child pipe

Explanation: ?

Action: ?

0x17122cc1 sec_rs_pwd_bogus_pickle

Severity: Fatal **Component:** sec/sec_s_rs

Text: Bogus password pickle

Explanation: Internal password representation incorrect.

Action: Log a defect.

0x17122e65 sec_rs_rep_incompat_version

Severity: Error **Component:** sec/sec_s_rs_rep

Text: Software version incompatible with master's version. Server is going to exit

Explanation: ?

Action: ?

0x17122e64 sec_rs_rep_not_master

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Replica is no longer the master.

Explanation: ?

Action: ?

0x17122d80 sec_rs_rpc_if_reg_succ

Severity: Notice **Component:** sec/sec_s_rs_rpc

Text: RPC interfaces registered.

Explanation: Security server has successfully registered the server interfaces with the RPC runtime and the end point mapper

Action: None required.

0x17122d83 sec_rs_rpc_if_unreg_succ

Severity: Notice **Component:** sec/sec_s_rs_rpc

Text: RPC interfaces unregistered.

Explanation: Security server has unregistered the server interfaces from the RPC runtime and the end point mapper

Action: None required.

0x17122d85 sec_rs_rpc_inq_bind_err

Severity: Error **Component:** sec/sec_s_rs_rpc

Text: Unable to establish server bindings

Explanation: ?

Action: ?

0x17122d81 sec_rs_rpc_propif_reg_succ

Severity: Notice **Component:** sec/sec_s_rs_rpc

Text: RPC propagation interfaces registered.

Explanation: Security server has successfully registered the interfaces required for security replication with the RPC runtime and the end point mapper.

Action: None required.

0x17122d82 sec_rs_rpc_propif_unreg_succ

Severity: Notice **Component:** sec/sec_s_rs_rpc

Text: RPC propagation interfaces unregistered.

Explanation: Security server has unregistered the interfaces required for security replication from the RPC runtime and the end point mapper.

Action: None required.

0x17122d87 sec_rs_rpc_prot_twr_err

Severity: Error **Component:** sec/sec_s_rs_rpc

Text: Unable to get server's protocol towers

Explanation: ?

Action: ?

0x17122d86 sec_rs_rpc_save_bind_err

Severity: Error **Component:** sec/sec_s_rs_rpc

Text: Unable to save server's bindings

Explanation: ?

Action: ?

0x17122d84 sec_rs_rpc_use_protseq_err

Severity: Error **Component:** sec/sec_s_rs_rpc

Text: Unable to listen on any protocol sequence

Explanation: ?

Action: ?

0x17122da1 sec_rs_thr_create_fail

Severity: Error **Component:** sec/sec_s_rs_thr

Text: Failed to created thread %s

Explanation: The specified thread could not be created . The actual cause of failure is logged prior to this.

Action: Depends on the error logged prior to this message.

0x17122da0 sec_rs_thr_exit_creat_fail

Severity: Varies **Component:** sec

Text: Exiting because thread creation failed.\n

Explanation: The security server exited because thread creation failed. To name of the thread which could not be created and the reason why it could not be created is logged by the status sec_rs_thr_create_fail.

Action: See the action recommended in the status sec_thr_create_fail.

0x17122da3 sec_rs_thr_exiting

Severity: Notice **Component:** sec/sec_s_rs_thr

Text: \"%s\" thread is going to exit

Explanation: The thread is about to exit.

Action: None required.

0x17122da2 sec_rs_thr_started

Severity: Notice **Component:** sec/sec_s_rs_thr

Text: \"%s\" thread started

Explanation: The specified thread has been started. This message is logged by a thread as soon as it is created and starts running.

Action: None required.

0x17122e60 sec_rs_vmcc_cant_register

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Unable to register virtual memory kerberos credential cache type

Explanation: ?

Action: Log a defect

0x17122e61 sec_rs_vmcc_cant_remove

Severity: Fatal **Component:** sec/sec_s_rs_rep

Text: Cannot remove individual credentials from VM ccache

Explanation: ?

Action: Log a defect

0x17122001 sec_s_authz_unsupp

Severity: Varies **Component:** sec

Text: authorization protocol unsupported by authentication protocol.

Explanation: The requested authorization protocol is not supported by the authentication protocol requested.

Action: Application should use an authorization/authentication protocol pair which are supported.

0x1712200d sec_s_bad_key_parity

Severity: Varies **Component:** sec

Text: DES key has bad parity

Explanation: Specified DES key did not pass a parity check.

Action: If error was encountered from a client application, that application may need to be fixed. If error was encountered within the DCE core components, notify support personnel.

0x17122003 sec_s_bad_nonce

Severity: Varies **Component:** sec

Text: incorrect response to challenge

Explanation: Client failed challenge issued by server in RPC DG callback. Could be caused by a bug in DCE, trouble with the network, or possibly a failed security attack.

Action: Ensure network is functioning properly. Ensure no obvious network attacks are in progress. Notify support personnel.

0x1609c006 sec_s_bsafe_alg_operation_unknown

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Unknown operation for an algorithm or algorithm info type

Explanation: Unknown operation for an algorithm or algorithm info type

Action: ?

0x1609c001 sec_s_bsafe_algorithm_already_set

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Algorithm object has already been set with algorithm info

Explanation: Algorithm object has already been set with algorithm info

Action: ?

0x1609c002 sec_s_bsafe_algorithm_info

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid algorithm info format

Explanation: Invalid algorithm info format

Action: ?

0x1609c003 sec_s_bsafe_algorithm_not_initialized

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Algorithm object has not been initialized

Explanation: Algorithm object has not been initialized

Action: ?

0x1609c004 sec_s_bsafe_algorithm_not_set

Severity: Error **Component:** psm/psm_s_bsafe

Text: Algorithm object has not been set with algorithm info

Explanation: Algorithm object has not been set with algorithm info

Action: ?

0x1609c005 sec_s_bsafe_algorithm_obj

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid algorithm object

Explanation: Invalid algorithm object

Action: ?

0x1609c007 sec_s_bsafe_alloc

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Insufficient memory

Explanation: Insufficient memory

Action: ?

0x1609c008 sec_s_bsafe_cancel

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Operation was canceled by the surrender function
Explanation: Operation was canceled by the surrender function
Action: ?

0x1609c009 sec_s_bsafe_data

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Generic data error
Explanation: Generic data error
Action: ?

0x1609c024 sec_s_bsafe_decryption_failure

Severity: Error **Component:** psm/psm_s_psm
Text: BSAFE2: decryption failure
Explanation: Wrong password or key supplied in decryption or verification
Action: Get the right password or key

0x1609c00a sec_s_bsafe_exponent_even

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Public exponent in key pair generation is not allowed to be even
Explanation: Invalid even value for public exponent in key pair generation
Action: ?

0x1609c00b sec_s_bsafe_exponent_len

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Invalid exponent length for public exponent in key pair generation
Explanation: Invalid exponent length for public exponent in key pair generation
Action: ?

0x1609c00c sec_s_bsafe hardware

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Cryptographic hardware error

Explanation: Cryptographic hardware error

Action: ?

0x1609c020 sec_s_bsafe_input_count

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Update called an invalid number of times for inputting data

Explanation: Update called an invalid number of times for inputting data

Action: ?

0x1609c00d sec_s_bsafe_input_data

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid format for input data

Explanation: Invalid format for input data

Action: ?

0x1609c00e sec_s_bsafe_input_len

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid length for input data

Explanation: Invalid length for input data

Action: ?

0x1609c00f sec_s_bsafe_key_already_set

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Key object has already been set with key info

Explanation: Key object has already been set with key info

Action: ?

0x1609c010 sec_s_bsafe_key_info

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid key info format

Explanation: Invalid key info format

Action: ?

0x1609c011 sec_s_bsafe_key_len

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid key length

Explanation: Invalid key length

Action: ?

0x1609c012 sec_s_bsafe_key_not_set

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Key object has not been set with key info

Explanation: Key object has not been set with key info

Action: ?

0x1609c013 sec_s_bsafe_key_obj

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid key object

Explanation: Invalid key object

Action: ?

0x1609c014 sec_s_bsafe_key_operation_unknown

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Unknown operation for a key info type

Explanation: Unknown operation for a key info type

Action: ?

0x1609c015 sec_s_bsafe_memory_obj

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid internal memory object

Explanation: Invalid internal memory object

Action: ?

0x1609c021 sec_s_bsafe_method_not_in_chooser

Severity: Error **Component:** psm/psm_s_bsafe

Text: Algorithm method required by the specified algorithm not in algorithm chooser

Explanation: Algorithm method required by the specified algorithm not in algorithm chooser

Action: ?

0x1609c025 sec_s_bsafe_mod_size_out_of_range

Severity: Error **Component:** psm/psm_s_psm

Text: BSAFE2: key modulus length should be between 256 - 1024

Explanation: key modulus length is too small or too big for public key generation

Action: Get the right modulus length

0x1609c016 sec_s_bsafe_modulus_len

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Invalid modulus length in public or private key

Explanation: Invalid modulus length in public or private key

Action: ?

0x1609c017 sec_s_bsafe_not_initialized

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Algorithm is not properly initialized

Explanation: Algorithm is not properly initialized

Action: ?

0x1609c018 sec_s_bsafe_not_supported

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Unsupported operation requested

Explanation: Unsupported operation requested

Action: ?

0x1609c022 sec_s_bsafe_output_count

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Update called an invalid number of times for outputting data

Explanation: Update called an invalid number of times for outputting data

Action: ?

0x1609c019 sec_s_bsafe_output_len

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Output data is larger than supplied buffer

Explanation: Output data is larger than supplied buffer

Action: ?

0x1609c01a sec_s_bsafe_over_32k

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Data block exceeds 32,767 bytes

Explanation: Data block exceeds 32,767 bytes

Action: ?

0x1609c01b sec_s_bsafe_random_not_initialized

Severity: Error **Component:** psm/psm_s_bsafe

Text: BSAFE2: Random algorithm has not been initialized

Explanation: Random algorithm has not been initialized

Action: ?

0x1609c01c sec_s_bsafe_random_obj

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Invalid algorithm object for the random algorithm
Explanation: Invalid algorithm object for the random algorithm
Action: ?

0x1609c01d sec_s_bsafe_signature

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Invalid signature
Explanation: Invalid signature
Action: ?

0x1609c023 sec_s_bsafe_unknown_error

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Unknown bsafe error
Explanation: Unknown bsafe error
Action: ?

0x1609c01e sec_s_bsafe_wrong_algorithm_info

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Wrong type of algorithm info
Explanation: Wrong type of algorithm info
Action: ?

0x1609c01f sec_s_bsafe_wrong_key_info

Severity: Error **Component:** psm/psm_s_bsafe
Text: BSAFE2: Wrong type of key info
Explanation: Wrong type of key info
Action: ?

0x17122d09 sec_secd_cl_bad_arg

Severity: Error **Component:** sec/sec_s_rs_main

Text: Bad argument for %s option

Explanation: The argument for the specified option is not correct.

Action: Specify the correct options.

0x17122d0c sec_secd_cl_bad_chkpt_interval

Severity: Error **Component:** sec/sec_s_rs_main

Text: Checkpoint interval not a positive number.

Explanation: Checkpoint interval specified on the command line is not a positive number.

Action: Run the command again with a positive value for the checkpoint interval

0x17122d0b sec_secd_cl_locksmith_opt

Severity: Error **Component:** sec/sec_s_rs_main

Text: Option %s can only be specified with -locksmith

Explanation: The specified option is valid and can be used only when -locksmith is also used.

Action: Specify -locksmith along with this option

0x17122d08 sec_secd_cl_missing_arg

Severity: Error **Component:** sec/sec_s_rs_main

Text: Missing argument for %s option

Explanation: The specified option requires an argument which was not specified.

Action: Specify the missing argument for the given option.

0x17122d0a sec_secd_cl_unknown_opt

Severity: Error **Component:** sec/sec_s_rs_main

Text: Unknown command line option : %s

Explanation: The specified option is either invalid or unknown.

Action: Run secd with correct option.

0x17122d07 sec_secd_cl_usage

Severity: Notice **Component:** sec/sec_s_rs_main

Text: Usage: secd [-bootstrap] [-restore_master] [-verbose] [-w serviceability]\n\t\t [-locksmith principal_name [-lockpw] [-remote]]

Explanation: secd started with incorrect arguments

Action: Run secd with correct options and arguments. Consult the secd nmanual page for details.

0x1712200e sec_s_invalid_auth_params

Severity: Varies **Component:** sec

Text: Invalid authentication params

Explanation: Invalid authentication parameter

Action: None required.

0x1712200b sec_s_invalid_nameservice_entry

Severity: Varies **Component:** sec

Text: invalid nameservice entry

Explanation: Registry server encountered an error while processing its nameservice entry. May be caused by an incomplete or incorrect configuration, or by duplicate secd replicas running simultaneously.

Action: Ensure configuration is complete. Ensure no duplicate secd replicas are running on the network.

0x17122f24 sec_site_bind_default

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Attempting to bind to a registry site using file %s

Explanation: ?

Action: None required.

0x17122f22 sec_site_bind_fail

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Failed to bind to registry site %s\n\t%s

Explanation: ?

Action: None required.

0x17122f20 sec_site_bind_start

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Attempting to bind to registry site %s

Explanation: ?

Action: None required.

0x17122f21 sec_site_bind_succ

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Successfully bound to registry site %s

Explanation: ?

Action: None required.

0x17122f23 sec_site_cell_bind_start

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Attempting to bind to an arbitrary registry site in cell %s

Explanation: ?

Action: None required.

0x17122f28 sec_site_lookup_file

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Retrieving RPC string binding handles for %s from file %s

Explanation: ?

Action: None required.

0x17122f2b sec_site_profile_search_fail

Severity: Notice **Component:** sec/sec_s_rybind
Text: Search for a security server using profile %s failed\n\t%s
Explanation: ?
Action: None required.

0x17122f29 sec_site_profile_search_start

Severity: Notice **Component:** sec/sec_s_rybind
Text: Starting search for security server using profile %s
Explanation: ?
Action: None required.

0x17122f2a sec_site_profile_search_succ

Severity: Notice **Component:** sec/sec_s_rybind
Text: Successfully located security server %s using profile %s
Explanation: ?
Action: None required.

0x17122f27 sec_site_rebind_fail

Severity: Notice **Component:** sec/sec_s_rybind
Text: Failed to rebind to an alternate registry site\n\t%s
Explanation: ?
Action: None required.

0x17122f25 sec_site_rebind_start

Severity: Notice **Component:** sec/sec_s_rybind
Text: Attempting to rebind to an alternate registry site
Explanation: ?
Action: None required.

0x17122f26 sec_site_rebind_succ

Severity: Notice **Component:** sec/sec_s_rgybind

Text: Successfully rebound to registry site %s

Explanation: ?

Action: None required.

0x17122002 sec_s_keytype_unsupp

Severity: Varies **Component:** sec

Text: unsupported session key type

Explanation: Most likely an internal error, caused by a defect in DCE.

Action: Notify support personnel.

0x17122012 sec_s_multiple_u2u_reg

Severity: Varies **Component:** sec

Text: server identity has already been registered

Explanation: rpc_server_register_auth_ident() has been called multiple times. Only one identity may be registered per server.

Action: Fix the application that's making the incorrect call.

0x17122009 sec_s_no_key_seed

Severity: Varies **Component:** sec

Text: no random key seed set yet.

Explanation: Security service has not yet been initialized, so there is no random key seed available.

Action: If this error was encountered in an application, that application should be fixed to initialize credentials before trying to use an API that generates a random key. If this error was encountered within DCE core components then notify support personnel.

0x17122007 sec_s_no_memory

Severity: Varies **Component:** sec

Text: unable to allocate memory.

Explanation: Unable to allocate memory for the requested operation.

Action: Check available system swap space and increase if necessary.

0x17122004 sec_s_none_registered

Severity: Varies **Component:** sec

Text: no identity set yet

Explanation: Application programming error. The server has not yet registered its identity with the security runtime.

Action: Application should register its identity with `rpc_server_register_auth_info()` before this point.

0x17122005 sec_s_no_pac

Severity: Varies **Component:** sec

Text: no privilege attributes available

Explanation: Improperly formed RPC authentication protocol message. Most likely caused by a defect in DCE.

Action: Notify support personnel.

0x17122006 sec_s_not_implemented

Severity: Varies **Component:** sec

Text: operation not implemented

Explanation: Requested operation is not implemented by this version of DCE.

Action: Do not attempt the requested operation with this version of DCE.

0x17122008 sec_s_not_trustworthy

Severity: Varies **Component:** sec

Text: data originated by untrustworthy security/privilege server

Explanation: Client field of an incoming ticket was not the known security/privilege server.

Action: Ensure that error is reproducible and not an artifact of someone attempting to break into the system. If error is reproducible, notify support personnel.

0x1712200a sec_s_null_param_illegal

Severity: Varies **Component:** sec

Text: parameter must be non-NULL

Explanation: A NULL argument was passed to the security API where a real argument was expected.

Action: If error was returned from your application, fix the call to the security API. If the error was returned from a base component of DCE then notify support personnel.

0x1712200c sec_s_pgmerr

Severity: Varies **Component:** sec

Text: security server program error

Explanation: Internal security server error.

Action: Notify DCE support personnel of the problem.

0x17122010 sec_s_svr_type_conflict

Severity: Varies **Component:** sec

Text: simultaneous registration of both keytable and identity not supported

Explanation: Application called both `rpc_server_register_auth_info()` and `rpc_server_register_auth_ident()`.

Action: Application should not call `rpc_server_register_auth_info()` and `rpc_server_register_auth_ident()` within the same process.

0x17122011 sec_s_user_to_user_disabled

Severity: Varies **Component:** sec

Text: account is not allowed to use user-to-user protocol registration

Explanation: Attempted to call `rpc_server_register_auth_ident()` with an identity that does not have the user to user flag set in the registry.

Action: Use `rpc_server_register_auth_info()` keytable based registration, or enable the user-to-user flag on the account.

0x1712200f sec_s_v1_1_no_support

Severity: Varies **Component:** sec

Text: security service does not support version 1.1 security features

Explanation: Client attempted to use a DCE1.1 security feature that the server doesn't support.

Action: Don't try to use a 1.1 feature if your security servers don't support them.

0x17122cd1 sec_svc_cant_get_msg

Severity: Varies **Component:** sec

Text: Unable to get message

Explanation: Serviceability component returns a error.

Action: None required.

0x1712217e sec_svc_not_authorized

Severity: Varies **Component:** sec

Text: Not authorized to perform serviceability operation

Explanation: Caller is not authorized to perform the requested serviceability operation.

Action: Determine who is authorized to perform the operation, then use that identity.

0x17122f6a sec_sys_errno_file_text

Severity: Error **Component:** sec/sec_s_syscall

Text: %s : %s

Explanation: The function call returned -1 and errno was set

Action: The action depends on the actual error.

0x17122f61 sec_sys_errno_text

Severity: Error **Component:** sec/sec_s_syscall

Text: %s failed ; errno text : %s

Explanation: The function call returned -1 and errno was set

Action: The action depends on the actual error.

0x17122f62 sec_sys_errno_text_only

Severity: Varies **Component:** sec

Text: errno text : %s

Explanation: The function call returned -1 and errno was set

Action: No action required. This text is logged by the security server and is almost always followed by another error message. That error message should be consulted for the action to be taken.

0x17122f69 sec_sys_file_ftruncate_fail

Severity: Varies **Component:** sec

Text: File could not be truncated (file descriptor = %d)

Explanation: An attempt to truncate the file using the call ftruncate() failed.

Action: ?

0x17122f63 sec_sys_file_lseek_fail

Severity: Varies **Component:** sec

Text: File seek failed (file descriptor = %d)

Explanation: ?

Action: None required.

0x17122f64 sec_sys_file_open_fail

Severity: Varies **Component:** sec

Text: Failed to open file %s

Explanation: ?

Action: None required.

0x17122f67 sec_sys_file_read_error

Severity: Varies **Component:** sec

Text: File read failed (file descriptor = %d)

Explanation: The requested number of bytes were not read from the file.

Action: ?

0x17122f68 sec_sys_file_write_error

Severity: Varies **Component:** sec

Text: File write failed (file descriptor = %d)

Explanation: The requested number of bytes were not written to the file.

Action: ?

0x17122f42 sec_thr_alert

Severity: Varies **Component:** sec

Text: Thread received an alert exception

Explanation: ?

Action: ?

0x17122f41 sec_thr_exit_cancel

Severity: Varies **Component:** sec

Text: %s thread cancelled. Execution terminated.

Explanation: The thread terminated execution because it received a thread cancel exception.

Action: ?

0x17122f43 sec_thr_exit_exc

Severity: Varies **Component:** sec

Text: Thread exiting due to an exception.

Explanation: The thread terminated execution because it received a exception.

Action: ?

0x17122f40 sec_thr_post_cancel

Severity: Varies **Component:** sec

Text: Posting a cancel to thread %s

Explanation: ?

Action: None required.

0x173ca00a svc_s_acl_corrupt

Severity: Varies **Component:** svc

Text: ACL file corrupt

Explanation: The file that stores the serviceability ACL has been corrupted. The global variable **errno** may contain more information.

Action: Restore the file from your backup and restart.

0x173ca00b svc_s_acl_open_error

Severity: Varies **Component:** svc

Text: ACL file could not be opened

Explanation: The file that stores the serviceability ACL cannot be opened for reading. The global variable **errno** may contain more information.

Action: Check the local file permissions and restart the server.

0x173ca00c svc_s_acl_read_error

Severity: Varies **Component:** svc

Text: ACL file could not be read

Explanation: The file that stores the serviceability ACL cannot be read. The global variable **errno** may contain more information.

Action: Check the system for reports of I/O failures, take the appropriate corrective action, and restart the server.

0x173ca00d svc_s_acl_write_error

Severity: Varies **Component:** svc

Text: ACL file could not be written

Explanation: The file that stores the serviceability ACL cannot be written. The global variable **errno** may contain more information.

Action: Check the system for reports of I/O failures, take the appropriate corrective action, and restart the server.

0x173ca007 svc_s_assertion_failed

Severity: Varies **Component:** svc

Text: Assertion **text** failed in **line**

Explanation: A programmer-developed compile-time assertion failed.

Action: Examine the source code to determine the proper action.

0x173ca006 svc_s_at_end

Severity: Varies **Component:** svc

Text: Reached end of file or argument list

Explanation: No more data is available.

Action: None required.

0x173ca004 svc_s_bad_routespec

Severity: Varies **Component:** svc

Text: Bad routing specification

Explanation: The routing specified in **dce_svc_routing** or **dce_svc_debug_routing** is invalid.

Action: The *where* parameter for **dce_svc_routing**, is a three-field routing specification in the format *severity:how:where*. The *where* parameter for **dce_svc_debug_routing** is a four-field routing specification in the format *component:flags:how:where*.

0x173ca005 svc_s_cantopen

Severity: Varies **Component:** svc

Text: Cannot open specified file

Explanation: Permission was denied or the file does not exist. Verify that the filename is correct or fix the permissions. The global variable **errno** may contain more information.

Action: Correct input and try again.

0x173ca003 **svc_s_no_filter**

Severity: Varies **Component:** svc

Text: No filter defined

Explanation: An attempt was made to send data to the filter-control handle for a component that does not have a filter registered.

Action: Verify the component name or do not invoke the operation.

0x173ca001 **svc_s_no_memory**

Severity: Varies **Component:** svc

Text: Out of memory

Explanation: Could not allocate memory for message table, string copy, or other internal requirement.

Action: Increase the swap or paging space or acquire more physical memory. Also check the program for bugs that resulted in bad pointers corrupting the heap allocation area.

0x173ca009 **svc_s_no_perm**

Severity: Varies **Component:** svc

Text: Permission denied

Explanation: There was insufficient permission to change the routing.

Action: Obtain the correct permission (for example, by modifying the ACL) or do not call this function.

0x173ca008 **svc_s_no_stats**

Severity: Varies **Component:** svc

Text: No statistics available

Explanation: This function is not yet implemented.

Action: Do not call this function.

0x00000000 **svc_s_ok**

Severity: Varies **Component:** svc

Text: Successful completion

Explanation: Operation performed.

Action: None required.

0x173ca002 svc_s_unknown_component

Severity: Varies **Component:** svc

Text: Unknown component

Explanation: An attempt was made to find the service handle for a component and could not do so.

Action: Verify that the component name is known or correct the incorrect reference in the program.

0x1771b008 tcl_s_basic_break_outside_of_loop

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invoked \"break\" outside of a loop

Explanation: The **break** command is used outside of a loop. This is not syntactically correct.

Action: Check your code and put the **break** command inside of a loop.

0x1771b00a tcl_s_basic_cmd_return_bad_code

Severity: Unknown **Component:** tcl/tcl_s_general

Text: command returned bad code: %d

Explanation: Return code from the executed command was invalid. It should be either **TCL_BREAK** or **TCL_CONTINUE**.

Action: Application dependent.

0x1771b009 tcl_s_basic_continue_outside_of_loop

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invoked \"continue\" outside of a loop

Explanation: The **continue** command is used outside of a loop. This is not syntactically correct.

Action: Check your code and put the **continue** command inside a loop.

0x1771b005 tcl_s_basic_interp_init_error

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't find [info library]/init.tcl; perhaps you need to \n install Tcl or set your TCL_LIBRARY environment variable?

Explanation: Tcl failed at initialization phase.

Action: If **Tcl** is not installed, install it. If you didn't set **TCL_LIBRARY** environment variable, set it and then execute **Tcl** again.

0x1771b007 tcl_s_basic_invalid_cmd_name

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invalid command name: \"%s\"

Explanation: Tcl detected an invalid command name.

Action: Check the spelling of a command. If the spelling is correct, make sure you are using the valid **Tcl** commands or application commands.

0x1771b006 tcl_s_basic_too_many_nested_calls

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too many nested calls to Tcl_Eval (infinite loop?)

Explanation: Tcl detected nested calls too deep to execute.

Action: Check your **Tcl** code to make sure that no infinite loop exists. Usually, an infinite loop is the reason for this error.

0x1771b015 tcl_s_ckalloc_bytes_allocated_at

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: %d bytes allocated at (%s %d)\n

Explanation: Tcl detected that the internal memory allocation request is invalid.

Action: Write down the message displayed, if possible. Before this message appears, **Tcl** will dump memory information onto a standard error output (**stderr**), so save the memory dump information with this error message. Then report to a vendor.

0x1771b01f tcl_s_ckalloc_error_accessing

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error accessing %s

Explanation: Tcl tried to access a nonexistent variable.

Action: Check the variable name and make sure it exists.

0x1771b017 tcl_s_ckalloc_hi_guard_byte

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: hi guard byte %d is 0x%x \t%c\n

Explanation: Tcl detected that the internal memory allocation request is invalid.

Action: Write down the message displayed, if possible. After this message appears, Tcl will dump memory information onto a standard error output (**stderr**), so save the memory dump information with this error message. Then report to a vendor.

0x1771b018 tcl_s_ckalloc_hi_guard_failed

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: high guard failed at %lx, %s %d\n

Explanation: Tcl detected that the internal memory allocation request is invalid.

Action: Write down the message displayed, if possible. Before this message appears, Tcl will dump memory information onto a standard error output (**stderr**), so save the memory dump information with this error message. Then report to a vendor.

0x1771b013 tcl_s_ckalloc_low_guard_byte

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: low guard byte %d is 0x%x \t%c\n

Explanation: Tcl detected that the internal memory allocation request is invalid.

Action: Write down the message displayed, if possible. After this message appears, Tcl will dump memory information onto a standard error output (**stderr**), so save the memory dump information with this error message. Then report to a vendor.

0x1771b014 tcl_s_ckalloc_low_guard_failed

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: low guard failed at %lx, %s %d\n

Explanation: Tcl detected that the internal memory allocation request is invalid.

Action: Write down the message displayed, if possible. Before this message appears, Tcl will dump memory information onto a standard error output (**stderr**), so save the memory dump information with this error message. Then report to a vendor.

0x1771b016 tcl_s_ckalloc_mem_val_failure

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: Memory validation failure

Explanation: Tcl detected that the internal memory allocation request is invalid.

Action: Write down the message displayed, if possible. Before this message appears, Tcl will dump memory information onto a standard error output (**stderr**), so save the memory dump information with this error message. Then report to a vendor.

0x1771b01b tcl_s_ckalloc_reached_malloc_break_limit

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: reached malloc break limit (%d)\n

Explanation: Tcl detected that too many memory allocation requests were executed internally.

Action: Check your Tcl code and modify the code not to call too many memory allocation commands, like **history**.

0x1771b023 tcl_s_ckalloc_unable_to_alloc

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unable to alloc %d bytes

Explanation: The **malloc** function failed. There is no memory left for a new allocation.

Action: Stop any unnecessary process and try again, or add more memory.

0x1771b019 tcl_s_ckalloc_unable_to_alloc_bytes_line

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: unable to alloc %d bytes, %s line %d

Explanation: The **malloc** function failed. There is no memory left for a new allocation.

Action: Stop any unnecessary process and try again, or add more memory.

0x1771b03a tcl_s_cmdah_arg_index_out_of_range

Severity: Unknown **Component:** tcl/tcl_s_general

Text: \"%n\$\" argument index out of range

Explanation: The **format** command detected that a number of arguments and number of format specifiers that didn't match.

Action: Check your **Tcl** code and correct the discrepancy.

0x1771b038 tcl_s_cmdah_bad_field_spec

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad field specifier \"%c\"

Explanation: The **format** command detected that there was an undefined field specifier in a format string.

Action: Check your **Tcl** code and correct the bad field specifier.

0x1771b039 tcl_s_cmdah_cannot_mix_conversion_specs

Severity: Unknown **Component:** tcl/tcl_s_general

Text: cannot mix \"%\" and \"%n\$\" conversion specifiers

Explanation: The **format** command detected that non-XPG (X/Open Portability Guide) and XPG style format specifiers were mixed in one format string.

Action: Check your **Tcl** code and use either XPG or non-XPG style format specifiers.

0x1771b029 tcl_s_cmdah_could_not_save_cmd_result

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't save command result in variable

Explanation: **Tcl** could not save the **catch** command execution result into a user specified variable.

Action: Check your **Tcl** code for spelling of the variable. Make sure the variable exists.

0x1771b034 tcl_s_cmdah_could_not_set_loop_var

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't set loop variable

Explanation: **Tcl** could not set the **foreach** command loop variable.

Action: Check your **Tcl** code for spelling of the variable. Make sure it exists.

0x1771b037 tcl_s_cmdah_fmt_str_ended_in_middle

Severity: Unknown **Component:** tcl/tcl_s_general

Text: format string ended in middle of field specifier

Explanation: The **format** command detected that the specified format was not complete.

Action: Check your **Tcl** code and complete the format specification.

0x1771b03b tcl_s_cmdah_not_enough_args

Severity: Unknown **Component:** tcl/tcl_s_general

Text: not enough arguments for all format specifiers

Explanation: The **format** command detected that there were not enough arguments specified for all the format specifiers.

Action: Check your **Tcl** code and correct the discrepancy.

0x1771b04e tcl_s_cmdil_bad_level

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad level \"%s\"

Explanation: The **info** command detected that the specified level is not correct.

Action: Check your **Tcl** code to make sure the correct level is used.

0x1771b062 tcl_s_cmdil_bad_search_mode

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad search mode \"%s\": must be -exact, -glob, or -regexp

Explanation: The **lsearch** command detected that the specified search mode is not correct.

Action: Check your **Tcl** command and make sure the spelling of search mode is correct.

0x1771b06a tcl_s_cmdil_com_cmd_ret_non_numeric

Severity: Unknown **Component:** tcl/tcl_s_general

Text: comparison command returned non-numeric result

Explanation: The **lsort** command detected that the user-defined comparison command failed.

Action: Check your **Tcl** command and correct the comparison command accordingly.

0x1771b066 tcl_s_cmdil_command_not_with_comparison

Severity: Unknown **Component:** tcl/tcl_s_general

Text: \"-command\" must be followed by comparison command

Explanation: The **lsort** command detected that **-command** option is not used correctly.

Action: Check your **Tcl** command and use the comparison command with this option.

0x1771b04b tcl_s_cmdil_could_not_store_def_val

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't store default value in variable \"%s\"

Explanation: The **info** command detected that the specified variable cannot be used for storing a default value.

Action: Check your **Tcl** code to make sure the spelling is right for the variable name.

0x1771b05e tcl_s_cmdil_expect_int_or_end

Severity: Unknown **Component:** tcl/tcl_s_general

Text: expected integer or 'end' but got '%s'

Explanation: The **lrange** command needs an integer or the 'end' keyword for the command syntax.

Action: Check your **Tcl** command and use an integer with the **lrange** command.

0x1771b060 tcl_s_cmdilfst_idx_greater_than_second

Severity: Unknown **Component:** tcl/tcl_s_syntax

Text: first index must not be greater than second

Explanation: The **lreplace** command detected that the first index is greater than the second index.

Action: Check your **Tcl** command and specify the larger value for the second index.

0x1771b044 tcl_s_cmdil_is_not_a_proc

Severity: Unknown **Component:** tcl/tcl_s_general

Text: '%s' isn't a procedure

Explanation: The **info** command detected that the number of arguments specified is not correct.

Action: Check your **Tcl** command and specify the correct procedure name.

0x1771b051 tcl_s_cmdil_no_tcl_library

Severity: Unknown **Component:** tcl/tcl_s_general

Text: there is no Tcl library at this installation

Explanation: The **info** command detected that there is no **Tcl** library installed currently.

Action: Install **Tcl** correctly, and try again.

0x1771b04a tcl_s_cmdil_proc_no_argument

Severity: Unknown **Component:** tcl/tcl_s_general

Text: procedure '%s' doesn't have an argument '%s'

Explanation: The **info** command detected that the specified procedure does not have the specified argument.

Action: Check your **Tcl** code to make sure the spelling is right for procedure and argument names.

0x1771b076 tcl_s_cmdmz_bad_comp_code_ok_err_ret_brk

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad completion code \"%s\": must be ok, error, return, break, continue, or an integer

Explanation: The **return** command detected that a bad switch is used.

Action: Check your **Tcl** command and specify the correct return value for the **return** command.

0x1771b095 tcl_s_cmdmz_bad_opr_more_rwu

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad operations \"%s\": should be one or more of rwu

Explanation: The **trace** command detected an invalid operation.

Action: Check your **Tcl** command and specify the correct operation.

0x1771b07b tcl_s_cmdmz_bad_scan_conv_char

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad scan conversion character \"%c\"

Explanation: The **scan** command detected that a wrong conversion character is specified.

Action: Check your **Tcl** command and use the correct conversion character.

0x1771b06f tcl_s_cmdmz_could_not_set_var

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't set variable \"%s\"

Explanation: **Tcl** detected that an error occurred while storing a string into a user-specified variable.

Action: Check your **Tcl** command and make sure you specified an existing variable.

0x1771b073 tcl_s_cmdmz_del_cmd_doesnot_exist

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't delete \"%s\": command doesn't exist

Explanation: The **rename** command detected that the user-specified command does not exist.

Action: Check your **Tcl** command and make sure the command name is spelled right.

0x1771b07c tcl_s_cmdmz_diff_num_var_field

Severity: Unknown **Component:** tcl/tcl_s_general

Text: different numbers of variable names and field specifiers

Explanation: The **scan** command detected that the number of variable names differs from the number of field specifiers provided.

Action: Check your **Tcl** command and make the number of variable names and field specifiers the same.

0x1771b06d tcl_s_cmdmz_err_while_match_pat

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error while matching pattern: %s

Explanation: **Tcl** detected that an error occurred with regular expression matching.

Action: Check your **Tcl** command and make sure you specified the correct regular expression.

0x1771b086 tcl_s_cmdmz_expt_int_or_end

Severity: Unknown **Component:** tcl/tcl_s_general

Text: expected integer or \"end\" but got \"%s\"

Explanation: The **string** command detected that the specified value is invalid.

Action: Check your **Tcl** command and specify the valid value.

0x1771b08c tcl_s_cmdmz_extra_switch_pat_no_body

Severity: Unknown **Component:** tcl/tcl_s_general

Text: extra switch pattern with no body

Explanation: The **switch** command detected that the number of switch pattern exceeds the number of instructions.

Action: Check your **Tcl** command and specify the missing instructions corresponding to the switch pattern, or delete the switch pattern.

0x1771b07a tcl_s_cmdmz fld_width_not_be_specified_in_c_conv

Severity: Unknown **Component:** tcl/tcl_s_general

Text: field width may not be specified in %c conversion

Explanation: The **scan** command detected that the field width is specified with the %c conversion.

Action: Check your **Tcl** command and delete the field width or change the %c conversion.

0x1771b08d tcl_s_cmdmz_no_body_spec_for_pat

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no body specified for pattern \"%s\"

Explanation: The **switch** command detected that no instructions are specified for the pattern.

Action: Check your **Tcl** command and specify the missing instructions corresponding to the pattern, or delete the pattern.

0x1771b074 tcl_s_cmdmz_rename_cmd_already_exist

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't rename to \"%s\": command already exists

Explanation: The **rename** command detected that the user-specified command already exists.

Action: Check your **Tcl** command and make sure the command name is spelled right.

0x1771b075 tcl_s_cmdmz_rename_cmd_doesnot_exist

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't rename \"%s\": command doesn't exist

Explanation: The **rename** command detected that the user-specified command does not exist.

Action: Check your **Tcl** command and make sure the command name is spelled right.

0x1771b079 tcl_s_cmdmz_too_many_fds_to_scan

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too many fields to scan

Explanation: The **scan** command detected that too many fields are specified.

Action: Check your **Tcl** command and reduce the number of fields.

0x1771b06e tcl_s_cmdmz_too_many_substr_var

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too many substring variables

Explanation: The **regexp** command detected too many substring variables.

Action: Check your **Tcl** command and reduce the number of substring variables.

0x1771b098 tcl_s_env_conf_arguments

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: EnvTraceProc called with confusing arguments

Explanation: **Tcl** detected the internal inconsistency for the interpreter.

Action: If the whole 'env' variable is being deleted, this message is displayed, and **Tcl** stops execution. This situation usually happens when the whole interpreter is being deleted. Since **Tcl** stops execution, there is nothing you can do at this point. Reexecute the **Tcl**.

0x1771b099 tcl_s_env_no_interpreter

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: EnvTraceProc couldn't find interpreter

Explanation: **Tcl** detected the internal inconsistency for the interpreter.

Action: If the whole 'env' variable is being deleted, this message is displayed, and **Tcl** stops execution. This situation usually happens when the whole interpreter is being

deleted. Since **Tcl** stops execution, there is nothing you can do at this point. Reexecute the **Tcl**.

0x1771b0a5 tcl_s_expr_arg_math_func_non_numeric

Severity: Unknown **Component:** tcl/tcl_s_general

Text: argument to math function didn't have numeric value

Explanation: The **expr** command detected that an argument to a mathematical function didn't have a numeric value.

Action: Check your **Tcl** code and make sure you used the correct argument.

0x1771b09f tcl_s_expr_colon_without_question

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't have : operator without ? first

Explanation: The **expr** command detected that a colon operator is used without a question mark.

Action: Check your **Tcl** code and add the question mark.

0x1771b09e tcl_s_expr_divide_by_zero

Severity: Unknown **Component:** tcl/tcl_s_general

Text: divide by zero

Explanation: The **expr** command detected that a user-supplied expression contains the division by zero.

Action: Check your **Tcl** code and correct the division operation.

0x1771b0a8 tcl_s_expr_domain_err

Severity: Unknown **Component:** tcl/tcl_s_general

Text: domain error: argument not in valid range

Explanation: The **expr** command detected that the argument value is out of range (out of a domain).

Action: Check your **Tcl** code and correct the argument to fit in a correct domain.

0x1771b0a7 tcl_s_expr_few_args_for_math_func

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too few arguments for math function

Explanation: **expr** command detected too few arguments to mathematical function.

Action: Check your **Tcl** code, and correct the number of arguments.

0x1771b0a1 tcl_s_expr_float_non_numeric_as_op

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't use floating-point value as operand of \"%s\"

Explanation: The **expr** command detected that a floating-point value is used illegally.

Action: Check your **Tcl** code and correct the usage of floating-point.

0x1771b0aa tcl_s_expr_float_val_too_large

Severity: Unknown **Component:** tcl/tcl_s_general

Text: floating-point value too large to represent

Explanation: The **expr** command detected that the supplied floating-point value is too large to represent.

Action: Check your **Tcl** code and correct the floating-point value.

0x1771b0a9 tcl_s_expr_float_val_too_small

Severity: Unknown **Component:** tcl/tcl_s_general

Text: floating-point value too small to represent

Explanation: The **expr** command detected that the supplied floating-point value is too small to represent.

Action: Check your **Tcl** code and correct the floating-point value.

0x1771b09a tcl_s_expr_int_val_too_large

Severity: Unknown **Component:** tcl/tcl_s_general

Text: integer value too large to represent

Explanation: The **expr** command detected that a result of the arithmetic operation overflow.

Action: Check your **Tcl** code and correct your arithmetic expression.

0x1771b0a6 tcl_s_expr_many_args_for_math_func

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too many arguments for math function

Explanation: The **expr** command detected too many arguments to a mathematical function.

Action: Check your **Tcl** code and correct the number of arguments.

0x1771b0a3 tcl_s_expr_non_numeric_exp

Severity: Unknown **Component:** tcl/tcl_s_general

Text: expression didn't have numeric value

Explanation: The **expr** command detected that a numeric value didn't exist with a user-supplied expression.

Action: Check your **Tcl** code and correct the expression to use the numeric value.

0x1771b0a2 tcl_s_expr_non_numeric_non_numeric_as_op

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't use non-numeric string as operand of \"%s\"

Explanation: **expr** command detected a floating-point value is used illegally.

Action: Check your **Tcl** code, and correct the usage of floating-point.

0x1771b09b tcl_s_expr_poor_flat_val_form

Severity: Unknown **Component:** tcl/tcl_s_general

Text: poorly-formed floating-point value

Explanation: The **expr** command detected that a specified floating-point format is not valid.

Action: Check your **Tcl** code and correct the floating-point format. **Tcl** accepts ANSI C forms, which are something like 2.1, 7.91e+16, 6E4, or 3.

0x1771b0a0 tcl_s_expr_syntax_err

Severity: Unknown **Component:** tcl/tcl_s_general

Text: syntax error in expression \"%s\"

Explanation: The **expr** command detected a syntax error in the user-supplied expression.

Action: Check your **Tcl** code and correct the syntax error.

0x1771b0ab tcl_s_expr_unknown_float_point_err

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unknown floating-point error, errno = %s

Explanation: The **expr** command detected an unknown floating-point error.

Action: Check your **Tcl** code and correct the floating-point operation.

0x1771b0a4 tcl_s_expr_unknown_math_func

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unknown math function \"%s\"

Explanation: The **expr** command detected that an invalid mathematical function is used.

Action: Check your **Tcl** code and make sure you spelled the mathematical function name correctly.

0x1771b09d tcl_s_expr_unknown_oper_in_expr

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unknown operator in expression

Explanation: The **expr** command detected an invalid operator in the user-supplied expression.

Action: Check your **Tcl** code and correct the invalid operator.

0x1771b09c tcl_s_expr_unmatch_parens_in_expr

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unmatched parentheses in expression \"%s\"

Explanation: The **expr** command detected an unmatched parenthesis in the user-supplied expression.

Action: Check your **Tcl** code and correct the unmatched parenthesis.

0x1771b0ae tcl_s_get_exp_boolean_but

Severity: Unknown **Component:** tcl/tcl_s_general

Text: expected boolean value but got \"%s\"

Explanation: **Tcl** detected an invalid string for a Boolean value.

Action: Check your **Tcl** code and correct the input for a Boolean value.

0x1771b0ad tcl_s_get_exp_float_but

Severity: Unknown **Component:** tcl/tcl_s_general

Text: expected floating-point number but got \"%s\"

Explanation: **Tcl** detected an invalid string for a floating-point number conversion.

Action: Check your **Tcl** code and correct the input for a floating-point number conversion.

0x1771b0ac tcl_s_get_exp_integer_but

Severity: Unknown **Component:** tcl/tcl_s_general

Text: expected integer but got \"%s\"

Explanation: **Tcl** detected an invalid string for an integer conversion.

Action: Check your **Tcl** code and correct the input for an integer conversion.

0x1771b0b0 tcl_s_glob_dir_unreadable

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't read directory \"%s\": %s

Explanation: The **glob** command could not read the specified directory.

Action: Check your **Tcl** code and make sure you spelled the directory name correctly.

0x1771b0b6 tcl_s_glob_no_files_match_plural

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no files matched glob patterns \"

Explanation: The **glob** command detected that the patterns specified by a user could not match any filename.

Action: Check your **Tcl** command and make sure you spelled glob patterns correctly.

0x1771b0b5 tcl_s_glob_no_files_match_single

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no files matched glob pattern \"

Explanation: The **glob** command detected that the pattern specified by a user could not match any filename.

Action: Check your **Tcl** command and make sure you spelled glob pattern correctly.

0x1771b0b1 tcl_s_glob_no_home_env

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't find HOME environment variable to expand \"%s\"

Explanation: The **glob** command could not perform tilde expansion.

Action: Check your **Tcl** code and make sure you spelled the filename correctly.

0x1771b0b2 tcl_s_glob_no_user

Severity: Unknown **Component:** tcl/tcl_s_general

Text: user \"%s\" doesn't exist

Explanation: The **glob** command could not find a user for tilde expansion.

Action: Check your **Tcl** code and make sure you spelled the filename correctly.

0x1771b0af tcl_s_glob_unmatched_open_brace

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unmatched open-brace in file name

Explanation: The **glob** command detected that unmatched open brace is used within a filename.

Action: Check your **Tcl** code and correct the unmatched open brace in a filename.

0x1771b0b7 tcl_s_hash_bad_bucket_chain

Severity: Unknown **Component:** tcl/tcl_s_general

Text: malformed bucket chain in Tcl_DeleteHashEntry

Explanation: Tcl detected a bad hash table entry in the **Tcl_DeleteHashEntry** function.

Action: Check your **Tcl** command and make sure you do not attempt to delete a non existing hash entry.

0x1771b0bd tcl_s_hash_bogus_create

Severity: Unknown **Component:** tcl/tcl_s_general

Text: called Tcl_CreateHashEntry on deleted table

Explanation: Tcl detected that a nonexisting table is used for the **Tcl_CreateHashEntry** function.

Action: Check your **Tcl** command, and make sure you do not attempt to use a nonexisting hash table.

0x1771b0bc tcl_s_hash_bogus_find

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: called Tcl_FindHashEntry on deleted table

Explanation: Tcl detected that a nonexisting table is used for the **Tcl_FindHashEntry** function.

Action: Check your **Tcl** command, and make sure you do not attempt to use a nonexisting hash table.

0x1771b0ce tcl_s_hist_evt_does_not_appear

Severity: Unknown **Component:** tcl/tcl_s_general

Text: \"%s\" doesn't appear in event

Explanation: The **history** command substitution failed because a specified string didn't match any of the events in a history.

Action: Check your **Tcl** command and specify the correct event for a **history** command.

0x1771b0cb tcl_s_hist_evt_has_not_occurred

Severity: Unknown **Component:** tcl/tcl_s_general

Text: event \"%s\" hasn't occurred yet

Explanation: The **history** command detected that the specified event hasn't occurred yet.

Action: Check your **Tcl** command and specify the correct event for a **history** command.

0x1771b0cd tcl_s_hist_evt_no_matches

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no event matches \"%s\"

Explanation: The **history** command detected that the specified string didn't match any of the events in a history.

Action: Check your **Tcl** command and specify the correct event for a **history** command.

0x1771b0cc tcl_s_hist_evt_too_far_past

Severity: Unknown **Component:** tcl/tcl_s_general

Text: event \"%s\" is too far in the past

Explanation: The **history** command detected that the specified event was executed too far behind to parse.

Action: Check your **Tcl** command and specify the correct event for a **history** command.

0x1771b0cf tcl_s_hist_evt_word_sele_non_existent

Severity: Unknown **Component:** tcl/tcl_s_general

Text: word selector \"%s\" specified non-existent words

Explanation: The **history** command detected that the word selector specified nonexistent words.

Action: Check your **Tcl** command and specify the correct word selector for a **history** command.

0x1771b0ca tcl_s_hist_hist_assert_failed

Severity: Unknown **Component:** tcl/tcl_s_general

Text: Assertion failed!

Explanation: The **history** command tried a history revision, but the amount of space needed for the revised event was too large.

Action: Check your **Tcl** command and make sure your history revision command is correct.

0x1771b0c4 tcl_s_hist_illegal_keep_count

Severity: Unknown **Component:** tcl/tcl_s_general

Text: illegal keep count \"%s\"

Explanation: The **history** command detected that the number specified for the keep count is not correct.

Action: Check your **Tcl** command and specify the correct keep count. The keep count should not be negative, and less than 1000.

0x1771b0e6 tcl_s_link_bad_linked_var_type

Severity: Unknown **Component:** tcl/tcl_s_general

Text: internal error: bad linked variable type

Explanation: **Tcl** detected a bad linked variable type. This is an internal error, which indicates **Tcl** could not recognize C variable value.

Action: Check your **Tcl** command and make sure your C variable is one of **TCL_LINK_INT**, **TCL_LINK_DOUBLE**, **TCL_LINK_BOOLEAN**, or **TCL_LINK_STRING**.

0x1771b0e7 tcl_s_link_linked_var_read_only

Severity: Unknown **Component:** tcl/tcl_s_general

Text: linked variable is read-only

Explanation: **Tcl** detected that a linked variable specified is read-only.

Action: Check your **Tcl** command and make sure you do not try to write a read-only linked variable.

0x1771b0e8 tcl_s_link_linked_var_unreadable

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: internal error: linked variable couldn't be read

Explanation: Tcl detected that a linked variable could not be read. This is an internal error and should not happen.

Action: Keep your **TCL** script and report to the vendor.

0x1771b0eb tcl_s_link_var_must_be_bool

Severity: Unknown **Component:** tcl/tcl_s_general

Text: variable must have boolean value

Explanation: Tcl detected that a nonreal value is used for the **TCL_LINK_BOOLEAN** type linked variable.

Action: Check your **Tcl** command and make sure to store the Boolean value to the linked variable.

0x1771b0e9 tcl_s_link_var_must_be_integer

Severity: Unknown **Component:** tcl/tcl_s_general

Text: variable must have integer value

Explanation: Tcl detected that noninteger value is used for the **TCL_LINK_INT** type linked variable.

Action: Check your **Tcl** command and make sure to store an integer value to the linked variable.

0x1771b0ea tcl_s_link_var_must_be_real

Severity: Unknown **Component:** tcl/tcl_s_general

Text: variable must have real value

Explanation: Tcl detected that a nonreal value is used for the **TCL_LINK_DOUBLE** type linked variable.

Action: Check your **Tcl** command and make sure to store a real value to the linked variable.

0x1771b0d1 tcl_s_main_appl_init_failed

Severity: Unknown **Component:** tcl/tcl_s_general

Text: Tcl_AppInit failed: %s\n

Explanation: An application-specified initialization for **Tcl** failed.

Action: Check your **Tcl** command and make sure your initialization procedure is correct.

0x1771b1a0 tcl_s_multibyte_conv_failed

Severity: Unknown **Component:** tcl/tcl_s_general

Text: multi-byte to wide character conversion failed for \"%s\"

Explanation: **mbstowcs** routine failed internally.

Action: Check if you set a correct **locale** for your environment. If the locale is the right one, check your program logic to make sure that it does not generate a bad multibyte sequence. Then report the problem to the vendor with the error message.

0x1771b0d8 tcl_s_parse_extra_char_brace

Severity: Unknown **Component:** tcl/tcl_s_general

Text: extra characters after close-brace

Explanation: **Tcl** detected, in a braces-quoted string parsing, that extra characters exists.

Action: Check your **Tcl** command and delete the extra characters.

0x1771b0d7 tcl_s_parse_extra_char_quote

Severity: Unknown **Component:** tcl/tcl_s_general

Text: extra characters after close-quote

Explanation: **Tcl** detected, in a double-quoted string parsing, that extra characters exists.

Action: Check your **Tcl** command and delete the extra characters.

0x1771b0d4 tcl_s_parse_missing_c

Severity: Unknown **Component:** tcl/tcl_s_general

Text: missing %c

Explanation: **Tcl** detected, in a double-quoted string parsing, that a terminal character is missing.

Action: Check your **Tcl** command and make sure you are terminating (closing) the double-quoted string.

0x1771b0d5 tcl_s_parse_missing_close_brace

Severity: Unknown **Component:** tcl/tcl_s_general

Text: missing close-brace

Explanation: **Tcl** detected, in a braces-quoted string parsing, that a closing brace is missing.

Action: Check your **Tcl** command and make sure you are closing a braces-quoted string.

0x1771b0d9 tcl_s_parse_missing_close_brace_var

Severity: Unknown **Component:** tcl/tcl_s_general

Text: missing close-brace for variable name

Explanation: **Tcl** detected, in a string parsing, that a variable name is not enclosed within braces.

Action: Check your **Tcl** command and add a closing brace.

0x1771b0d6 tcl_s_parse_missing_close_bracket

Severity: Unknown **Component:** tcl/tcl_s_general

Text: missing close-bracket

Explanation: **Tcl** detected, in a bracket-quoted string parsing, that a closing bracket is missing.

Action: Check your **Tcl** command and make sure you are closing a bracket-quoted string.

0x1771b0de tcl_s_proc_bad_level

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad level \"%s\"

Explanation: The **uplevel** or **upvar** command detected that wrong level information was given.

Action: Check your **Tcl** command and give the correct level information.

0x1771b0e4 tcl_s_proc_break_outside_loop

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invoked \"break\" outside of a loop

Explanation: **Tcl** detected, in the course of executing a user-defined procedure, that **break** is invoked outside of a loop.

Action: Check your **Tcl** command and put the **break** command within a loop.

0x1771b0e2 tcl_s_proc_called_with_too_many_args

Severity: Unknown **Component:** tcl/tcl_s_general

Text: called \"%s\" with too many arguments

Explanation: **Tcl** detected that there were too many arguments specified to a user-defined procedure.

Action: Check your **Tcl** command and specify the correct arguments.

0x1771b0e5 tcl_s_proc_continue_outside_loop

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invoked \"continue\" outside of a loop

Explanation: **Tcl** detected, in the course of executing a user-defined procedure, that **continue** is invoked outside of a loop.

Action: Check your **Tcl** command and put the **continue** command within a loop.

0x1771b0dd tcl_s_proc_no_name_arg

Severity: Unknown **Component:** tcl/tcl_s_general

Text: procedure \"%s\" has argument with no name

Explanation: The **proc** command detected an argument without the name given.

Action: Check your **Tcl** command and give all arguments names.

0x1771b0e1 tcl_s_proc_no_val_given_to_par

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no value given for parameter \"%s\" to \"%s\"

Explanation: Tcl detected that there was no value specified for a parameter to a user-defined procedure.

Action: Check your Tcl command and give the value to a parameter.

0x1771b0dc tcl_s_proc_too_many_fds_in_arg

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too many fields in argument specifier \"%s\"

Explanation: The **proc** command detected that an argument contains too many fields.

Action: Check your Tcl command and specify the correct argument.

0x1771b1a1 tcl_s_single_multibyte_conv_failed

Severity: Unknown **Component:** tcl/tcl_s_general

Text: multi-byte to wide character conversion failed for \"%c\"

Explanation: **mbtowc** routine failed internally.

Action: Check if you set a correct **locale** for your environment. If the locale is the right one, check your program logic to make sure that it does not generate a bad multibyte sequence. Then report the problem to the vendor with the error message.

0x1771b189 tcl_s_tclregexp_corrupted_opcode

Severity: Unknown **Component:** tcl/tcl_s_general

Text: corrupted opcode

Explanation: While matching a regular expression, Tcl detected the internal operation code (opcode) for this operation was corrupted.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b182 tcl_s_tclregexp_corrupted_pgm

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: corrupted program

Explanation: While matching a regular expression, **Tcl** detected that the internal **regexp** program was wrong.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b184 tcl_s_tclregexp_corrupted_ptr

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: corrupted pointers

Explanation: While matching a regular expression, **Tcl** detected the discrepancy between pointers.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b17e tcl_s_tclregexp_follows_nothing

Severity: Unknown **Component:** tcl/tcl_s_general

Text: ?+* follows nothing

Explanation: While compiling a regular expression, **Tcl** detected that **?**, **+**, or ***** didn't follow anything meaningful.

Action: Check your regular expression given to **Tcl** and correct the problem.

0x1771b180 tcl_s_tclregexp_int_disaster

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: internal disaster

Explanation: While compiling a regular expression, **Tcl** detected that the **strcspn** system call failed.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b185 tcl_s_tclregexp_internal_foulup

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: internal foulup

Explanation: While matching a regular expression, **Tcl** detected the internal discrepancy within the **regrepeat** internal routine.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b17d tcl_s_tclregexp_internal_urp

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: internal inconsistency found

Explanation: While compiling a regular expression, **Tcl** detected some internal inconsistency. This error takes place within the **regatom** internal routine, and it should not happen.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b17b tcl_s_tclregexp_invalid_squ_range

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invalid [] range

Explanation: While compiling a regular expression, **Tcl** detected that the range given with brackets was wrong.

Action: Check your regular expression given to **Tcl**. Correct the invalid range within the brackets.

0x1771b178 tcl_s_tclregexp_junk_end

Severity: Unknown **Component:** tcl/tcl_s_general

Text: junk on end

Explanation: While compiling a regular expression, **Tcl** detected that some unrecognized string followed the regular expression.

Action: Check your regular expression given to **Tcl** and delete an extra string from an end of the regular expression.

0x1771b183 tcl_s_tclregexp_mem_corruption

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: memory corruption

Explanation: While matching a regular expression, **Tcl** detected that the internal memory was corrupted, so it could not continue processing.

Action: Check **errorInfo** global variable information and report the problem to the vendor.

0x1771b17a tcl_s_tclregexp_nested_ops

Severity: Unknown **Component:** tcl/tcl_s_general

Text: nested *?+

Explanation: While compiling a regular expression, **Tcl** detected that the *, +, or ? operand is used within a nested structure.

Action: Check your regular expression given to **Tcl**. You cannot use the *, ?, or + operand within a nested structure.

0x1771b173 tcl_s_tclregexp_null_arg

Severity: Unknown **Component:** tcl/tcl_s_general

Text: NULL argument

Explanation: While compiling a regular expression, **Tcl** detected no regular expression was passed to the routine.

Action: Check your regular expression given to **Tcl** and correct the problem.

0x1771b181 tcl_s_tclregexp_null_parameter

Severity: Unknown **Component:** tcl/tcl_s_general

Text: NULL parameter

Explanation: While matching a regular expression, **Tcl** detected that either the regular expression or the string matching against the regular expression was **NULL**.

Action: Check your regular expression given to **Tcl** and correct the problem.

0x1771b179 tcl_s_tclregexp_op_can_be_empty

Severity: Unknown **Component:** tcl/tcl_s_general

Text: *+ operand could be empty

Explanation: While compiling a regular expression, **Tcl** detected an illegal use of the * or + operand.

Action: Check your regular expression given to **Tcl**. This error occurs when the * or + operand was applied to a possibly null operand.

0x1771b175 tcl_s_tclregexp_out_of_space

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: out of space

Explanation: While compiling a regular expression, **Tcl** could not allocate a necessary amount of memory.

Action: Check your regular expression given to **Tcl** and reduce the complexity of the regular expression. Kill unnecessary processes and try again, or add more memory.

0x1771b174 tcl_s_tclregexp_too_big

Severity: Unknown **Component:** tcl/tcl_s_general

Text: regexp too big

Explanation: While compiling a regular expression, **Tcl** detected that the regular expression was too big to process.

Action: Check your regular expression given to **Tcl** and correct the problem.

0x1771b176 tcl_s_tclregexp_too_many_bra

Severity: Unknown **Component:** tcl/tcl_s_general

Text: too many ()

Explanation: While compiling a regular expression, **Tcl** detected that too many parentheses were used.

Action: Check your regular expression given to **Tcl** and reduce the number of parentheses used.

0x1771b17f tcl_s_tclregexp_trailing_backslash

Severity: Unknown **Component:** tcl/tcl_s_general

Text: trailing backslash

Explanation: While compiling a regular expression, **Tcl** detected that a backslash is the last character for the regular expression given.

Action: Check your regular expression given to **Tcl** and correct the problem.

0x1771b177 tcl_s_tclregexp_unmatch_br

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unmatched ()

Explanation: While compiling a regular expression, **Tcl** detected the incomplete parentheses.

Action: Check your regular expression given to **Tcl** and complete the parentheses used.

0x1771b17c tcl_s_tclregexp_unmatch_squ_bra

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unmatched []

Explanation: While compiling a regular expression, **Tcl** detected that incomplete brackets were used.

Action: Check your regular expression given to **Tcl**. Complete the erroneous bracket expression.

0x1771b16f tcl_s_tclutil_bad_index

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad index \"%s\": must be integer or \"end\"

Explanation: **Tcl** failed to parse a list index.

Action: Check your **Tcl** command and change the bad string to an integer or **end** keyword.

0x1771b172 tcl_s_tclutil_improp_val_prec

Severity: Unknown **Component:** tcl/tcl_s_general

Text: improper value for precision

Explanation: **Tcl** detected a format conversion error in printing a value for the **Tcl_PrintDouble** procedure.

Action: Check your regular expression given to **Tcl**. The reason why compiling the regular expression failed is also displayed.

0x1771b16e tcl_s_tclutil_internal_err_splitlist

Severity: Unknown **Component:** tcl/tcl_s_general

Text: internal error in Tcl_SplitList

Explanation: **Tcl** detected an invalid list structure. **Tcl_SplitList** failed internally.

Action: Check **errorInfo** global variable information and figure out where the problem took place, then correct it.

0x1771b16a tcl_s_tclutil_list_ele_in_braces

Severity: Unknown **Component:** tcl/tcl_s_general

Text: list element in braces followed by \"%. *s\" instead of space

Explanation: **Tcl** detected an invalid list structure. The list element in braces should be followed by space.

Action: Check your **Tcl** command and modify the list structure.

0x1771b16b tcl_s_tclutil_list_ele_in_quotes

Severity: Unknown **Component:** tcl/tcl_s_general

Text: list element in quotes followed by \"%. *s\" instead of space

Explanation: **Tcl** detected an invalid list structure. The list element in quotes should be followed by space.

Action: Check your **Tcl** command and modify the list structure.

0x1771b170 tcl_s_tclutil_reg_compile_err

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't compile regular expression pattern: %s

Explanation: **Tcl** detected an error while compiling the regular expression given.

Action: Check your regular expression given to **Tcl**. The reason why compiling the regular expression failed is also displayed.

0x1771b171 tcl_s_tclutil_reg_match_err

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error while matching regular expression: %s

Explanation: **Tcl** detected an error while performing regular expression matching operation.

Action: Check your regular expression given to **Tcl**. The reason why compiling the regular expression failed is also displayed.

0x1771b16c tcl_s_tclutil_unmatch_open_brace

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unmatched open brace in list

Explanation: **Tcl** detected an invalid list structure. The list was not terminated by a closing brace.

Action: Check your **Tcl** command and modify the list structure.

0x1771b16d tcl_s_tclutil_unmatch_open_quote

Severity: Unknown **Component:** tcl/tcl_s_general

Text: unmatched open quote in list

Explanation: **Tcl** detected an invalid list structure. The list was not terminated by a closing quote.

Action: Check your **Tcl** command and modify the list structure.

0x1771b19f tcl_s_tclvar_dangling_upvar

Severity: Unknown **Component:** tcl/tcl_s_general

Text: upvar refers to element in deleted array

Explanation: **Tcl** detected that the array didn't exist.

Action: Check your **Tcl** code to make sure you spelled the element name correctly.

0x1771b19a tcl_s_tclvar_illegal_search

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't find search \"%s\"

Explanation: Tcl detected that the specified search failed.

Action: Depends on the application.

0x1771b198 tcl_s_tclvar_illegal_search_id

Severity: Unknown **Component:** tcl/tcl_s_general

Text: illegal search identifier \"%s\"

Explanation: Tcl detected that the specified search identifier was wrong.

Action: Check Tcl code and correct the search identifier.

0x1771b19d tcl_s_tclvar_is_array

Severity: Unknown **Component:** tcl/tcl_s_general

Text: variable is array

Explanation: Tcl detected that the variable specified by the user was an array.

Action: Check your Tcl code to make sure you spelled the variable name correctly.

0x1771b18e tcl_s_tclvar_isnt_array

Severity: Unknown **Component:** tcl/tcl_s_general

Text: \"%s\" isn't an array

Explanation: The **array** command detected that the argument specified was not an array.

Action: Check the Tcl code and specify an array to the **array** command.

0x1771b19e tcl_s_tclvar_need_array

Severity: Unknown **Component:** tcl/tcl_s_general

Text: variable isn't array

Explanation: Tcl detected that the variable specified by the user was not an array.

Action: Check your Tcl code to make sure you spelled the variable name correctly.

0x1771b19c tcl_s_tclvar_no_such_ele

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no such element in array

Explanation: **Tcl** detected that the element specified by the user didn't exist in an array.

Action: Check your **Tcl** code to make sure you spelled the element name correctly.

0x1771b19b tcl_s_tclvar_no_such_var

Severity: Unknown **Component:** tcl/tcl_s_general

Text: no such variable

Explanation: **Tcl** detected that the variable specified by the user was wrong.

Action: Check your **Tcl** code to make sure you spelled the variable name correctly.

0x1771b199 tcl_s_tclvar_search_id_var

Severity: Unknown **Component:** tcl/tcl_s_general

Text: search identifier \"%s\" isn't for variable \"%s\"

Explanation: **Tcl** detected that the specified search identifier and variable combination was wrong.

Action: Check your **Tcl** code and correct the search identifier or the variable displayed.

0x1771b196 tcl_s_tclvar_var_already_exists

Severity: Unknown **Component:** tcl/tcl_s_general

Text: variable \"%s\" already exists

Explanation: The **upvar** or **global** command detected that the specified variable already exists.

Action: Check your **Tcl** code and correct the spelling of variable, or make sure the variable does not exist.

0x1771b0ee tcl_s_test_bogus_interpreter

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bogus interpreter argument!

Explanation: **Tcl** detected that the interpreter passed to **Tcl_CallWhenDeleted** was not valid.

Action: Check your **Tcl** command and make sure to pass the valid interpreter to the **Tcl_CallWhenDeleted** call.

0x1771b118 tcl_s_unixaz_access_mode_must_inc

Severity: Unknown **Component:** tcl/tcl_s_general

Text: access mode must include either RONLY, WRONLY, or RDWR

Explanation: The **open** command detected that the access mode didn't include the required mode.

Action: Check your **Tcl** command and add the necessary access mode.

0x1771b116 tcl_s_unixaz_access_mode_not_supported

Severity: Unknown **Component:** tcl/tcl_s_general

Text: access mode \"%s\" not supported by this system

Explanation: The **open** command detected that the access mode specified was not supported.

Action: The **NOCTTY** access mode is not supported by this system. Do not use it.

0x1771b0f6 tcl_s_unixaz_cannot_change_work_dir

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't change working directory to \"%s\": %s

Explanation: The **cd** command could not change the current working directory to a user-specified directory.

Action: Check your **Tcl** command and make sure you spelled a directory name correctly, or that the directory exists.

0x1771b111 tcl_s_unixaz_cannot_open

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't open \"%s\": %s

Explanation: The **open** command could not open the specified file.

Action: Check your **Tcl** command and make sure you spelled a filename correctly, or that the file exists.

0x1771b112 tcl_s_unixaz_cannot_read_output

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't read output from command: standard output was redirected

Explanation: The **open** command detected that standard output was redirected.

Action: Check your **Tcl** command and correct the wrong redirection.

0x1771b113 tcl_s_unixaz_cannot_write_input

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't write input to command: standard input was redirected

Explanation: The **open** command detected that standard input was redirected.

Action: Check your **Tcl** command and correct the wrong redirection.

0x1771b12c tcl_s_unixaz_child_abend_exit

Severity: Unknown **Component:** tcl/tcl_s_general

Text: child process exited abnormally

Explanation: The **Tcl** command failed, and the child process existed abnormally.

Action: Check other **Tcl** error messages within the **errorInfo** global variable, then correct the failed **Tcl** command.

0x1771b128 tcl_s_unixaz_child_killed

Severity: Unknown **Component:** tcl/tcl_s_general

Text: child killed: %s\n

Explanation: The **Tcl** command failed, and the child process was killed.

Action: Check other **Tcl** error messages within the **errorInfo** global variable, then correct the failed **Tcl** command.

0x1771b12a tcl_s_unixaz_child_st_no_sense

Severity: Unknown **Component:** tcl/tcl_s_general

Text: child wait status didn't make sense\n

Explanation: The **Tcl** command failed, and the child wait status was wrong.

Action: Check other **Tcl** error messages within the **errorInfo** global variable, then correct the failed **Tcl** command.

0x1771b129 tcl_s_unixaz_child_suspended

Severity: Unknown **Component:** tcl/tcl_s_general

Text: child suspended: %s\n

Explanation: The **Tcl** command failed, and the child process was suspended.

Action: Check other **Tcl** error messages within the **errorInfo** global variable, then correct the failed **Tcl** command.

0x1771b11e tcl_s_unixaz_cwd_name_too_long

Severity: Unknown **Component:** tcl/tcl_s_general

Text: working directory name is too long

Explanation: The **pwd** command noticed the supplied directory name was too long to process.

Action: Check your **Tcl** command and make the directory name shorter.

0x1771b0f8 tcl_s_unixaz_error_closing

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error closing \"%s\": %s\n

Explanation: The **close** command could not close the specified file.

Action: Check your **Tcl** command and make sure you spelled a filename correctly, or that the file exists.

0x1771b123 tcl_s_unixaz_error_during_seek

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: error during seek: %s

Explanation: The **seek** command detected that the **fseek** system call failed.

Action: Write down your **Tcl** command and the error message, then report to the vendor.

0x1771b10d tcl_s_unixaz_error_flushing

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error flushing \"%s\": %s

Explanation: The **flush** command could not flush the specified file.

Action: Check your **Tcl** command and make sure you spelled a filename correctly, or that the file exists.

0x1771b0fb tcl_s_unixaz_error_read_from_out_pipe

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: error reading from output pipe: %s

Explanation: The **exec** command detected that the reading from output pipe failed.

Action: Save your **Tcl** script, write down the error message, and report to the vendor.

0x1771b10f tcl_s_unixaz_error_reading

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: error reading \"%s\": %s

Explanation: The **gets** command could not read the specified file.

Action: Write down your **Tcl** command and the error message, then report to the vendor.

0x1771b12b tcl_s_unixaz_error_read_stderr

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: error reading stderr output file: %s

Explanation: The **read** system call failed internally.

Action: Write down your **Tcl** command and the error message, then report to the vendor.

0x1771b127 tcl_s_unixaz_error_wait_exit

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: error waiting for process to exit: %s

Explanation: The `waitpid` system call failed internally.

Action: Write down your `Tcl` command and the error message, then report to the vendor.

0x1771b11f tcl_s_unixaz_error_with_cwd_name

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error getting working directory name: %s

Explanation: The `pwd` command could not get the current directory name.

Action: Check your `Tcl` command and make sure you spelled the directory name correctly, or verify that the directory exists.

0x1771b11c tcl_s_unixaz_error_writing

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: error writing \"%s\": %s

Explanation: The `puts` command could not write to the specified file.

Action: Write down your `Tcl` command and the error message, then report to the vendor.

0x1771b114 tcl_s_unixaz_illegal_access_mode

Severity: Unknown **Component:** tcl/tcl_s_general

Text: illegal access mode \"%s\"

Explanation: The `open` command detected that the access mode specified was illegal.

Action: Check your `Tcl` command and correct the wrong access mode. The valid access modes are `r`, `w`, and `a`.

0x1771b117 tcl_s_unixaz_invalid_access_mode

Severity: Unknown **Component:** tcl/tcl_s_general

Text: invalid access mode \"%s\": must be RDONLY, WRONLY, RDWR, APPEND, CREAT, EXCL, NOCTTY, NONBLOCK, or TRUNC

Explanation: The `open` command detected that the access mode specified was wrong.

Action: Check your `Tcl` command and correct the wrong access mode as specified.

0x1771b100 tcl_s_unixaz_no_lstat

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't lstat \"%s\": %s

Explanation: The **file** command detected that the **lstat** command failed with a user-specified argument.

Action: Save your **Tcl** script, write down the error message, and report to the vendor. This error indicates that the **lstat** system call failed.

0x1771b101 tcl_s_unixaz_no_readlink

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't readlink \"%s\": %s

Explanation: The **file** command detected that the **readlink** operation failed with a user-specified argument.

Action: Save your **Tcl** script, write down the error message, and report to the vendor. This error indicates that the **readlink** system call failed.

0x1771b103 tcl_s_unixaz_no_stat

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't stat \"%s\": %s

Explanation: The **file** command detected that the **stat** command failed with a user-specified-argument.

Action: Save your **Tcl** script, write down the error message, and report to the vendor. This error indicates that the **stat** system call failed.

0x1771b12d tcl_s_unixstr_unknown_err

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: unknown error

Explanation: The **Tcl** command failed, and the current **errno** value was not recognized.

Action: Check other **Tcl** error messages within the **errorInfo** global variable, then guess the cause of failure. If you cannot make any guess, report to the vendor.

0x1771b12e tcl_s_unixstr_unknown_signal

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: unknown signal

Explanation: The **Tcl** command execution generated a signal, but **Tcl** could not recognize the signal.

Action: Check other **Tcl** error messages within the **errorInfo** global variable, then guess the cause of failure. If you cannot make any guess, report to the vendor.

0x1771b166 tcl_s_unixutil_bad_file_id

Severity: Unknown **Component:** tcl/tcl_s_general

Text: bad file identifier \"%s\"

Explanation: **Tcl** detected that a file ID passed to the **Tcl_GetOpenFile** routine was invalid.

Action: Check **errorInfo** global variable information and figure out where the problem took place, then correct it.

0x1771b15c tcl_s_unixutil_cannot_create_input_pipe

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't create the input pipe for command: %s

Explanation: **Tcl** could not create the input pipe specified.

Action: The **pipe** system call failed internally. The reason why the **pipe** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b15d tcl_s_unixutil_cannot_create_output_pipe

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't create output pipe: %s

Explanation: **Tcl** could not create the output pipe specified.

Action: The **pipe** system call failed internally. The reason why the **pipe** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b160 tcl_s_unixutil_cannot_create_pipe

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't create pipe: %s

Explanation: Tcl could not create a specified pipe.

Action: The **pipe** system call failed internally. The reason why the **pipe** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b15e tcl_s_unixutil_cannot_creat_err_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't create error file for command: %s

Explanation: Tcl could not create error file with a command that uses a pipeline.

Action: The **open** system call failed internally. Check the permission of a directory in which your Tcl command tried to create a file. The reason why the **open** system call failed is also displayed.

0x1771b159 tcl_s_unixutil_cannot_creat_input_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't create input file for command: %s

Explanation: Tcl could not create input file with a command that uses a pipeline.

Action: The **open** system call failed internally. Check the permission of a directory in which your Tcl command tried to create a file. The reason why the **open** system call failed is also displayed.

0x1771b162 tcl_s_unixutil_cannot_fork_chld_proc

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't fork child process: %s

Explanation: Tcl could not fork a child process.

Action: The **fork** system call failed internally. The reason why the **pipe** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b165 tcl_s_unixutil_cannot_read_file

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't read file \"%s\": %s

Explanation: Tcl could not read a file.

Action: The **open** system call failed internally while processing redirection. The reason why the **open** system call failed is also displayed. Check your **Tcl** command to make sure the file you specified exists. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b15f tcl_s_unixutil_cannot_remove_err_file

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't remove error file for command: %s

Explanation: Tcl could not remove file with a command that uses pipeline.

Action: The **unlink** system call failed internally. The reason why the **unlink** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b15b tcl_s_unixutil_cannot_reset_remove_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't reset or remove input file for command: %s

Explanation: Tcl could not reset a file pointer or remove a file with a command that uses pipeline.

Action: The **lseek** or **unlink** system call failed internally. The reason why the **seek** or **unlink** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b157 tcl_s_unixutil_cannot_spec_as_last

Severity: Unknown **Component:** tcl/tcl_s_general

Text: can't specify \"%s\" as last word in command

Explanation: Tcl detected an illegal syntax for using a pipeline in a command or redirection in a command.

Action: Check your **Tcl** command and eliminate the illegal syntax for using a pipeline or redirection in a command.

0x1771b163 tcl_s_unixutil_cannot_write_file

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't write file \"%s\": %s

Explanation: **Tcl** could not write a file.

Action: **open** system call failed internally while processing redirection. The reason why the **open** system call failed is also displayed. Check your **Tcl** command to make sure the file you specified exists. After you examined **errorInfo** global variable information, and could not make sense, report the error to the vendor.

0x1771b15a tcl_s_unixutil_cannot_write_file_input

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't write file input for command: %s

Explanation: **Tcl** could not write file with a command with pipeline.

Action: The **write** system call failed internally. Check the permission of a directory your **Tcl** command tried to write a file. The reason why the **write** system call failed is also displayed. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b154 tcl_s_unixutil_err_close_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error closing file \"%s\": \"%s\"

Explanation: **Tcl** detected an error when it tried to close a specified file.

Action: Check other **Tcl** error messages within the **errorInfo** global variable. The reason why the **close** operation failed is also displayed. Based on the information you got, take an appropriate action.

0x1771b153 tcl_s_unixutil_err_read_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: error in reading file \"%s\": \"%s\"

Explanation: Tcl detected an error while reading a specified file.

Action: Check other **Tcl** error messages within the **errorInfo** global variable. The reason why the **read** operation failed is also displayed. Based on the information you got, take an appropriate action.

0x1771b167 tcl_s_unixutil_file_not_open

Severity: Unknown **Component:** tcl/tcl_s_general

Text: file \"%s\" isn't open

Explanation: Tcl detected that a file ID passed to the **Tcl_GetOpenFile** routine was not open.

Action: Check **errorInfo** global variable information and figure out where the problem took place, then correct it.

0x1771b169 tcl_s_unixutil_file_not_open_reading

Severity: Unknown **Component:** tcl/tcl_s_general

Text: \"%s\" wasn't opened for reading

Explanation: Tcl detected that a file ID passed to the **Tcl_GetOpenFile** routine was not open for reading.

Action: Check **errorInfo** global variable information and figure out where the problem took place, then correct it.

0x1771b168 tcl_s_unixutil_file_not_open_writing

Severity: Unknown **Component:** tcl/tcl_s_general

Text: \"%s\" wasn't opened for writing

Explanation: Tcl detected that a file ID passed to the **Tcl_GetOpenFile** routine was not open for writing.

Action: Check **errorInfo** global variable information and figure out where the problem took place, then correct it.

0x1771b161 tcl_s_unixutil_forked_proc_useless

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: forked process couldn't set up input/output\n

Explanation: **Tcl** could not set up a pipe correctly.

Action: The **dup2** system call failed internally. After you examine **errorInfo** global variable information and cannot make sense, report the error to the vendor.

0x1771b156 tcl_s_unixutil_illegal_use_pipeline

Severity: Unknown **Component:** tcl/tcl_s_general

Text: illegal use of | or |& in command

Explanation: **Tcl** detected an illegal pipe usage in a user-specified command.

Action: Check your **Tcl** command. This error was probably caused by an unfinished command line. Correct the **Tcl** command to use a pipeline correctly.

0x1771b158 tcl_s_unixutil_no_command_to_exec

Severity: Unknown **Component:** tcl/tcl_s_general

Text: didn't specify command to execute

Explanation: **Tcl** detected that there was no command to execute with a pipeline.

Action: Check your **Tcl** command, which includes a pipeline, and add a command to execute.

0x1771b151 tcl_s_unixutil_no_read_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't read file \"%s\": %s

Explanation: **Tcl** could not read a specified file.

Action: Check other **Tcl** error messages within the **errorInfo** global variable. The reason why the **read** operation failed is also displayed. Based on the information you got, take an appropriate action.

0x1771b152 tcl_s_unixutil_no_stat_file

Severity: Unknown **Component:** tcl/tcl_s_general

Text: couldn't stat file \"%s\": \"%s\"

Explanation: **Tcl** could not get the status of a specified file.

Action: Check other **Tcl** error messages within the **errorInfo** global variable. The reason why the **stat** operation failed is also displayed. Based on the information you got, take an appropriate action.

0x1771b164 tcl_s_unixutil_not_find_to_exec

Severity: Unknown **Component:** tcl/tcl_s_fatal

Text: couldn't find \"%s\" to execute\n

Explanation: **Tcl** could not execute a command specified.

Action: **execvp** system call failed internally. Check your **Tcl** command to make sure the command exists. After you examined **errorInfo** global variable information, and could not make sense, report the error to the vendor.

0x1771b1a2 tcl_s_wchar_conv_failed

Severity: Unknown **Component:** tcl/tcl_s_general

Text: wide character to multi-byte conversion failed

Explanation: Either **wctomb** or **wcstombs** routine failed internally.

Action: Check if you set a correct **locale** for your environment. If the locale is the right one, report to a vendor with the error message.

0x177db088 thd_s_internal_error

Severity: Error **Component:** thd/thd_svc_general

Text: A fatal internal error has occurred in DCE Threads.

Explanation: An internal inconsistency in the DCE Threads library has been detected. The threads library dumped core by raising a SIGIOT signal. The application calling the threads library is not at fault.

Action: Contact the vendor from whom the application was obtained.

0x177db081 thd_s_malloc_failure

Severity: Error **Component:** thd/thd_svc_general

Text: A failed malloc of a necessary internal data structure in the DCE Threads library has resulted in the termination of the program

Explanation: Either the users maximum allowed data limit was exceeded or the system paging space was exhausted

Action: Have your system administrator check your maximum allowable memory and the system paging space availability possibly increasing one or both

0x17083075 tty_bad_data_format

Severity: Varies **Component:** sad

Text: Input not in the expected format (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083079 tty_bad_domain

Severity: Varies **Component:** sad

Text: Operation not valid on the specified domain (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083070 tty_cant_parse

Severity: Varies **Component:** sad

Text: Unable to parse input (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083078 tty_entry_is_required

Severity: Varies **Component:** sad

Text: Required input not found (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083076 tty_err_input_too_long

Severity: Varies **Component:** sad

Text: Input data length exceeds allocated buffer size (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083071 tty_incompatible_options

Severity: Varies **Component:** sad

Text: Incompatible options (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083077 tty_input_out_of_range

Severity: Varies **Component:** sad

Text: Input out of range (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083073 tty_invalid_argument

Severity: Varies **Component:** sad

Text: Unknown or redundant keyword (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083072 tty_invalid_option

Severity: Varies **Component:** sad

Text: Unknown or redundant keyword (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x17083074 tty_opt_requires_arg

Severity: Varies **Component:** sad

Text: Required option argument is missing (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x1708307b tty_PAD1

Severity: Varies **Component:** sad

Text: tty_PAD1

Explanation: ?

Action: None required

0x1708307c tty_PAD2

Severity: Varies **Component:** sad

Text: tty_PAD2

Explanation: ?

Action: None required

0x1708307d tty_PAD3

Severity: Varies **Component:** sad

Text: tty_PAD3

Explanation: ?

Action: None required

0x1708307e tty_PAD4

Severity: Varies **Component:** sad

Text: tty_PAD4

Explanation: ?

Action: None required

0x1708307f tty_PAD5

Severity: Varies **Component:** sad

Text: tty_PAD5

Explanation: ?

Action: None required

0x17083080 tty_PAD6

Severity: Varies **Component:** sad

Text: tty_PAD6

Explanation: ?

Action: None required

0x17083081 tty_PAD7

Severity: Varies **Component:** sad

Text: tty_PAD7

Explanation: ?

Action: None required

0x17083082 tty_PAD8

Severity: Varies **Component:** sad

Text: tty_PAD8

Explanation: ?

Action: None required

0x17083083 tty_PAD9

Severity: Varies **Component:** sad

Text: tty_PAD9

Explanation: ?

Action: None required

0x17083084 tty_PADa

Severity: Varies **Component:** sad

Text: tty_PADa

Explanation: ?

Action: None required

0x17083085 tty_PADb

Severity: Varies **Component:** sad

Text: tty_PADb

Explanation: ?

Action: None required

0x17083086 tty_PADc

Severity: Varies **Component:** sad

Text: tty_PADc

Explanation: ?

Action: None required

0x17083087 tty_PADd

Severity: Varies **Component:** sad

Text: tty_PADd

Explanation: ?

Action: None required

0x17083088 tty_PADe

Severity: Varies **Component:** sad

Text: tty_PADe

Explanation: ?

Action: None required

0x17083089 tty_PADf

Severity: Varies **Component:** sad

Text: tty_PADf

Explanation: ?

Action: None required

0x1708307a tty_pwd_gen_req

Severity: Varies **Component:** sad

Text: Password must be generated by password management server (Registry Editor/TTY Interface)

Explanation: ?

Action: None required

0x16c9a0c7 twr_s_not_implemented

Severity: Varies **Component:** rpc

Text: Not implemented

Explanation: An application attempted to execute code not yet implemented.

Action: Check to see that your application uses only the supported protocol sequences. If the problem persists, report to your vendor.

0x16c9a0c5 twr_s_unknown_sa

Severity: Varies **Component:** rpc

Text: Unknown sockaddr

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a0c6 twr_s_unknown_tower

Severity: Varies **Component:** rpc

Text: Unknown tower

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x1460101f utils_s_802_addr_format

Severity: Varies **Component:** lib

Text: Bad format in IEEE 802 address file

Explanation: In `dce_get_802_addr()` the file containing the IEEE 802 address was found to contain a bad format. Note that the method of determining this address is system-dependent.

Action: Examine the file manually to determine if it is correct.

0x1460101e utils_s_802_cant_read

Severity: Varies **Component:** lib

Text: Could not open or read IEEE 802 address file or device

Explanation: In `dce_get_802_addr()` the file or device containing the IEEE 802 address could not be opened or read. Note that the method of determining this address is system-dependent.

Action: The global variable `errno` may indicate what action to take.

0x14601020 utils_s_802_undef_failure

Severity: Varies **Component:** lib

Text: in IEEE 802 address file

Explanation: In `dce_get_802_addr()` the call to `uname()` failed. Note that the method of determining this address is system-dependent.

Action: The global variable `errno` may indicate what action to take.

0x17e43002 uuidgen_st_cantopen

Severity: Varies **Component:** uid

Text: Cannot open file `file`

Explanation: The `uuidgen` command could not open the specified file for writing.\n

Action: Verify that the file name provided on the `-o` option is valid, that you have the appropriate privilege to write into the file, and that the device is not full.

0x17e43001 uuidgen_st_failure

Severity: Varies **Component:** uid

Text: The **func** call failed with the following error:\n**error text**\n

Explanation: The specified DCE function failed.

Action: Take the corrective action as indicated for the specified error text.

0x16c9a088 uuid_s_bad_version

Severity: Varies **Component:** rpc

Text: Bad UUID version

Explanation: An application passed a UUID as input to the RPC runtime but the UUID was unrecognized.

Action: Fix the application.

0x16c9a08e uuid_s_coding_error

Severity: Varies **Component:** rpc

Text: UUID coding error

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a08a uuid_s_getconf_failure

Severity: Varies **Component:** rpc

Text: get_configuration failure

Explanation: The RPC runtime's UUID generator was unable to get hardware interface configuration information.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a08d uuid_s_internal_error

Severity: Varies **Component:** rpc

Text: Internal error

Explanation: An internal error occurred.

Action: Report the error to your vendor.

0x16c9a08f uuid_s_invalid_string_uuid

Severity: Varies **Component:** rpc

Text: Invalid string UUID

Explanation: The contents of the string passed to **uuid_from_string** was not in the valid UUID string format.

Action: Supply a correctly formatted UUID.

0x16c9a08b uuid_s_no_address

Severity: Varies **Component:** rpc

Text: No IEEE 802 hardware address

Explanation: The RPC runtime's UUID generator was unable to get the local system's IEEE 802 address.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

0x16c9a089 uuid_s_socket_failure

Severity: Varies **Component:** rpc

Text: Socket failure

Explanation: The RPC runtime's UUID generator was unable to create a socket it needs in the course of obtaining the local system's IEEE 802 address.

Action: Make sure the underlying network transport service is working. Try a non-RPC application that uses this service (for example, file transfer or remote login).

Appendix A

Message Numbers and Symbolic Names

The table in this appendix provides a cross-reference between the number of a message and its symbolic name. If you have only the message number to go by, look up that number in the following listing to find the symbolic name. You can then look at the table in Appendix B that contains a cross-reference of message texts and symbolic names to find detailed information about the message.

Message Number	Symbolic Name
0x00000000	dce_cf_st_ok
0x00000000	svc_s_ok
0x00000000	msg_s_ok
0x0000ff01	dce_cf_e_no_match
0x0000ff02	dce_cf_e_no_mem
0x0000ff03	dce_cf_e_file_open

Message Number	Symbolic Name
0x10323001	aud_s_dmn_work_dir
0x10323002	aud_s_dmn_starts
0x10323003	aud_s_dmn_trail_name
0x10323004	aud_s_dmn_trail_size
0x10323005	aud_s_dmn_usage
0x10323006	aud_s_dmn_cannot_get_context
0x10323007	aud_s_dmn_cannot_release_context
0x10323008	aud_s_dmn_cannot_get_mp_context
0x10323009	aud_s_dmn_cannot_open_trail
0x1032300a	aud_s_dmn_cannot_open_central_trail
0x1032300b	aud_s_dmn_ready_to_listen
0x1032300c	aud_s_dmn_register_auth_info
0x1032300d	aud_s_dmn_identity_file
0x1032300e	aud_s_dmn_identity
0x1032300f	aud_s_dmn_binding_file
0x10323010	aud_s_dmn_register_interface
0x10323011	aud_s_dmn_locale
0x10323012	aud_s_dmn_privilege
0x10323013	aud_s_dmn_esl_mutex
0x10323014	aud_s_dmn_state_mutex
0x10323015	aud_s_dmn_trail_mutex
0x10323016	aud_s_dmn_protseq
0x10323017	aud_s_dmn_bindings
0x10323018	aud_s_dmn_acl_obj_init
0x10323019	aud_s_dmn_acl_register_obj_type
0x1032301a	aud_s_dmn_acl_obj_add_user_entry

Message Number	Symbolic Name
0x1032301b	aud_s_dmn_acl_obj_add_group_entry
0x1032301c	aud_s_dmn_acl_obj_add_obj_entry
0x1032301d	aud_s_dmn_acl_obj_add_unauth_entry
0x1032301e	aud_s_dmn_db_open
0x1032301f	aud_s_dmn_db_open_create
0x10323020	aud_s_dmn_db_store_uuid
0x10323021	aud_s_dmn_acl
0x10323022	aud_s_dmn_interfaces
0x10323023	aud_s_dmn_acl_mgr_interface
0x10323024	aud_s_dmn_svc_mgr_export_interface
0x10323025	aud_s_dmn_control_export_interface
0x10323026	aud_s_dmn_svc_mgr_register_bindings
0x10323027	aud_s_dmn_control_register_bindings
0x10323028	aud_s_dmn_auth_info
0x10323029	aud_s_dmn_listener_thread
0x1032302a	aud_s_dmn_thread_join_listener
0x1032302b	aud_s_dmn_distinguished_thread_fault
0x1032302c	aud_s_dmn_non_distinguished_thread_fault
0x1032302d	aud_s_dmn_distinguished_thread_exit
0x1032302e	aud_s_dmn_normal_exit
0x1032302f	aud_s_rgy_server_unavailable
0x10323030	aud_s_wrong_protection_level
0x10323031	aud_s_cannot_authenticate
0x10323032	aud_s_cannot_gettime
0x10323033	aud_s_cannot_getgmtime
0x10323034	aud_s_cannot_audit

Message Number	Symbolic Name
0x10323035	aud_s_permission_denied
0x10323036	aud_s_log_access_denied
0x10323037	aud_s_rpc_count
0x10323038	aud_s_free_encoding_service_handle
0x10323039	aud_s_unknown_principal_rc
0x1032303a	aud_s_unknown_principal
0x1032303b	aud_s_unknown_foreign_principal_rc
0x1032303c	aud_s_unknown_foreign_principal
0x1032303d	aud_s_unknown_group_rc
0x1032303e	aud_s_unknown_group
0x1032303f	aud_s_unknown_foreign_group_rc
0x10323040	aud_s_unknown_foreign_group
0x10323041	aud_s_unknown_cell_rc
0x10323042	aud_s_unknown_cell
0x10323043	aud_s_invalid_guide
0x10323044	aud_s_invalid_esl_type_rc
0x10323045	aud_s_invalid_esl_type
0x10323046	aud_s_invalid_action_bit_set
0x10323047	aud_s_invalid_condition_bit_set
0x10323048	aud_s_empty_event_class_list
0x10323049	aud_s_trl_invalid_stostrategy
0x1032304a	aud_s_trl_invalid_open_flags
0x1032304b	aud_s_rename_trail_file_rc
0x1032304c	aud_s_rename_trail_file
0x1032304d	aud_s_rename_trail_index_file_rc
0x1032304e	aud_s_rename_trail_index_file

Message Number	Symbolic Name
0x1032304f	aud_s_cannot_reopen_trail_file_rc
0x10323050	aud_s_cannot_reopen_trail_file
0x10323051	aud_s_cannot_reopen_trail_index_file_rc
0x10323052	aud_s_cannot_reopen_trail_index_file
0x10323053	aud_s_rename_esl_file
0x10323054	aud_s_rename_esl_update_file
0x10323055	aud_s_lock_esl_file
0x10323056	aud_s_open_esl_file
0x10323057	aud_s_open_esl_update_file
0x10323058	aud_s_stat_esl_update_file
0x10323059	aud_s_retry_lock_esl_updt_file
0x1032305a	aud_s_wrong_version_esl_updt_file
0x1032305b	aud_s_cant_open_client_binding_file_rc
0x1032305c	aud_s_cant_open_client_binding_file
0x1032305d	aud_s_remove_file_client_update_binding_failed
0x1032305e	aud_s_remove_dir_client_update_binding_failed
0x1032305f	aud_s_unable_to_sync_client
0x10323060	aud_s_trl_write_failure
0x10323061	aud_s_trl_full
0x10323062	aud_s_dmn_disabled
0x10323063	aud_s_dmn_disabled_in_selfaudit
0x10323064	aud_s_uuid_hash_failed
0x10323065	aud_s_retry_lock_esl_file
0x10323066	aud_s_wrong_esl_file_version
0x10323067	aud_s_wrong_esl_updt_file_version
0x10323068	aud_s_cannot_allocate_memory

Message Number	Symbolic Name
0x10323069	aud_s_cannot_read_file
0x1032306a	aud_s_action_bit_set
0x1032306b	aud_s_condition_bit_set
0x1032306c	aud_s_evt_classes
0x1032306d	aud_s_invalid_event_class_file
0x1032306e	aud_s_unknown_event_class
0x1032306f	aud_s_line_too_long_in_class_file
0x10323070	aud_s_invalid_line_in_class_file
0x10323071	aud_s_cannot_open_event_class_file
0x10323072	aud_s_cannot_open_event_class_dir
0x10323073	aud_s_no_filter
0x10323074	aud_s_no_current_login_context
0x10323075	aud_s_cannot_open_dmn_binding_file
0x10323076	aud_s_cannot_open_dmn_identity_file
0x10323077	aud_s_stat_esl_file
0x10323078	aud_s_cannot_mkdir
0x10323079	aud_s_cannot_open_trail_file_rc
0x1032307a	aud_s_cannot_open_trail_file
0x1032307b	aud_s_client_esl_mutex
0x1032307c	aud_s_trail_file_corrupted
0x1032307d	aud_s_invalid_record_descriptor
0x1032307e	aud_s_invalid_outcome
0x1032307f	aud_s_outcomes_inconsistent
0x10323080	aud_s_invalid_trail_descriptor
0x10323081	aud_s_evt_tail_info_exceeds_limit
0x10323082	aud_s_trl_file_size_limit

Message Number	Symbolic Name
0x10323083	aud_s_invalid_audit_trail_size_limit
0x10323084	aud_s_cannot_init_trail_mutex
0x10323085	aud_s_dmn_create_update_thread
0x10323086	aud_s_client_updt_mutex_init_fail
0x10323087	aud_s_client_updt_cond_init_fail
0x10323088	aud_s_client_updt_mutex_lock_fail
0x10323089	aud_s_client_updt_mutex_unlock_fail
0x1032308a	aud_s_updt_opendir_fail
0x1032308b	aud_s_got_server_uuid
0x1032308c	aud_s_rewind_trail_file
0x1032308d	aud_s_rewind_index_file
0x10d0a001	CDS_SUCCESS
0x10d0a003	CDS_PENDING
0x10d0a064	cds_s_cache_semop
0x10d0a065	cds_s_cache_toosmall
0x10d0a066	cds_s_cache_writeshmid
0x10d0a067	cds_s_cache_createshmid
0x10d0a068	cds_s_cache_openshmid
0x10d0a069	cds_s_cache_readshmid
0x10d0a06a	cds_s_cache_badheaderid
0x10d0a06b	cds_s_cache_inuse
0x10d0a06c	cds_s_cache_creatormapped
0x10d0a06d	cds_s_cache_usermapped
0x10d0a06e	cds_s_cache_rmid
0x10d0a06f	cds_s_cache_reuseid
0x10d0a070	cds_s_cache_shmidremove

Message Number	Symbolic Name
0x10d0a071	cds_s_cache_createversion
0x10d0a072	cds_s_cache_readversion
0x10d0a073	cds_s_cache_badversion
0x10d0a074	cds_s_cache_opencache
0x10d0a075	cds_s_cache_readcache
0x10d0a076	cds_s_cache_badcacheheader
0x10d0a077	cds_s_cache_oldversion
0x10d0a078	cds_s_cache_cachesize
0x10d0a079	cds_s_cache_writcache
0x10d0a07a	cds_s_cache_createcache
0x10d0a07b	cds_s_cache_snapshot_file
0x10d0a07c	cds_s_cache_header_a
0x10d0a07d	cds_s_cache_pattern_a
0x10d0a07e	cds_s_cache_inuse_a
0x10d0a07f	cds_s_cache_flink_a
0x10d0a080	cds_s_cache_blink_a
0x10d0a081	cds_s_cache_type_a
0x10d0a082	cds_s_cache_version_a
0x10d0a083	cds_s_cache_clock_a
0x10d0a084	cds_s_cache_glock_a
0x10d0a085	cds_s_cache_llock_a
0x10d0a086	cds_s_cache_inlist_a
0x10d0a087	cds_s_cache_notinlist_a
0x10d0a088	cds_s_cache_notinuse_a
0x10d0a089	cds_s_cache_carefs_a
0x10d0a08a	cds_s_cache_islocked_a

Message Number	Symbolic Name
0x10d0a08b	cds_s_cache_nolocked_a
0x10d0a12c	cds_s_gda_startup
0x10d0a12e	cds_s_gda_eb
0x10d0a12f	cds_s_gda_eg
0x10d0a130	cds_s_gda_badnsuuid
0x10d0a131	cds_s_gda_badchuuid
0x10d0a132	cds_s_gda_connect
0x10d0a133	cds_s_gda_writev
0x10d0a134	cds_s_gda_write
0x10d0a135	cds_s_gda_read
0x10d0a136	cds_s_gda_sendto
0x10d0a137	cds_s_gda_nox500
0x10d0a138	cds_s_gda_nodns
0x10d0a139	cds_s_gda_updatepp
0x10d0a13a	cds_s_gda_badreplicatype
0x10d0a13b	cds_s_gda_badtower
0x10d0a13c	cds_s_gda_uuidfile_eb
0x10d0a13d	cds_s_gda_socket
0x10d0a13e	cds_s_gda_bind_eb
0x10d0a13f	cds_s_gda_recvfrom_eb
0x10d0a140	cds_s_gda_list_a
0x10d0a141	cds_s_gda_include
0x10d0a142	cds_s_gda_origin
0x10d0a143	cds_s_gda_dname
0x10d0a144	cds_s_gda_ttl
0x10d0a145	cds_s_gda_class

Message Number	Symbolic Name
0x10d0a146	cds_s_gda_type
0x10d0a147	cds_s_gda_data
0x10d0a148	cds_s_gda_option
0x10d0a149	cds_s_gda_unsupporteddata
0x10d0a14a	cds_s_gda_inorder
0x10d0a14b	cds_s_gda_initsec_eb
0x10d0a14c	cds_s_gda_initrpc_eb
0x10d0a14d	cds_s_gda_export
0x10d0a14e	cds_s_gda_acl_file
0x10d0a14f	cds_s_gda_acl_init
0x10d0a154	cds_s_addcell_cellinfo
0x10d0a155	cds_s_addcell_workspace
0x10d0a156	cds_s_addcell_nameobj
0x10d0a157	cds_s_addcell_entryexists
0x10d0a158	cds_s_addcell_om
0x10d0a159	cds_s_addcell_success
0x10d0a15b	cds_s_addcell_xds_error
0x10d0a15c	cds_s_addcell_xds_unknown
0x10d0a1f4	cds_s_child_servernotmember
0x10d0a1f5	cds_s_child_badshmem_eb
0x10d0a1f6	cds_s_child_cacheload_eb
0x10d0a1f7	cds_s_child_noshmem_eb
0x10d0a1f8	cds_s_child_nocommunication
0x10d0a1fa	cds_s_child_exiting_eg
0x10d0a1fb	cds_s_child_sigwait_eb
0x10d0a1fc	cds_s_child_signal_eg

Message Number	Symbolic Name
0x10d0a1fd	cds_s_child_starting
0x10d0a2bd	cds_s_adver_cache_a
0x10d0a2be	cds_s_adver_socket
0x10d0a2bf	cds_s_adver_bind
0x10d0a2c0	cds_s_adver_listen
0x10d0a2c1	cds_s_adver_fork
0x10d0a2c2	cds_s_adver_execve
0x10d0a2c3	cds_s_adver_eg
0x10d0a2c4	cds_s_adver_badadver
0x10d0a2c5	cds_s_adver_aclinit
0x10d0a2c6	cds_s_adver_eb
0x10d0a2c7	cds_s_adver_noacl
0x10d0a2c8	cds_s_adver_aclwrite
0x10d0a2c9	cds_s_adver_aclfail
0x10d0a2ca	cds_s_adver_hostfail
0x10d0a2cb	cds_s_adver_groupfail
0x10d0a2cc	cds_s_adver_startup
0x10d0a2cd	cds_s_adver_mkfifo
0x10d0a2ce	cds_s_adver_open
0x10d0a2cf	cds_s_adver_routing
0x10d0a3e9	CDS_INVALIDARGUMENT
0x10d0a3ea	CDS_INVALIDNAME
0x10d0a3eb	CDS_NONSRESOURCES
0x10d0a3ec	CDS_NOCOMMUNICATION
0x10d0a3ed	CDS_ACCESSDENIED
0x10d0a3ee	CDS_CANNOTAUTHENTICATE

Message Number	Symbolic Name
0x10d0a3ef	CDS_CONFLICTINGARGUMENTS
0x10d0a3f0	CDS_TIMEOUTNOTDONE
0x10d0a3f1	CDS_TIMEOUTMAYBEDONE
0x10d0a3f3	CDS_ENTRYEXISTS
0x10d0a3f4	CDS_UNKNOWNENTRY
0x10d0a3f5	CDS_NOTSUPPORTED
0x10d0a3f6	CDS_NOTIMPLEMENTED
0x10d0a3f7	CDS_INVALIDUPDATE
0x10d0a3f8	CDS_UNKNOWNCLEARINGHOUSE
0x10d0a3f9	CDS_NOTAREPLICA
0x10d0a3fa	CDS_ALREADYREPLICA
0x10d0a3fc	CDS_NOTEMPTY
0x10d0a3fd	CDS_NOTLINKED
0x10d0a3fe	CDS_POSSIBLECYCLE
0x10d0a3ff	CDS_DANGLINGLINK
0x10d0a400	CDS_NOTAGROUP
0x10d0a401	CDS_CLEARINGHOUSEDOWN
0x10d0a402	CDS_BADEPOCH
0x10d0a403	CDS_BADCLOCK
0x10d0a404	CDS_DATACORRUPTION
0x10d0a405	CDS_WRONGATTRIBUTETYPE
0x10d0a406	CDS_MORETHANONEREPLICA
0x10d0a408	CDS_OLDSKULK
0x10d0a409	CDS_UNTRUSTEDCH
0x10d0a40a	CDS_VERSIONSKEW
0x10d0a40b	CDS_NEWVERSIONSKEW

Message Number	Symbolic Name
0x10d0a44d	CDS_WRONGSTATE
0x10d0a450	CDS_NOTROOT
0x10d0a451	CDS_NOTCHDIRECTORY
0x10d0a452	CDS_ROOTLOST
0x10d0a455	CDS_UNKNOWNATTRIBUTE
0x10d0a456	CDS_NOTINCELL
0x10d0a457	CDS_NOT_AN_ALIAS
0x10d0a458	CDS_PREFERRED_EXISTS
0x10d0a459	CDS_CANNOT_REM_PREFERRED
0x10d0a45a	CDS_MISSING_ALLUPTO
0x10d0a45b	CDS_REM_NOT_SAFE
0x10d0a45c	CDS_MULT_PREFERRED
0x10d0a45d	CDS_CANNOT_REM_CELLNAME
0x10d0a45e	CDS_ALIASTOOLONG
0x10d0a45f	CDS_LOWDIRVERSION
0x10d0a460	CDS_ALIASCYCLE
0x10d0a461	CDS_MISSING_DIRECTORYVERSION
0x10d0a462	CDS_ALIASTOOSHORT
0x10d0a463	CDS_NOTPREFERREDHIERARCHY
0x10d0a464	CDS_NOPREFERRED_EXISTS
0x10d0a7ce	CDS_CLERKBUG
0x10d0a7cf	CDS_NAMESERVERBUG
0x10d0a7d0	CDS_ACCESSVIOLATION
0x10d0a7d1	CDS_RESOURCEERROR
0x10d0a7e9	CDS_NOROOM
0x10d0a89d	CDS_EMPTY

Message Number	Symbolic Name
0x10d0a89f	CDS_SUCCESS_STALE
0x10d0a96c	CDS_SOCKET
0x10d0a96f	CDS_CL_READ
0x10d0a972	CDS_PROPAGATE_FAIL
0x10d0a9c4	cds_s_library_threads
0x10d0a9c5	cds_s_library_refresh
0x10d0a9c6	cds_s_library_refresh_eb
0x10d0a9c7	cds_s_library_pipe
0x10d0a9c8	cds_s_library_fork
0x10d0a9c9	cds_s_library_alreadyrunning
0x10d0a9ca	cds_s_library_cd_eg
0x10d0a9cb	cds_s_library_cdsmalloc_a
0x10d0a9cc	cds_s_library_setsid
0x10d0a9cd	cds_s_library_forkself
0x10d0a9cf	cds_s_library_threadsbug
0x10d0aa28	cds_s_server_startup
0x10d0aa29	cds_s_server_eg
0x10d0aa2a	cds_s_server_eb
0x10d0aa2b	cds_s_server_version_eb
0x10d0aa2c	cds_s_server_loadfail_eb
0x10d0aa2d	cds_s_server_sec_eb
0x10d0aa2e	cds_s_server_dacl_eb
0x10d0aa2f	cds_s_server_newread_eb
0x10d0aa30	cds_s_server_exportfail_eb
0x10d0aa31	cds_s_server_towerfail_eb
0x10d0aa32	cds_s_server_rpc_eb

Message Number	Symbolic Name
0x10d0aa33	cds_s_server_initcomplete
0x10d0aa35	cds_s_server_read
0x10d0aa36	cds_s_server_create
0x10d0aa37	cds_s_server_open
0x10d0aa38	cds_s_server_write
0x10d0aa39	cds_s_server_lseek
0x10d0aa3a	cds_s_server_close
0x10d0aa3b	cds_s_server_unlink
0x10d0aa3c	cds_s_server_setrlimit
0x10d0aa3d	cds_s_server_diag
0x10d0aa3e	cds_s_server_timestamp
0x10d0aa3f	cds_s_server_dbindex
0x10d0aa40	cds_s_server_chstate
0x10d0aa41	cds_s_server_readchaddr
0x10d0aa42	cds_s_server_fixchdir
0x10d0aa43	cds_s_server_creclenomem
0x10d0aa45	cds_s_server_crecleobj
0x10d0aa46	cds_s_server_crecleskulk
0x10d0aa47	cds_s_server_clecrects
0x10d0aa48	cds_s_server_clecrefailed
0x10d0aa49	cds_s_server_rebuildindex_a
0x10d0aa4a	cds_s_server_setbad_a
0x10d0aa4b	cds_s_server_namebad_a
0x10d0aa4c	cds_s_server_gethostname
0x10d0aa4d	cds_s_server_cvtsimple
0x10d0aa4e	cds_s_server_badauthn

Message Number	Symbolic Name
0x10d0aa4f	cds_s_server_badauthz
0x10d0aa50	cds_s_server_dbkeytype_a
0x10d0aa51	cds_s_server_dbnodetype_a
0x10d0aa52	cds_s_server_autofail
0x10d0aa53	cds_s_server_enablefail
0x10d0aa54	cds_s_server_skulkfailevent
0x10d0aa55	cds_s_server_rootlostevent
0x10d0aa56	cds_s_server_pathbrokenevent
0x10d0aa57	cds_s_server_securityevent
0x10d0aa58	cds_s_server_attributemissing
0x10d0aa59	cds_s_server_possiblecycleevent
0x10d0aa5a	cds_s_server_childupdateevent
0x10d0aa5b	cds_s_server_noupgradeevent
0x10d0aa5c	cds_s_server_wrongstate
0x10d0aa5d	cds_s_server_crucialevent
0x10d0aa5e	cds_s_server_clearinghousedeleted
0x10d0aa5f	cds_s_server_clearinghousecreated
0x10d0aa60	cds_s_server_timeback
0x10d0aa78	cds_s_server_skulkstat1
0x10d0aa79	cds_s_server_skulkstat2
0x10d0aa7a	cds_s_server_aliasnotroot
0x10d0aa7b	cds_s_server_aliasnotmaster
0x10d0aa7c	cds_s_server_aliasbadptr
0x10d0aa7d	cds_s_server_aliasmultiprfd
0x10d0aa7e	cds_s_server_aliasnoprfd
0x10d0aa7f	cds_s_server_aliasoverflow

Message Number	Symbolic Name
0x10d0aa80	cds_s_server_aliaschild
0x10d0aa81	cds_s_server_aliasdelchild
0x10d0aa82	cds_s_server_aliascreatesl
0x10d0aa83	cds_s_server_aliasbackoutchild
0x10d0aa84	cds_s_replay_badlog
0x10d0aa85	cds_s_replay_stats
0x10d0aa86	cds_s_replay_dirmem_a
0x10d0aa87	cds_s_replay_dirinternal_a
0x10d0aa88	cds_s_replay_objmem_a
0x10d0aa89	cds_s_replay_objinternal_a
0x10d0aa8a	cds_s_dbcmp_treenotnull_a
0x10d0aa8b	cds_s_dbcmp_toobig_a
0x10d0aa8c	cds_s_dbcmp_1_a
0x10d0aa8d	cds_s_dbcmp_nonnullptr_a
0x10d0aa8e	cds_s_dbcmp_nullfp_a
0x10d0aa8f	cds_s_dbcmp_levelbad_a
0x10d0aa90	cds_s_dbcmp_nullctxstart_a
0x10d0aa91	cds_s_dbcmp_nullctxwrite_a
0x10d0aa92	cds_s_dbcmp_nullctxend_a
0x10d0aa93	cds_s_dbcmp_nullctxfinish_a
0x10d0aaae	cds_s_delegdirversion
0x10d0aaaf	cds_s_pseudo_load
0x10d0aab0	cds_s_finddir
0x10d0aab1	cds_s_insertdirstore
0x10d0ab54	cds_s_cfgetcellname
0x10d0ab55	cds_s_cfgethostname

Message Number	Symbolic Name
0x10d0ab56	cds_s_cfprinnamefromhost
0x10d0ab57	cds_s_nopriv_eb
0x10d0ab58	cds_s_define_table
0x10d0ab59	cds_s_debug_routing_eb
0x10d0ab5a	cds_s_svc_routing_eb
0x10d0ab5b	cds_s_alloc
0x10d0ab5c	cds_s_alloc_a
0x10d0ab5d	cds_s_uuidfromstr
0x10d0ab5e	cds_s_rpctowerfrombinding
0x10d0ab5f	cds_s_rpcserverlisten
0x10d0ab60	cds_s_rpcbindingreset
0x10d0ab61	cds_s_rpcregisterep
0x10d0ab62	cds_s_rpcunregisterep
0x10d0ab63	cds_s_rpcregisterif
0x10d0ab64	cds_s_rpcuseallprotseqs
0x10d0ab65	cds_s_rpcinqbindings
0x10d0ab66	cds_s_rpcsetobject
0x10d0ab67	cds_s_rpcresolvebinding
0x10d0ab68	cds_s_rpcregisterauthinfo
0x10d0ab69	cds_s_rpcstringtobinding
0x10d0ab6a	cds_s_rpcstringbindingcompose
0x10d0ab6b	cds_s_rpctowervectorfrombind
0x10d0ab6c	cds_s_rpctowertobinding
0x10d0ab6d	cds_s_rpcbindingfromstring
0x10d0ab6e	cds_s_rpcseverinit
0x10d0ab6f	cds_s_rpcbindinginqauth

Message Number	Symbolic Name
0x10d0ab70	cds_s_rpcsetauthinfo
0x10d0ab71	cds_s_rpcbindingexport
0x10d0ab72	cds_s_rpcbindingunexport
0x10d0ab73	cds_s_secrgycellbind
0x10d0ab74	cds_s_secrgysitebind
0x10d0ab75	cds_s_secrgysiteopen
0x10d0ab76	cds_s_secidparsename
0x10d0ab77	cds_s_secrgypgoismember
0x10d0ab78	cds_s_secrgypgonametoid
0x10d0ab79	cds_s_secimportctx
0x10d0ab7a	cds_s_threadcreate
0x10d0ab7b	cds_s_threadcreate_a
0x10d0ab7c	cds_s_threadkeycreate
0x10d0ab7d	cds_s_threadattrcreate
0x10d0ab7e	cds_s_threadsetspecific
0x10d0ab7f	cds_s_threadattrsetstacksize
0x10d0ab80	cds_s_threadmutexinit
0x10d0ab81	cds_s_threadmutexinit_a
0x10d0ab82	cds_s_threadmutexlock
0x10d0ab83	cds_s_threadmutexlock_a
0x10d0ab84	cds_s_threadmutexunlock
0x10d0ab85	cds_s_threadmutexunlock_a
0x10d0ab86	cds_s_threadmutexdestroy
0x10d0ab87	cds_s_threadmutexdestroy_a
0x10d0ab88	cds_s_threadmutextrylock
0x10d0ab89	cds_s_threadcondbroadcast

Message Number	Symbolic Name
0x10d0ab8a	cds_s_threadcondbroadcast_a
0x10d0ab8b	cds_s_threadconddestroy
0x10d0ab8c	cds_s_threadconddestroy_a
0x10d0ab8d	cds_s_threadcondtimedwait
0x10d0ab8e	cds_s_threadcondtimedwait_a
0x10d0ab8f	cds_s_threadcondwait
0x10d0ab90	cds_s_threadcondwait_a
0x10d0ab91	cds_s_threadcondinit
0x10d0ab92	cds_s_threadcondinit_a
0x10d0ab93	cds_s_threadcondsignal
0x10d0ab94	cds_s_threadcondsignal_a
0x10d0ab95	cds_s_threaddelay_a
0x10d0ab96	cds_s_bad_rpc_alloc
0x10d0ab97	cds_s_bad_register_obj
0x10d0ab98	cds_s_bad_acl_init_obj
0x10d0ab99	cds_s_bad_add_user_acl
0x10d0ab9a	cds_s_bad_add_group_acl
0x10d0ab9b	cds_s_bad_add_any_acl
0x10d0ab9c	cds_s_bad_add_unauth_acl
0x10d0ab9d	cds_s_site_bind
0x10d0ab9e	cds_s_parse_name
0x10d0ab9f	cds_s_export_thread
0x10d0aba0	cds_s_aclinit
0x10d0aba1	cds_s_noacl
0x10d0aba2	cds_s_aclwrite
0x10d0aba3	cds_s_aclfail

Message Number	Symbolic Name
0x10d0aba4	cds_s_hostfail
0x10d0aba5	cds_s_groupfail
0x10d0aca4	CDS_CSTAGUNKNOWN
0x10d0aca5	CDS_CSTAGEXISTS
0x10d0aca6	CDS_CSCLHEXISTS
0x10d0aca7	CDS_CSNOCLH
0x10d0aecc	CDSCP_DUPCL
0x10d0aecd	CDSCP_TWO_MASTERS
0x10d0aece	CDSCP_NOMASTER
0x10d0aecf	CDSCP_MISEXCL
0x10d0aed0	CDSCP_NOREP
0x10d0aed2	CDSCP_PARSE_VERSION
0x10d0aed3	CDSCP_CANT_OPEN_PARSE_TABLE
0x10d0aed4	CDSCP_READ_ERROR
0x10d0aed5	CDSCP_NO_FIT
0x10d0aed6	CDSCP_LOAD_FAILURE
0x10d0aed7	CDSCP_NO_FILE_MEM
0x10d0aed8	CDSCP_CANT_OPEN
0x10d0aed9	CDSCP_PARSE_ERROR
0x10d0aeda	CDSCP_MSG_PARSE_STATUS
0x10d0aef1	CDSCP_NOMEM_DOFIELD
0x10d0aef2	CDSCP_CMD_TOOBIG
0x10d0aef3	CDSCP_NOMEM_REPSET
0x10d0aef4	CDSCP_NOGETHAND
0x10d0aef8	CDSCP_ACC_DENIED
0x10d0af1c	CDSCP_UNK_CLRK_ATT

Message Number	Symbolic Name
0x10d0af1d	CDSCP_UNIMPL_OUT_FNC
0x10d0af1e	CDSCP_NOMEM
0x10d0af1f	CDSCP_UNK_CA_CLE_ATT
0x10d0af20	CDSCP_UNK_CLE_CTR
0x10d0af21	CDSCP_UNK_SVR_ATT
0x10d0af23	CDSCP_ASKNOMEM
0x10d0af24	CDSCP_CMD_DFL
0x10d0af2e	CDSCP_GRATTRS_1
0x10d0af31	CDSCP_CMD_TOO_BIG
0x10d0af32	CDSCP_FILE_NOT_OPEN
0x10d0af33	CDSCP_BUG_EMIT_LINE
0x10d0afd3	CDS_GDB_ERROR
0x10d0afd4	CDS_GDB_SECONDARY
0x10d0afd5	CDS_GDB_NO_SECONDARY
0x10d0afd6	CDS_GDB_NOT_FOUND
0x10d0afd7	CDS_GDB_EXISTS
0x10d0afd9	cds_s_gdb_corrupt_db
0x10d0afda	cds_s_gdb_corrupt_db_ch
0x10d0afdb	cds_s_gdb_changedirstore
0x10d0afdc	cds_s_gdb_corrupt_dirstore
0x10d0afdd	cds_s_gdb_open_namespace
0x10d0afde	cds_s_gdb_open_dirstore
0x10d0afdf	cds_s_gdb_begin_xtn
0x10d0afe0	cds_s_gdb_commit_xtn
0x10d0afe1	cds_s_gdb_rollback_xtn
0x10d0afe2	cds_s_server_delete_entries

Message Number	Symbolic Name
0x10d0afff	CDS_ERROR
0x10f61003	csrc_s_lex_error
0x10f61004	csrc_s_cannot_open_input
0x10f61005	csrc_s_duplicate_field
0x10f61006	csrc_s_missing_field
0x10f61007	csrc_s_internal_unknown_type
0x10f61009	csrc_s_no_output
0x10f6100a	csrc_s_cannot_open_output
0x10f6100b	csrc_s_cannot_open_logfile
0x10f6100c	csrc_s_no_memory
0x10f6100d	csrc_s_cannot_copy_intermediate
0x10f6100e	csrc_s_too_many_intermediate
0x1131f003	dcp_s_ok
0x1131f004	dcp_s_no_memory
0x1131f005	dcp_s_var_unset_readonly
0x1131f006	dcp_s_var_set_readonly
0x1131f007	dcp_s_wrong_num_args
0x1131f008	dcp_s_bad_arg
0x1131f009	dcp_s_too_many_args
0x1131f00a	dcp_s_need_arg
0x1131f00b	dcp_s_bad_arg_list
0x1131f00c	dcp_s_bad_use_of_local
0x1131f00d	dcp_s_null_arg
0x1131f00e	dcp_s_expected_int_arg
0x1131f00f	dcp_s_opt_requires_int
0x1131f010	dcp_s_opt_requires_string

Message Number	Symbolic Name
0x1131f011	dcp_s_opt_requires_float
0x1131f012	dcp_s_expected_float_arg
0x1131f013	dcp_s_ambiguous_arg
0x1131f014	dcp_s_attr_not_unique
0x1131f015	dcp_s_bad_arg_type
0x1131f016	dcp_s_bad_attribute
0x1131f017	dcp_s_bad_opt
0x1131f018	dcp_s_need_opt
0x1131f019	dcp_s_mutex_init_fail
0x1131f01a	dcp_s_mutex_lock_fail
0x1131f01b	dcp_s_mutex_unlock_fail
0x1131f01c	dcp_s_too_few_list_elements
0x1131f01d	dcp_s_too_many_list_elements
0x1131f01e	dcp_s_list_too_short
0x1131f01f	dcp_s_list_too_long
0x1131f021	dcp_s_missing_req_opts
0x1131f022	dcp_s_opt_requires_more_args
0x1131f023	dcp_s_mut_excl_opts
0x1131f027	dcp_s_object_needs_verb
0x1131f028	dcp_s_initial_context_fail
0x1131f029	dcp_s_illegal_command
0x1131f02a	dcp_s_help_no_verbose
0x1131f02b	dcp_s_errtext_invalid_code
0x1131f02f	dcp_s_signal_bug
0x1131f030	dcp_s_bad_signal_format
0x1131f031	dcp_s_too_many_signals

Message Number	Symbolic Name
0x1131f032	dcp_s_signal_list_not_empty
0x1131f033	dcp_s_signal_invalid_num
0x1131f034	dcp_s_signal_invalid_name
0x1131f035	dcp_s_signal_posix_unavailable
0x1131f036	dcp_s_signal_trap_req_cmd
0x1131f037	dcp_s_signal_invalid_action
0x1131f038	dcp_s_signal_takes_no_cmd
0x1131f039	dcp_s_signal_lost_interp
0x1131f03e	dcp_s_login_needs_user
0x1131f03f	dcp_s_login_refresh_no_user
0x1131f040	dcp_s_login_no_ktb_and_pass
0x1131f041	dcp_s_login_euid_not_uid
0x1131f042	dcp_s_login_get_context_fail
0x1131f043	dcp_s_login_refresh_fail
0x1131f044	dcp_s_login_bad_pw_read
0x1131f045	dcp_s_login_reset_password
0x1131f046	dcp_s_login_local_creds
0x1131f047	dcp_s_login_from_local_override
0x1131f048	dcp_s_login_invalid_pw
0x1131f049	dcp_s_login_invalid_user
0x1131f04a	dcp_s_not_logged_in
0x1131f04b	dcp_s_purge_initial_context
0x1131f04c	dcp_s_resolve_need_binding
0x1131f04d	dcp_s_resolve_bad_version
0x1131f04e	dcp_s_resolve_not_found
0x1131f04f	dcp_s_resolve_need_if

Message Number	Symbolic Name
0x1131f050	dcp_s_shell_fork_fail
0x1131f080	dcp_s_rpc_no_entry_name
0x1131f081	dcp_s_rpc_no_group_name
0x1131f082	dcp_s_rpc_no_profile_name
0x1131f083	dcp_s_rpc_no_member_name
0x1131f084	dcp_s_rpc_interface_no_version
0x1131f085	dcp_s_rpc_bad_version_opt
0x1131f086	dcp_s_rpc_no_binding_found
0x1131f087	dcp_s_rpc_no_interface_id
0x1131f088	dcp_s_rpc_no_interface_id_def
0x1131f089	dcp_s_rpc_version_no_interface
0x1131f08a	dcp_s_rpc_bad_endpoint_binding
0x1131f08b	dcp_s_rpc_bad_priority
0x1131f08c	dcp_s_rpc_bad_max_value
0x1131f08d	dcp_s_rpc_no_binding
0x1131f08e	dcp_s_rpc_no_objects
0x1131f08f	dcp_s_rpc_default_with_others
0x1131f090	dcp_s_rpc_priority_with_others
0x1131f091	dcp_s_rpc_uuid_with_others
0x1131f092	dcp_s_rpc_member_or_annot
0x1131f131	dcp_s_cds_only_one_server
0x1131f132	dcp_s_cds_only_one_client
0x1131f133	dcp_s_cds_no_cds_server
0x1131f134	dcp_s_cds_no_cds_client
0x1131f135	dcp_s_cds_wrong_options
0x1131f136	dcp_s_cds_internal_error

Message Number	Symbolic Name
0x1131f137	dcp_s_dir_mod_bad_num_masters
0x1131f138	dcp_s_dir_mod_bad_num_dirs
0x1131f139	dcp_s_dir_mod_duplicate_found
0x1131f13a	dcp_s_dir_mod_missing_new_entry
0x1131f13b	dcp_s_dir_mod_bad_new_entry
0x1131f13c	dcp_s_cds_no_handle
0x1131f13d	dcp_s_cds_no_dir_name
0x1131f13e	dcp_s_cds_dir_created
0x1131f13f	dcp_s_cds_dir_not_created
0x1131f140	dcp_s_cds_no_binding_specified
0x1131f141	dcp_s_cds_fname_too_long
0x1131f142	dcp_s_cds_no_attr_list_value
0x1131f143	dcp_s_cds_no_obj_name
0x1131f144	dcp_s_cds_no_link_name
0x1131f145	dcp_s_cds_no_obj_mod_operation
0x1131f146	dcp_s_cds_no_linkto_value
0x1131f147	dcp_s_cds_no_dir_mod_operation
0x1131f148	dcp_s_cds_single_no_add
0x1131f149	dcp_s_cds_single_no_attr
0x1131f14a	dcp_s_cds_types_no_remove
0x1131f14b	dcp_s_cds_no_link_mod_operation
0x1131f14c	dcp_s_cds_no_clearinghouse_option
0x1131f14d	dcp_s_cds_tree_replica_option
0x1131f14e	dcp_s_cds_force_replica_option
0x1131f14f	dcp_s_cds_clh_replica_option
0x1131f150	dcp_s_cds_merge_no_target

Message Number	Symbolic Name
0x1131f151	dcp_s_cds_invalid_confidence
0x1131f152	dcp_s_cds_no_clearinghouse_name
0x1131f153	dcp_s_cds_not_valid_clearinghouse
0x1131f154	dcp_s_cds_no_cdsalias_name
0x1131f155	dcp_s_cds_no_member
0x1131f156	dcp_s_cds_no_cache_name
0x1131f157	dcp_s_cds_no_cache_server
0x1131f158	dcp_s_cds_cache_show
0x1131f159	dcp_s_cds_illegal_byte_attr
0x1131f15a	dcp_s_cadump_fail
0x1131f15b	dcp_s_cadump_not_root
0x1131f15c	dcp_s_cds_ill_attr_val
0x1131f15d	dcp_s_cds_bad_attribute_list
0x1131f15e	dcp_s_cds_bad_attribute_name
0x1131f15f	dcp_s_cds_bad_attribute_type
0x1131f160	dcp_s_cds_no_checkpoint
0x1131f161	dcp_s_cds_no_timestamps
0x1131f162	dcp_s_cds_bad_timeout_value
0x1131f163	dcp_s_cds_unknown_data_type
0x1131f26e	dcp_s_rgy_no_modify_operation
0x1131f26f	dcp_s_rgy_no_random_password
0x1131f270	dcp_s_rgy_invalid_pwd_val_type
0x1131f271	dcp_s_rgy_no_name_to_rename
0x1131f272	dcp_s_rgy_schema_rename_no_newname
0x1131f273	dcp_s_rgy_sch_entry_not_found
0x1131f274	dcp_s_rgy_missing_encoding_type

Message Number	Symbolic Name
0x1131f275	dcp_s_rgy_no_fggroup
0x1131f276	dcp_s_rgy_con_no_forg
0x1131f277	dcp_s_rgy_con_no_faccount
0x1131f278	dcp_s_rgy_con_no_org
0x1131f279	dcp_s_rgy_con_no_group
0x1131f27a	dcp_s_rgy_con_no_mypwd
0x1131f27b	dcp_s_rgy_con_no_cred
0x1131f27c	dcp_s_rgy_con_bad_cell
0x1131f27d	dcp_s_rgy_con_no_fmypwd
0x1131f27e	dcp_s_rgy_con_no_cell_name
0x1131f27f	dcp_s_rgy_con_no_set_valid
0x1131f280	dcp_s_rgy_con_no_set_fvalid
0x1131f281	dcp_s_rgy_bad_quota_attr_val
0x1131f282	dcp_s_rgy_bad_alias_attr_val
0x1131f283	dcp_s_rgy_bad_inprojlist_attr_val
0x1131f284	dcp_s_rgy_bad_fullname_attr_val
0x1131f285	dcp_s_rgy_bad_uid_attr_val
0x1131f286	dcp_s_rgy_bad_gid_attr_val
0x1131f287	dcp_s_rgy_bad_orgid_attr_val
0x1131f288	dcp_s_rgy_bad_uuid_attr_val
0x1131f289	dcp_s_rgy_bad_pwdlife_attr_val
0x1131f28a	dcp_s_rgy_bad_pwdminlen_attr_val
0x1131f28b	dcp_s_rgy_bad_pwdexdate_attr_val
0x1131f28c	dcp_s_rgy_bad_pwdspaces_attr_val
0x1131f28d	dcp_s_rgy_bad_pwdalpha_attr_val
0x1131f28e	dcp_s_rgy_bad_acctlife_attr_val

Message Number	Symbolic Name
0x1131f28f	dcp_s_rgy_missing_acl_mgr_set
0x1131f290	dcp_s_rgy_unknown_encoding_type
0x1131f291	dcp_s_rgy_ambig_encoding_type
0x1131f292	dcp_s_rgy_invalid_acl_mgr_syntax
0x1131f293	dcp_s_rgy_invalid_acl_mgr_name
0x1131f294	dcp_s_rgy_ambig_acl_mgr_name
0x1131f295	dcp_s_rgy_invalid_intercell_action
0x1131f296	dcp_s_rgy_ambig_intercell_action
0x1131f297	dcp_s_rgy_invalid_trigger_type
0x1131f298	dcp_s_rgy_ambig_trigger_type
0x1131f299	dcp_s_rgy_invalid_permset_char
0x1131f29a	dcp_s_rgy_bad_use_of_verbose
0x1131f29b	dcp_s_rgy_verbose_missing_replica
0x1131f29c	dcp_s_rgy_invalid_pnvalue
0x1131f29d	dcp_s_rgy_invalid_attribute
0x1131f29e	dcp_s_rgy_no_versions_found
0x1131f29f	dcp_s_rgy_illegal_version
0x1131f2a0	dcp_s_rgy_full_or_simple
0x1131f2a1	dcp_s_rgy_checkpoint_bad_cpi
0x1131f2a2	dcp_s_rgy_sa_no_replica
0x1131f2a3	dcp_s_rgy_sa_only_one_replica
0x1131f2a4	dcp_s_rgy_sa_replica_not_master
0x1131f2a5	dcp_s_rgy_sa_already_master
0x1131f2a6	dcp_s_rgy_sa_force_set_master
0x1131f2a7	dcp_s_rgy_sa_seqno_high
0x1131f2a8	dcp_s_rgy_bad_expdate

Message Number	Symbolic Name
0x1131f2a9	dcp_s_uid_not_allowed
0x1131f2aa	dcp_s_gid_not_allowed
0x1131f2ab	dcp_s_maxuid_out_of_range
0x1131f2ac	dcp_s_maxuid_is_negative
0x1131f2ad	dcp_s_maxuid_not_int
0x1131f2ae	dcp_s_minorgid_not_int
0x1131f2af	dcp_s_minorgid_out_of_range
0x1131f2b0	dcp_s_minorgid_is_negative
0x1131f2b1	dcp_s_minuid_not_int
0x1131f2b2	dcp_s_minuid_out_of_range
0x1131f2b3	dcp_s_minuid_is_negative
0x1131f2b4	dcp_s_mingid_not_int
0x1131f2b5	dcp_s_mingid_out_of_range
0x1131f2b6	dcp_s_mingid_is_negative
0x1131f2b7	dcp_s_orgid_not_allowed
0x1131f2b8	dcp_s_rgy_no Princ_name
0x1131f2b9	dcp_s_rgy_no_group_name
0x1131f2ba	dcp_s_rgy_no_org_name
0x1131f2bb	dcp_s_rgy_no_acct_name
0x1131f2bc	dcp_s_rgy_bad_schema_name
0x1131f2bd	dcp_s_rgy_no_schema_name
0x1131f2be	dcp_s_rgy_no_uid
0x1131f2bf	dcp_s_rgy_no_gid
0x1131f2c0	dcp_s_rgy_uuid_and_alias
0x1131f2c1	dcp_s_rgy_list_and_switches
0x1131f2c2	dcp_s_rgy_bad_attribute_list

Message Number	Symbolic Name
0x1131f2c3	dcp_s_rgy_bad_attribute_name
0x1131f2c4	dcp_s_rgy_bad_attribute_value
0x1131f2c5	dcp_s_rgy_invalid_cell
0x1131f2c6	dcp_s_rgy_no_member_name
0x1131f2c7	dcp_s_rgy_bad_time_string
0x1131f2c8	dcp_s_rgy_bad_reftime_string
0x1131f2c9	dcp_s_rgy_uid_out_of_range
0x1131f2ca	dcp_s_rgy_gid_out_of_range
0x1131f2cb	dcp_s_rgy_orgid_out_of_range
0x1131f2cc	dcp_s_rgy_uid_is_wrong
0x1131f2cd	dcp_s_rgy_gid_is_wrong
0x1131f2ce	dcp_s_rgy_orgid_is_wrong
0x1131f2cf	dcp_s_rgy_quota_not_int
0x1131f2d0	dcp_s_rgy_quota_out_of_range
0x1131f2d1	dcp_s_rgy_quota_is_negative
0x1131f2d2	dcp_s_rgy_acct_is_bad
0x1131f2d3	dcp_s_rgy_pwdminlen_not_int
0x1131f2d4	dcp_s_rgy_pwdminlen_out_of_range
0x1131f2d5	dcp_s_rgy_pwdminlen_is_negative
0x1131f2d6	dcp_s_rgy_pwdlife_is_bad
0x1131f2d7	dcp_s_rgy_acct_no_group
0x1131f2d8	dcp_s_rgy_acct_no_org
0x1131f2d9	dcp_s_rgy_acct_no_passwd
0x1131f2da	dcp_s_rgy_acct_passwd_long
0x1131f2db	dcp_s_rgy_acct_desc_long
0x1131f2dc	dcp_s_rgy_acct_home_long

Message Number	Symbolic Name
0x1131f2dd	dcp_s_rgy_acct_shell_long
0x1131f2de	dcp_s_rgy_illegal_attr
0x1131f2df	dcp_s_rgy_era_not_int
0x1131f2e0	dcp_s_rgy_era_codeset_not_valid
0x1131f2e1	dcp_s_rgy_era_invalid_byte
0x1131f2e2	dcp_s_rgy_era_not_present
0x1131f2e3	dcp_s_rgy_era_void_already_exists
0x1131f2e4	dcp_s_rgy_era_too_many_voids
0x1131f2e5	dcp_s_rgy_bad_use_of_types_option
0x1131f2e6	dcp_s_rgy_era_out_of_range
0x1131f2e7	dcp_s_rgy_era_not_uuid
0x1131f2e8	dcp_s_rgy_era_not_multi_valued
0x1131f2e9	dcp_s_rgy_era_wrong_num_values
0x1131f2ea	dcp_s_rgy_era_type_and_value
0x1131f2eb	dcp_s_rgy_era_any_unknown_enc_type
0x1131f2ec	dcp_s_rgy_era_any_ambig_enc_type
0x1131f2ed	dcp_s_rgy_era_any_illegal_enc_type
0x1131f2ee	dcp_s_rgy_era_any_illegal_remove
0x1131f2ef	dcp_s_rgy_era_unknown_encoding_type
0x1131f2f0	dcp_s_rgy_era_unknown_binding_type
0x1131f2f1	dcp_s_rgy_era_illegal_switches
0x1131f2f2	dcp_s_rgy_era_illegal_attribute_list
0x1131f2f3	dcp_s_rgy_era_illegal_change_command
0x1131f2f4	dcp_s_rgy_era_no_attribute_exists
0x1131f2f5	dcp_s_rgy_era_internal_error
0x1131f2f6	dcp_s_rgy_no_name_to_parse

Message Number	Symbolic Name
0x1131f2f7	dcp_s_rgy_no_binding_to_parse
0x1131f2f8	dcp_s_rgy_era_invalid_binding_syntax
0x1131f2f9	dcp_s_rgy_era_invalid_i18ndata_syntax
0x1131f2fa	dcp_s_rgy_era_invalid_protection
0x1131f2fb	dcp_s_rgy_era_invalid_authentication
0x1131f2fc	dcp_s_rgy_era_invalid_authorization
0x1131f2fd	dcp_s_rgy_server_unavailable
0x1131f2fe	dcp_s_rgy_pk_invalid_storage
0x1131f2ff	dcp_s_rgy_pk_unknown_attr
0x1131f300	dcp_s_rgy_pk_too_many_attr
0x1131f301	dcp_s_rgy_pk_genkey_not_int
0x1131f302	dcp_s_rgy_pk_genkey_out_of_range
0x1131f303	dcp_s_rgy_pk_genkey_is_negative
0x1131f304	dcp_s_rgy_pk_gen_and_key
0x1131f305	dcp_s_rgy_pk_gen_and_pass
0x1131f306	dcp_s_rgy_pk_missing_key
0x1131f307	dcp_s_rgy_pk_illegal_oldpass
0x1131f308	dcp_s_rgy_pk_missing_oldpass
0x1131f309	dcp_s_rgy_pk_missing_newpass
0x1131f30a	dcp_s_rgy_pk_missing_eitherpass
0x1131f30b	dcp_s_rgy_pk_inconsistent_passphrase
0x1131f30c	dcp_s_rgy_pk_missing_argument
0x1131f30d	dcp_s_rgy_pk_same_filename
0x1131f30e	dcp_s_rgy_pk_same_pk_string
0x1131f30f	dcp_s_rgy_pk_file_open_fail
0x1131f310	dcp_s_rgy_pk_file_read_fail

Message Number	Symbolic Name
0x1131f32f	dcp_s_dts_bind_file_open_fail
0x1131f330	dcp_s_dts_time_conversion_fail
0x1131f331	dcp_s_dts_modify_invalid_courier_role
0x1131f332	dcp_s_dts_modify_excl_opts
0x1131f333	dcp_s_dts_comm_failure
0x1131f334	dcp_s_dts_no_more_bindings
0x1131f345	dcp_s_clock_set_invalid_epoch
0x1131f346	dcp_s_clock_set_need_epoch
0x1131f347	dcp_s_clock_set_need_abruptly
0x1131f348	dcp_s_clock_set_need_time
0x1131f349	dcp_s_clock_set_epoch_no_abrupt
0x1131f34a	dcp_s_clock_abrupt_present
0x1131f34b	dcp_s_clock_set_bypass_and_others
0x1131f34c	dcp_s_clock_set_bypass_and_hostname
0x1131f34d	dcp_s_clock_missing_hostname
0x1131f34e	dcp_s_clock_time_conversion_fail
0x1131f34f	dcp_s_clock_get_local_time_fail
0x1131f350	dcp_s_clock_get_dced_time_fail
0x1131f351	dcp_s_clock_dced_server_time_fail
0x1131f352	dcp_s_clock_get_inetd_time_fail
0x1131f353	dcp_s_clock_set_failed
0x1131f35b	dcp_s_log_no_server
0x1131f35c	dcp_s_log_no_modify_op
0x1131f35d	dcp_s_log_inv_routing
0x1131f35e	dcp_s_log_no_debug
0x1131f375	dcp_s_acl_no_object

Message Number	Symbolic Name
0x1131f376	dcp_s_acl_could_not_bind
0x1131f377	dcp_s_acl_not_rpc_entry
0x1131f378	dcp_s_sbind_entry_option
0x1131f379	dcp_s_acl_mgr_not_found
0x1131f37a	dcp_s_acl_no_acl_modify_op
0x1131f37b	dcp_s_acl_no_mask_with_option
0x1131f37c	dcp_s_acl_inv_mask_option_value
0x1131f37d	dcp_s_acl_one_cell_attr
0x1131f37e	dcp_s_too_many_types
0x1131f37f	dcp_s_acl_would_grant_perms
0x1131f380	dcp_s_acl_new_mask_obj_failed
0x1131f381	dcp_s_acl_inv_entry
0x1131f382	dcp_s_acl_inv_entry_type
0x1131f383	dcp_s_acl_inv_entry_key
0x1131f384	dcp_s_acl_entry_not_found
0x1131f385	dcp_s_acl_entry_already_exists
0x1131f386	dcp_s_acl_mask_obj_specified
0x1131f387	dcp_s_acl_no_acl_replace_op
0x1131f388	dcp_s_acl_replace_dup_entries
0x1131f389	dcp_s_acl_inv_cell_name
0x1131f3a7	dcp_s_aud_dmn_binding_file_open_fail
0x1131f3a8	dcp_s_aud_id_file_open_fail
0x1131f3a9	dcp_s_aud_id_file_read_fail
0x1131f3aa	dcp_s_aud_cannot_open_trail_file
0x1131f3ab	dcp_s_aud_trail_file_corrupt
0x1131f3ac	dcp_s_aud_modify_bad_stostrategy

Message Number	Symbolic Name
0x1131f3ad	dcp_s_aud_modify_need_opt
0x1131f3ae	dcp_s_aud_modify_bad_state
0x1131f3af	dcp_s_aud_show_state_invalid
0x1131f3b0	dcp_s_aud_show_stostrategy_invalid
0x1131f3b1	dcp_s_aud_empty_ec_list
0x1131f3b2	dcp_s_audtrail_outfile_open_fail
0x1131f3b3	dcp_s_audevents_get_events_fail
0x1131f3b4	dcp_s_audfilter_invalid_type
0x1131f3b5	dcp_s_audfilter_need_key
0x1131f3b6	dcp_s_audfilter_extra_key
0x1131f3b7	dcp_s_audfilter_no_filter
0x1131f3b8	dcp_s_audfilter_invalid_condition
0x1131f3b9	dcp_s_audfilter_invalid_action
0x1131f3ba	dcp_s_audfilter_invalid_ec
0x1131f3bb	dcp_s_audfilter_modify_need_option
0x1131f3bc	dcp_s_audfilter_create_need_attr
0x1131f3df	dcp_s_sr_missing_req_opt
0x1131f3e0	dcp_s_sr_obj_not_found
0x1131f3e1	dcp_s_sr_unknown_serv_flag
0x1131f3e2	dcp_s_sr_wrong_stop_mthd
0x1131f3e3	dcp_s_sr_wrong_timeout_code
0x1131f3e4	dcp_s_sr_bad_if_attr
0x1131f3e5	dcp_s_sr_uuid_mul_used
0x1131f3fe	dcp_s_kt_missing_key_version
0x1131f3ff	dcp_s_kt_bad_key_type
0x1131f400	dcp_s_kt_bad_key_value

Message Number	Symbolic Name
0x1131f401	dcp_s_kt_key_value_missing
0x1131f41c	dcp_s_dhd_invalid_args
0x1131f41d	dcp_s_dhd_no_object
0x1131f41e	dcp_s_dhd_bad_attribute_list
0x1131f41f	dcp_s_dhd_bad_key_data
0x1131f420	dcp_s_dhd_too_many_opts
0x1131f421	dcp_s_dhd_mod_invalid_attr
0x1131f422	dcp_s_dhd_data_on_entry_ops
0x1131f423	dcp_s_dhd_data_attr_missing
0x1131f424	dcp_s_dhd_wrong_service_req
0x1131f425	dcp_s_dhd_miss_objname
0x1131f426	dcp_s_dhd_too_many_ifnames
0x1131f42f	dcp_s_utc_bad_time
0x1131f430	dcp_s_utc_bad_rel_time
0x1131f431	dcp_s_utc_add_two_abs
0x1131f432	dcp_s_utc_add_failed
0x1131f433	dcp_s_utc_conv_fail
0x1131f434	dcp_s_utc_compare_diff_ts
0x1131f435	dcp_s_utc_compare_failed
0x1131f436	dcp_s_utc_convert_failed
0x1131f437	dcp_s_utc_multiply_failed
0x1131f438	dcp_s_utc_bad_mult
0x1131f439	dcp_s_utc_sub_abs_from_rel
0x1131f43a	dcp_s_utc_sub_failed
0x113db064	dced_s_bad_binding
0x113db065	dced_s_no_memory

Message Number	Symbolic Name
0x113db066	dced_s_invalid_arg
0x113db067	dced_s_no_more_entries
0x113db068	dced_s_not_found
0x113db069	dced_s_no_support
0x113db06a	dced_s_unknown_attr_type
0x113db06b	dced_s_unknown_list_type
0x113db06c	dced_s_unknown_object_type
0x113db06d	dced_s_unknown_service
0x113db06e	dced_s_not_started_by_dced
0x113db06f	dced_s_need_one_server_prin
0x113db070	dced_s_no_server_keyfile
0x113db071	dced_s_data_unavailable
0x113db072	dced_s_name_missing
0x113db073	dced_s_cannot_create_key_mgmt_thr
0x113db074	dced_s_cannot_detach_key_mgmt_thr
0x113db075	dced_s_server_attr_not_found
0x113db076	dced_s_empty_replist
0x113db0c9	dced_s_import_cant_access
0x113db0ca	dced_s_import_already_exists
0x113db0cb	dced_s_cant_open_storage_file
0x113db0cc	dced_s_cant_remove_storage_file
0x113db0cd	dced_s_invalid_attr_type
0x113db0ce	dced_s_already_exists
0x113db0ed	dced_s_bad_keydir
0x113db12c	dced_s_no_postprocessors
0x113db12d	dced_s_postprocessor_file_fail

Message Number	Symbolic Name
0x113db12e	dced_s_postprocessor_spawn_fail
0x113db12f	dced_s_postprocessor_ok
0x113db130	dced_s_postprocessor_bad
0x113db190	dced_s_bad_key_data
0x113db191	dced_s_key_version_mismatch
0x113db192	dced_s_key_v0_not_allowed
0x113db193	dced_s_random_key_not_allowed
0x113db194	dced_s_need_privacy
0x113db1f4	dced_s_sc_invalid_attr_type
0x113db1f5	dced_s_sc_cant_fork
0x113db1f6	dced_s_sc_setup_failed
0x113db1f7	dced_s_sc_open_file_failed
0x113db258	dced_s_sx_missing_instance
0x113db2bc	dced_s_sv_already_enabled
0x113db2bd	dced_s_sv_not_enabled
0x113db2c4	dced_s_sv_update_pe_site_fail
0x113db320	dced_s_attr_bad_name
0x113db321	dced_s_attr_bad_sch_name
0x113db322	dced_s_attr_bad_encoding_type
0x113db323	dced_s_attr_bad_acl_mgr_set
0x113db324	dced_s_attr_invalid_manager_type
0x113db325	dced_s_attr_acl_bad_permset
0x113db326	dced_s_attr_bad_entry_flag
0x113db327	dced_s_attr_bad_intercell_action
0x113db328	dced_s_attr_bad_trig_types
0x113db329	dced_s_attr_bad_uniq_query_accept

Message Number	Symbolic Name
0x113db32a	dced_s_attr_bad_trig_binding
0x113db32b	dced_s_attr_not_supported_for_update
0x113db44c	dced_s_mutex_init_fail
0x113db44d	dced_s_cond_init_fail
0x113db44e	dced_s_mutex_lock_failed
0x113db44f	dced_s_mutex_unlock_failed
0x113db450	dced_s_cond_wait_failed
0x113db451	dced_s_cond_signal_failed
0x113db452	dced_s_cond_bcast_failed
0x113db453	dced_s_startup_interrupted
0x113db514	dced_s_pkcache_usage_unsupp
0x113db515	dced_s_pkcache_key_write_failure
0x113db516	dced_s_pkcache_cell_invalid
0x113db517	dced_s_pkcache_mkdir_error
0x113db518	dced_s_pkcache_key_fresh
0x115ca001	dts_s_normal
0x115ca002	dts_s_synching
0x115ca003	dts_s_updating_time
0x115ca004	dts_s_epoch_range
0x115ca005	dts_s_has_provider
0x115ca006	dts_s_is_started
0x115ca007	dts_s_servers_range
0x115ca008	dts_s_read_only
0x115ca009	dts_s_nopriv
0x115ca00a	dts_s_created
0x115ca00b	dts_s_not_created

Message Number	Symbolic Name
0x115ca00c	dts_s_not_enabled
0x115ca00d	dts_s_no_time_updated
0x115ca00e	dts_s_not_server
0x115ca00f	dts_s_another_time_serv
0x115ca010	dts_s_alloc_virt
0x115ca011	dts_s_error_create
0x115ca012	dts_s_open_ethernet
0x115ca013	dts_s_open_decnet
0x115ca014	dts_s_set_error
0x115ca015	dts_s_failed
0x115ca016	dts_s_wrong_state
0x115ca017	dts_s_comm_failure
0x115ca018	dts_s_shut_down
0x115ca019	dts_s_not_global_server
0x115ca01a	dts_s_cp_init_rpc
0x115ca01b	dts_s_cp_init_prs
0x115ca01c	dts_s_prsfile_open
0x115ca01d	dts_s_prsfile_read
0x115ca01e	dts_s_prsfile_version
0x115ca01f	dts_s_prsfile_fatal
0x115ca020	dts_s_prsfile_format
0x115ca021	dts_s_prsact_fatal
0x115ca022	dts_s_bad_command
0x115ca023	dts_s_prs_unknown
0x115ca024	dts_s_dtsd_comm
0x115ca025	dts_s_cp_error

Message Number	Symbolic Name
0x115ca034	dts_s_mgt_no_read
0x115ca035	dts_s_mgt_no_write
0x115ca036	dts_s_mgt_unauthn
0x115ca037	dts_s_serv_not_in_ts_group
0x115ca038	dts_s_starting
0x115ca039	dts_s_aud_open_file_failed
0x115ca03a	dts_s_aud_open_daemon_failed
0x115ca03b	dts_s_cannot_open_audit_trail
0x115ca03c	dts_s_exiting
0x115ca03d	dts_s_superuser
0x115ca03e	dts_s_dtsdate_usage
0x115ca03f	dts_s_interface_id
0x115ca040	dts_s_uuid_to_string
0x115ca041	dts_s_ep_resolve_binding
0x115ca042	dts_s_clerk_request
0x115ca043	dts_s_clockset
0x115ca044	dts_s_adjustlocal
0x115ca045	dts_s_resetlocal
0x115ca046	dts_s_global_nointersect
0x115ca047	dts_s_local_nointersect
0x115ca048	dts_s_sync_complete
0x115ca049	dts_s_update_complete
0x115ca04a	dts_s_too_few_servers
0x115ca04b	dts_s_startup_done
0x115ca04c	dts_s_shutdown_complete
0x115ca04d	dts_s_startup_done_set

Message Number	Symbolic Name
0x115ca04e	dts_s_different_epoch
0x115ca04f	dts_s_toomany_servers
0x115ca050	dts_s_bad_timestamp
0x115ca051	dts_s_no_global_servers
0x115ca052	dts_server_not_responding
0x115ca053	dts_server_no_memory
0x115ca054	dts_server_epoch_changed
0x115ca055	dts_s_provider_failed
0x115ca056	dts_s_provider_timeout
0x115ca057	dts_s_system_error
0x115ca058	dts_s_dce_error
0x115ca059	dts_s_no_profile
0x115ca05a	dts_s_not_in_group
0x115ca05b	dts_s_write_bindings
0x115ca05c	dts_s_read_bindings
0x115ca05d	dts_s_binding_file_write_error
0x115ca05e	dts_s_binding_file_read_error
0x115ca05f	dts_s_get_cell_name
0x115ca060	dts_s_get_profile_name
0x115ca061	dts_s_binding_import
0x115ca062	dts_s_set_exp_age
0x115ca063	dts_s_binding_inq_name
0x115ca064	dts_s_inq_server_princ
0x115ca065	dts_s_sec_id_parse
0x115ca066	dts_s_set_auth_info
0x115ca067	dts_s_entry_object_inq_next

Message Number	Symbolic Name
0x115ca068	dts_s_entry_object_inq_begin
0x115ca069	dts_s_binding_import_next
0x115ca06a	dts_s_ep_register_tp
0x115ca06b	dts_s_export_gts
0x115ca06c	dts_s_add_profile
0x115ca06d	dts_s_profile_remove
0x115ca06e	dts_s_cf_hostname
0x115ca06f	dts_s_register_acl_if
0x115ca070	dts_s_export_acl_if
0x115ca071	dts_s_rpc_sm_enable
0x115ca072	dts_s_acl_dbopen_read
0x115ca073	dts_s_fetch_uuid
0x115ca074	dts_s_acl_dbopen_create
0x115ca075	dts_s_acl_register_obj_types
0x115ca076	dts_s_acl_create_default
0x115ca077	dts_s_db_store_uuid
0x115ca078	dts_s_aclv1_unregister
0x115ca079	dts_s_aclv0_unregister
0x115ca07a	dts_s_aclv1_runtime_register
0x115ca07b	dts_s_aclv1_register
0x115ca07c	dts_s_aclv0_runtime_register
0x115ca07d	dts_s_aclv0_register
0x115ca07e	dts_s_init_mgmt_acl
0x115ca07f	dts_s_server_reg_auth_info
0x115ca080	dts_s_select_strbind
0x115ca081	dts_s_tp_binding

Message Number	Symbolic Name
0x115ca082	dts_s_tp_ep_begin
0x115ca083	dts_s_tp_ep_next
0x115ca084	dts_s_tp_name_search
0x115ca085	dts_s_tp_auth_info
0x115ca086	dts_s_mgmt_srvr_listening
0x115ca087	dts_s_srvr_controlv2
0x115ca088	dts_s_srvr_serviceability
0x115ca089	dts_s_inq_bindings
0x115ca08a	dts_s_ep_register_controlv2
0x115ca08b	dts_s_ep_register_serviceability
0x115ca08c	dts_s_export_control
0x115ca08d	dts_s_sec_key_mgmt
0x115ca08e	dts_s_validate_srvr_id
0x115ca08f	dts_s_refresh_identity
0x115ca090	dts_s_get_expiration
0x115ca091	dts_s_tservicev1_ep_register
0x115ca092	dts_s_export_tservicev1
0x115ca093	dts_s_tservicev1_profile_add
0x115ca094	dts_s_export_tservicev2
0x115ca095	dts_s_cf_profile_name
0x115ca096	dts_s_profile_begin
0x115ca097	dts_s_svc_ep_unregister
0x115ca098	dts_s_control_ep_unregister
0x115ca099	dts_s_control_unexport
0x115ca09a	dts_s_service_unexport
0x115ca09b	dts_s_service_ep_unreister

Message Number	Symbolic Name
0x115ca09c	dts_s_tserver_profile_remove
0x115ca09d	dts_s_unregister_acl_mgr
0x115ca09e	dts_s_unexport_acl_mgr
0x115ca09f	dts_s_pgo_is_member
0x115ca0a0	dts_s_prin_host
0x115ca0a1	dts_s_cell_name
0x115ca0a2	dts_s_rgy_site_open
0x115ca0a3	dts_s_id_parse_name
0x115ca0a4	dts_s_pgo_name_id
0x115ca0a5	dts_s_mgmt_srvr_listen_timeout
0x115ca0a6	dts_s_inq_attr
0x115ca0a7	dts_s_attr_encoding
0x115ca0a8	dts_s_server_only
0x115ca0a9	dts_s_invalid_type
0x115ca0aa	dts_s_bad_attr
0x115ca0ab	dts_s_invalid_attr_value
0x115ca0ac	dts_s_mutexattr_create
0x115ca0ad	dts_s_mutex_init
0x115ca0ae	dts_s_mutexattr_setkind
0x115ca0af	dts_s_bad_attr_type
0x115ca0b0	dts_s_usage_error
0x115ca0b1	dts_s_security_init
0x115ca0b2	dts_s_routing_switch
0x115ca0b3	dts_s_user_reset
0x1260a0c8	GDS_S_NOMEMORY
0x1260a0c9	GDS_S_FOPEN_ERR

Message Number	Symbolic Name
0x1260a0ca	GDS_S_FCLOSE_ERR
0x1260a0cb	GDS_S_FFLUSH_ERR
0x1260a0cc	GDS_S_FCNTL_ERR
0x1260a0cd	GDS_S_FREAD_ERR
0x1260a0ce	GDS_S_FWRITE_ERR
0x1260a0cf	GDS_S_FEOF
0x1260a0d0	GDS_S_OPEN_ERR
0x1260a0d1	GDS_S_READ_ERR
0x1260a0d2	GDS_S_WRITE_ERR
0x1260a0d3	GDS_S_SEEK_ERR
0x1260a0d4	GDS_S_CLOSE_ERR
0x1260a0d5	GDS_S_LINK_ERR
0x1260a0d6	GDS_S_UNLINK_ERR
0x1260a0d7	GDS_S_MKNOD_ERR
0x1260a0d8	GDS_S_SEMOP_ERR
0x1260a0d9	GDS_S_FTOK_ERR
0x1260a0da	GDS_S_SHMGET_ERR
0x1260a0db	GDS_S_SHMAT_ERR
0x1260a0dc	GDS_S_SHMCTL_ERR
0x1260a0dd	GDS_S_SEMGET_ERR
0x1260a0de	GDS_S_SEMCTL_ERR
0x1260a0df	GDS_S_MSGGET_ERR
0x1260a0e0	GDS_S_MSGCTL_ERR
0x1260a0e1	GDS_S_MSGSND_ERR
0x1260a0e2	GDS_S_MSGRCV_ERR
0x1260a0e3	GDS_S_FORK_ERR

Message Number	Symbolic Name
0x1260a0e4	GDS_S_WAIT_ERR
0x1260a0e5	GDS_S_SIGHDL_ERR
0x1260a0e6	GDS_S_SYSTEM_ERR
0x1260a0e7	GDS_S_CHILD_EXIT
0x1260a0e8	GDS_S_CHILD_SIGNAL
0x1260a0e9	GDS_S_EXECV_ERR
0x1260a0ea	GDS_S_ROUTING_ERR
0x1260a0eb	GDS_S_DBG_ROUTING_ERR
0x1260a0ec	GDS_S_ROUTINGS_ERR
0x1260a0ed	GDS_S_BAD_ROUTE_SPEC
0x1260a0ee	GDS_S_STAT_ERR
0x1260a190	GDS_S_SIGNAL_ERR
0x1260a191	GDS_S_ENVVAR_ERR
0x1260a192	GDS_S_NUM_ASN1_ATTR_ERR
0x1260a193	GDS_S_ILL_ASN1_ATTR_ENTRY_ERR
0x1260a194	GDS_S_OBID_ASN1_ATTR_ERR
0x1260a195	GDS_S_INSUFF_INFO
0x1260a196	GDS_S_INCONS_INSTREAM
0x1260a3e8	GDS_S_ENTRYCACHE
0x1260a3e9	GDS_S_EXITCACHE
0x1260a3ea	GDS_S_CACHE_REORG_SZ_ERR
0x1260a3eb	GDS_S_CACHE_DESCR_SZ_ERR
0x1260a3ec	GDS_S_CACHE_HASH_SZ_ERR
0x1260a3ed	GDS_S_CACHE_INFO_SZ_ERR
0x1260a3ee	GDS_S_CACHE_VERSION_ERR
0x1260a3ef	GDS_S_CACHE_INCONS_ERR

Message Number	Symbolic Name
0x1260a3f0	GDS_S_CACHE_RESULT_ERR
0x1260a3f1	GDS_S_CACHE_WAITIN_ERR
0x1260a3f2	GDS_S_CACHE_BUFSZ_ERR
0x1260a3f3	GDS_S_CACHE_REQSZ_ERR
0x1260a3f4	GDS_S_CACHE_INFSZ_ERR
0x1260a3f5	GDS_S_CACHE_INVRQ_ERR
0x1260a3f6	GDS_S_CACHE_INVVERS_ERR
0x1260a3f7	GDS_S_CACHE_INVDIRID_ERR
0x1260a3f8	GDS_S_CACHE_INVSTC_ERR
0x1260a3f9	GDS_S_CACHE_INVMSGTAG_ERR
0x1260a3fa	GDS_S_CACHE_INCONSMMSG_ERR
0x1260a3fb	GDS_S_CACHE_INVMATCH_ERR
0x1260a3fc	GDS_S_CACHE_INVFILT_ERR
0x1260a3fd	GDS_S_CACHE_INVOIDLEN_ERR
0x1260a3fe	GDS_S_CACHE_INVAVLEN_ERR
0x1260a3ff	GDS_S_CACHE_INVSLIM_ERR
0x1260a400	GDS_S_CACHE_INVATTRS_ERR
0x1260a401	GDS_S_CACHE_INVDNS_ERR
0x1260a402	GDS_S_CACHE_HSHFULL_ERR
0x1260a44c	GDS_S_ENTRYMONITOR
0x1260a44d	GDS_S_EXITMONITOR
0x1260a44e	GDS_S_ENTRY_RPCSERVER
0x1260a44f	GDS_S_RPC_BINDINFO
0x1260a450	GDS_S_RPC_RUNTIME_ERR
0x1260a451	GDS_S_RPC_THREADS_ERR
0x1260a452	GDS_S_RPC_UNSUPPORTED

Message Number	Symbolic Name
0x1260a453	GDS_S_RPC_GDSINFO_ERR
0x1260a454	GDS_S_RPC_GDSINFO_DIR_ERR
0x1260a455	GDS_S_RPC_SVCINFO
0x1260a456	GDS_S_RPC_SVC_FAILED
0x1260a457	GDS_S_RPC_DISTCMD_ERR
0x1260a458	GDS_S_IPCVERSIL_ERR
0x1260a459	GDS_S_IPCVERS_ERR
0x1260a45a	GDS_S_IPCSVIDIL_ERR
0x1260a45b	GDS_S_IPCASIDIL_ERR
0x1260a45c	GDS_S_IPCWYPIL_ERR
0x1260a45d	GDS_S_IPCMYPIL_ERR
0x1260a45e	GDS_S_IPCMREFIL_ERR
0x1260a45f	GDS_S_IPCILNIL_ERR
0x1260a460	GDS_S_IPCRLNIL_ERR
0x1260a461	GDS_S_IPCRSTYIL_ERR
0x1260a462	GDS_S_IPCEVMOIL_ERR
0x1260a463	GDS_S_IPCSVMOIL_ERR
0x1260a464	GDS_S_IPCINVIL_ERR
0x1260a465	GDS_S_IPCOPIDIL_ERR
0x1260a466	GDS_S_IPCPTYEIL_ERR
0x1260a467	GDS_S_IPCDIRIDIL_ERR
0x1260a468	GDS_S_IPCTMOUTIL_ERR
0x1260a469	GDS_S_IPCPARSZIL_ERR
0x1260a46a	GDS_S_IPCSTATEIL_ERR
0x1260a46b	GDS_S_IPCUNLDIL_ERR
0x1260a46c	GDS_S_IPCSTATE_ERR

Message Number	Symbolic Name
0x1260a46d	GDS_S_IPCNOSERV_ERR
0x1260a46e	GDS_S_IPCSYNC_ERR
0x1260a46f	GDS_S_IPCSMSG_ERR
0x1260a470	GDS_S_IPCRMMSG_ERR
0x1260a471	GDS_S_IPCSSATT_ERR
0x1260a472	GDS_S_IPCSRATT_ERR
0x1260a473	GDS_S_IPCGETRES_ERR
0x1260a474	GDS_S_IPCHEAPREL_ERR
0x1260a475	GDS_S_IPCTMEX_ERR
0x1260a476	GDS_S_IPCLIMASS_ERR
0x1260a477	GDS_S_IPCSLIMSVR_ERR
0x1260a478	GDS_S_IPCLIMREG_ERR
0x1260a479	GDS_S_IPCLIMDIST_ERR
0x1260a47a	GDS_S_IPCLIMHEAP_ERR
0x1260a47b	GDS_S_IPCLIMCRED_ERR
0x1260a47c	GDS_S_IPCMSGSZ_ERR
0x1260a47d	GDS_S_IPCVPID_ERR
0x1260a47e	GDS_S_IPCNOREG_ERR
0x1260a47f	GDS_S_IPCMXDIST_ERR
0x1260a480	GDS_S_IPCMXREG_ERR
0x1260a481	GDS_S_IPCMXBUFS_ERR
0x1260a482	GDS_S_IPCMXSRV_ERR
0x1260a483	GDS_S_IPCMXCLT_ERR
0x1260a484	GDS_S_IPCMXCRD_ERR
0x1260a485	GDS_S_IPCMXHP_ERR
0x1260a486	GDS_S_IPCEXTSPEC_ERR

Message Number	Symbolic Name
0x1260a487	GDS_S_IPCUNKNOWN_ERR
0x1260a488	GDS_S_IPCINUSE_ERR
0x1260a578	GDS_S_ENTRYSTUB
0x1260a579	GDS_S_CREAD_ERR
0x1260a57a	GDS_S_CREADMSG_ERR
0x1260a57b	GDS_S_ACONTEXT_ERR
0x1260a57c	GDS_S_IOVERFLOW_ERR
0x1260a57d	GDS_S_ROVERFLOW_ERR
0x1260a57e	GDS_S_INVRCVBUFFER_ERR
0x1260a57f	GDS_S_INVABSID_ERR
0x1260a580	GDS_S_ROSFUFAILED_ERR
0x1260a581	GDS_S_NOTRSYNTAX_ERR
0x1260a582	GDS_S_INVVERSNO_ERR
0x1260a583	GDS_S_INVTRANS_ERR
0x1260a584	GDS_S_INVDATA_ERR
0x1260a585	GDS_S_NOTPBUF_ERR
0x1260a586	GDS_S_INVOPENID_ERR
0x1260a587	GDS_S_REG_ERR
0x1260a588	GDS_S_IPCEV_ERR
0x1260a589	GDS_S_SELECT_ERR
0x1260a58a	GDS_S_ILLSTATE_ERR
0x1260a58b	GDS_S_ILLSTATE_EVENT_ERR
0x1260a58c	GDS_S_ATTRFILE_ERR
0x1260a58d	GDS_S_CUPJOB_QUEUE_FULL
0x1260a58e	GDS_S_LARGE_CUPMSG_ELEMENT
0x1260a7d0	GDS_S_NDS_TSAP_ERR

Message Number	Symbolic Name
0x1260a7d1	GDS_S_NDS_TSEL_ERR
0x1260a7d2	GDS_S_NDS_NSAP_ERR
0x1260a7d3	GDS_S_NDS_NSAP_ERR1
0x1260a7d4	GDS_S_NDS_DNSAP_ERR
0x1260a7d5	GDS_S_NDS_MAPNSAP_ERR
0x1260a7d6	GDS_S_NDS_BUF_ERR
0x1260a7d7	GDS_S_NDS_PROV_ERR
0x1260a7d8	GDS_S_NDS_RULES_ERR
0x1260a7d9	GDS_S_NDS_OPMODE_ERR
0x1260a7da	GDS_S_NDS_MAP_ERR
0x1260a7db	GDS_S_NDS_SEL_ERR
0x1260a7dc	GDS_S_NDS_XTI_ERR
0x1260a7dd	GDS_S_NDS_VERS_ERR
0x1260a7de	GDS_S_NDS_NBGUID_ERR
0x1260a7df	GDS_S_NDS_NBGUIDV_ERR
0x1260a7e0	GDS_S_NDS_NBNAME_ERR
0x1260a7e1	GDS_S_NDS_NBNAMEV_ERR
0x1260a7e2	GDS_S_NDS_TPID_ERR
0x1260a7e3	GDS_S_NDS_REGION_ERR
0x1260a7e4	GDS_S_NDS_REGIONV_ERR
0x1260a7e5	GDS_S_NDS_PROC_ERR
0x1260a7e6	GDS_S_NDS_PROCV_ERR
0x1260a7e7	GDS_S_NDS_MAC_ERR
0x1260a7e8	GDS_S_NDS_MACV_ERR
0x1260a7e9	GDS_S_NDS_SUBID_ERR
0x1260a7ea	GDS_S_NDS_X121IP_ERR

Message Number	Symbolic Name
0x1260a7eb	GDS_S_NDS_X121DCC_ERR
0x1260a7ec	GDS_S_NDS_X121_ERR
0x1260a7ed	GDS_S_NDS_X121V_ERR
0x1260a7ee	GDS_S_NDS_E163IP_ERR
0x1260a7ef	GDS_S_NDS_E163NP_ERR
0x1260a7f0	GDS_S_NDS_E163CC_ERR
0x1260a7f1	GDS_S_NDS_E163AC_ERR
0x1260a7f2	GDS_S_NDS_E163_ERR
0x1260a7f3	GDS_S_NDS_E163V_ERR
0x1260a7f4	GDS_S_NDS_E164IP_ERR
0x1260a7f5	GDS_S_NDS_E164CC_ERR
0x1260a7f6	GDS_S_NDS_E164NDC_ERR
0x1260a7f7	GDS_S_NDS_E164_ERR
0x1260a7f8	GDS_S_NDS_E164V_ERR
0x1260a7f9	GDS_S_NDS_X21_ERR
0x1260a7fa	GDS_S_NDS_X21V_ERR
0x1260a7fb	GDS_S_NDS_PVC_ERR
0x1260a7fc	GDS_S_NDS_PVCV_ERR
0x1260a7fd	GDS_S_NDS_WORKSPACE
0x1260a7fe	GDS_S_NDS_NETADDR
0x1260a7ff	GDS_S_NDS_USAGE_ERR
0x1260a800	GDS_S_NDS_OCONF_ERR
0x1260a801	GDS_S_NDS_OCONFO_ERR
0x1260a802	GDS_S_NDS_WCONFO_ERR
0x1260a803	GDS_S_NDS_REDIR_ERR
0x1260a804	GDS_S_NDS_WSPACE_ERR

Message Number	Symbolic Name
0x1260a805	GDS_S_NDS_NETSPACE_ERR
0x1260a806	GDS_S_NDS_IFDESC_ERR
0x1260a807	GDS_S_NDS_IFMXDESC_ERR
0x1260a808	GDS_S_NDS_IFNM_ERR
0x1260a809	GDS_S_NDS_MXPROF_ERR
0x1260a80a	GDS_S_NDS_NONSAP_ERR
0x1260a80b	GDS_S_NDS_PROFID_ERR
0x1260a80c	GDS_S_NDS_DEVNM_ERR
0x1260a80d	GDS_S_NDS_PRIO_ERR
0x1260a80e	GDS_S_NDS_MXNET_ERR
0x1260a80f	GDS_S_NDS_CNSAP_ERR
0x1260a810	GDS_S_NDS_REGCOMP_ERR
0x1260a811	GDS_S_NDS_ENSAP_ERR
0x1260a812	GDS_S_NDS_MXOPT_ERR
0x1260a813	GDS_S_NDS_OPTMEM_ERR
0x1260a814	GDS_S_NDS_UWSPACE_ERR
0x1260a815	GDS_S_NDS_MISX121_ERR
0x1260a816	GDS_S_NDS_MISE164_ERR
0x1260a817	GDS_S_NDS_MISE163_ERR
0x1260a818	GDS_S_NDS_MISPROF_ERR
0x1260a819	GDS_S_NDS_YACC_ERR
0x1260a81a	GDS_S_NDS_LEX_ERR
0x1260a81b	GDS_S_NDS_LEX_ERR1
0x1260a81c	GDS_S_NDS_LEX_ERR2
0x1260a81d	GDS_S_NDS_LEX_ERR3
0x1260a81e	GDS_S_NDS_LEX_ERR4

Message Number	Symbolic Name
0x1260a81f	GDS_S_NDS_UNKNOWNREP_ERR
0x1260a898	GDS_S_ENTRYDSA
0x1260a899	GDS_S_EXITDSA
0x1260a89a	GDS_S_INITDSA
0x1260a89b	GDS_S_NO_DATAVERSION
0x1260a89c	GDS_S_DATAVERSION_ERR
0x1260a89d	GDS_S_ILL_SCHEMA_NAME
0x1260a89e	GDS_S_OPAT_MISSING
0x1260a89f	GDS_S_BAD_SOUNDEX
0x1260a8a0	GDS_S_BAD_DSACONF
0x1260a8a1	GDS_S_ACQU_CRED_ERR
0x1260a8a2	GDS_S_INIT_SEC_ERR
0x1260a8c2	GDS_S_ISBUILD_ERR
0x1260a8c3	GDS_S_ISADDINDEX_ERR
0x1260a8c4	GDS_S_ISOPEN_ERR
0x1260a8c5	GDS_S_ISCLOSE_ERR
0x1260a8c6	GDS_S_ISUNIQUEID_ERR
0x1260a8c8	GDS_S_ISSTART_ERR
0x1260a8c9	GDS_S_ISREAD_ERR
0x1260a8ca	GDS_S_ISWRITE_ERR
0x1260a8cb	GDS_S_ISDELETE_ERR
0x1260a8cc	GDS_S_ISLOCK_ERR
0x1260a8cd	GDS_S_ISRELEASE_ERR
0x1260a8ce	GDS_S_POOL_OPEN_OVFLW
0x1260a8cf	GDS_S_ILL_AT_SYNTAX
0x1260a8d0	GDS_S_MAX_DN_INDEX

Message Number	Symbolic Name
0x1260a8d1	GDS_S_MAX_DN_MEMORY
0x1260a8d2	GDS_S_ILL_DN_INDEX
0x1260a8d3	GDS_S_ILL_ACC_RIGHT
0x1260a8d4	GDS_S_ILL_ACC_CLASS
0x1260a8d5	GDS_S_ILL_DN_INTRPRTN
0x1260a8d6	GDS_S_DB_INCONSISTENT
0x1260a960	GDS_S_ENTRY_DAEMON
0x1260a961	GDS_S_EXIT_DAEMON
0x1260a962	GDS_S_SUP_USAGE
0x1260a963	GDS_S_SUP_WRONG_OPMODE
0x1260a964	GDS_S_SUP_ILL_DIRID
0x1260a965	GDS_S_SUP_LOCK_ERR
0x1260a966	GDS_S_SUP_ATTACH_ERR
0x1260a967	GDS_S_SUP_SYNC_DSA_ERR
0x1260a968	GDS_S_SUP_RESYNC_DSA_ERR
0x1260a969	GDS_S_SUP_FOPEN_ERR
0x1260a96a	GDS_S_SUP_NO_FILE_INFO
0x1260a96b	GDS_S_SUP_LOCDSA_ERR
0x1260a96c	GDS_S_SUP_LOCDSA_DNLIST_ERR
0x1260a96d	GDS_S_SUP_HEADER_ERR
0x1260a96e	GDS_S_SUP_REMDSA_DNLIST_ERR
0x1260a96f	GDS_S_SUP_INSUFF_MEM
0x1260a970	GDS_S_SUP_WR_HEADER_INFO
0x1260a971	GDS_S_SUP_OPENDIR_ERR
0x1260a972	GDS_S_SUP_DNLIST_REMDSA_ERR
0x1260a973	GDS_S_SUP_REM_UNUSED_ERR

Message Number	Symbolic Name
0x1260a974	GDS_S_SUP_SEARCH_ERR
0x1260a975	GDS_S_SUP_SEARCH_STATE_ERR
0x1260a976	GDS_S_SUP_UPD_OP_ERR
0x1260a977	GDS_S_SUP_CHANGE_ERRLOG_ERR
0x1260a978	GDS_S_SUP_DELENTN_ERRLOG_ERR
0x1260a979	GDS_S_SUP_READ_LOG_ERR
0x1260a97a	GDS_S_SUP_READ_COMPL_LOG_ERR
0x1260a97b	GDS_S_SUP_WRITE_LOG_ERR
0x1260aa28	GDS_S_ENTRY_MKISS
0x1260aa29	GDS_S_EXIT_MKISS
0x1260aa8c	GDS_S_ENTRY_GENDB
0x1260aa8d	GDS_S_EXIT_GENDB
0x1260aa8e	GDS_S_CBL_ERR
0x1260aa8f	GDS_S_SRT_SUP_MISSING
0x1260aa90	GDS_S_SRT_NNAM_AT_ERR
0x1260aa91	GDS_S_SRT_OC_INVALID
0x1260aa92	GDS_S_SRT_NSTR_OC_ERR
0x1260aa93	GDS_S_OCT_SUP_MISSING
0x1260aa94	GDS_S_OCT_NAUX_OC_ERR
0x1260aa95	GDS_S_OCT_AT_INVALID
0x1260aa96	GDS_S_ATSYNTAX_UNKNOWN
0x1260aa97	GDS_S_NAMAT_RECUR
0x1260aa98	GDS_S_SCH_INSUFFICIENT
0x1260aa99	GDS_S_SCH_INCONSISTENT
0x1260aa9a	GDS_S_BADSRT_ENTRY
0x1260aa9b	GDS_S_BADOCT_ENTRY

Message Number	Symbolic Name
0x1260aa9c	GDS_S_BADAT_ENTRY
0x1260aaf0	GDS_S_ENTRY_TRANSFER
0x1260aaf1	GDS_S_EXIT_TRANSFER
0x1260ab54	GDS_S_ENTRY_MKUPD
0x1260ab55	GDS_S_EXIT_MKUPD
0x1260ace4	gc_t_conflicting_option
0x1260ace5	gc_t_unknown_option
0x1260ace6	gc_t_missing_directory_id
0x1260ace7	gc_t_missing_authentication_type
0x1260ace8	gc_t_missing_object_name
0x1260ace9	gc_t_missing_attribute_info
0x1260acea	gc_t_missing_new_attribute_info
0x1260aceb	gc_t_missing_dsa_name
0x1260acec	gc_t_missing_psap_address
0x1260aced	gc_t_missing_user_name
0x1260acee	gc_t_missing_user_password
0x1260acef	gc_t_missing_filter
0x1260acf0	gc_t_missing_scope_of_search
0x1260acf1	gc_t_missing_time_limit
0x1260acf2	gc_t_missing_size_limit
0x1260acf3	gc_t_missing_arguments
0x1260acf4	gc_t_invalid_directory_id
0x1260acf5	gc_t_invalid_time_limit
0x1260acf6	gc_t_invalid_size_limit
0x1260acf7	gc_t_unknown_argument
0x1260acf8	gc_t_cannot_initialize_workspace

Message Number	Symbolic Name
0x1260acf9	gc_t_bind_not_made
0x1260acfa	gc_t_missing_value
0x1260acfb	gc_t_format_error
0x1260acfc	gc_t_mismatched_quotes
0x1260acfd	gc_t_invalid_parameter
0x1260acfe	gc_t_too_many_arguments
0x1260acff	gc_t_entry_not_found
0x1260ad00	gc_t_subordinates_not_found
0x1260ad01	gc_t_memory_insufficient
0x1260ad02	gc_t_ambiguous_option
0x1260ad03	gc_t_too_many_values
0x1260ad04	gc_t_unknown_gcp_error
0x1260ad06	gc_t_admin_limit_exceeded
0x1260ad07	gc_t_size_limit_exceeded
0x1260ad08	gc_t_time_limit_exceeded
0x1260ad09	gc_t_unavailable_crit_ext
0x1260ad0a	gc_t_referral_returned
0x1260ad0b	gc_t_incomplete_referral_returned
0x1260ad1e	gc_i_warning_file_eval
0x1260ad1f	gc_i_cannot_open_dir
0x1260ad20	gc_i_file_does_not_exist
0x1260ad21	gc_i_incorrect_usage
0x1260ad26	gc_i_invalid_argument
0x1260ad27	gc_i_unknown_operation
0x1260ad28	gc_i_missing_operation
0x1260ad29	gc_i_ambiguous_operation

Message Number	Symbolic Name
0x1260ad2a	gc_i_cannot_unset_var
0x1260ad6e	gc_t_omx_cannot_read_schema
0x1260ad6f	gc_t_omx_schema_not_read
0x1260ad71	gc_t_omx_no_start_obj_block
0x1260ad72	gc_t_omx_no_end_obj_block
0x1260ad73	gc_t_omx_empty_obj_block
0x1260ad74	gc_t_omx_obj_format_error
0x1260ad75	gc_t_omx_duplicate_obj_abbrev
0x1260ad76	gc_t_omx_duplicate_obj_obj_id
0x1260ad77	gc_t_omx_no_start_attr_block
0x1260ad78	gc_t_omx_no_end_attr_block
0x1260ad79	gc_t_omx_empty_attr_block
0x1260ad7a	gc_t_omx_attr_format_error
0x1260ad7b	gc_t_omx_duplicate_attr_abbrev
0x1260ad7c	gc_t_omx_duplicate_attr_obj_id
0x1260ad7d	gc_t_omx_no_start_class_block
0x1260ad7e	gc_t_omx_no_end_class_block
0x1260ad7f	gc_t_omx_empty_class_block
0x1260ad80	gc_t_omx_class_format_error
0x1260ad81	gc_t_omx_no_class_name
0x1260ad82	gc_t_omx_duplicate_class_block
0x1260ad83	gc_t_omx_class_block_undefined
0x1260ad84	gc_t_omx_invalid_abbrev
0x1260ad85	gc_t_omx_invalid_obj_id
0x1260ad86	gc_t_omx_invalid_class_name
0x1260ad87	gc_t_omx_invalid_syntax

Message Number	Symbolic Name
0x1260ad88	gc_t_omx_memory_insufficient
0x1260ad89	gc_t_omx_invalid_parameter
0x1260ad8a	gc_t_omx_unknown_abbrev
0x1260ad8b	gc_t_omx_unknown_obj_id
0x1260ad8c	gc_t_omx_unknown_omtype
0x1260ad8d	gc_t_omx_missing_ava
0x1260ad8e	gc_t_omx_missing_abbrev
0x1260ad8f	gc_t_omx_format_error
0x1260ad90	gc_t_omx_unknown_error
0x1260ad91	gc_t_omx_missing_rdn_delimiter
0x1260ad92	gc_t_omx_mismatched_quotes
0x1260ad93	gc_t_omx_missing_equal_operator
0x1260ad94	gc_t_omx_missing_attr_value
0x1260ad95	gc_t_omx_missing_attr_info
0x1260ad96	gc_t_omx_missing_class_start_op
0x1260ad97	gc_t_omx_missing_class_end_op
0x1260ad98	gc_t_omx_missing_class_value
0x1260ad99	gc_t_omx_missing_comp_value
0x1260ad9a	gc_t_omx_mismatched_brackets
0x1260ad9b	gc_t_omx_unexpected_operator
0x1260ad9c	gc_t_omx_wrong_value
0x1260ad9d	gc_t_omx_unknown_keyword
0x1260ad9e	gc_t_omx_missing_operator
0x1260ad9f	gc_t_omx_missing_compound_op
0x1260ada0	gc_t_unknown_conv_lib_error
0x1260ada1	gc_t_om_encoding_invalid

Message Number	Symbolic Name
0x1260ada2	gc_t_om_function_declined
0x1260ada3	gc_t_om_function_interrupted
0x1260ada4	gc_t_om_memory_insufficient
0x1260ada5	gc_t_om_network_error
0x1260ada6	gc_t_om_no_such_class
0x1260ada7	gc_t_om_no_such_exclusion
0x1260ada8	gc_t_om_no_such_modification
0x1260ada9	gc_t_om_no_such_object
0x1260adaa	gc_t_om_no_such_rules
0x1260adab	gc_t_om_no_such_syntax
0x1260adac	gc_t_om_no_such_type
0x1260adad	gc_t_om_no_such_workspace
0x1260adae	gc_t_om_not_an_encoding
0x1260adaf	gc_t_om_not_concrete
0x1260adb0	gc_t_om_not_present
0x1260adb1	gc_t_om_not_private
0x1260adb2	gc_t_om_not_the_services
0x1260adb3	gc_t_om_permanent_error
0x1260adb4	gc_t_om_pointer_invalid
0x1260adb5	gc_t_om_system_error
0x1260adb6	gc_t_om_temporary_error
0x1260adb7	gc_t_om_too_many_values
0x1260adb8	gc_t_om_values_not_adjacent
0x1260adb9	gc_t_om_wrong_value_length
0x1260adba	gc_t_om_wrong_value_makeup
0x1260adbb	gc_t_om_wrong_value_number

Message Number	Symbolic Name
0x1260adb0	gc_t_om_wrong_value_position
0x1260adb1	gc_t_om_wrong_value_syntax
0x1260adb2	gc_t_om_wrong_value_type
0x1260adb3	gc_t_omx_class_not_found_in_schema_file
0x1260adb4	gc_t_unknown_xom_error
0x1260ae11	gsu_existing_error
0x1260ae12	gsu_fopen_error
0x1260ae13	gsu_fclose_error
0x1260ae14	gsu_inter_write_error
0x1260ae15	gsu_unknown_switch
0x1260ae27	gsu_readline_dsas_found
0x1260ae28	gsu_default_schema_failed
0x1260ae29	gsu_missing_local_dsa_name
0x1260ae2a	gsu_missing_principal_name
0x1260ae2b	gsu_missing_psap_name
0x1260ae2c	gsu_local_schema_error
0x1260ae2e	gsu_config_type_failed
0x1260ae2f	gsu_max_clients
0x1260ae30	gsu_max_servers
0x1260ae31	gsu_max_dir_id
0x1260ae32	gsu_access_right_failed
0x1260ae38	gsu_input_file_poss
0x1260ae39	gsu_secur_false
0x1260ae3a	gsu_psap_must_same
0x1260ae43	gsu_dirid_client_no_overwrite
0x1260ae44	gsu_dirid_server_no_overwrite

Message Number	Symbolic Name
0x1260afa0	GST_INV_DEBUG_LEVEL
0x1260afa1	GST_NO_LOGFILE
0x1260afa2	GST_LOGOPEN_ERR
0x1260afa3	GST_LOGCLOSE_ERR
0x1260afa4	GST_OFFSET_ERR
0x1260afa5	GST_ERR_OVERFLOW
0x1260afa6	GST_CONVCHAR_MISSING
0x1260afa7	GST_LOGREAD_ERR
0x12862016	gssdce_s_invalid_handle
0x12862017	gssdce_s_no_login_context
0x12862019	gssdce_s_credential_corrupt
0x1286201a	gssdce_s_unimplemented_feature
0x1286201b	gssdce_s_bad_usage
0x1286201c	gssdce_s_name_required
0x1286201d	gssdce_s_bad_name
0x1286201e	gssdce_s_unknown_principal_name
0x12862020	gssdce_s_couldnt_validate_context
0x12862021	gssdce_s_no_rgy_available
0x12862022	gssdce_s_couldnt_translate_name
0x12862024	gssdce_s_out_of_memory
0x12862025	gssdce_s_param_required
0x12862026	gssdce_s_unsupported_mechanism
0x12862027	gssdce_s_couldnt_get_mech_cred
0x1286202a	gssdce_s_invalid_context_state
0x1286202f	gssdce_s_ber_decoding_error
0x12862030	gssdce_s_authentication_error

Message Number	Symbolic Name
0x12862032	gssdce_s_unsupported_name_type
0x12862034	gssdce_s_bindings_length_error
0x12862035	gssdce_s_bindings_value_error
0x12862036	gssdce_s_no_buffer
0x12862039	gssdce_s_bad_signature
0x1286203a	gssdce_s_bad_sig_seq
0x1286203c	gssdce_s_reflected_packet
0x1286203d	gssdce_s_message_omitted
0x1286203e	gssdce_s_message_already_seen
0x1286203f	gssdce_s_message_late
0x12862040	gssdce_s_message_out_of_order
0x12862041	gssdce_s_unsupported_signature_algorithm
0x12862042	gssdce_s_unrecognized_token_type
0x12862043	gssdce_s_seal_algorithm_not_allowed
0x12862044	gssdce_s_unsupported_encryption_algorithm
0x12862045	gssdce_s_short_token
0x12862046	gssdce_s_unexpected_token_type
0x12862047	gssdce_s_couldnt_decrypt_token
0x12862048	gssdce_s_bad_plaintext_padding
0x12862049	gssdce_s_incorrect_server_principal
0x1286204a	gssdce_s_bad_status_type
0x1286204b	gssdce_s_bad_status_value
0x1286204c	gssdce_s_need_acceptor_context
0x1286204d	gssdce_s_no_pac_available
0x1286204e	gssdce_s_no_conf
0x1286204f	gssdce_s_no_such_key

Message Number	Symbolic Name
0x12862050	gssdce_s_delegation_error
0x12862056	gss_s_nomem_1
0x12862059	gss_s_cant_reg_table
0x1286205a	gss_s_cant_create_gss_mutex_attr
0x1286205b	gss_s_cant_set_gss_attributes
0x1286205c	gss_s_cant_create_gss_mutex
0x1286205d	gss_s_cant_delete_gss_mutex_attr
0x1286205e	gss_s_cant_create_cred_mutex_attr
0x1286205f	gss_s_cant_set_cred_attributes
0x12862060	gss_s_cant_create_cred_mutex
0x12862061	gss_s_cant_delete_cred_mutex_attr
0x12862062	gss_s_cant_create_ctx_mutex_attr
0x12862063	gss_s_cant_set_ctx_attributes
0x12862064	gss_s_cant_create_ctx_mutex
0x12862065	gss_s_cant_delete_ctx_mutex_attr
0x12862066	gss_s_cant_create_rgy_mutex_attr
0x12862067	gss_s_cant_set_rgy_attributes
0x12862068	gss_s_cant_create_rgy_mutex
0x12862069	gss_s_cant_delete_rgy_mutex_attr
0x1286206a	gss_s_cant_create_elem_mutex_attr
0x1286206b	gss_s_cant_set_elem_attributes
0x1286206e	gss_s_free_cred_handle_fail
0x1286206f	gss_s_res_cred_lock_failed
0x12862071	gss_s_res_cred_not_found
0x12862072	gss_s_alloc_cred_nomem
0x12862073	gss_s_alloc_cred_nonew

Message Number	Symbolic Name
0x12862074	gss_s_alloc_cred_allocated
0x12862075	gss_s_create_cred_nolock
0x12862076	gss_s_citg_nolock_cred
0x12862077	gss_s_resolve_ctx_nolock
0x12862078	gss_s_alloc_ctx_nomem
0x12862079	gss_s_create_ctx_nolock
0x1286207b	gss_s_destroy_ctx_nolock
0x1286207d	gss_s_citg_nolock_ctx
0x12862090	gss_s_gac_err_ctx_exp
0x12862094	gss_s_gac_err_ctx_exp1
0x1286209d	gss_s_gac_sls_failed
0x1286209f	gss_s_gac_cred_inv
0x128620a3	gss_s_gac_slv_failed
0x128620a9	gss_s_frc_bind_retrying
0x128620aa	gss_s_frc_retry_exceeded
0x128620ab	gss_s_cei_frc_failed
0x128620ad	gss_s_cei_referral
0x128620ae	gss_s_cei_server_unavailable
0x128620af	gss_s_cei_parse_failed
0x128620b1	gss_s_cei_gn_failed
0x128620b3	gss_s_ptn_inv_cred
0x128620b5	gss_s_ptn_frc_failed
0x128620b7	gss_s_ptn_scg_failed
0x128620b8	gss_s_ptn_scgp_failed
0x128620ba	gss_s_ptn_referral
0x128620bb	gss_s_ptn_server_unavailable

Message Number	Symbolic Name
0x128620bc	gss_s_ptn_retry_exceeded
0x128620bd	gss_s_ptn_gn_failed
0x128620bf	gss_s_ptn_not_null
0x128620c0	gss_s_ptn_nomem
0x128620c4	gss_s_ctn_not_null
0x128620c5	gss_s_oc_nomem
0x128620c6	gss_s_osc_nomem
0x128620c7	gss_s_osa_nomem
0x128620ca	gss_s_wnd_reverse
0x128620d2	gss_s_lcc_null
0x128620db	gss_s_lcc_no_def_ctx
0x128620dc	gss_s_lcc_no_pac
0x128620dd	gss_s_lcc_cred_nomem
0x128620e0	gss_s_ac_named_init
0x128620e1	gss_s_ac_bad_usage
0x128620e2	gss_s_ac_noname_default
0x128620e3	gss_s_ac_ini_failed
0x128620e4	gss_s_ac_cred_nomem1
0x128620e5	gss_s_ac_cred_nomem2
0x128620e7	gss_s_ac_reg_failed
0x128620e9	gss_s_wrap_mech_long
0x128620ea	gss_s_wrap_ber_long
0x128620eb	gss_s_wrap_nomem
0x128620ee	gss_s_unwrap_inv1
0x128620ef	gss_s_unwrap_inv2
0x128620f0	gss_s_unwrap_inv3

Message Number	Symbolic Name
0x128620f1	gss_s_unwrap_inv4
0x128620f2	gss_s_unwrap_inv5
0x128620f3	gss_s_unwrap_nomem
0x128620f5	gss_s_gdt_scgi_failed
0x128620f6	gss_s_gdt_scic_failed
0x128620f7	gss_s_gdt_slgi_failed
0x128620f8	gss_s_gdt_slic_failed
0x128620fa	gss_s_ic_null_context
0x128620fc	gss_s_ic_inv_context
0x128620ff	gss_s_ic_no_def_ctx
0x12862100	gss_s_ic_cred_nomem
0x12862101	gss_s_ic_inv_cred
0x12862102	gss_s_ic_cred_not_init
0x12862103	gss_s_ic_ctx_nomem
0x12862104	gss_s_ic_inv_cred_mech
0x12862105	gss_s_ic_cred_nodce
0x12862106	gss_s_ic_cred_nokrb
0x12862107	gss_s_ic_inv_req_mech
0x12862109	gss_s_ic_deleg_type_unk
0x1286210b	gss_s_ic_cant_disable_deleg
0x1286210e	gss_s_ic_cant_delegate
0x1286210f	gss_s_ic_no_krb_cred_cache
0x12862111	gss_s_ic_bad_name
0x12862112	gss_s_ic_bad_name1
0x12862113	gss_s_ic_no_server_ticket
0x12862116	gss_s_ic_skbm_failed

Message Number	Symbolic Name
0x1286211a	gss_s_ic_no_token
0x1286211b	gss_s_ic_inv_wrapper
0x1286211d	gss_s_ic_mutual_bad_mech
0x1286211e	gss_s_ic_bad_mutual_type
0x12862123	gss_s_ic_mutual_dec_failed
0x1286212a	gss_s_ic_error_purging
0x12862130	gss_s_ac_null_ctx
0x12862131	gss_s_ac_bad_ctx
0x12862132	gss_s_ac_bad_ctx_state
0x12862134	gss_s_ac_bad_cred
0x12862135	gss_s_ac_ctx_nomem
0x12862136	gss_s_ac_nomem1
0x12862137	gss_s_ac_bad_token_wrapper
0x1286213a	gss_s_ac_inv_mech
0x1286213b	gss_s_ac_bad_tok_type
0x1286213e	gss_s_ac_skdm_failed
0x12862143	gss_s_ac_cei_failed
0x12862144	gss_s_ac_names_differ
0x12862146	gss_s_ac_nomem2
0x12862149	gss_s_ac_hash_bad_length
0x1286214a	gss_s_ac_bindings_mismatch
0x1286214c	gss_s_ac_no_pac_name
0x1286214e	gss_s_ac_unk_authz
0x12862153	gss_s_ac_skbr_failed
0x12862157	gss_s_ac_cli_name_noconv
0x1286215c	gss_s_ac_unk_deleg_type

Message Number	Symbolic Name
0x1286215d	gss_s_ac_no_lc
0x1286215e	gss_s_ac_no_deleg1
0x1286215f	gss_s_ac_trace_no_lc
0x12862160	gss_s_ac_no_deleg2
0x12862161	gss_s_ac_inv_deleg
0x12862162	gss_s_ac_unk_deleg_type1
0x12862165	gss_s_bp_inv_state
0x12862166	gss_s_bp_unk_sig_alg
0x12862167	gss_s_bp_inv_tok_type
0x12862168	gss_s_bp_noseal
0x12862169	gss_s_bp_unk_enc_alg
0x1286216c	gss_s_bp_inv_seal_alg
0x1286216d	gss_s_bp_nomem1
0x12862181	gss_s_vrs_seq_invalid
0x12862182	gss_s_dmh_unwrap_failed
0x12862183	gss_s_dmh_short_token
0x12862184	gss_s_dmh_unk_tok_type
0x12862185	gss_s_dmh_unk_sign_alg
0x12862186	gss_s_dmh_unk_enc_alg
0x12862187	gss_s_dmh_seal_sd
0x12862188	gss_s_dmh_seq_num_inv
0x12862189	gss_s_dmh_refl_tok
0x1286218a	gss_s_pct_no_token
0x1286218b	gss_s_pct_inv_ctx
0x1286218c	gss_s_pct_inv_ctx_state
0x1286218d	gss_s_pct_inv_cksum

Message Number	Symbolic Name
0x1286218e	gss_s_dsc_inv_ctx
0x1286218f	gss_s_sign_bad_buffer
0x12862190	gss_s_sign_inv_ctx
0x12862191	gss_s_sign_inv_ctx_state
0x12862192	gss_s_sign_bpm_failed
0x12862193	gss_s_vfy_bad_buffer
0x12862194	gss_s_vfy_inv_ctx
0x12862195	gss_s_vfy_inv_ctx_state
0x12862196	gss_s_vfy_dmh_failed
0x12862197	gss_s_vfy_bad_tok_type
0x1286219b	gss_s_vfy_sign_unk
0x1286219c	gss_s_vfy_bad_sig
0x1286219d	gss_s_uns_dmh_failed
0x1286219e	gss_s_uns_nomem
0x128621a0	gss_s_uns_decr_failed
0x128621a1	gss_s_uns_inv_pad_byte
0x128621a2	gss_s_uns_inv_pad_check
0x128621a3	gss_s_disp_nomem
0x128621a4	gss_s_reln_null_name
0x128621a5	gss_s_xps_inv_ctx
0x128621a6	gss_s_xps_inv_ctx_state
0x128621a7	gss_s_xps_no_pac
0x128621a8	gss_s_xcc_inv_ctx
0x128621a9	gss_s_xcc_inv_ctx_state
0x128621aa	gss_s_xcc_no_creds
0x128621ae	gss_s_fmi_ksched_failed

Message Number	Symbolic Name
0x128621b0	gss_s_fmi_md5_nomem
0x128621b1	gss_s_seca_timestamp
0x128621b3	gss_s_seca_null_bindings
0x128621b6	gss_s_seca_skdmc_failed
0x128621ba	gss_s_seca_cksum_type_wrong
0x128621bb	gss_s_seca_cksum_too_short
0x128621bc	gss_s_seca_cksum_length_wrong
0x128621bd	gss_s_seca_nomem1
0x128621be	gss_s_seca_zero_channel_binding
0x128621bf	gss_s_seca_no_cksum
0x128621c3	gss_s_seca_bad_cksum_type
0x128621c4	gss_s_seca_copy_kblock_failed
0x128621c5	gss_s_seca_skbmc_failed
0x128621d1	gss_s_ds_bad_mech
0x128621d7	gss_s_gdt_scgdt_failed
0x128621da	gss_s_ac_lcc_failed
0x128621ec	gssdce_s_invalid_ownership
0x13283001	NIDL_MESSAGE_VERSION
0x13283002	NIDL_CMDERR
0x13283003	NIDL_DEFAUTOHAN
0x13283004	NIDL_FILESOURCE
0x13283005	NIDL_FLOATPROM
0x13283006	NIDL_IMPORTIDL
0x13283007	NIDL_INCLCREATE
0x13283008	NIDL_LEGALVALS
0x13283009	NIDL_LINEFILE

Message Number	Symbolic Name
0x1328300a	NIDL_NAMEDECLAT
0x1328300b	NIDL_NAMEREFAT
0x1328300c	NIDL_NEWUUID
0x1328300d	NIDL_OPTIONSTABLE
0x1328300e	NIDL_PROCESSACF
0x1328300f	NIDL_RUNCPP
0x13283010	NIDL_STUBCOMPILE
0x13283011	NIDL_STUBCREATE
0x13283012	NIDL_STUBDELETE
0x13283013	NIDL_TYPEREPAS
0x13283014	NIDL_USAGE
0x13283015	NIDL_VERSION
0x13283016	NIDL_DUPPROTOCOL
0x13283017	NIDL_ENDPOINTSYNTAX
0x13283018	NIDL_EXTRAPUNCT
0x13283019	NIDL_FPHANATTR
0x1328301a	NIDL_IDTOOLONG
0x1328301b	NIDL_INCLUDEXT
0x1328301c	NIDL_INCLTYPE
0x1328301d	NIDL_INTSIZEREQ
0x1328301e	NIDL_LINENONSCAL
0x1328301f	NIDL_MISSPTRCLASS
0x13283020	NIDL_MIXEDARRATTR
0x13283021	NIDL_MULATTRDEF
0x13283022	NIDL_NAMETOOLONG
0x13283023	NIDL_NOCODEOPS

Message Number	Symbolic Name
0x13283024	NIDL_NOENDPOINT
0x13283025	NIDL_NONPORTCHAR
0x13283026	NIDL_NOSEMCHK
0x13283027	NIDL_OLDUUID
0x13283028	NIDL_OUTDIRIGN
0x13283029	NIDL_REFUNIQUE
0x1328302a	NIDL_SRVNOCODE
0x1328302b	NIDL_SYSIDLNAME
0x1328302c	NIDL_REQCMDOPT
0x1328302d	NIDL_ACFINIDL
0x1328302e	NIDL_ANONPIPE
0x1328302f	NIDL_ANONTYPE
0x13283030	NIDL_ARMREFPTR
0x13283031	NIDL_ARRELEMCFMT
0x13283032	NIDL_ARRELEMCTX
0x13283033	NIDL_ARRELEMPIPE
0x13283034	NIDL_ARRSIZEINFO
0x13283035	NIDL_ARRCFMTDIM
0x13283036	NIDL_ARRPTRPRM
0x13283037	NIDL_ARRSYNTAX
0x13283038	NIDL_ARRVARYDIM
0x13283039	NIDL_ARRXMITOPEN
0x1328303a	NIDL_ATTRTRANS
0x1328303b	NIDL_ATTRVALIND
0x1328303c	NIDL_BADTAGREF
0x1328303d	NIDL_BROADPIPE

Message Number	Symbolic Name
0x1328303e	NIDL_CASEDISCTYPE
0x1328303f	NIDL_CASECONENUM
0x13283040	NIDL_CFMTARRREF
0x13283041	NIDL_CFMTBASETYP
0x13283042	NIDL_CFMTFLDLAST
0x13283043	NIDL_CFMTUNION
0x13283044	NIDL_CONFHANATTR
0x13283045	NIDL_CONFLINEATTR
0x13283046	NIDL_CONFLICTATTR
0x13283047	NIDL_CONFREPRTYPE
0x13283048	NIDL_CONSTNOTFND
0x13283049	NIDL_CONSTTTYPE
0x1328304a	NIDL_HYPERCONST
0x1328304b	NIDL_MISSONINTER
0x1328304c	NIDL_MISSONATTR
0x1328304d	NIDL_MISSONARR
0x1328304e	NIDL_MISSONOP
0x1328304f	NIDL_MISSONPARAM
0x13283050	NIDL_CTXBASETYP
0x13283051	NIDL_CTXPTRVOID
0x13283052	NIDL_CTXSTRFLD
0x13283053	NIDL_CTXUNIMEM
0x13283054	NIDL_DEFNOTCOMP
0x13283055	NIDL_DUPCASEVAL
0x13283056	NIDL_EOF
0x13283057	NIDL_EOFNEAR

Message Number	Symbolic Name
0x13283058	NIDL_ERRINATTR
0x13283059	NIDL_ERRSTATDEF
0x1328305a	NIDL_FILENOTDIR
0x1328305b	NIDL_FILENOTFND
0x1328305c	NIDL_FIRSTINATTR
0x1328305d	NIDL_FIRSTYPEINT
0x1328305e	NIDL_FLOATCONSTNOSUP
0x1328305f	NIDL_FPCFMTARR
0x13283060	NIDL_FPLOCINT
0x13283061	NIDL_FPHANPRM
0x13283062	NIDL_FPINPRM
0x13283063	NIDL_FPPIPEBASE
0x13283064	NIDL_FPSTRFLD
0x13283065	NIDL_FPUNIMEM
0x13283066	NIDL_FUNTYPDCL
0x13283067	NIDL_HANARRELEM
0x13283068	NIDL_HANDLEIN
0x13283069	NIDL_HANDLEPTR
0x1328306a	NIDL_HANFIRSTPRM
0x1328306b	NIDL_HANPIPEBASE
0x1328306c	NIDL_HANPRMIN
0x1328306d	NIDL_HANSTRFLD
0x1328306e	NIDL_HANUNIMEM
0x1328306f	NIDL_HANXMITAS
0x13283070	NIDL_IDEMPIPE
0x13283071	NIDL_IGNARRELEM

Message Number	Symbolic Name
0x13283072	NIDL_IGNATTRPTR
0x13283073	NIDL_ILLFIELDATTR
0x13283074	NIDL_ILLPARAMATTR
0x13283075	NIDL_ILLYPEATTR
0x13283076	NIDL_ILLOPATTR
0x13283077	NIDL_ILLINTATTR
0x13283078	NIDL_ILLMEMATTR
0x13283079	NIDL_IMPHANVAR
0x1328307a	NIDL_IMPORTLOCAL
0x1328307b	NIDL_INCOMPATV1
0x1328307c	NIDL_INTCODEATTR
0x1328307d	NIDL_INTDIVBY0
0x1328307e	NIDL_INTLINEATTR
0x1328307f	NIDL_INTNAMDIF
0x13283080	NIDL_INTOVERFLOW
0x13283081	NIDL_INTCONSTINVAL
0x13283082	NIDL_INTUIDREQ
0x13283083	NIDL_INVARRIND
0x13283084	NIDL_INVCASETYP
0x13283085	NIDL_INVCHARLIT
0x13283086	NIDL_INVOCTDIGIT
0x13283087	NIDL_INVOKECPP
0x13283088	NIDL_INVOOLPRM
0x13283089	NIDL_INVOPTION
0x1328308a	NIDL_INVPARAMS
0x1328308b	NIDL_INVPTRCTX

Message Number	Symbolic Name
0x1328308c	NIDL_INVPTRPIPE
0x1328308d	NIDL_LASTINATTR
0x1328308e	NIDL_LASTLENCONF
0x1328308f	NIDL_LASTYPEINT
0x13283090	NIDL_LBLESSUB
0x13283091	NIDL_LENINATTR
0x13283092	NIDL_LENTYPEINT
0x13283093	NIDL_MAJORTOOLARGE
0x13283094	NIDL_MAXCFMTYPE
0x13283095	NIDL_MAXIDINTF
0x13283096	NIDL_MAXIDTYPTA
0x13283097	NIDL_MAXIDTYPHAN
0x13283098	NIDL_MAXIDTYPCH
0x13283099	NIDL_MAXIDTYPPT
0x1328309a	NIDL_MAXIDTYPPPIPE
0x1328309b	NIDL_MAXIDTYPPRA
0x1328309c	NIDL_MAXIDTYPOOL
0x1328309d	NIDL_MAXINATTR
0x1328309e	NIDL_MAXSIZEATTR
0x1328309f	NIDL_MAXSIZECONF
0x132830a0	NIDL_MAXTYPEINT
0x132830a1	NIDL_BFINNTYPE
0x132830a2	NIDL_MAYBEOUTPRM
0x132830a3	NIDL_MINATTREQ
0x132830a4	NIDL_MINCFMTYPE
0x132830a5	NIDL_MININATTR

Message Number	Symbolic Name
0x132830a6	NIDL_MINORTOOLARGE
0x132830a7	NIDL_MINTYPEINT
0x132830a8	NIDL_NAMEALRDEC
0x132830a9	NIDL_NAMENOTCONST
0x132830aa	NIDL_NAMENOTFIELD
0x132830ab	NIDL_NAMENOTFND
0x132830ac	NIDL_NAMENOTPARAM
0x132830ad	NIDL_NAMENOTTYPE
0x132830ae	NIDL_NAMEPREVDECLAT
0x132830af	NIDL_NLSCATVER
0x132830b0	NIDL_NLSWRONG
0x132830b1	NIDL_NONINTEXP
0x132830b2	NIDL_NYSALIGN
0x132830b3	NIDL_NYSINSHAPE
0x132830b4	NIDL_NYSNONZEROLB
0x132830b5	NIDL_NYSOUTSHAPE
0x132830b6	NIDL_NYSUNIQUE
0x132830b7	NIDL_OPCODEATTR
0x132830b8	NIDL_OPENREAD
0x132830b9	NIDL_OPENWRITE
0x132830ba	NIDL_OPNOTDEF
0x132830bb	NIDL_OUTCFMTARR
0x132830bc	NIDL_OUTPRMREF
0x132830bd	NIDL_OUTPTRPRM
0x132830be	NIDL_OUTUNIQUE
0x132830bf	NIDL_OPRESPIPE

Message Number	Symbolic Name
0x132830c0	NIDL_OUTSTAR
0x132830c1	NIDL_OUTUNIQRPM
0x132830c2	NIDL_PIPEBASETYP
0x132830c3	NIDL_PIPESTRFLD
0x132830c4	NIDL_PIPEUNIMEM
0x132830c5	NIDL_PIPEXMITAS
0x132830c6	NIDL_PRMBYREF
0x132830c7	NIDL_PRMINOROUT
0x132830c8	NIDL_PRMLINEATTR
0x132830c9	NIDL_PRMNOTDEF
0x132830ca	NIDL_PTRATTRHAN
0x132830cb	NIDL_PTRATTRPTR
0x132830cc	NIDL_PTRBASETYP
0x132830cd	NIDL_PTRCFMTARR
0x132830ce	NIDL_PTRCTXHAN
0x132830cf	NIDL_PTRPIPE
0x132830d0	NIDL_PTRV1ENUM
0x132830d1	NIDL_PTRVARYARR
0x132830d2	NIDL_PTRVOIDCTX
0x132830d3	NIDL_REFATTRPTR
0x132830d4	NIDL_REFFUNRES
0x132830d5	NIDL_RENAMEFAILED
0x132830d6	NIDL_REPASNEST
0x132830d7	NIDL_SCOPELVLS
0x132830d8	NIDL_SIZEARRTYPE
0x132830d9	NIDL_SIZECFMTYPE

Message Number	Symbolic Name
0x132830da	NIDL_SIZEINATTR
0x132830db	NIDL_SIZEMISMATCH
0x132830dc	NIDL_SIZEPRMPTR
0x132830dd	NIDL_SIZEATYPEINT
0x132830de	NIDL_SIZEVARREPAS
0x132830df	NIDL_SIZEVARXMITAS
0x132830e0	NIDL_SMALLARRSYN
0x132830e1	NIDL_SMALLCFMT
0x132830e2	NIDL_SMALLINV
0x132830e3	NIDL_SMALLMINFIRST
0x132830e4	NIDL_SMALLMULTID
0x132830e5	NIDL_SMALLOPENLB
0x132830e6	NIDL_STRARRAY
0x132830e7	NIDL_STRARRAYV1
0x132830e8	NIDL_STRCHARBYTE
0x132830e9	NIDL_STRUCTXMITCFMT
0x132830ea	NIDL_STRUNTERM
0x132830eb	NIDL_STRV1ARRAY
0x132830ec	NIDL_STRV1FIXED
0x132830ed	NIDL_STRVARY
0x132830ee	NIDL_STSATTRONCE
0x132830ef	NIDL_STSPRMOUT
0x132830f0	NIDL_STSRETVAl
0x132830f1	NIDL_STSVRTYPE
0x132830f2	NIDL_SYNTAXERR
0x132830f3	NIDL_SYNTAXNEAR

Message Number	Symbolic Name
0x132830f4	NIDL_SYNTAXUUID
0x132830f5	NIDL_SYSERRMSG
0x132830f6	NIDL_TOOMANYELEM
0x132830f7	NIDL_TOOMANYPORT
0x132830f8	NIDL_TYPENOTFND
0x132830f9	NIDL_TYPLINEATTR
0x132830fa	NIDL_TYPNOTDEF
0x132830fb	NIDL_UNBALPARENS
0x132830fc	NIDL_UNBALBRACKETS
0x132830fd	NIDL_UNBALBRACES
0x132830fe	NIDL_UNIDISCTYP
0x132830ff	NIDL_UNIQATTRHAN
0x13283100	NIDL_UNIQATTRPTR
0x13283101	NIDL_UNIQCTXHAN
0x13283102	NIDL_UNIQFUNRES
0x13283103	NIDL_UNKNOWNATTR
0x13283104	NIDL_USESTRANS
0x13283105	NIDL_UUIDINV
0x13283106	NIDL_VARDECLNOSUP
0x13283107	NIDL_VOIDOPPTR
0x13283108	NIDL_XMITASREP
0x13283109	NIDL_XMITCFMTARR
0x1328310a	NIDL_XMITPIPEBASE
0x1328310b	NIDL_XMITPTR
0x1328310c	NIDL_XMITTYPEATTRS
0x1328310d	NIDL_BUGNOBUG

Message Number	Symbolic Name
0x1328310e	NIDL_CONFLICTOPT
0x1328310f	NIDL_COMMENTEOF
0x13283110	NIDL_COMPABORT
0x13283111	NIDL_INTERNAL_ERROR
0x13283112	NIDL_INVBUG
0x13283113	NIDL_INVNOBUG
0x13283114	NIDL_MAXWARN
0x13283115	NIDL_OPTNOVAL
0x13283116	NIDL_OUTOFMEM
0x13283117	NIDL_SRCFILELEN
0x13283118	NIDL_SRCFILEREQ
0x13283119	NIDL_UNKFLAG
0x1328311a	NIDL_NOPORTNEU
0x1328311b	NIDL_NOPORTUNIQUE
0x1328311c	NIDL_DISCRIMIN
0x1328311d	NIDL_DISCRIMOUT
0x1328311e	NIDL_DISCRIMREPAS
0x1328311f	NIDL_DISCRIMXMITAS
0x13283120	NIDL_EUMEMATTR
0x13283121	NIDL_NEUARRAY
0x13283122	NIDL_NEUREPAS
0x13283123	NIDL_NEUREPTYPE
0x13283124	NIDL_NEUSWATTR
0x13283125	NIDL_NEUSWPTR
0x13283126	NIDL_NEUSWTYPE
0x13283127	NIDL_NEUXMITAS

Message Number	Symbolic Name
0x13283128	NIDL_NEUXMITYPE
0x13283129	NIDL_PTRNEUNION
0x1328312a	NIDL_SWATTRNEU
0x1328312b	NIDL_SWDATATYPE
0x1328312c	NIDL_SWTYPENEU
0x1328312d	NIDL_FLDXMITCFMT
0x1328312e	NIDL_TYPEREPCFMT
0x1328312f	NIDL_ARMUNIQUEPTR
0x13283130	NIDL_LANGCFMTSTRCT
0x13283131	NIDL_LANGCFMTSTRNG
0x13283132	NIDL_LANGMAPCHAR
0x13283133	NIDL_LANGPIPESNS
0x13283134	NIDL_LANGUNSFNRS
0x13283135	NIDL_LANGMAXDIM
0x13283136	NIDL_LANGMIXCASE
0x13283137	NIDL_LANGATTRNS
0x13283138	NIDL_ARRFUNRES
0x13283139	NIDL_ATTRPTRVOID
0x1328313a	NIDL_HANATTRTRAN
0x1328313b	NIDL_FWDTAGREF
0x1328313c	NIDL_ATTRUSEMULT
0x1328313d	NIDL_TYPEATTRUSE
0x1328313e	NIDL_NOPORTNZLB
0x1328313f	NIDL_NOPORTCFMT
0x13283140	NIDL_NOPORTVARY
0x13283141	NIDL_ENCNOPARAMS

Message Number	Symbolic Name
0x13283142	NIDL_DECNOPARAMS
0x13283143	NIDL_OPREFDELIN
0x13283144	NIDL_ENCOUTONLY
0x13283145	NIDL_DECINONLY
0x13283146	NIDL_ENCDECDIR
0x13283147	NIDL_ENCDECPipe
0x13283148	NIDL_ENCDECBIND
0x13283149	NIDL_EXCNOTDEF
0x1328314a	NIDL_INVFILESPEC
0x1328314b	NIDL_FILESPECREQ
0x1328314c	NIDL_OPNOTAGS
0x1328314d	NIDL_TYPENEST
0x1328314e	NIDL_DUPPRMATTR
0x1328314f	NIDL_OPINCCHAR
0x13283150	NIDL_OPOUTCCHAR
0x13283151	NIDL_ARRATTRSHR
0x13283152	NIDL_ATTROUTCFMTCS
0x13283153	NIDL_CSARRSYN
0x13283154	NIDL_ARRPTRUNIQU
0x13283155	NIDL_XMITCTYPE
0x13283156	NIDL_TAGBEFDATA
0x13283157	NIDL_TAGAFDATA
0x13283158	NIDL_HANCTYPE
0x13283159	NIDL_PIPECTYPE
0x1328315a	NIDL_ARRMULTID
0x1328315b	NIDL_ARRTYPATTR

Message Number	Symbolic Name
0x1328315c	NIDL_TYPECTYPE
0x1328315d	NIDL_TYPEOFBYTES
0x1328315e	NIDL_TAGPRMTYPE
0x1328315f	NIDL_MAXIDTYPE
0x13283160	NIDL_NOPORTEXCEPT
0x13283161	NIDL_NOPORTATTR
0x13283162	NIDL_PRMDEPATTR
0x13283163	NIDL_CPPCMDOPT
0x13283164	NIDL_NOPORTANON
0x13283165	NIDL_NOFLTPARAM
0x13283166	NIDL_CONSTRUCTOR
0x13283167	NIDL_INTREFNOTALO
0x13283168	NIDL_PTRATTBIGN
0x13283169	NIDL_STATICIGN
0x1328316a	NIDL_LOOKUPNOTVAL
0x1328316b	NIDL_NEWNOTVAL
0x1328316c	NIDL_INHERITNOTVAL
0x1328316d	NIDL_INHERITNOTDEF
0x1328316e	NIDL_DELEGATENOTVAL
0x14601001	db_s_not_open
0x14601002	db_s_no_name_specified
0x14601003	db_s_no_more
0x14601004	db_s_bad_index_type
0x14601005	db_s_index_type_mismatch
0x14601006	db_s_bad_header_type
0x14601007	db_s_missing_convert

Message Number	Symbolic Name
0x14601008	db_s_key_not_found
0x14601009	db_s_open_already_exists
0x1460100a	db_s_open_failed_enoent
0x1460100b	db_s_open_failed_eacces
0x1460100c	db_s_open_failed
0x1460100d	db_s_store_failed
0x1460100e	db_s_fetch_failed
0x1460100f	db_s_del_failed
0x14601010	db_s_readonly
0x14601011	db_s_no_header
0x14601012	db_s_not_std_header
0x14601013	db_s_already_locked
0x14601014	db_s_not_locked
0x14601015	db_s_mutex_init_fail
0x14601016	db_s_mutex_lock_fail
0x14601017	db_s_iter_not_allowed
0x14601018	acl_s_bad_manager_type
0x14601019	acl_s_type_not_registered
0x1460101a	acl_s_no_acl_entries
0x1460101b	acl_s_owner_not_allowed
0x1460101c	acl_s_group_not_allowed
0x1460101d	acl_s_no_control_entries
0x1460101e	utils_s_802_cant_read
0x1460101f	utils_s_802_addr_format
0x14601020	utils_s_802_uname_failure
0x14601021	dce_attr_s_bad_name

Message Number	Symbolic Name
0x14601022	dce_attr_s_bad_schema_name
0x14601023	dce_attr_s_unknown_auth_info_type
0x14601024	dce_attr_s_no_memory
0x14601025	dce_attr_s_bad_binding
0x14601026	dce_attr_s_bad_cursor
0x14601027	dce_attr_s_not_implemented
0x14601028	db_s_file_lock_fail
0x14601029	db_s_stat_fail
0x15f52001	pkc_s_asn_internal_error
0x15f52002	pkc_s_asn_no_default_value
0x15f52003	pkc_s_asn_out_of_range
0x15f52004	pkc_s_asn_unset
0x15f52005	pkc_s_asn_inv_type
0x15f52006	pkc_s_asn_bad_param
0x15f52007	pkc_s_nomem
0x15f52008	pkc_s_asn_wrong_type
0x15f52009	pkc_s_asn_no_more_data
0x15f5200a	pkc_s_asn_inv_length
0x15f5200b	pkc_s_asn_inv_value
0x15f5200c	pkc_s_asn_bad_indefinite
0x15f5200d	pkc_s_asn_value_overflow
0x15f5200e	pkc_s_asn_invalid_value
0x15f5200f	pkc_s_asn_not_supported
0x15f52010	pkc_s_asn_value_already_set
0x15f52011	pkc_s_asn_unexpected_call
0x15f52012	pkc_s_x500_unsupported_syntax

Message Number	Symbolic Name
0x15f52013	pkc_s_x500_unsupported_attribute
0x15f52014	pkc_s_x500_at_root
0x15f52015	pkc_s_invalid_version
0x15f52016	pkc_s_replaced
0x15f52017	pkc_s_no_more_items
0x15f52018	pkc_s_invalid_handle
0x15f52019	pkc_s_unsupported_algorithm
0x15f5201a	pkc_s_locking_violation
0x15f5201b	pkc_s_delete_pending
0x15f5201c	pkc_s_unimplemented
0x15f5201d	pkc_s_initialization_failure
0x15f5201e	pkc_s_inv_lock_type
0x15f5201f	pkc_s_policy_unavailable
0x15f52020	pkc_s_key_not_found
0x15f52021	pkc_s_forbidden
0x15f52022	pkc_s_policy_open_failure
0x15f52023	pkc_s_policy_close_failure
0x15f52024	pkc_s_policy_retrieve_failure
0x15f52025	pkc_s_bad_value
0x15f52026	pkc_s_bad_attribute
0x15f52027	pkc_s_failure
0x15f52028	pkc_s_bad_certificate_handle
0x15f52029	pkc_s_bad_time
0x15f5202a	pkc_s_alg_deleted
0x15f5202b	pkc_s_alg_already_registered
0x15f5202c	pkc_s_unsupported

Message Number	Symbolic Name
0x15f5202d	pkc_s_no_value
0x15f5202e	pkc_s_init_error
0x15f5202f	pkc_s_conversion_error
0x15f52030	pkc_s_unimplemented_syntax
0x15f52031	pkc_s_insufficient_rdns
0x15f52032	pkc_s_unsupported_policy
0x15f52033	pkc_s_plcy_deleted
0x15f52034	pkc_s_plcy_already_registered
0x15f52035	pkc_s_key_not_trusted
0x15f52036	pkc_s_key_not_certified
0x15f52037	pkc_s_cert_not_verified_validity
0x15f52038	pkc_s_cert_not_verified_signature
0x15f52039	pkc_s_invalid_public_key
0x15f5203a	pkc_s_cert_invalid_algid
0x15f5203b	pkc_s_cert_not_added
0x15f5203c	pkc_s_certificate_not_revoked
0x15f5203d	pkc_s_certificate_revoked
0x15f5203e	pkc_s_index_out_of_range
0x15f5203f	pkc_s_internal_error
0x15f52040	pkc_s_bad_param
0x15f52048	pkc_s_cant_create_mutex
0x15f52049	pkc_s_cant_delete_mutex
0x15f5204a	pkc_s_cant_lock_mutex
0x15f5204b	pkc_s_cant_unlock_mutex
0x15f5204c	pkc_s_delete_not_pending
0x15f5204d	pkc_s_init_cant_create_mutexattr

Message Number	Symbolic Name
0x15f5204e	pkc_s_init_cant_init_mutexattr
0x15f5204f	pkc_s_init_failure_locks
0x15f52050	pkc_s_init_failure_asn
0x15f52051	pkc_s_init_failure_pkc
0x15f62001	pks_s_no_memory
0x15f62002	pks_s_no_gen_reply
0x15f62003	pks_s_invalid_arg
0x15f62004	pks_s_invalid_arg_1_parm
0x15f62005	pks_s_cant_open_storage_file
0x15f62006	pks_s_no_config_file
0x15f62007	pks_s_no_group_name
0x15f62008	pks_s_already_initialized
0x15f62009	pks_s_cant_remove_storage_file
0x15f6200a	pks_s_no_acl
0x15f6200b	pks_s_bad_acl
0x15f6200c	pks_s_bad_acl_type
0x15f6200d	pks_s_invalid_op
0x15f6200f	pks_s_pipe_error
0x15f62010	sec_pkss_pipe_encrypt_fail
0x15f62011	sec_pkss_pipe_decrypt_fail
0x15f62012	pks_s_pipe_svr_encrypt_fail
0x15f62013	pks_s_pipe_svr_decrypt_fail
0x15f62014	pks_s_fork_error
0x15f62015	pks_s_pipe_data_error
0x15f62016	pks_s_int_length_error
0x15f62017	pks_s_int_length_errorp

Message Number	Symbolic Name
0x15f62018	pks_s_exec_e2big
0x15f62019	pks_s_exec_eaccess
0x15f6201a	pks_s_exec_eloop
0x15f6201b	pks_s_exec_enametoolong
0x15f6201c	pks_s_exec_enoent
0x15f6201d	pks_s_exec_enomem
0x15f6201e	pks_s_exec_enotdir
0x15f6201f	pks_s_exec_enoexec
0x15f62020	pks_s_exec_fail
0x15f62021	pks_s_pipsvr_nomem
0x15f62022	pks_s_pipclt_nomem
0x15f62023	pks_s_pipclt_bad_msg
0x15f62024	pks_s_bad_msg_type
0x15f62025	pks_s_pipsvr_decode_error
0x15f62026	pks_s_pipsvr_decode_errorp
0x15f62027	pks_s_unexpected_termination
0x15f6202a	pks_s_ready_to_listen
0x15f62051	pks_s_acl_not_authorized
0x1609c001	sec_s_bsafe_algorithm_already_set
0x1609c002	sec_s_bsafe_algorithm_info
0x1609c003	sec_s_bsafe_algorithm_not_initialized
0x1609c004	sec_s_bsafe_algorithm_not_set
0x1609c005	sec_s_bsafe_algorithm_obj
0x1609c006	sec_s_bsafe_alg_operation_unknown
0x1609c007	sec_s_bsafe_alloc
0x1609c008	sec_s_bsafe_cancel

Message Number	Symbolic Name
0x1609c009	sec_s_bsafe_data
0x1609c00a	sec_s_bsafe_exponent_even
0x1609c00b	sec_s_bsafe_exponent_len
0x1609c00c	sec_s_bsafe_hardware
0x1609c00d	sec_s_bsafe_input_data
0x1609c00e	sec_s_bsafe_input_len
0x1609c00f	sec_s_bsafe_key_already_set
0x1609c010	sec_s_bsafe_key_info
0x1609c011	sec_s_bsafe_key_len
0x1609c012	sec_s_bsafe_key_not_set
0x1609c013	sec_s_bsafe_key_obj
0x1609c014	sec_s_bsafe_key_operation_unknown
0x1609c015	sec_s_bsafe_memory_obj
0x1609c016	sec_s_bsafe_modulus_len
0x1609c017	sec_s_bsafe_not_initialized
0x1609c018	sec_s_bsafe_not_supported
0x1609c019	sec_s_bsafe_output_len
0x1609c01a	sec_s_bsafe_over_32k
0x1609c01b	sec_s_bsafe_random_not_initialized
0x1609c01c	sec_s_bsafe_random_obj
0x1609c01d	sec_s_bsafe_signature
0x1609c01e	sec_s_bsafe_wrong_algorithm_info
0x1609c01f	sec_s_bsafe_wrong_key_info
0x1609c020	sec_s_bsafe_input_count
0x1609c021	sec_s_bsafe_method_not_in_chooser
0x1609c022	sec_s_bsafe_output_count

Message Number	Symbolic Name
0x1609c023	sec_s_bsafe_unknown_error
0x1609c024	sec_s_bsafe_decryption_failure
0x1609c025	sec_s_bsafe_mod_size_out_of_range
0x1609c026	sec_pvtkey_mechanism_not_init
0x1609c027	sec_pvtkey_invalid_handle
0x1609c028	sec_pvtkey_same_domain_and_usage_key_already_exist
0x1609c029	sec_pvtkey_same_domain_and_usage_key_exist_with_diff_pwd
0x1609c02a	sec_pvtkey_no_matched_private_key
0x1609c02b	sec_pvtkey_key_generation_not_supported
0x1609c02c	sec_pvtkey_invalid_pwd
0x1609c02d	sec_pvtkey_no_more_memory
0x1609c02e	sec_pvtkey_key_deletion_not_supported
0x1609c02f	sec_pvtkey_private_key_is_not_supplied
0x1609c030	sec_pvtkey_new_password_required
0x1609c031	sec_pvtkey_internal_error
0x1609c032	sec_pvtkey_file_locked
0x1609c033	sec_pvtkey_file_cannot_open_key_file
0x1609c034	sec_pvtkey_privileged
0x1609c035	sec_pvtkey_capability_not_supported
0x1609c036	sec_pvtkey_unsupported_capability_name
0x1609c037	sec_pvtkey_multiple_key_usages
0x1609c038	sec_pvtkey_no_more_data
0x1609c039	sec_pvtkey_wrong_passwd
0x1609c03a	sec_pvtkey_version_not_exist
0x1609c03b	sec_pvtkey_old_pass_required
0x1609c03c	sec_psm_unable_to_open_pvtkey

Message Number	Symbolic Name
0x1609c03d	sec_psm_not_init
0x1609c03e	sec_psm_invalid_handle
0x1609c03f	sec_psm_no_more_memory
0x1609c040	sec_psm_wrong_pub_key_type
0x1609c041	sec_psm_internal_error
0x1609c042	sec_psm_unsupported_algorithm_id
0x1609c043	sec_psm_keystore_not_found
0x1609c044	sec_psm_keystore_list_corrupt
0x1609c045	sec_psm_invalid_keystore_handle
0x1609c046	sec_psm_keystore_attr_read_failed
0x1609c047	sec_psm_keystore_already_registered
0x1609c048	sec_psm_keystore_list_full
0x1609c049	sec_psm_i_lookup_keystore
0x1609c04a	sec_psm_i_bad_domain
0x1609c04b	sec_psm_i_no_prin_keystore_era
0x1609c04c	sec_psm_i_no_def_keystore_era
0x1609c04d	sec_psm_i_bad_keystore_list
0x1609c04e	sec_psm_i_def_keystore
0x1609c04f	sec_psm_i_no_keystore
0x1609c050	sec_psm_i_era_lookup_failure
0x1609c051	sec_psm_i_chosen_keystore
0x1609c052	sec_psm_i_matchall_keystore
0x1609c053	sec_psm_i_searching_explicit
0x1609c054	sec_psm_i_searching_matchall
0x1609c055	sec_psm_i_discarded_keystore
0x1609c056	sec_psm_i_bad_keystore_id

Message Number	Symbolic Name
0x1609c057	sec_psm_i_bad_keystore_id1
0x16c9a001	rpc_s_op_rng_error
0x16c9a002	rpc_s_cant_create_socket
0x16c9a003	rpc_s_cant_bind_socket
0x16c9a006	rpc_s_wrong_boot_time
0x16c9a00d	rpc_s_in_args_too_big
0x16c9a010	rpc_s_binding_has_no_auth
0x16c9a011	rpc_s_unknown_authn_service
0x16c9a012	rpc_s_no_memory
0x16c9a014	rpc_s_call_faulted
0x16c9a016	rpc_s_comm_failure
0x16c9a017	rpc_s_rpcd_comm_failure
0x16c9a01a	rpc_s_coding_error
0x16c9a01b	rpc_s_object_not_found
0x16c9a01c	rpc_s_cthread_not_found
0x16c9a01d	rpc_s_invalid_binding
0x16c9a01e	rpc_s_already_registered
0x16c9a01f	rpc_s_endpoint_not_found
0x16c9a020	rpc_s_invalid_rpc_protseq
0x16c9a021	rpc_s_desc_not_registered
0x16c9a022	rpc_s_already_listening
0x16c9a023	rpc_s_no_protseqs
0x16c9a024	rpc_s_no_protseqs_registered
0x16c9a025	rpc_s_no_bindings
0x16c9a026	rpc_s_max_descs_exceeded
0x16c9a027	rpc_s_no_interfaces

Message Number	Symbolic Name
0x16c9a028	rpc_s_invalid_timeout
0x16c9a029	rpc_s_cant_inq_socket
0x16c9a02a	rpc_s_invalid_naf_id
0x16c9a02b	rpc_s_inval_net_addr
0x16c9a02c	rpc_s_unknown_if
0x16c9a02d	rpc_s_unsupported_type
0x16c9a02e	rpc_s_invalid_call_opt
0x16c9a02f	rpc_s_no_fault
0x16c9a030	rpc_s_cancel_timeout
0x16c9a031	rpc_s_call_cancelled
0x16c9a034	rpc_s_cannot_connect
0x16c9a035	rpc_s_connection_aborted
0x16c9a036	rpc_s_connection_closed
0x16c9a037	rpc_s_cannot_accept
0x16c9a038	rpc_s_assoc_grp_not_found
0x16c9a03a	rpc_s_invalid_object
0x16c9a03e	rpc_s_protocol_error
0x16c9a040	rpc_s_invalid_string_binding
0x16c9a041	rpc_s_connect_timed_out
0x16c9a042	rpc_s_connect_rejected
0x16c9a043	rpc_s_network_unreachable
0x16c9a044	rpc_s_connect_no_resources
0x16c9a045	rpc_s_rem_network_shutdown
0x16c9a046	rpc_s_too_many_rem_connects
0x16c9a047	rpc_s_no_rem_endpoint
0x16c9a048	rpc_s_rem_host_down

Message Number	Symbolic Name
0x16c9a049	rpc_s_host_unreachable
0x16c9a04a	rpc_s_access_control_info_inv
0x16c9a04b	rpc_s_loc_connect_aborted
0x16c9a04c	rpc_s_connect_closed_by_rem
0x16c9a04d	rpc_s_rem_host_crashed
0x16c9a04e	rpc_s_invalid_endpoint_format
0x16c9a050	rpc_s_unknown_mgr_type
0x16c9a052	rpc_s_assoc_grp_max_exceeded
0x16c9a054	rpc_s_sm_invalid_state
0x16c9a056	rpc_s_assoc_shutdown
0x16c9a057	rpc_s_tsyntaxes_unsupported
0x16c9a058	rpc_s_context_id_not_found
0x16c9a05a	rpc_s_no_addrs
0x16c9a05b	rpc_s_cant_getpeername
0x16c9a05c	rpc_s_cant_get_if_id
0x16c9a05d	rpc_s_protseq_not_supported
0x16c9a05e	rpc_s_call_orphaned
0x16c9a05f	rpc_s_who_are_you_failed
0x16c9a060	rpc_s_unknown_reject
0x16c9a061	rpc_s_type_already_registered
0x16c9a063	rpc_s_invalid_arg
0x16c9a064	rpc_s_not_supported
0x16c9a065	rpc_s_wrong_kind_of_binding
0x16c9a066	rpc_s_authn_authz_mismatch
0x16c9a067	rpc_s_call_queued
0x16c9a068	rpc_s_cannot_set_nodelay

Message Number	Symbolic Name
0x16c9a069	rpc_s_not_rpc_tower
0x16c9a06c	rpc_s_call_timeout
0x16c9a06d	rpc_s_mgmt_op_disallowed
0x16c9a06e	rpc_s_manager_not_entered
0x16c9a06f	rpc_s_calls_too_large_for_wk_ep
0x16c9a070	rpc_s_server_too_busy
0x16c9a072	rpc_s_rpc_prot_version_mismatch
0x16c9a073	rpc_s_ss_no_import_cursor
0x16c9a074	rpc_s_fault_addr_error
0x16c9a075	rpc_s_fault_context_mismatch
0x16c9a076	rpc_s_fault_fp_div_by_zero
0x16c9a077	rpc_s_fault_fp_error
0x16c9a078	rpc_s_fault_fp_overflow
0x16c9a079	rpc_s_fault_fp_underflow
0x16c9a07a	rpc_s_fault_ill_inst
0x16c9a07b	rpc_s_fault_int_div_by_zero
0x16c9a07c	rpc_s_fault_int_overflow
0x16c9a07d	rpc_s_fault_invalid_bound
0x16c9a07e	rpc_s_fault_invalid_tag
0x16c9a07f	rpc_s_fault_pipe_closed
0x16c9a080	rpc_s_fault_pipe_comm_error
0x16c9a081	rpc_s_fault_pipe_discipline
0x16c9a082	rpc_s_fault_pipe_empty
0x16c9a083	rpc_s_fault_pipe_memory
0x16c9a084	rpc_s_fault_pipe_order
0x16c9a085	rpc_s_fault_remote_comm_failure

Message Number	Symbolic Name
0x16c9a086	rpc_s_fault_remote_no_memory
0x16c9a087	rpc_s_fault_unspec
0x16c9a088	uuid_s_bad_version
0x16c9a089	uuid_s_socket_failure
0x16c9a08a	uuid_s_getconf_failure
0x16c9a08b	uuid_s_no_address
0x16c9a08d	uuid_s_internal_error
0x16c9a08e	uuid_s_coding_error
0x16c9a08f	uuid_s_invalid_string_uuid
0x16c9a093	rpc_s_name_service_unavailable
0x16c9a094	rpc_s_incomplete_name
0x16c9a096	rpc_s_invalid_name_syntax
0x16c9a097	rpc_s_no_more_members
0x16c9a09c	rpc_s_not_found
0x16c9a0a0	rpc_s_entry_not_found
0x16c9a0a1	rpc_s_invalid_inquiry_context
0x16c9a0a2	rpc_s_interface_not_found
0x16c9a0a3	rpc_s_group_member_not_found
0x16c9a0a4	rpc_s_entry_already_exists
0x16c9a0a6	rpc_s_unsupported_name_syntax
0x16c9a0a7	rpc_s_no_more_elements
0x16c9a0a8	rpc_s_no_ns_permission
0x16c9a0a9	rpc_s_invalid_inquiry_type
0x16c9a0aa	rpc_s_profile_element_not_found
0x16c9a0ab	rpc_s_profile_element_replaced
0x16c9a0b1	rpc_s_no_interfaces_exported

Message Number	Symbolic Name
0x16c9a0b5	rpc_s_no_more_bindings
0x16c9a0b6	rpc_s_invalid_priority
0x16c9a0b7	rpc_s_not_rpc_entry
0x16c9a0b9	rpc_s_binding_vector_full
0x16c9a0ba	rpc_s_cycle_detected
0x16c9a0bb	rpc_s_nothing_to_export
0x16c9a0bc	rpc_s_nothing_to_unexport
0x16c9a0bd	rpc_s_invalid_vers_option
0x16c9a0bf	rpc_s_mbr_picked
0x16c9a0c0	rpc_s_not_all_objs_unexported
0x16c9a0c1	rpc_s_no_entry_name
0x16c9a0c2	rpc_s_priority_group_done
0x16c9a0c3	rpc_s_partial_results
0x16c9a0c4	rpc_s_no_env_setup
0x16c9a0c5	twr_s_unknown_sa
0x16c9a0c6	twr_s_unknown_tower
0x16c9a0c7	twr_s_not_implemented
0x16c9a0c8	rpc_s_max_calls_too_small
0x16c9a0c9	rpc_s_cthread_create_failed
0x16c9a0ca	rpc_s_cthread_pool_exists
0x16c9a0cb	rpc_s_cthread_no_such_pool
0x16c9a0cc	rpc_s_cthread_invoke_disabled
0x16c9a0cd	ept_s_cant_perform_op
0x16c9a0ce	ept_s_no_memory
0x16c9a0cf	ept_s_database_invalid
0x16c9a0d0	ept_s_cant_create

Message Number	Symbolic Name
0x16c9a0d1	ept_s_cant_access
0x16c9a0d2	ept_s_database_already_open
0x16c9a0d3	ept_s_invalid_entry
0x16c9a0d4	ept_s_update_failed
0x16c9a0d5	ept_s_invalid_context
0x16c9a0d6	ept_s_not_registered
0x16c9a0d8	rpc_s_underspecified_name
0x16c9a0d9	rpc_s_invalid_ns_handle
0x16c9a0da	rpc_s_unknown_error
0x16c9a0db	rpc_s_ss_char_trans_open_fail
0x16c9a0dc	rpc_s_ss_char_trans_short_file
0x16c9a0dd	rpc_s_ss_context_damaged
0x16c9a0de	rpc_s_ss_in_null_context
0x16c9a0df	rpc_s_socket_failure
0x16c9a0e0	rpc_s_unsupported_protect_level
0x16c9a0e1	rpc_s_invalid_checksum
0x16c9a0e2	rpc_s_invalid_credentials
0x16c9a0e3	rpc_s_credentials_too_large
0x16c9a0e4	rpc_s_call_id_not_found
0x16c9a0e5	rpc_s_key_id_not_found
0x16c9a0e6	rpc_s_auth_bad_integrity
0x16c9a0e7	rpc_s_auth_tkt_expired
0x16c9a0e8	rpc_s_auth_tkt_nyv
0x16c9a0e9	rpc_s_auth_repeat
0x16c9a0ea	rpc_s_auth_not_us
0x16c9a0eb	rpc_s_auth_badmatch

Message Number	Symbolic Name
0x16c9a0ec	rpc_s_auth_skew
0x16c9a0ed	rpc_s_auth_badaddr
0x16c9a0ee	rpc_s_auth_badversion
0x16c9a0ef	rpc_s_auth_msg_type
0x16c9a0f0	rpc_s_auth_modified
0x16c9a0f1	rpc_s_auth_badorder
0x16c9a0f2	rpc_s_auth_badkeyver
0x16c9a0f3	rpc_s_auth_nokey
0x16c9a0f4	rpc_s_auth_mut_fail
0x16c9a0f5	rpc_s_auth_baddirection
0x16c9a0f6	rpc_s_auth_method
0x16c9a0f7	rpc_s_auth_badseq
0x16c9a0f8	rpc_s_auth_inapp_cksum
0x16c9a0f9	rpc_s_auth_field_toolong
0x16c9a0fa	rpc_s_invalid_crc
0x16c9a0fb	rpc_s_binding_incomplete
0x16c9a0fc	rpc_s_key_func_not_allowed
0x16c9a0fd	rpc_s_unknown_stub_rtl_if_vers
0x16c9a0fe	rpc_s_unknown_ifspec_vers
0x16c9a0ff	rpc_s_proto_unsupp_by_auth
0x16c9a100	rpc_s_authn_challenge_malformed
0x16c9a101	rpc_s_protect_level_mismatch
0x16c9a102	rpc_s_no_mepv
0x16c9a103	rpc_s_stub_protocol_error
0x16c9a104	rpc_s_class_version_mismatch
0x16c9a105	rpc_s_helper_not_running

Message Number	Symbolic Name
0x16c9a106	rpc_s_helper_short_read
0x16c9a107	rpc_s_helper_catatonic
0x16c9a108	rpc_s_helper_aborted
0x16c9a109	rpc_s_not_in_kernel
0x16c9a10a	rpc_s_helper_wrong_user
0x16c9a10b	rpc_s_helper_overflow
0x16c9a10c	rpc_s_dg_need_way_auth
0x16c9a10d	rpc_s_unsupported_auth_subtype
0x16c9a10e	rpc_s_wrong_pickle_type
0x16c9a10f	rpc_s_not_listening
0x16c9a110	rpc_s_ss_bad_buffer
0x16c9a111	rpc_s_ss_bad_es_action
0x16c9a112	rpc_s_ss_wrong_es_version
0x16c9a113	rpc_s_fault_user_defined
0x16c9a114	rpc_s_ss_incompatible_codesets
0x16c9a115	rpc_s_tx_not_in_transaction
0x16c9a116	rpc_s_tx_open_failed
0x16c9a117	rpc_s_partial_credentials
0x16c9a118	rpc_s_ss_invalid_codeset_tag
0x16c9a119	rpc_s_mgmt_bad_type
0x16c9a11a	rpc_s_ss_invalid_char_input
0x16c9a11b	rpc_s_ss_short_conv_buffer
0x16c9a11c	rpc_s_ss_iconv_error
0x16c9a11d	rpc_s_ss_no_compat_codeset
0x16c9a11e	rpc_s_ss_no_compat_charsets
0x16c9a11f	dce_cs_c_ok

Message Number	Symbolic Name
0x16c9a120	dce_cs_c_unknown
0x16c9a121	dce_cs_c_notfound
0x16c9a122	dce_cs_c_cannot_open_file
0x16c9a123	dce_cs_c_cannot_read_file
0x16c9a124	dce_cs_c_cannot_allocate_memory
0x16c9a125	rpc_s_ss_cleanup_failed
0x16c9a144	rpc_m_cn_ill_state_trans_sa
0x16c9a145	rpc_m_cn_ill_state_trans_ca
0x16c9a146	rpc_m_cn_ill_state_trans_sg
0x16c9a147	rpc_m_cn_ill_state_trans_cg
0x16c9a148	rpc_m_cn_ill_state_trans_sr
0x16c9a149	rpc_m_cn_ill_state_trans_cr
0x16c9a14a	rpc_m_bad_pkt_type
0x16c9a14b	rpc_m_prot_mismatch
0x16c9a14c	rpc_m_frag_toobig
0x16c9a14d	rpc_m_unsupp_stub_rtl_if
0x16c9a14e	rpc_m_unhandled_callstate
0x16c9a14f	rpc_m_call_failed
0x16c9a150	rpc_m_call_failed_no_status
0x16c9a151	rpc_m_call_failed_errno
0x16c9a152	rpc_m_call_failed_s
0x16c9a153	rpc_m_call_failed_c
0x16c9a154	rpc_m_errmsg_toobig
0x16c9a155	rpc_m_invalid_srchattr
0x16c9a156	rpc_m_nts_not_found
0x16c9a157	rpc_m_invalid_accbytcnt

Message Number	Symbolic Name
0x16c9a158	rpc_m_pre_v2_ifspec
0x16c9a159	rpc_m_unk_ifspec
0x16c9a15a	rpc_m_recvbuf_toosmall
0x16c9a15b	rpc_m_unalign_authtrl
0x16c9a15c	rpc_m_unexpected_exc
0x16c9a15d	rpc_m_no_stub_data
0x16c9a15e	rpc_m_eventlist_full
0x16c9a15f	rpc_m_unk_sock_type
0x16c9a160	rpc_m_unimp_call
0x16c9a161	rpc_m_invalid_seqnum
0x16c9a162	rpc_m_cant_create_uuid
0x16c9a163	rpc_m_pre_v2_ss
0x16c9a164	rpc_m_dgpkt_pool_corrupt
0x16c9a165	rpc_m_dgpkt_bad_free
0x16c9a166	rpc_m_lookaside_corrupt
0x16c9a167	rpc_m_alloc_fail
0x16c9a168	rpc_m_realloc_fail
0x16c9a169	rpc_m_cant_open_file
0x16c9a16c	rpc_m_ctxrundown_nomem
0x16c9a16d	rpc_m_ctxrundown_exc
0x16c9a16e	rpc_s_fault_codeset_conv_error
0x16c9a16f	rpc_s_ss_codeset_conv_error
0x16c9a170	rpc_s_fault_no_client_stub
0x16c9a171	rpc_s_no_server_stub
0x17083001	ek_null_handle
0x17083002	ek_bad_format

Message Number	Symbolic Name
0x17083003	ek_required_field
0x17083004	ek_field_unused
0x17083005	ek_field_readonly
0x17083006	ek_bad_field
0x17083007	ek_bad_op_id
0x17083008	ek_field_no_data
0x17083009	ek_kernel_failure
0x1708300a	ek_PAD0
0x1708300b	ek_PAD1
0x1708300c	ek_PAD2
0x1708300d	ek_PAD3
0x1708300e	ek_PAD4
0x1708300f	ek_PAD5
0x17083010	ek_PAD6
0x17083011	ek_PAD7
0x17083012	ek_PAD8
0x17083013	ek_PAD9
0x17083014	ek_err_person_bad_name_chars
0x17083015	ek_err_group_bad_name_chars
0x17083016	ek_err_org_bad_name_chars
0x17083017	ek_err_person_name_too_long
0x17083018	ek_err_group_name_too_long
0x17083019	ek_err_org_name_too_long
0x1708301a	ek_err_person_exists
0x1708301b	ek_err_group_exists
0x1708301c	ek_err_org_exists

Message Number	Symbolic Name
0x1708301d	ek_err_person_does_not_exist
0x1708301e	ek_err_group_does_not_exist
0x1708301f	ek_err_org_does_not_exist
0x17083020	ek_err_not_member_group
0x17083021	ek_err_not_member_org
0x17083022	ek_err_not_member_go
0x17083023	ek_err_bad_unix_num
0x17083024	ek_err_unix_num_exists
0x17083025	ek_err_unix_num_change
0x17083026	ek_err_no_wildcard
0x17083027	ek_err_incomplete_login_name
0x17083028	ek_err_login_name_too_long
0x17083029	ek_err_acct_exists
0x1708302a	ek_err_acct_does_not_exist
0x1708302b	ek_err_passwd_invalid
0x1708302c	ek_err_passwd_too_short
0x1708302d	ek_err_passwd_too_long
0x1708302e	ek_err_passwd_non_alpha
0x1708302f	ek_err_passwd_spaces
0x17083030	ek_err_fullname_too_long
0x17083031	ek_err_misc_info_too_long
0x17083032	ek_err_homedir_too_long
0x17083033	ek_err_shell_too_long
0x17083034	ek_err_unix_acct_exists
0x17083035	ek_err_bad_date
0x17083036	ek_err_date_out_of_range

Message Number	Symbolic Name
0x17083037	ek_err_bad_id
0x17083038	ek_err_id_exists
0x17083039	ek_err_non_numeric
0x1708303a	ek_err_int_out_of_range
0x1708303b	ek_err_bad_lifespan
0x1708303c	ek_err_lifespan_out_of_range
0x1708303d	ek_err_bad_passwd_len
0x1708303e	ek_err_reserved
0x1708303f	ek_err_object_exists
0x17083040	ek_err_data_too_long
0x17083041	ek_err_name_exists
0x17083042	ek_err_g_mbr_unauth
0x17083043	ek_err_o_mbr_unauth
0x17083044	ek_err_auth_plcy_unauth
0x17083045	ek_err_attr_bad_enc_type
0x17083046	ek_err_attr_bad_name_chars
0x17083047	ek_err_attr_name_too_long
0x17083048	ek_err_PAD6
0x17083049	ek_err_PAD7
0x1708304a	ek_err_PAD8
0x1708304b	ek_err_PAD9
0x1708304c	ek_err_PADa
0x1708304d	ek_err_PADb
0x1708304e	ek_err_PADc
0x1708304f	ek_err_PADd
0x17083050	ek_err_PADe

Message Number	Symbolic Name
0x17083051	ek_err_PADf
0x17083052	ek_misc_no_site
0x17083053	ek_misc_no_update_site
0x17083054	ek_misc_server_unavailable
0x17083055	ek_misc_read_only
0x17083056	ek_misc_not_authorized
0x17083057	ek_misc_no_more_entries
0x17083058	ek_misc_object_not_found
0x17083059	ek_misc_no_members
0x1708305a	ek_misc_not_implemented
0x1708305b	ek_misc_bad_data
0x1708305c	ek_misc_bad_domain
0x1708305d	ek_misc_is_an_alias
0x1708305e	ek_misc_acct_partial_op
0x1708305f	ek_misc_unauth_binding
0x17083060	ek_misc_chg_name_fail
0x17083061	ek_misc_chg_gmem_fail
0x17083062	ek_misc_chg_omem_fail
0x17083063	ek_misc_chg_passwd_fail
0x17083064	ek_misc_chg_admin_fail
0x17083065	ek_misc_chg_uinfo_fail
0x17083066	ek_misc_chg_auth_pley
0x17083067	ek_misc_PAD7
0x17083068	ek_misc_PAD8
0x17083069	ek_misc_PAD9
0x1708306a	ek_misc_PADa

Message Number	Symbolic Name
0x1708306b	ek_misc_PADb
0x1708306c	ek_misc_PADc
0x1708306d	ek_misc_PADd
0x1708306e	ek_misc_PADe
0x1708306f	ek_misc_PADf
0x17083070	tty_cant_parse
0x17083071	tty_incompatible_options
0x17083072	tty_invalid_option
0x17083073	tty_invalid_argument
0x17083074	tty_opt_requires_arg
0x17083075	tty_bad_data_format
0x17083076	tty_err_input_too_long
0x17083077	tty_input_out_of_range
0x17083078	tty_entry_is_required
0x17083079	tty_bad_domain
0x1708307a	tty_pwd_gen_req
0x1708307b	tty_PAD1
0x1708307c	tty_PAD2
0x1708307d	tty_PAD3
0x1708307e	tty_PAD4
0x1708307f	tty_PAD5
0x17083080	tty_PAD6
0x17083081	tty_PAD7
0x17083082	tty_PAD8
0x17083083	tty_PAD9
0x17083084	tty_PADa

Message Number	Symbolic Name
0x17083085	tty_PADb
0x17083086	tty_PADc
0x17083087	tty_PADd
0x17083088	tty_PADe
0x17083089	tty_PADf
0x1708308a	deif_err_file_open
0x1708308b	deif_err_file_read
0x1708308c	deif_err_entry_not_found
0x1708308d	deif_err_invalid_entry
0x1708308e	deif_err_invalid_entry_type
0x1708308f	deif_err_invalid_perm
0x17083090	deif_err_invalid_key
0x17083091	deif_err_invalid_entry_op
0x17083092	deif_err_invalid_entry_key
0x17083093	deif_err_rgy_not_found
0x17083094	ae_tty_cant_parse
0x17083095	ae_tty_incompatible_options
0x17083096	ae_tty_invalid_option
0x17083097	ae_tty_invalid_argument
0x17083098	ae_tty_opt_requires_arg
0x17083099	ae_tty_bad_data_format
0x1708309a	ae_tty_err_input_too_long
0x1708309b	ae_tty_input_out_of_range
0x1708309c	ae_tty_entry_is_required
0x1708309d	ae_tty_bad_domain
0x1708309e	ae_tty_too_many_args

Message Number	Symbolic Name
0x1708309f	ae_tty_args_not_command
0x170830a0	ae_tty_would_grant_perms
0x170830a1	SEC_ACL_EDIT_PAD1
0x170830a2	SEC_ACL_EDIT_PAD2
0x170830a3	SEC_ACL_EDIT_PAD3
0x170830a4	SEC_ACL_EDIT_PAD4
0x170830a5	SEC_ACL_EDIT_PAD5
0x170830a6	SEC_ACL_EDIT_PAD6
0x170830a7	SEC_ACL_EDIT_PAD7
0x170830a8	SEC_ACL_EDIT_PAD8
0x170830a9	SEC_ACL_EDIT_PAD9
0x170830aa	SEC_ACL_EDIT_PADa
0x170830ab	SEC_ACL_EDIT_PADb
0x170830ac	SEC_ACL_EDIT_PADc
0x170830ad	SEC_ACL_EDIT_PADd
0x170830ae	SEC_ACL_EDIT_PADe
0x170830af	SEC_ACL_EDIT_PADf
0x170830b0	pwd_imp_err_path_too_long
0x170830b1	pwd_imp_err_no_pwd_access
0x170830b2	pwd_imp_err_no_grp_access
0x170830b3	pwd_imp_err_fatal
0x170830b4	pwd_imp_err_pname_too_long
0x170830b5	pwd_imp_err_gname_too_long
0x170830b6	pwd_imp_err_ogname_too_long
0x170830b7	pwd_imp_err_pname_bad_char
0x170830b8	pwd_imp_err_DELO

Message Number	Symbolic Name
0x170830b9	pwd_imp_err_DEL1
0x170830ba	pwd_imp_err_internal_error
0x170830bb	pwd_imp_err_pname_exist_match
0x170830bc	pwd_imp_err_pname_exist_nmatch
0x170830bd	pwd_imp_err_gname_exist_match
0x170830be	pwd_imp_err_gname_exist_nmatch
0x170830bf	pwd_imp_err_puid_exists
0x170830c0	pwd_imp_err_guid_exists
0x170830c1	pwd_imp_err_invalid_option
0x170830c2	pwd_imp_err_invalid_uid
0x170830c3	pwd_imp_err_data_too_long
0x170830c4	pwd_imp_err_cache_e_not_found
0x170830c5	pwd_imp_err_dup_name
0x170830c6	pwd_imp_err_dup_num
0x170830c7	pwd_imp_err_no_memory
0x170830c8	pwd_imp_err_unknown_princ
0x170830c9	pwd_imp_err_unknown_group
0x170830ca	pwd_imp_err_PAD0
0x170830cb	pwd_imp_err_PAD1
0x170830cc	pwd_imp_err_PAD2
0x170830cd	pwd_imp_err_PAD3
0x170830ce	pwd_imp_inf_create_groups
0x170830cf	pwd_imp_inf_prepare_import
0x170830d0	pwd_imp_inf_close_import
0x170830d1	pwd_imp_inf_prepare_rgy
0x170830d2	pwd_imp_inf_close_rgy

Message Number	Symbolic Name
0x170830d3	pwd_imp_inf_ignore_conflict
0x170830d4	pwd_imp_inf_need_new_name
0x170830d5	pwd_imp_inf_need_new_uid
0x170830d6	pwd_imp_inf_choices
0x170830d7	pwd_imp_inf_check_org
0x170830d8	pwd_imp_inf_create_accounts
0x170830d9	pwd_imp_inf_add_members
0x170830da	pwd_imp_inf_PAD0
0x170830db	pwd_imp_inf_PAD1
0x170830dc	pwd_imp_inf_PAD2
0x170830dd	pwd_imp_inf_PAD3
0x170830de	pwd_exp_cl_usage
0x170830df	pwd_exp_cl_bad_arg
0x170830e0	pwd_exp_cl_bad_opt_m
0x170830e1	pwd_exp_cl_bad_opt_d
0x170830e2	pwd_exp_cl_bad_entries
0x170830e3	pwd_exp_rgy_connect_rejected
0x170830e4	pwd_exp_rgy_error_passwd
0x170830e5	pwd_exp_rgy_error_group
0x170830e6	pwd_exp_rgy_cannot_open
0x170830e7	pwd_exp_rgy_cannot_close
0x170830e8	pwd_exp_f_cannot_open_prime_group
0x170830e9	pwd_exp_f_cannot_open_temp_group
0x170830ea	pwd_exp_f_cannot_open_temp_passwd
0x170830eb	pwd_exp_env_fail_change_dir
0x170830ec	pwd_exp_env_fail_getcwd

Message Number	Symbolic Name
0x170830ed	pwd_imp_cl_usage
0x170830ee	pwd_imp_rgy_bad_org
0x170830ef	pwd_imp_err_auth
0x170830f0	pwd_imp_err_bad_name
0x170830f1	pwd_imp_err_input_too_long
0x170830f2	pwd_imp_err_add_pgo
0x170830f3	pwd_imp_err_add_group_member
0x170830f4	pwd_imp_err_add_princ_group
0x170830f5	pwd_imp_err_internal_cache
0x170830f6	pwd_imp_err_add_org_member
0x170830f7	pwd_imp_err_group_conflict
0x170830f8	pwd_imp_msg_conflict
0x170830f9	pwd_imp_msg_add_acct_fail
0x170830fa	pwd_imp_msg_conflict_rgy_st
0x170830fb	pwd_imp_msg_conflict_entry
0x170830fc	pwd_imp_msg_enter_group_name
0x170830fd	pwd_imp_msg_temp_group_name
0x170830fe	pwd_imp_msg_enter_new_name
0x170830ff	pwd_imp_qus_enter_conflict_action
0x17083100	pwd_imp_qus_group_conflict
0x17083101	pwd_imp_prompt_print
0x17083102	pwd_imp_prompt_enter_user_name
0x17083103	pwd_imp_prompt_enter_unix_id
0x17083104	pwd_imp_prompt_select_conflict_action
0x17083105	pwd_imp_msg_add_entry
0x17083106	pwd_imp_msg_add_entry_gen_unix_id

Message Number	Symbolic Name
0x17083107	pwd_imp_msg_import
0x17083108	pwd_imp_err_bad_ask_y_n
0x1708310b	pwd_exp_no_space
0x1708310c	pwd_exp_err_no_memory
0x17122001	sec_s_authz_unsupp
0x17122002	sec_s_keytype_unsupp
0x17122003	sec_s_bad_nonce
0x17122004	sec_s_none_registered
0x17122005	sec_s_no_pac
0x17122006	sec_s_not_implemented
0x17122007	sec_s_no_memory
0x17122008	sec_s_not_trustworthy
0x17122009	sec_s_no_key_seed
0x1712200a	sec_s_null_param_illegal
0x1712200b	sec_s_invalid_nameservice_entry
0x1712200c	sec_s_pgmerr
0x1712200d	sec_s_bad_key_parity
0x1712200e	sec_s_invalid_auth_params
0x1712200f	sec_s_v1_1_no_support
0x17122010	sec_s_svr_type_conflict
0x17122011	sec_s_user_to_user_disabled
0x17122012	sec_s_multiple_u2u_reg
0x17122016	sec_acl_not_implemented
0x17122017	sec_acl_cant_allocate_memory
0x17122018	sec_acl_invalid_site_name
0x17122019	sec_acl_unknown_manager_type

Message Number	Symbolic Name
0x1712201a	sec_acl_object_not_found
0x1712201b	sec_acl_no_acl_found
0x1712201c	sec_acl_invalid_entry_name
0x1712201d	sec_acl_expected_user_obj
0x1712201e	sec_acl_expected_group_obj
0x1712201f	sec_acl_invalid_entry_type
0x17122020	sec_acl_invalid_acl_type
0x17122021	sec_acl_bad_key
0x17122022	sec_acl_invalid_manager_type
0x17122023	sec_acl_read_only
0x17122024	sec_acl_site_read_only
0x17122025	sec_acl_invalid_permission
0x17122026	sec_acl_bad_acl_syntax
0x17122027	sec_acl_no_owner
0x17122028	sec_acl_invalid_entry_class
0x17122029	sec_acl_unable_to_authenticate
0x1712202a	sec_acl_name_resolution_failed
0x1712202b	sec_acl_rpc_error
0x1712202c	sec_acl_bind_error
0x1712202d	sec_acl_invalid_acl_handle
0x1712202e	sec_acl_no_update_sites
0x1712202f	sec_acl_mgr_file_open_error
0x17122030	sec_acl_missing_required_entry
0x17122031	sec_acl_duplicate_entry
0x17122032	sec_acl_bad_parameter
0x17122033	sec_acl_not_authorized

Message Number	Symbolic Name
0x17122034	sec_acl_server_bad_state
0x17122035	sec_acl_invalid_dfs_acl
0x17122036	sec_acl_mgr_no_space
0x17122037	sec_acl_bad_permset
0x17122043	sec_key_mgmt_e_key_unavailable
0x17122044	sec_key_mgmt_e_authn_invalid
0x17122045	sec_key_mgmt_e_auth_unavailable
0x17122046	sec_key_mgmt_e_unauthorized
0x17122047	sec_key_mgmt_e_key_unsupported
0x17122048	sec_key_mgmt_e_key_version_ex
0x17122049	sec_key_mgmt_e_not_implemented
0x1712204a	sec_key_mgmt_e_keytab_not_found
0x1712204b	sec_key_mgmt_e_ktfile_err
0x1712205a	sec_priv_s_server_unavailable
0x1712205b	sec_priv_s_invalid_principal
0x1712205c	sec_priv_s_not_member_any_group
0x1712205d	sec_priv_s_no_mem
0x1712205e	sec_priv_s_invalid_authn_svc
0x1712205f	sec_priv_s_invalid_authz_svc
0x17122060	sec_priv_s_invalid_trust_path
0x17122061	sec_priv_s_invalid_request
0x17122063	sec_priv_s_bad_compat_mode
0x17122064	sec_priv_s_bad_deleg_type
0x17122065	sec_priv_s_deleg_not_enabled
0x17122066	sec_priv_s_deleg_token_exp
0x17122067	sec_priv_s_corrupt_deleg_chain

Message Number	Symbolic Name
0x17122068	sec_priv_s_invalid_dlg_token
0x17122069	sec_priv_s_intercell_deleg_req
0x1712206a	sec_priv_s_invalid_server_name
0x1712206b	sec_priv_s_invalid_protect_lvl
0x1712206c	sec_priv_s_cmode_not_enabled
0x17122073	sec_rgy_not_implemented
0x17122074	sec_rgy_bad_domain
0x17122075	sec_rgy_object_exists
0x17122076	sec_rgy_name_exists
0x17122077	sec_rgy_unix_id_changed
0x17122078	sec_rgy_is_an_alias
0x17122079	sec_rgy_no_more_entries
0x1712207a	sec_rgy_object_not_found
0x1712207b	sec_rgy_server_unavailable
0x1712207c	sec_rgy_not_member_group
0x1712207d	sec_rgy_not_member_org
0x1712207e	sec_rgy_not_member_group_org
0x1712207f	sec_rgy_incomplete_login_name
0x17122080	sec_rgy_passwd_invalid
0x17122081	sec_rgy_not_authorized
0x17122082	sec_rgy_read_only
0x17122083	sec_rgy_bad_alias_owner
0x17122084	sec_rgy_bad_data
0x17122085	sec_rgy_cant_allocate_memory
0x17122086	sec_rgy_dir_not_found
0x17122087	sec_rgy_dir_not_empty

Message Number	Symbolic Name
0x17122088	sec_rgy_bad_name
0x17122089	sec_rgy_dir_could_not_create
0x1712208a	sec_rgy_dir_move_illegal
0x1712208b	sec_rgy_quota_exhausted
0x1712208c	sec_rgy_foreign_quota_exhausted
0x1712208d	sec_rgy_no_more_unix_ids
0x1712208e	sec_rgy_uuid_bad_version
0x1712208f	sec_rgy_key_bad_version
0x17122090	sec_rgy_key_version_in_use
0x17122091	sec_rgy_key_bad_type
0x17122092	sec_rgy_crypt_bad_type
0x17122093	sec_rgy_bad_scope
0x17122094	sec_rgy_object_not_in_scope
0x17122095	sec_rgy_cant_authenticate
0x17122096	sec_rgy_alias_not_allowed
0x17122097	sec_rgy_bad_chksum_type
0x17122098	sec_rgy_bad_integrity
0x17122099	sec_rgy_key_bad_size
0x1712209a	sec_rgy_mkey_cant_read_stored
0x1712209b	sec_rgy_mkey_bad_stored
0x1712209c	sec_rgy_mkey_bad
0x1712209d	sec_rgy_bad_handle
0x1712209e	sec_rgy_s_pgo_is_required
0x1712209f	sec_rgy_host_context_not_avail
0x171220a0	sec_rgy_mkey_file_io_failed
0x171220a1	sec_rgy_tower_rebind_failed

Message Number	Symbolic Name
0x171220a2	sec_rgy_site_not_absolute
0x171220a3	sec_rgy_bad_nameservice_name
0x171220a4	sec_rgy_log_entry_out_of_range
0x171220a5	sec_rgy_era_pwd_mgmt_auth_type
0x171220a6	sec_rgy_passwd_too_short
0x171220a7	sec_rgy_passwd_non_alpha
0x171220a8	sec_rgy_passwd_spaces
0x171220a9	sec_rgy_rep_pgmerr
0x171220aa	sec_rgy_rep_bad_db_version
0x171220ab	sec_rgy_rep_cannot_create_db
0x171220ac	sec_rgy_rep_cannot_open_db
0x171220ad	sec_rgy_rep_cannot_read_db
0x171220ae	sec_rgy_rep_cannot_save_db
0x171220af	sec_rgy_rep_cannot_rename_db
0x171220b0	sec_rgy_rep_master_not_found
0x171220b1	sec_rgy_rep_master
0x171220b2	sec_rgy_rep_not_master
0x171220b3	sec_rgy_rep_not_from_master
0x171220b4	sec_rgy_rep_bad_state
0x171220b5	sec_rgy_rep_name_unavailable
0x171220b6	sec_rgy_rep_bad_binding
0x171220b7	sec_rgy_rep_deleted
0x171220b8	sec_rgy_rep_db_locked
0x171220b9	sec_rgy_rep_clock_skew
0x171220ba	sec_rgy_rep_update_seqno_high
0x171220bb	sec_rgy_rep_update_seqno_low

Message Number	Symbolic Name
0x171220bc	sec_rgy_rep_doppelganger
0x171220bd	sec_rgy_rep_babel
0x171220be	sec_rgy_rep_not_on_replist
0x171220bf	sec_rgy_rep_prop_complete
0x171220c0	sec_rgy_rep_prop_busy
0x171220c1	sec_rgy_rep_prop_from_rep
0x171220c2	sec_rgy_rep_bad_arg
0x171220c3	sec_rgy_rep_no_default_replica
0x171220c4	sec_rgy_rep_invalid_entry
0x171220c5	sec_rgy_rep_init_ekey_invalid
0x171220c6	sec_rgy_rep_bad_sw_vers
0x171220c7	sec_rgy_rep_marked_for_init
0x171220c8	sec_rgy_rep_bad_init_id
0x171220c9	sec_rgy_rep_already_initied
0x171220ca	sec_rgy_rep_bad_prop_type
0x171220cb	sec_rgy_rep_master_bad_sw_vers
0x171220cc	sec_rgy_rep_slave_bad_sw_vers
0x171220cd	sec_rgy_rep_master_dup
0x171220ce	sec_rgy_rep_must_init_slave
0x171220cf	sec_rgy_rep_bad_master_seqno
0x171220d0	sec_rgy_rep_sw_rev_nosup
0x171220d1	sec_rgy_rep_sw_rev_no_setback
0x171220d4	sec_id_e_name_too_long
0x171220d5	sec_id_e_bad_cell_uuid
0x171220d6	sec_id_e_foreign_cell_referral
0x171220d7	sec_id_e_no_at_hack

Message Number	Symbolic Name
0x171220e7	sec_login_s_not_implemented
0x171220e8	sec_login_s_no_memory
0x171220e9	sec_login_s_auth_local
0x171220ea	sec_login_s_handle_invalid
0x171220eb	sec_login_s_context_invalid
0x171220ec	sec_login_s_no_current_context
0x171220ed	sec_login_s_groupset_invalid
0x171220ee	sec_login_s_info_not_avail
0x171220ef	sec_login_s_already_valid
0x171220f0	sec_login_s_default_use
0x171220f1	sec_login_s_privileged
0x171220f2	sec_login_s_not_certified
0x171220f3	sec_login_s_config
0x171220f4	sec_login_s_internal_error
0x171220f5	sec_login_s_no_override_info
0x171220f6	sec_login_s_acct_invalid
0x171220f7	sec_login_s_null_password
0x171220f8	sec_login_s_unsupp_passwd_type
0x171220f9	sec_login_s_no_identity
0x171220fa	sec_login_s_refresh_ident_bad
0x171220fb	sec_login_s_override_failure
0x171220fc	sec_login_s_ovrd_ent_not_found
0x171220fd	sec_login_s_invalid_password
0x171220fe	sec_login_s_incomplete_ovrd_ent
0x171220ff	sec_login_s_invalid_deleg_type
0x17122100	sec_login_s_compound_delegate

Message Number	Symbolic Name
0x17122101	sec_login_s_invalid_compat_mode
0x17122102	sec_login_s_deleg_not_enabled
0x17122103	sec_login_s_preauth_failed
0x17122105	sec_login_s_unix_id_overflow
0x17122117	sec_lrgy_s_max_lt_num_entries
0x17122118	sec_lrgy_s_not_found
0x17122119	sec_lrgy_s_cannot_create
0x1712211a	sec_lrgy_s_no_access
0x1712211b	sec_lrgy_s_internal_error
0x1712211c	sec_lrgy_s_no_matching_entry
0x1712211d	sec_lrgy_s_no_matching_tgt
0x1712211e	sec_lrgy_s_no_more_entries
0x1712212e	sec_cred_s_no_more_entries
0x1712212f	sec_cred_s_invalid_auth_handle
0x17122130	sec_cred_s_invalid_pa_handle
0x17122131	sec_cred_s_invalid_cursor
0x17122132	sec_cred_s_authz_cannot_comply
0x17122133	sec_cred_s_invalid_key
0x17122134	sec_cred_s_key_not_found
0x17122135	sec_cred_s_no_more_key
0x17122143	sec_attr_sch_entry_not_found
0x17122144	sec_attr_inst_not_found
0x17122145	sec_attr_not_all_avail
0x17122146	sec_attr_set_member_missing
0x17122147	sec_attr_rgy_obj_not_found
0x17122148	sec_attr_inst_exists

Message Number	Symbolic Name
0x17122149	sec_attr_unauthorized
0x1712214a	sec_attr_svr_read_only
0x1712214b	sec_attr_svr_unavailable
0x1712214c	sec_attr_trig_svr_unavailable
0x1712214d	sec_attr_name_exists
0x1712214e	sec_attr_type_id_exists
0x1712214f	sec_attr_field_no_update
0x17122150	sec_attr_bad_type
0x17122151	sec_attr_bad_acl_mgr_set
0x17122152	sec_attr_bad_acl_mgr_type
0x17122153	sec_attr_bad_bind_info
0x17122154	sec_attr_bad_permset
0x17122155	sec_attr_no_memory
0x17122156	sec_attr_not_unique
0x17122157	sec_attr_bad_name
0x17122158	sec_attr_bad_encoding_type
0x17122159	sec_attr_bad_scope
0x1712215a	sec_attr_bad_comment
0x1712215b	sec_attr_bad_intercell_action
0x1712215c	sec_attr_bad_trig_type
0x1712215d	sec_attr_trig_bind_info_missing
0x1712215e	sec_attr_bad_uniq_query_accept
0x1712215f	sec_attr_bad_bind_svr_name
0x17122160	sec_attr_bad_bind_prot_level
0x17122161	sec_attr_bad_bind_authn_svc
0x17122162	sec_attr_bad_bind_authz_svc

Message Number	Symbolic Name
0x17122163	sec_attr_bad_cursor
0x17122164	sec_attr_not_implemented
0x17122165	sec_attr_trig_query_not_sup
0x17122166	sec_attr_bad_object_type
0x17122167	sec_attr_not_multi_valued
0x17122168	sec_attr_val_printstring_bad
0x17122169	sec_attr_val_string_array_bad
0x1712216a	sec_attr_val_bytes_bad
0x1712216b	sec_attr_val_attr_set_bad
0x1712216c	sec_attr_no_more_entries
0x1712216d	sec_attr_bad_param
0x1712216e	sec_attr_sch_reserved
0x1712216f	sec_attr_unique_no_update
0x17122170	sec_attr_multi_inst_no_update
0x17122171	sec_attr_trig_types_no_update
0x17122172	sec_attr_qry_trig_bad_enc_type
0x17122173	sec_attr_multi_inst_disallowed
0x17122176	sec_pwd_mgmt_str_check_failed
0x17122177	sec_pwd_mgmt_not_authorized
0x17122178	sec_pwd_mgmt_svr_error
0x17122179	sec_pwd_mgmt_svr_unavail
0x1712217a	sec_pwd_mgmt_proxy_req
0x1712217b	sec_authn_s_missing_epac
0x1712217c	sec_authn_s_no_seal
0x1712217d	sec_authn_s_bad_seal
0x1712217e	sec_svc_not_authorized

Message Number	Symbolic Name
0x1712217f	sec_rgy_homedir_too_long
0x17122180	sec_authn_bad_cell_name
0x17122181	sec_rgy_rep_sw_rev_multi
0x17122182	sec_rgy_rep_sw_rev_outstanding
0x17122183	sec_pk_e_domain_unsupported
0x17122184	sec_pk_e_usage_unsupported
0x17122185	sec_pk_e_key_vers_unsupported
0x17122186	sec_pk_e_key_vers_unavailable
0x17122187	sec_pk_e_key_attr_read_failed
0x17122188	sec_pk_e_no_memory
0x17122189	sec_pk_e_cell_too_long
0x1712218a	sec_pk_e_no_key_value
0x1712218b	sec_pk_e_kf_param_not_alloc
0x1712218c	sec_pk_e_kf_open_err
0x1712218d	sec_pk_e_kf_read_err
0x1712218e	sec_pk_e_kf_write_err
0x1712218f	sec_pk_e_kf_format_err
0x17122190	sec_pk_e_kf_version_err
0x17122191	sec_pk_e_rsdb_keystore_err
0x17122192	sec_rsdb_acct_bad_keytype
0x17122193	sec_pk_login_client_fail
0x17122cc0	sec_rrs_cant_get_next_key
0x17122cc1	sec_rs_pwd_bogus_pickle
0x17122cc2	sec_lksm_def_yes_prompt
0x17122cc3	sec_lksm_def_no_prompt
0x17122cc4	sec_lksm_bad_input

Message Number	Symbolic Name
0x17122cc5	sec_lksm_create_acct
0x17122cc6	sec_lksm_set_pwd_valid
0x17122cc7	sec_lksm_set_client_valid
0x17122cc8	sec_lksm_set_server_valid
0x17122cc9	sec_lksm_set_acct_valid
0x1712cca	sec_lksm_set_date_now
0x1712ccb	sec_lksm_set_acct_span
0x1712ccc	sec_lksm_set_expire
0x1712ccd	sec_lksm_set_polpwd_expire_now
0x1712cce	sec_lksm_set_polpwd_expire
0x1712ccf	sec_lksm_passwd_prompt
0x1712cd0	sec_lksm_passwd_verify
0x1712cd1	sec_svc_cant_get_msg
0x1712cd2	sec_rs_pipe_not_created
0x1712cd3	sec_res_host_key_set_err
0x1712cd4	sec_res_princ_cvt_err
0x1712cd5	sec_res_uuid_cvt_err
0x1712cd6	sec_res_pgo_add_err
0x1712cd7	sec_res_mem_add_err
0x1712cd8	sec_res_acct_add_err
0x1712cd9	sec_res_attr_sch_add_err
0x1712cda	sec_res_pk_attr_sch_add_err
0x1712d00	sec_rgy_not_root
0x1712d01	sec_rgy_db_init
0x1712d02	sec_rgy_thr_join
0x1712d03	sec_rgy_thr_exit_alert

Message Number	Symbolic Name
0x17122d04	sec_rgy_thr_exit_exc
0x17122d05	sec_rgy_startup_done
0x17122d06	sec_rgy_shutdown_done
0x17122d07	sec_secd_cl_usage
0x17122d08	sec_secd_cl_missing_arg
0x17122d09	sec_secd_cl_bad_arg
0x17122d0a	sec_secd_cl_unknown_opt
0x17122d0b	sec_secd_cl_locksmith_opt
0x17122d0c	sec_secd_cl_bad_chkpt_interval
0x17122d0d	sec_rgy_aud_open
0x17122d0e	sec_rgy_unauth_cred_handle_init
0x17122d0f	sec_rgy_set_stack_size
0x17122d10	sec_rgy_init_rpc_bind
0x17122d11	sec_rgy_log_init_mgr
0x17122d12	sec_rgy_db_init_err
0x17122d13	sec_rgy_rep_init_replica
0x17122d14	sec_rgy_acl_init
0x17122d15	sec_rgy_locksmith_init
0x17122d16	sec_rgy_svr_register
0x17122d17	sec_rgy_host_identity
0x17122d18	sec_rgy_auth_init
0x17122d19	sec_rgy_rep_host_identity
0x17122d1a	sec_rgy_dce_rgy_identity
0x17122d1b	sec_rgy_ns_register
0x17122d1c	sec_rgy_checkpt_start_task
0x17122d1d	sec_rgy_sigcatch_start_task

Message Number	Symbolic Name
0x17122d1e	sec_rgy_thr_set_pool
0x17122d20	sec_rs_login_wrong_call
0x17122d21	sec_rs_login_null_handle
0x17122d22	sec_rs_login_null_name
0x17122d23	sec_rs_login_refresh_wait
0x17122d24	sec_rs_login_refresh
0x17122d25	sec_rs_login_cant_refresh
0x17122d26	sec_rgy_get_local_host_princ
0x17122d27	sec_rs_login_bad_name
0x17122d40	sec_rs_ns_null_profile
0x17122d41	sec_rs_ns_null_vl_group
0x17122d42	sec_rs_ns_grp_ent_create_fail
0x17122d43	sec_rs_ns_grp_ent_create_succ
0x17122d44	sec_rs_ns_grp_mbr_add_fail
0x17122d45	sec_rs_ns_grp_mbr_add_succ
0x17122d46	sec_rs_ns_prof_elt_add_fail
0x17122d47	sec_rs_ns_prof_elt_add_succ
0x17122d48	sec_rs_ns_prof_elt_rm_fail
0x17122d49	sec_rs_ns_prof_elt_rm_succ
0x17122d4a	sec_rs_ns_prof_elt_inq_fail
0x17122d4b	sec_rs_ns_prof_elt_inq_succ
0x17122d4c	sec_rs_ns_bind_export
0x17122d4d	sec_rs_ns_bind_export_succ
0x17122d4e	sec_rs_ns_bind_remove_succ
0x17122d4f	sec_rs_ns_name_del_succ
0x17122d50	sec_rs_ns_name_not_removed

Message Number	Symbolic Name
0x17122d51	sec_rs_ns_cant_rm_name
0x17122d52	sec_rs_ns_cant_rm_member
0x17122d53	sec_rgy_ns_svr_get_binding
0x17122d54	sec_rgy_svr_register_ns
0x17122d80	sec_rs_rpc_if_reg_succ
0x17122d81	sec_rs_rpc_propif_reg_succ
0x17122d82	sec_rs_rpc_propif_unreg_succ
0x17122d83	sec_rs_rpc_if_unreg_succ
0x17122d84	sec_rs_rpc_use_protseq_err
0x17122d85	sec_rs_rpc_inq_bind_err
0x17122d86	sec_rs_rpc_save_bind_err
0x17122d87	sec_rs_rpc_prot_twr_err
0x17122da0	sec_rs_thr_exit_creat_fail
0x17122da1	sec_rs_thr_create_fail
0x17122da2	sec_rs_thr_started
0x17122da3	sec_rs_thr_exiting
0x17122dc0	sec_crdb_site_file_create_fail
0x17122dc1	sec_crdb_site_file_create_succ
0x17122dc2	sec_crdb_site_file_upd_succ
0x17122dc3	sec_crdb_site_file_upd_fail
0x17122dc4	sec_crdb_cr_master_db
0x17122dc5	sec_crdb_cr_rep_db
0x17122dc6	sec_crdb_cr_db_succ
0x17122dc7	sec_crdb_db_exists
0x17122dc8	sec_crdb_at_char_in_cellname
0x17122dc9	sec_crdb_cl_bad_name

Message Number	Symbolic Name
0x17122dca	sec_crdb_cl_dup_option
0x17122dcb	sec_crdb_cl_missing_arg
0x17122dcc	sec_crdb_cl_long_rgyname
0x17122dcd	sec_crdb_cl_long_passwd
0x17122dce	sec_crdb_cl_unknown_option
0x17122dcf	sec_crdb_cl_null_myname
0x17122dd0	sec_crdb_cl_usage
0x17122dd1	sec_crdb_cl_alt_dir_no_arg
0x17122dd2	sec_crdb_cant_get_hostname
0x17122dd3	sec_crdb_cant_create_celluid
0x17122dd4	sec_crdb_cant_setup_rgycreator
0x17122dd5	sec_crdb_cant_get_host_prname
0x17122dd6	sec_crdb_db_not_created
0x17122dd7	sec_crdb_cant_register_ns
0x17122dd8	sec_crdb_cant_add_replica
0x17122dd9	sec_crdb_cant_upd_rgyst_file
0x17122dda	sec_crdb_rep_not_registered
0x17122ddb	sec_crdb_inherit_hostident_err
0x17122ddc	sec_crdb_cant_bind_updsite
0x17122ddd	sec_crdb_cant_com_master
0x17122e00	sec_rs_log_bad_version
0x17122e01	sec_rs_log_open_fail
0x17122e02	sec_rs_log_file_closed
0x17122e03	sec_rs_log_propq_add_fail
0x17122e04	sec_rs_log_replay
0x17122e05	sec_rs_log_replay_succ

Message Number	Symbolic Name
0x17122e06	sec_rs_log_base_prop_seq
0x17122e07	sec_rs_log_replay_entry
0x17122e08	sec_rs_log_replay_err
0x17122e09	sec_rgy_rep_pack_entry
0x17122e20	sec_rgy_mky_bad_cellname
0x17122e21	sec_rs_mkey_actver_mismatch
0x17122e22	sec_rs_mkey_unknown
0x17122e23	sec_rs_mkey_long_keyseed
0x17122e24	sec_rgy_mky_get_realm_name
0x17122e25	sec_rgy_mky_setup_mkey_name
0x17122e26	sec_rgy_mky_init_keyseed
0x17122e27	sec_rgy_mky_process_keyseed
0x17122e28	sec_rgy_mky_init_random
0x17122e29	sec_rgy_mky_gen_random
0x17122e2a	sec_rgy_mky_process_master_key
0x17122e2b	sec_rgy_mky_store_disk
0x17122e2c	sec_rgy_mky_store_db
0x17122e2d	sec_rgy_mky_not_match
0x17122e40	sec_prop_no_prop_thrs
0x17122e41	sec_prop_not_master
0x17122e42	sec_prop_no_master_info
0x17122e43	sec_prop_bad_type
0x17122e44	sec_prop_succ
0x17122e45	sec_prop_fail
0x17122e46	sec_prop_send_init_slave
0x17122e47	sec_prop_chk_prop_slave_init

Message Number	Symbolic Name
0x17122e48	sec_prop_slave_init_done
0x17122e49	sec_prop_updates_to_slaves
0x17122e4a	sec_prop_send_delete_rep
0x17122e4b	sec_rgy_rep_master_obsolete
0x17122e4c	sec_prop_propq_clean_fail
0x17122e60	sec_rs_vmcc_cant_register
0x17122e61	sec_rs_vmcc_cant_remove
0x17122e62	sec_rep_corrupt_auth_handle
0x17122e63	sec_rep_invalid_auth_handle
0x17122e64	sec_rs_rep_not_master
0x17122e65	sec_rs_rep_incompat_version
0x17122e66	sec_rep_rm_not_in_service
0x17122e67	sec_rep_mseq_not_dup_master
0x17122e68	sec_rep_maint_not_master
0x17122e69	sec_rep_dupe_not_master
0x17122e6a	sec_rep_dupe_cant_start
0x17122e6b	sec_rep_nm_not_deleted
0x17122e6c	sec_rep_not_on_replist
0x17122e6d	sec_rep_msrepl_not_initiated
0x17122e6e	sec_rep_cant_start_prop_tasks
0x17122e6f	sec_rep_prop_in_progress
0x17122e70	sec_rep_prop_type_not_init
0x17122e71	sec_rgy_rep_entry_not_found
0x17122e72	sec_rep_recv_init_slave
0x17122e73	sec_rep_init_slave_succ
0x17122e74	sec_rep_init_slave_fail

Message Number	Symbolic Name
0x17122e75	sec_rep_recv_i_am_master
0x17122e76	sec_rep_recv_become_master
0x17122e77	sec_rep_recv_stop_sw_compat
0x17122e78	sec_rgy_rsd_b_checkpoint
0x17122e79	sec_rgy_rep_mst_restart_prop
0x17122e7a	sec_rgy_rep_slv_restart_prop
0x17122e7b	sec_rgy_rep_set_state
0x17122e7c	sec_rgy_rep_set_init_id
0x17122e7d	sec_rgy_rep_set_volatile_state
0x17122e7e	sec_rgy_rep_recover_db
0x17122e7f	sec_rgy_rep_add_my_replica
0x17122e80	sec_rgy_rep_add_master_replica
0x17122e81	sec_rgy_rsd_b_checkpoint_uninit
0x17122e82	sec_rep_cant_get_sw_rev_fatal
0x17122e83	sec_rep_adopt_sw_rev_fatal
0x17122ea0	sec_rsd_b_log_file_open
0x17122ea1	sec_rsd_b_db_unrecog_state
0x17122ea2	sec_rsd_b_ent_not_xlated
0x17122ea3	sec_logent_out_of_bounds
0x17122ea4	sec_rsd_b_logent_replay_err
0x17122ea5	sec_rsd_b_db_chkpt_err
0x17122ea6	sec_rsd_b_log_chkpt_err
0x17122ea7	sec_rsd_b_file_rename_err
0x17122ea8	sec_rsd_b_rep_state_not_saved
0x17122ea9	sec_rsd_b_dbstore_fail
0x17122eaa	sec_rsd_b_repl_fail

Message Number	Symbolic Name
0x17122eab	sec_rgy_bad_rgy_db
0x17122eac	sec_rgy_checkpoint_log_file
0x17122ead	sec_rgy_checkpoint_rename_files
0x17122eae	sec_rgy_checkpoint_save_rep_state
0x17122eaf	sec_rgy_checkpoint
0x17122eb0	sec_rgy_checkpoint_succ
0x17122eb1	sec_rsdb_file_stat_fail
0x17122eb2	sec_rsdb_readver_fail
0x17122eb3	sec_rsdb_db_write_fail
0x17122eb4	sec_rsdb_acct_reset
0x17122eb5	sec_rsdb_acct_cant_getid
0x17122eb6	sec_rsdb_acct_noaliases
0x17122eb7	sec_rsdb_acct_add_curkey
0x17122eb8	sec_rsdb_acct_end_list
0x17122eb9	sec_attr_cant_get_attrlist
0x17122eba	sec_attr_num_attr_ltzero
0x17122ebb	sec_attr_cant_get_instance
0x17122ebc	sec_attr_cant_get_attrinst
0x17122ebd	sec_rgy_rsdb_attr_set_id
0x17122ebe	sec_rgy_rsdb_attr_import
0x17122ebf	sec_rgy_rsdb_attr_delete
0x17122ec0	sec_rgy_rsdb_attr_export
0x17122ec1	sec_rsdb_list_not_terminated
0x17122ec2	sec_rsdb_no_open_slot
0x17122ec3	sec_rsdb_cant_set_properties
0x17122ec4	sec_rsdb_cant_set_realm

Message Number	Symbolic Name
0x17122ec5	sec_rsdb_cant_set_policy
0x17122ec6	sec_rsdb_cant_set_auth_policy
0x17122ec7	sec_rsdb_inconsistent_creds
0x17122ec8	sec_rsdb_cant_get_pgo_creds
0x17122ec9	sec_rsdb_cant_get_item
0x17122eca	sec_rsdb_cant_walk_alias_chain
0x17122ecb	sec_rsdb_bad_policy_data
0x17122ecc	sec_rsdb_bad_policy_key
0x17122ecd	sec_rsdb_cant_cntr_item_name
0x17122ece	sec_rsdb_corrupt_alias_chain
0x17122ecf	sec_rsdb_end_memb_list
0x17122ed0	sec_rsdb_db_inconsistent
0x17122ed1	sec_rsdb_cant_store_new_item
0x17122ed2	sec_rsdb_cant_get_item_seqid
0x17122ed3	sec_rsdb_cant_get_person_creds
0x17122ed4	sec_rsdb_cant_get_group_creds
0x17122ed5	sec_rsdb_cant_get_org_creds
0x17122ed6	sec_rsdb_cant_get_member_data
0x17122ed7	sec_rsdb_cant_get_key
0x17122ed8	sec_rsdb_fetch_error
0x17122ed9	sec_rsdb_cant_init_acl
0x17122eda	sec_rsdb_unknown_aclmgr_type
0x17122edb	sec_rsdb_cant_get_mgr_typuuid
0x17122edc	sec_attr_schema_cant_reset
0x17122edd	sec_attr_schema_cant_lookup
0x17122ede	sec_rs_lock_fatal_exc

Message Number	Symbolic Name
0x17122edf	sec_rs_global_lock_fatal_exc
0x17122ee0	rsdb_journal_open
0x17122ee1	rsdb_journal_create_fail
0x17122ee2	rsdb_journal_hdr_write_failed
0x17122ee3	rsdb_journal_cant_init_list
0x17122ee4	rsdb_journal_cant_open
0x17122ee5	rsdb_login_cant_init_list
0x17122ee6	sec_rgy_chkpt_save_file
0x17122ee7	sec_rgy_chkpt_save_relation
0x17122ee8	sec_rgy_compat_log_replay
0x17122ee9	rsdb_check_cell_failure
0x17122eea	rsdb_cell_mismatch
0x17122eeb	sec_rgy_checkpoint_bad_at_time_str
0x17122f20	sec_site_bind_start
0x17122f21	sec_site_bind_succ
0x17122f22	sec_site_bind_fail
0x17122f23	sec_site_cell_bind_start
0x17122f24	sec_site_bind_default
0x17122f25	sec_site_rebind_start
0x17122f26	sec_site_rebind_succ
0x17122f27	sec_site_rebind_fail
0x17122f28	sec_site_lookup_file
0x17122f29	sec_site_profile_search_start
0x17122f2a	sec_site_profile_search_succ
0x17122f2b	sec_site_profile_search_fail
0x17122f2c	sec_ns_import_begin

Message Number	Symbolic Name
0x17122f2d	sec_ns_import_next
0x17122f2e	sec_ns_import_done
0x17122f2f	sec_rca_op_status
0x17122f30	sec_rca_site_rebind
0x17122f31	sec_rca_site_rebind_succ
0x17122f32	sec_rca_site_rebind_fail
0x17122f40	sec_thr_post_cancel
0x17122f41	sec_thr_exit_cancel
0x17122f42	sec_thr_alert
0x17122f43	sec_thr_exit_exc
0x17122f60	sec_buf_too_small
0x17122f61	sec_sys_errno_text
0x17122f62	sec_sys_errno_text_only
0x17122f63	sec_sys_file_lseek_fail
0x17122f64	sec_sys_file_open_fail
0x17122f65	sec_rgy_get_cellname
0x17122f66	sec_rgy_db_create
0x17122f67	sec_sys_file_read_error
0x17122f68	sec_sys_file_write_error
0x17122f69	sec_sys_file_ftruncate_fail
0x17122f6a	sec_sys_errno_file_text
0x173ca001	svc_s_no_memory
0x173ca002	svc_s_unknown_component
0x173ca003	svc_s_no_filter
0x173ca004	svc_s_bad_routespec
0x173ca005	svc_s_cantopen

Message Number	Symbolic Name
0x173ca006	svc_s_at_end
0x173ca007	svc_s_assertion_failed
0x173ca008	svc_s_no_stats
0x173ca009	svc_s_no_perm
0x173ca00a	svc_s_acl_corrupt
0x173ca00b	svc_s_acl_open_error
0x173ca00c	svc_s_acl_read_error
0x173ca00d	svc_s_acl_write_error
0x173ca00f	msg_s_bad_id
0x173ca010	msg_s_no_memory
0x173ca011	msg_s_no_default
0x173ca012	msg_s_not_found
0x173ca013	msg_s_no_cat_open
0x173ca014	msg_s_no_cat_perm
0x173ca015	msg_s_no_catalog
0x173ca016	msg_s_ok_text
0x1771b005	tcl_s_basic_interp_init_error
0x1771b006	tcl_s_basic_too_many_nested_calls
0x1771b007	tcl_s_basic_invalid_cmd_name
0x1771b008	tcl_s_basic_break_outside_of_loop
0x1771b009	tcl_s_basic_continue_outside_of_loop
0x1771b00a	tcl_s_basic_cmd_return_bad_code
0x1771b013	tcl_s_ckalloc_low_guard_byte
0x1771b014	tcl_s_ckalloc_low_guard_failed
0x1771b015	tcl_s_ckalloc_bytes_allocated_at
0x1771b016	tcl_s_ckalloc_mem_val_failure

Message Number	Symbolic Name
0x1771b017	tcl_s_ckalloc_hi_guard_byte
0x1771b018	tcl_s_ckalloc_hi_guard_failed
0x1771b019	tcl_s_ckalloc_unable_to_alloc_bytes_line
0x1771b01b	tcl_s_ckalloc_reached_malloc_break_limit
0x1771b01f	tcl_s_ckalloc_error_accessing
0x1771b023	tcl_s_ckalloc_unable_to_alloc
0x1771b029	tcl_s_cmdah_could_not_save_cmd_result
0x1771b034	tcl_s_cmdah_could_not_set_loop_var
0x1771b037	tcl_s_cmdah_fmt_str_ended_in_middle
0x1771b038	tcl_s_cmdah_bad_field_spec
0x1771b039	tcl_s_cmdah_cannot_mix_conversion_specs
0x1771b03a	tcl_s_cmdah_arg_index_out_of_range
0x1771b03b	tcl_s_cmdah_not_enough_args
0x1771b044	tcl_s_cmdil_is_not_a_proc
0x1771b04a	tcl_s_cmdil_proc_no_argument
0x1771b04b	tcl_s_cmdil_could_not_store_def_val
0x1771b04e	tcl_s_cmdil_bad_level
0x1771b051	tcl_s_cmdil_no_tcl_library
0x1771b05e	tcl_s_cmdil_expect_int_or_end
0x1771b060	tcl_s_cmdil_fst_idx_greater_than_second
0x1771b062	tcl_s_cmdil_bad_search_mode
0x1771b066	tcl_s_cmdil_command_not_with_comparison
0x1771b06a	tcl_s_cmdil_com_cmd_ret_non_numeric
0x1771b06d	tcl_s_cmdmz_err_while_match_pat
0x1771b06e	tcl_s_cmdmz_too_many_substr_var
0x1771b06f	tcl_s_cmdmz_could_not_set_var

Message Number	Symbolic Name
0x1771b073	tcl_s_cmdmz_del_cmd_doesnot_exist
0x1771b074	tcl_s_cmdmz_rename_cmd_already_exist
0x1771b075	tcl_s_cmdmz_rename_cmd_doesnot_exist
0x1771b076	tcl_s_cmdmz_bad_comp_code_ok_err_ret_brk
0x1771b079	tcl_s_cmdmz_too_many_fds_to_scan
0x1771b07a	tcl_s_cmdmz fld_width_not_be_specified_in_c_conv
0x1771b07b	tcl_s_cmdmz_bad_scan_conv_char
0x1771b07c	tcl_s_cmdmz_diff_num_var_field
0x1771b086	tcl_s_cmdmz_expt_int_or_end
0x1771b08c	tcl_s_cmdmz_extra_switch_pat_no_body
0x1771b08d	tcl_s_cmdmz_no_body_spec_for_pat
0x1771b095	tcl_s_cmdmz_bad_opr_more_rwu
0x1771b098	tcl_s_env_conf_arguments
0x1771b099	tcl_s_env_no_interpreter
0x1771b09a	tcl_s_expr_int_val_too_large
0x1771b09b	tcl_s_expr_poor_flat_val_form
0x1771b09c	tcl_s_expr_unmatch_parens_in_expr
0x1771b09d	tcl_s_expr_unknown_oper_in_expr
0x1771b09e	tcl_s_expr_divide_by_zero
0x1771b09f	tcl_s_expr_colon_without_question
0x1771b0a0	tcl_s_expr_syntax_err
0x1771b0a1	tcl_s_expr_float_non_numeric_as_op
0x1771b0a2	tcl_s_expr_non_numeric_non_numeric_as_op
0x1771b0a3	tcl_s_expr_non_numeric_exp
0x1771b0a4	tcl_s_expr_unknown_math_func
0x1771b0a5	tcl_s_expr_arg_math_func_non_numeric

Message Number	Symbolic Name
0x1771b0a6	tcl_s_expr_many_args_for_math_func
0x1771b0a7	tcl_s_expr_few_args_for_math_func
0x1771b0a8	tcl_s_expr_domain_err
0x1771b0a9	tcl_s_expr_float_val_too_small
0x1771b0aa	tcl_s_expr_float_val_too_large
0x1771b0ab	tcl_s_expr_unknown_float_point_err
0x1771b0ac	tcl_s_get_exp_integer_but
0x1771b0ad	tcl_s_get_exp_float_but
0x1771b0ae	tcl_s_get_exp_boolean_but
0x1771b0af	tcl_s_glob_unmatched_open_brace
0x1771b0b0	tcl_s_glob_dir_unreadable
0x1771b0b1	tcl_s_glob_no_home_env
0x1771b0b2	tcl_s_glob_no_user
0x1771b0b5	tcl_s_glob_no_files_match_single
0x1771b0b6	tcl_s_glob_no_files_match_plural
0x1771b0b7	tcl_s_hash_bad_bucket_chain
0x1771b0bc	tcl_s_hash_bogus_find
0x1771b0bd	tcl_s_hash_bogus_create
0x1771b0c4	tcl_s_hist_illegal_keep_count
0x1771b0ca	tcl_s_hist_hist_assert_failed
0x1771b0cb	tcl_s_hist_evt_has_not_occurred
0x1771b0cc	tcl_s_hist_evt_too_far_past
0x1771b0cd	tcl_s_hist_evt_no_matches
0x1771b0ce	tcl_s_hist_evt_does_not_appear
0x1771b0cf	tcl_s_hist_evt_word_sele_non_existent
0x1771b0d1	tcl_s_main_appl_init_failed

Message Number	Symbolic Name
0x1771b0d4	tcl_s_parse_missing_c
0x1771b0d5	tcl_s_parse_missing_close_brace
0x1771b0d6	tcl_s_parse_missing_close_bracket
0x1771b0d7	tcl_s_parse_extra_char_quote
0x1771b0d8	tcl_s_parse_extra_char_brace
0x1771b0d9	tcl_s_parse_missing_close_brace_var
0x1771b0dc	tcl_s_proc_too_many_fds_in_arg
0x1771b0dd	tcl_s_proc_no_name_arg
0x1771b0de	tcl_s_proc_bad_level
0x1771b0e1	tcl_s_proc_no_val_given_to_par
0x1771b0e2	tcl_s_proc_called_with_too_many_args
0x1771b0e4	tcl_s_proc_break_outside_loop
0x1771b0e5	tcl_s_proc_continue_outside_loop
0x1771b0e6	tcl_s_link_bad_linked_var_type
0x1771b0e7	tcl_s_link_linked_var_read_only
0x1771b0e8	tcl_s_link_linked_var_unreadable
0x1771b0e9	tcl_s_link_var_must_be_integer
0x1771b0ea	tcl_s_link_var_must_be_real
0x1771b0eb	tcl_s_link_var_must_be_bool
0x1771b0ee	tcl_s_test_bogus_interpreter
0x1771b0f6	tcl_s_unixaz_cannot_change_work_dir
0x1771b0f8	tcl_s_unixaz_error_closing
0x1771b0fb	tcl_s_unixaz_error_read_from_out_pipe
0x1771b100	tcl_s_unixaz_no_lstat
0x1771b101	tcl_s_unixaz_no_readlink
0x1771b103	tcl_s_unixaz_no_stat

Message Number	Symbolic Name
0x1771b10d	tcl_s_unixaz_error_flushing
0x1771b10f	tcl_s_unixaz_error_reading
0x1771b111	tcl_s_unixaz_cannot_open
0x1771b112	tcl_s_unixaz_cannot_read_output
0x1771b113	tcl_s_unixaz_cannot_write_input
0x1771b114	tcl_s_unixaz_illegal_access_mode
0x1771b116	tcl_s_unixaz_access_mode_not_supported
0x1771b117	tcl_s_unixaz_invalid_access_mode
0x1771b118	tcl_s_unixaz_access_mode_must_inc
0x1771b11c	tcl_s_unixaz_error_writing
0x1771b11e	tcl_s_unixaz_cwd_name_too_long
0x1771b11f	tcl_s_unixaz_error_with_cwd_name
0x1771b123	tcl_s_unixaz_error_during_seek
0x1771b127	tcl_s_unixaz_error_wait_exit
0x1771b128	tcl_s_unixaz_child_killed
0x1771b129	tcl_s_unixaz_child_suspended
0x1771b12a	tcl_s_unixaz_child_st_no_sense
0x1771b12b	tcl_s_unixaz_error_read_stderr
0x1771b12c	tcl_s_unixaz_child_abend_exit
0x1771b12d	tcl_s_unixstr_unknown_err
0x1771b12e	tcl_s_unixstr_unknown_signal
0x1771b151	tcl_s_unixutil_no_read_file
0x1771b152	tcl_s_unixutil_no_stat_file
0x1771b153	tcl_s_unixutil_err_read_file
0x1771b154	tcl_s_unixutil_err_close_file
0x1771b156	tcl_s_unixutil_illegal_use_pipeline

Message Number	Symbolic Name
0x1771b157	tcl_s_unixutil_cannot_spec_as_last
0x1771b158	tcl_s_unixutil_no_command_to_exec
0x1771b159	tcl_s_unixutil_cannot_creat_input_file
0x1771b15a	tcl_s_unixutil_cannot_write_file_input
0x1771b15b	tcl_s_unixutil_cannot_reset_remove_file
0x1771b15c	tcl_s_unixutil_cannot_create_input_pipe
0x1771b15d	tcl_s_unixutil_cannot_create_output_pipe
0x1771b15e	tcl_s_unixutil_cannot_creat_err_file
0x1771b15f	tcl_s_unixutil_cannot_remove_err_file
0x1771b160	tcl_s_unixutil_cannot_create_pipe
0x1771b161	tcl_s_unixutil_forked_proc_useless
0x1771b162	tcl_s_unixutil_cannot_fork_chld_proc
0x1771b163	tcl_s_unixutil_cannot_write_file
0x1771b164	tcl_s_unixutil_not_find_to_exec
0x1771b165	tcl_s_unixutil_cannot_read_file
0x1771b166	tcl_s_unixutil_bad_file_id
0x1771b167	tcl_s_unixutil_file_not_open
0x1771b168	tcl_s_unixutil_file_not_open_writing
0x1771b169	tcl_s_unixutil_file_not_open_reading
0x1771b16a	tcl_s_tclutil_list_ele_in_braces
0x1771b16b	tcl_s_tclutil_list_ele_in_quotes
0x1771b16c	tcl_s_tclutil_unmatch_open_brace
0x1771b16d	tcl_s_tclutil_unmatch_open_quote
0x1771b16e	tcl_s_tclutil_internal_err_splitlist
0x1771b16f	tcl_s_tclutil_bad_index
0x1771b170	tcl_s_tclutil_reg_compile_err

Message Number	Symbolic Name
0x1771b171	tcl_s_tclutil_reg_match_err
0x1771b172	tcl_s_tclutil_improp_val_prec
0x1771b173	tcl_s_tclregexp_null_arg
0x1771b174	tcl_s_tclregexp_too_big
0x1771b175	tcl_s_tclregexp_out_of_space
0x1771b176	tcl_s_tclregexp_too_many_bra
0x1771b177	tcl_s_tclregexp_unmatch_br
0x1771b178	tcl_s_tclregexp_junk_end
0x1771b179	tcl_s_tclregexp_op_can_be_empty
0x1771b17a	tcl_s_tclregexp_nested_ops
0x1771b17b	tcl_s_tclregexp_invalid_squ_range
0x1771b17c	tcl_s_tclregexp_unmatch_squ_bra
0x1771b17d	tcl_s_tclregexp_internal_urp
0x1771b17e	tcl_s_tclregexp_follows_nothing
0x1771b17f	tcl_s_tclregexp_trailing_backslash
0x1771b180	tcl_s_tclregexp_int_disaster
0x1771b181	tcl_s_tclregexp_null_parameter
0x1771b182	tcl_s_tclregexp_corrupted_pgm
0x1771b183	tcl_s_tclregexp_mem_corruption
0x1771b184	tcl_s_tclregexp_corrupted_ptr
0x1771b185	tcl_s_tclregexp_internal_foulup
0x1771b189	tcl_s_tclregexp_corrupted_opcode
0x1771b18e	tcl_s_tclvar_isnt_array
0x1771b196	tcl_s_tclvar_var_already_exists
0x1771b198	tcl_s_tclvar_illegal_search_id
0x1771b199	tcl_s_tclvar_search_id_var

Message Number	Symbolic Name
0x1771b19a	tcl_s_tclvar_illegal_search
0x1771b19b	tcl_s_tclvar_no_such_var
0x1771b19c	tcl_s_tclvar_no_such_ele
0x1771b19d	tcl_s_tclvar_is_array
0x1771b19e	tcl_s_tclvar_need_array
0x1771b19f	tcl_s_tclvar_dangling_upvar
0x1771b1a0	tcl_s_multibyte_conv_failed
0x1771b1a1	tcl_s_single_multibyte_conv_failed
0x1771b1a2	tcl_s_wchar_conv_failed
0x177db001	exc_s_exception
0x177db003	exc_s_uninitexc
0x177db005	exc_s_illaddr
0x177db006	exc_s_exquota
0x177db007	exc_s_insmem
0x177db008	exc_s_nopriv
0x177db009	exc_s_normal
0x177db00a	exc_s_illinstr
0x177db00b	exc_s_resaddr
0x177db00c	exc_s_privinst
0x177db00d	exc_s_resoper
0x177db00e	exc_s_SIGTRAP
0x177db00f	exc_s_SIGIOT
0x177db010	exc_s_SIGEMT
0x177db011	exc_s_aritherr
0x177db012	exc_s_SIGSYS
0x177db013	exc_s_SIGPIPE

Message Number	Symbolic Name
0x177db014	exc_s_excpu
0x177db015	exc_s_exflsiz
0x177db016	exc_s_intovf
0x177db017	exc_s_intdiv
0x177db018	exc_s_ftovf
0x177db019	exc_s_ftdiv
0x177db01a	exc_s_ftund
0x177db01b	exc_s_decovf
0x177db01c	exc_s_subrng
0x177db01d	exc_s_illopc
0x177db01e	exc_s_illopn
0x177db01f	exc_s_illadr
0x177db020	exc_s_illtrp
0x177db021	exc_s_prvopc
0x177db022	exc_s_prvreg
0x177db023	exc_s_coproc
0x177db024	exc_s_badstk
0x177db025	exc_s_brkpt
0x177db026	exc_s_trace
0x177db027	exc_s_ftinv
0x177db028	exc_s_maperr
0x177db029	exc_s_accerr
0x177db02a	exc_s_adraln
0x177db02b	exc_s_adrerr
0x177db02c	exc_s_objerr
0x177db02d	exc_s_ftres

Message Number	Symbolic Name
0x177db032	cma_s_badparam
0x177db033	cma_s_bugcheck
0x177db035	cma_s_existence
0x177db036	cma_s_in_use
0x177db037	cma_s_use_error
0x177db038	cma_s_wrongmutex
0x177db039	cma_s_stackovf
0x177db03a	cma_s_nostackmem
0x177db03b	cma_s_notcmastack
0x177db03d	cma_s_unimp
0x177db03e	cma_s_inialrpro
0x177db03f	cma_s_defer_q_full
0x177db040	cma_s_signal_q_full
0x177db041	cma_s_alert_nesting
0x177db081	thd_s_malloc_failure
0x177db088	thd_s_internal_error
0x17e43001	uuidgen_st_failure
0x17e43002	uuidgen_st_cantopen
_____	DS_E_LOOPED_DETECTED
_____	DS_E_BAD_ARGUMENT
_____	DS_E_COMMUNICATIONS_PROBLEM
_____	DS_E_MISCELLANEOUS
_____	DS_E_ALIAS_PROBLEM
_____	DS_E_ALIAS_DEREFERENCING_PROBLEM
_____	DS_E_ATTRIBUTE_OR_VALUE_EXISTS
_____	DS_E_NOT_SUPPORTED

Message Number	Symbolic Name
_____	DS_E_CANNOT_ABANDON
_____	DS_E_MIXED_SYNCHRONOUS
_____	DS_E_INAPPROP_MATCHING
_____	DS_E_DIT_ERROR
_____	DS_E_BAD_CONTEXT
_____	DS_E_BAD_NAME
_____	DS_E_BAD_SESSION
_____	DS_E_BAD_WORKSPACE
_____	DS_E_CHAINING_REQUIRED
_____	EINVAL
_____	DS_E_AFFECTS_MULTIPLE_DSAS
_____	DS_E_NOT_ALLOWED_ON_NON_LEAF
_____	DS_E_TOO_MANY_OPERATIONS
_____	DS_E_TOO_MANY_SESSIONS
_____	ESRCH
_____	ENOMEM
_____	DS_E_ADMIN_LIMIT_EXCEEDED
_____	ENOTSUP
_____	EPERM
_____	EBUSY
_____	EDEADLK
_____	EAGAIN
_____	ERANGE
_____	DS_E_UNWILLING_TO_PERFORM
_____	DS_E_UNAVAILABLE
_____	DS_E_UNABLE_TO_PROCEED

Message Number	Symbolic Name
_____	DS_E_INVALID_REF
_____	DS_E_NO_SUCH_OPERATION
_____	DS_E_PROTECTION_REQUIRED
_____	DS_E_BUSY
_____	DS_E_OUT_OF_SCOPE
_____	DS_E_BAD_CLASS
_____	DS_E_CONSTRAINT_VIOLATION
_____	DS_E_MISSING_TYPE
_____	DS_E_UNDEFINED_ATTRIBUTE_TYPE
_____	DS_E_INVALID_ATTRIBUTE_SYNTAX
_____	DS_E_INVALID_ATTRIBUTE_VALUE
_____	DS_E_INAPPROP_AUTHENTICATION
_____	DS_E_OBJECT_CLASS_MOD_PROHIB
_____	DS_E_NOT_ALLOWED_ON_RDN
_____	DS_E_OBJECT_CLASS_VIOLATION
_____	DS_E_NAMING_VIOLATION
_____	DS_E_ENTRY_EXISTS
_____	DS_E_TIME_LIMIT_EXCEEDED
_____	DS_E_TOO_LATE
_____	DS_E_NO_INFO
_____	DS_E_UNAVAILABLE_CRIT_EXT
_____	DS_E_INVALID_CREDENTIALS
_____	DS_E_INSUFFICIENT_ACCESS_RIGHTS
_____	DS_E_INVALID_SIGNATURE
_____	DS_E_NO_SUCH_ATTRIBUTE_OR_VALUE
_____	DS_E_NO_SUCH_OBJECT

Appendix B

Message Text and Symbolic Names

The table in this appendix provides a cross-reference between the text of a message and its symbolic name. If you have only the text to go by, look up that text in the following listing to find the symbolic name. You can then look in Appendix A, which contains a cross-reference of message numbers and symbolic names, to find the symbolic name.

Message Text	Symbolic Name
()successfully logged in.	KDDS22001-I
Adding %s entry for: %s %dn	pwd_imp_msg_add_entry
Adding %s entry for: %s (generate-UNIX-id)n	pwd_imp_msg_add_entry_ gen_unix_id
- Authentication failure	pwd_imp_err_auth
?+* follows nothing	tcl_s_tclregexp_follows_nothing
Import %s: n	pwd_imp_msg_import
*+ operand could be empty	tcl_s_tclregexp_op_can_be_empty

Message Text	Symbolic Name
The group (%s)exists in the registry with this id.n	pwd_imp_err_group_conflict
%-12s Trustee is [%s]	KDDS23200-I
%1\$s	NIDL_NEWUUID
%1\$s requires the %2\$s command line option	NIDL_REQCMDOPT
%1\$sError messages may be incorrect	NIDL_NLSWRONG
%1\$sNLS message catalog version mismatch in "%2\$s", Expected: "%3\$lu", Actual: "%4\$s"	NIDL_NLSCATVER
3077	NIDL_MESSAGE_VERSION
A [%1\$s] parameter must have the [%2\$s] attribute	NIDL_PRMDEPATTR
A address not mapped to object exception has been raised	exc_s_maperr
A bad argument was supplied.	DS_E_BAD_ARGUMENT
A bad stack exception has been raised	exc_s_badstk
A bad system call exception has been raised	exc_s_SIGSYS
A bit field specification can be applied only to simple, integral types	NIDL_BFINTTYPE
A broken pipe exception has been raised	exc_s_SIGPIPE
A call to dce_svc_debug_routing has failed,	GDS_S_DBG_ROUTING_ERR
A call to dce_svc_routing has failed,	GDS_S_ROUTING_ERR
A call to dce_svc_routings has failed,	GDS_S_ROUTINGS_ERR
A call to execv has failed, errno = %d.	GDS_S_EXEVCV_ERR
A call to fork has failed, errno = %d.	GDS_S_FORK_ERR
A call to select has failed, errno = %d	GDS_S_SELECT_ERR

Message Text	Symbolic Name
A call to sigaction/signal has failed, signal = %d, errno = %d	GDS_S_SIGHDL_ERR
A call to system has failed, errno = %d.	GDS_S_SYSTEM_ERR
A call to wait has failed, errno = %d.	GDS_S_WAIT_ERR
A C-ISAM File could not be locked, iserrno = %d.	GDS_S_ISLOCK_ERR
A C-ISAM-index could not be added, iserrno = %d.	GDS_S_ISADDINDEX_ERR
A client side context handle has been incorrectly modified	rpc_s_ss_context_damaged
A command is required for trapping signals.	dcp_s_signal_trap_req_cmd
A command may not be specified for the '%s' action.	dcp_s_signal_takes_no_cmd
A communication error has occurred.	DS_E_COMMUNICATIONS_PROBLEM
A conformant field must be the last field in the structure	NIDL_CFMTFLDLAST
A conformant [v1_array] must also be varying	NIDL_SMALLCFMT
A co-processor exception has been raised	exc_s_coproc
A copy of the root directory not found in clearinghouse %s.	cds_s_server_rootlostevent
A CPU-time limit exception has been raised	exc_s_excpu
A credential cache entry could not be established.	gssdce_s_couldnt_get_mech_cred
A [cs_rtag] parameter must precede any [out] [cs_char] data in a parameter list	NIDL_TAGAFTDATA
A [cs_stag] parameter must precede any [in] [cs_char] data in a parameter list	NIDL_TAGBEFDATA

Message Text	Symbolic Name
A current stack was not allocated by thread library exception has been raised	cma_s_notcmastack
A [cxx_new] operation must return an interface pointer	NIDL_CONSTRUCTOR
A database inconsistency was detected.	GDS_S_DB_INCONSISTENT
A 'dced' name missing object name.	dcp_s_dhd_miss_objname
A decimal point overflow exception has been raised	exc_s_decovf
A DSA detected a loop within the directory.	DS_E_LOOPED_DETECTED
A failed malloc of a necessary internal data structure in the DCE Threads library has resulted in the termination of the program	thd_s_malloc_failure
A fatal internal error has occurred in DCE Threads.	cma_s_bugcheck
A fatal internal error has occurred in DCE Threads.	thd_s_internal_error
A File size limit exception has been raised	exc_s_exfilsiz
A [first_is] variable must be a small, short, or long integer	NIDL_FIRSTYPEINT
A floating point divide by zero exception has been raised	exc_s_ftdiv
A floating point overflow exception has been raised	exc_s_ftovf
A floating point overflow exception has been raised	exc_s_ftund
A ftok system call has failed (path =%s, key = %c, errno = %d).	GDS_S_FTOK_ERR
A [handle] binding parameter cannot contain a [%1\$s] type	NIDL_HANCTYPE

Message Text	Symbolic Name
A [handle] binding parameter must be [in] or [in,out]	NIDL_HANDLEIN
A handle_t as other than the first parameter requires a [transmit_as]	NIDL_HANFIRSTPRM
A handle_t binding parameter must be an [in] parameter	NIDL_HANPRMIN
A handle_t first parameter must not have [transmit_as] type	NIDL_HANXMITAS
A hyper constant type is not allowed	NIDL_HYPERCONST
A [last_is] variable must be a small, short, or long integer	NIDL_LASTYPEINT
A [length_is] variable must be a small, short, or long integer	NIDL_LENYPEINT
A line is too long in event class file %s	aud_s_line_too_long_in_class_file
A locked C-ISAM File could not be released or unlocked,	GDS_S_ISRELEASE_ERR
A logged data element could not be read from the logfile.	GST_LOGREAD_ERR
A lookup on parent directory %s failed.	cds_s_server_pathbrokenevent
A loop of softlinks exists for %s.	cds_s_server_possiblecycleevent
A 'mask_obj' entry and '-mask' option were both intentionally specified.	dcp_s_acl_mask_obj_specified
A [max_is] parameter must have the [in] attribute	NIDL_MAXINATTR
A [max_is] variable must be a small, short, or long integer	NIDL_MAXTYPEINT
A [maybe] operation cannot have [out] parameters or a function result	NIDL_MAYBEOUTPRM
A [min_is] parameter must have the [in] attribute	NIDL_MININATTR

Message Text	Symbolic Name
A [min_is] variable must be a small, short, or long integer	NIDL_MINTYPEINT
A miscellaneous error occurred	DS_E_MISCELLANEOUS
A msgctl system call has failed (command = %d, errno = %d).	GDS_S_MSGCTL_ERR
A msgget system call has failed (key = %d	GDS_S_MSGGET_ERR
A msgrcv system call has failed (errno = %d).	GDS_S_MSGRCV_ERR
A msgsnd system call has failed (errno = %d).	GDS_S_MSGSND_ERR
A no space currently available to process condition signal exception has been raised	cma_s_signal_q_full
A no space currently available to process interrupt request exception has been raised	cma_s_defer_q_full
A no space to create a stack exception has been raised.	cma_s_nostackmem
A nonencapsulated union cannot have a [represent_as] type	NIDL_NEUREPTYPE
A nonencapsulated union cannot have a [transmit_as] type	NIDL_NEUXMITYPE
A nonencapsulated union declaration must have a [switch_is] attribute	NIDL_NEUSWATTR
A nonencapsulated union type must have a [switch_type] attribute	NIDL_NEUSWTYPE
A Non-existent physical address exception has been raised	exc_s_adrerr
A nonlocal interface cannot import a local interface	NIDL_IMPORTLOCAL
A parameter must have either or both the [in] and [out] attributes	NIDL_PRMINOROUT

Message Text	Symbolic Name
A parameter with [%1\$s] cannot be passed by value	NIDL_PRMBYREF
A parameter with [%1\$s] must be an [out] parameter	NIDL_STSPRMOUT
A parameter with [%1\$s] must be of type error_status_t	NIDL_STSVARTYPE
A pipe cannot have a [transmit_as] type	NIDL_PIPEXMITAS
A previous security server software version change is still underway	sec_rgy_rep_sw_rev_outstanding
A principal name must be given.	gssdce_s_name_required
A privileged instruction exception has been raised	exc_s_privinst
A privileged opcode exception has been raised	exc_s_prvopc
A Privileged register exception has been raised	exc_s_privreg
A process breakpoint exception has been raised	exc_s_brkpt
A process trace exception has been raised	exc_s_trace
a proxy agent is required for secure transmission of data	sec_pwd_mgmt_proxy_req
A [ref] function result is not valid	NIDL_REFFUNRES
a replica has a propagation in progress	sec_rep_prop_in_progress
A replica of directory %s was in the wrong state %d.	cds_s_server_wrongstate
A [represent_as] type cannot be a nonencapsulated union	NIDL_NEUREPAS
A requested key type is not supported	sec_key_mgmt_e_key_unsupported
A required gss_buffer_t parameter was not supplied.	gssdce_s_no_buffer

Message Text	Symbolic Name
A required parameter was missing.	gssdce_s_param_required
A reserved addressing exception has been raised	exc_s_resaddr
A reserved operand exception has been raised	exc_s_resoper
A ROS-function failed (code = %d, class = %d, value = %d)	GDS_S_ROSFUFAILED_ERR
A secondary index has been created already on this database	CDS_GDB_SECONDARY
A semctl system call has failed (command = %d, errno = %d).	GDS_S_SEMCTL_ERR
A semget system call has failed (key = %d	GDS_S_SEMGET_ERR
A shmat system call has failed (errno = %d).	GDS_S_SHMAT_ERR
A shmctl system call has failed (command = %d, errno = %d).	GDS_S_SHMCTL_ERR
A shmget system call has failed (key = %d	GDS_S_SHMGET_ERR
A size attribute variable must not have a represent_as type	NIDL_SIZEVARREPAS
A size attribute variable must not have a transmit_as type	NIDL_SIZEVARXMITAS
A [size_is] or [max_is] attribute cannot be applied to a pointer to a [cs_char] type	NIDL_CSARRSYN
A [size_is] parameter must have the [in] attribute	NIDL_SIZEINATTR
A [size_is] variable must be a small, short, or long integer	NIDL_SIZETYPEINT
A skulk failed for directory %s: status = %ld.	cds_s_server_skulkfailedevent
A source IDL filename is required	NIDL_SRCFILEREQ

Message Text	Symbolic Name
A [string] array cannot have varying array attributes	NIDL_STRVARY
A structure field cannot be of a presented type for which the transmitted type is conformant	NIDL_FLDXMITCFMT
A subscript out of range exception has been raised	exc_s_subrng
A [switch_is] attribute is only valid on a nonencapsulated union	NIDL_SWATTRNEU
A [switch_is] variable must not have a [represent_as] type	NIDL_DISCRIMREPAS
A [switch_is] variable must not have a [transmit_as] type	NIDL_DISCRIMXMITAS
A [switch_type] attribute is only valid on a nonencapsulated union type	NIDL_SWTYPENEU
A threads library initialization is already in progress exception has been raised	cma_s_inialpro
A trace or breakpoint exception has been raised	exc_s_SIGTRAP
A translated transmittable type cannot contain [%1\$s] pointers	NIDL_XMITPTR
A [transmit_as] or [represent_as] type cannot be a conformant array	NIDL_XMITCFMTARR
A [transmit_as] transmitted type cannot contain a [%1\$s] type	NIDL_XMITCTYPE
A [transmit_as] type cannot be a nonencapsulated union	NIDL_NEUXMITAS
A type used in a [transmit_as] clause cannot have a [represent_as] type	NIDL_XMITASREP
A type with the [represent_as] attribute cannot be conformant	NIDL_TYPEREPCFMT

Message Text	Symbolic Name
A type with [transmit_as] cannot have other type attributes	NIDL_XMITTYPEATTRS
A UFS path was entered: The selected operation is good for LFS only	KDDS23016-W
A union discriminator type must be small, short, long, char, boolean, or enum	NIDL_UNIDISCTYP
A [unique] function result is not valid	NIDL_UNIQFUNRES
A unique ID could not be generated for a C-ISAM-File,	GDS_S_ISUNIQUEID_ERR
A 'uuid' cannot be specified when attempting to create an alias.	dcp_s_rgy_uuid_and_alias
A [v1_array] can be conformant or varying in first dimension only	NIDL_SMALLMULTID
A [v1_array] cannot have a conformant lower bound	NIDL_SMALLOPENLB
A [v1_string] must be an array of char with fixed bounds	NIDL_STRV1FIXED
A value was out of range.	pkc_s_asn_out_of_range
A write operation to NDS-configuration data base file '%s' failed (errno = %d)	GDS_S_NDS_WCONFO_ERR
A wrong 'dced' service has been requested.	dcp_s_dhd_wrong_service_req
A wrong mutex specified in condition wait exception has been raised	cma_s_wrongmutex
Abbreviation unknown - %s.	gc_t_omx_unknown_abbrev
'-abruptly' option not specified.	dcp_s_clock_set_need_abruptly
Access control information invalid at remote host	rpc_s_access_control_info_inv
Access denied for attempted operation	dts_s_nopriv
Access denied.n	CDSCP_ACC_DENIED

Message Text	Symbolic Name
Access error while file was being dumped.	KDDS11801-E
access mode must include either RDONLY, WRONLY, or RDWR	tcl_s_unixaz_access_mode_must_inc
access mode "%s" not supported by this system	tcl_s_unixaz_access_mode_not_supported
Access violation.	CDS_ACCESSVIOLATION
Account already exists (Registry Edit Kernel)	ek_err_acct_exists
Account description too long. Maximum description length is %d.	dcp_s_rgy_acct_desc_long
Account does not exist (Registry Edit Kernel)	ek_err_acct_does_not_exist
Account for %s doesn't exist. Should this be created ?	sec_lksm_create_acct
Account home name too long. Maximum home name length is %d.	dcp_s_rgy_acct_home_long
account is not allowed to use user-to-user protocol registration	sec_s_user_to_user_disabled
Account name is too long (Registry Edit Kernel)	ek_err_login_name_too_long
ACCOUNT NOT ADDED: (%s %s %s)n	pwd_imp_msg_add_acct_fail
account not valid for login	sec_login_s_acct_invalid
Account password not entered correctly.	dcp_s_rgy_acct_no_passwd
Account password too long. Maximum password length is %d.	dcp_s_rgy_acct_passwd_long
Account shell name too long. Maximum shell name length is %d.	dcp_s_rgy_acct_shell_long
Account's master_key version doesn't match old or new	sec_rs_mkey_actver_mismatch

Message Text	Symbolic Name
ACF attribute [cxx_delegate] is only valid for -lang cxx	NIDL_DELEGATENOTVAL
ACF attribute [cxx_lookup] is only valid for -lang cxx	NIDL_LOOKUPNOTVAL
ACF attribute [cxx_new] is only valid for -lang cxx	NIDL_NEWNOTVAL
ACF attributes in the IDL file, require the -app_config command line option	NIDL_ACFINIDL
ACF interface name %1\$s differs from IDL interface name %2\$s	NIDL_INTNAMDIF
ACL entry exists.	dcp_s_acl_entry_already_exists
ACL entry not found.	dcp_s_acl_entry_not_found
acl entry type not valid	sec_acl_invalid_entry_type
ACL file corrupt	svc_s_acl_corrupt
ACL file could not be opened	svc_s_acl_open_error
ACL file could not be read	svc_s_acl_read_error
ACL file could not be written	svc_s_acl_write_error
acl manager file open error	sec_acl_mgr_file_open_error
ACL manager name specified not found.	dcp_s_acl_mgr_not_found
acl manager type invalid	sec_acl_invalid_manager_type
acl manager type not recognized	sec_acl_unknown_manager_type
acl object not found	sec_acl_object_not_found
ACL object not specified.	dcp_s_acl_no_object
acl operation expected group_obj	sec_acl_expected_group_obj
acl operation expected user_obj	sec_acl_expected_user_obj
acl operation is read only	sec_acl_read_only
acl operation not implemented	sec_acl_not_implemented
acl operation unable to allocate memory	sec_acl_cant_allocate_memory

Message Text	Symbolic Name
acl server state doesn't support operation	sec_acl_server_bad_state
acl type not valid	sec_acl_invalid_acl_type
Acquire credentials failed for auth. mech. %d, nmessage	GDS_S_ACQU_CRED_ERR
Acquire_cred - Bad usage parameter	gss_s_ac_bad_usage
Acquire_cred - Inquire_net_info failed (%x)	gss_s_ac_ini_failed
Acquire_cred - Out of memory creating cred (pt1)	gss_s_ac_cred_nomem1
Acquire_cred - Out of memory creating cred (pt2)	gss_s_ac_cred_nomem2
Acquire_cred - Server_register_auth_info failed (%x)	gss_s_ac_reg_failed
Acronym %s cannot have unlimited recurrence.n	GDS_S_NAMAT_RECUR
Action cannot be performed by IDL Encoding Services	rpc_s_ss_bad_es_action
Active soundex algorithm: %s,	GDS_S_BAD_SOUNDEX
Add memberships from imported group file.n	pwd_imp_inf_add_members
Add to propagation queue failed.	sec_rs_log_propq_add_fail
add_cell_alias: Could not create child pointer in parent directory: status = %ld.	cds_s_server_aliaschild
add_cell_alias: Could not create soft link in place of previous child pointer in parent directory: status = %ld	cds_s_server_aliascreatesl
add_cell_alias: Could not delete old child pointer in parent directory: status = %ld.	cds_s_server_aliasdelchild

Message Text	Symbolic Name
add_cell_alias: Previous error occurred, failed to back out and delete the child pointer in the parent directory: status = %ld.	cds_s_server_aliasbackoutchild
Added entry %s to X.500	cds_s_addcell_success
Adding two absolute timestamps is not allowed.	dcp_s_utc_add_two_abs
Administration process terminated due to an unexpected error.	KDDS02032-E
Administration threads successfully initialized.	KDDS11640-I
Administration threads successfully terminated.	KDDS11643-I
Administration utility cannot be executed.	KDDS10001-E
Administration utility cannot run on this NetWare version.	KDDS10028-E
Administration utility detected self-contradiction: error	KDDS10030-E
Administrator has invalid DCE account or password.	KDDS11661-E
AdminThread detected timeout. AdminThread will be restarted.	KDDS11050-I
AdvertiseService failed: error code xxx.	KDDS11010-E
Agent administrator is not registered with master key file.	KDDS01302-E
Agent error.	KDDS02620-E
Agent failed to access master key.	KDDS11223-I
Agent failed to get memory. xxx (yyy)	KDDS02500-E
Agent failed to get shared memory.	KDDS02520-E
Agent has reported error: error code xxx.	KDDS11663-E

Message Text	Symbolic Name
Agent information contains invalid data. The invalid data will	KDDS10024-W
Agent is already stopped.	KDDS01102-E
Agent is already up and running.	KDDS02005-E
Agent is being initialized. No command accepted.	KDDS01103-E
Agent is being terminated. No command accepted.	KDDS01104-E
Agent is not in root-mode.	KDDS11662-E
Agent is not registered with gateway.	KDDS11206-E
Agent is not running.	KDDS22416-W
Agent is not up and running.	KDDS11217-E
Agent is running. Cannot execute setdfakey command.	KDDS01307-E
Agent is taking emergency exit. No command accepted.	KDDS01105-E
Agent options cannot be used.	KDDS10005-E
Agent successfully initialized.	KDDS02001-I
Agent successfully terminated.	KDDS02004-I
Agent terminated due to an unexpected error. (xxx)	KDDS02007-E
Agent will be killed.	KDDS11809-I
Agent will be terminated in n sec.	KDDS02002-I
Agent will be terminated in xxx sec.	KDDS11808-I
Agent will take an emergency exit.	KDDS02003-I
Algorithm method required by the specified algorithm not in algorithm chooser	sec_s_bsafe_method_not_in_chooser

Message Text	Symbolic Name
Algorithm object has not been set with algorithm info	sec_s_bsafe_algorithm_not_set
(a)lias to existing entry, (g)enerate id automatically	pwd_imp_inf_choices
All non-zombie replicas are either busy or have received the specified update	sec_rgy_rep_prop_busy
All non-zombie replicas have received the specified update	sec_rgy_rep_prop_complete
All users have been logged out.	KDDS11222-I
All users will be logged out.	KDDS11221-I
Allocated new cred-id: %ld	gss_s_alloc_cred_allocated
Allocation of %d byte failed.	GDS_S_NOMEMORY
Allocation of IPC-resources failed	GDS_S_IPCGETRES_ERR
Alloc_cred - Couldn't invent cred-id	gss_s_alloc_cred_nonew
Alloc_cred - out of memory	gss_s_alloc_cred_nomem
Alloc_ctx - out of memory	gss_s_alloc_ctx_nomem
Already at root.	pkc_s_x500_at_root
Already listening	rpc_s_already_listening
Already logged in to DCE	KDDS22006-W
Already registered	rpc_s_already_registered
Alternative authentication method required	rpc_s_auth_method
Ambiguous ACL manager name.	dcp_s_rgy_ambig_acl_mgr_name
Ambiguous argument '%s':	dcp_s_ambiguous_arg
Ambiguous intercell action.	dcp_s_rgy_ambig_intercell_action
Ambiguous operation %s.	gc_i_ambiguous_operation
Ambiguous option %s.	gc_t_ambiguous_option
Ambiguous trigger type.	dcp_s_rgy_ambig_trigger_type
An address exception has occurred	exc_s_exception

Message Text	Symbolic Name
An alias is dereferenced that names an object that does not exist.	DS_E_ALIAS_PROBLEM
An alias is encountered where an alias is not permitted.	DS_E_ALIAS_DEREFERENCING_PROBLEM
An 'any' attribute requires both a value and an encoding type.	dcp_s_rgy_era_type_and_value
An arithmetic trap exception has been raised	exc_s_aritherr
An arm of a union cannot be or contain a [ref] pointer	NIDL_ARMREFPTR
An arm of a union cannot be or contain a [unique] pointer	NIDL_ARMUNIQUEPTR
An array with [%1\$s] base type cannot have the [ptr] or [unique] attributes	NIDL_ARRPTRUNIQ
An array with a pointer attribute is valid only as a parameter	NIDL_ARRPTRPRM
An attempt is made to add an attribute or value that already exists.	DS_E_ATTRIBUTE_OR_VALUE_EXISTS
An attempt is made to use optional	DS_E_NOT_SUPPORTED
An attempt was made to abandon an operation. It failed.	DS_E_CANNOT_ABANDON
An attempt was made to start a	DS_E_MIXED_SYNCHRONOUS
An attempt was made to use an	DS_E_INAPPROP_MATCHING
An attempted stack overflow exception has been raised	cma_s_stackovf
An attribute value is absent.	gc_t_om_not_present
An attribute variable cannot be an indirect field reference	NIDL_ATTRVALIND
An object specific exception has been raised	exc_s_objerr

Message Text	Symbolic Name
An element of the cache update message is longer than	GDS_S_LARGE_CUPMSG_ELEMENT
An emulation trap exception has been raised	exc_s_SIGEMT
An encapsulated union member cannot have the [%1\$s] attribute	NIDL_EUMEMATTR
An entry in the asn1_attr file with illegal format was	GDS_S_ILL_ASN1_ATTR_ENTRY_ERR
An entry with the specified offset could not be found.	GST_OFFSET_ERR
An environment variable %s is missing.	GDS_S_ENVVAR_ERR
An error occured calling a CDS API function.	CDS_ERROR
An error occurred while creating the time service	dts_s_error_create
An error occurred while delegating access rights	gssdce_s_delegation_error
An error was detected in a retrieved ACL.	pks_s_bad_acl
An illegal instruction exception has been raised	exc_s_illinstr
An illegal opcode exception has been raised	exc_s_illopc
An illegal operand exception has been raised	exc_s_illopn
An illegal operand exception has been raised	exc_s_illadr
An illegal routing specification character %c was	GDS_S_BAD_ROUTE_SPEC
An illegal trap exception has been raised	exc_s_illtrp

Message Text	Symbolic Name
An [implicit_handle] variable must either be of type handle_t or have the handle attribute	NIDL_IMPHANVAR
An [in] or [in,out] union must have an [in] discriminator	NIDL_DISCRIMIN
An inconsistency is detected in the DIT.	DS_E_DIT_ERROR
An inconsistent schema object was detected.n	GDS_S_SCH_INCONSISTENT
An [in,out] or [out] union must have an [out] discriminator	NIDL_DISCRIMOUT
An input file contains insufficient information.	GDS_S_INCONS_INSTREAM
An [in,size_is] parameter for an [out,cs_char] array cannot be used for other array attributes	NIDL_ATTRROUTCFMTCS
An instance of the specified 'void' attribute already exists.	dcp_s_rgy_era_void_already_exists
An insufficient privilege exception has been raised	exc_s_nopriv
An insufficient memory exception has been raised	exc_s_insfmem
An insufficient quota exception has been raised	exc_s_exquota
An insufficient schema object record was detected.n	GDS_S_SCH_INSUFFICIENT
An integer divide by zero exception has been raised	exc_s_intdiv
An interger overflow exception has been raised	exc_s_intovf
An internal list is out of order. Thread will exit.	cds_s_gda_inorder

Message Text	Symbolic Name
An invalid address alignment exception has been raised	exc_s_adraln
An invalid address exception has been raised	exc_s_illaddr
An invalid audit record descriptor was used.	aud_s_invalid_record_descriptor
An invalid audit trail descriptor was used	aud_s_invalid_trail_descriptor
An invalid context argument was supplied.	DS_E_BAD_CONTEXT
An invalid conversion character is found in message 0x%lx.	GST_CONVCHAR_MISSING
An invalid floating point operation exception has been raised	exc_s_ftinv
An invalid line %s was found in event class file %s	aud_s_invalid_line_in_class_file
An invalid name argument was supplied.	DS_E_BAD_NAME
An Invalid parameter exception has been raise	cma_s_badparam
An invalid permissions exception has been raised	exc_s_accerr
An invalid pointer supplied as a function argument.	gc_t_om_pointer_invalid
An invalid registry checkpoint time was specified.	dcp_s_rgy_checkpoint_bad_cpi
An invalid session argument was supplied.	DS_E_BAD_SESSION
An invalid state was returned from the server.	dcp_s_aud_show_state_invalid
An invalid storage strategy was returned from the server.	dcp_s_aud_show_stostrategy_invalid
An invalid value (%s) was entered for the attribute %sn	dts_s_invalid_attr_value

Message Text	Symbolic Name
An invlaid workspace argument was supplied.	DS_E_BAD_WORKSPACE
An IOT exception has been raised	exc_s_SIGIOT
An IPC-association table overflow was detected	GDS_S_Ioverflow_ERR
An Object referenced does not currently exist exception has been raised	cma_s_existence
An object referenced is already in use exception has been raised	cma_s_in_use
An object with the specified name already exists (Registry Edit Kernel)	ek_err_name_exists
An object with the specified Unix id already exists (Registry Edit Kernel)	ek_err_unix_num_exists
An object with the specified uuid is already defined (Registry Edit Kernel)	ek_err_id_exists
An operation inappropriate for specified object exception has been raised	cma_s_use_error
An operation result cannot be a pipe	NIDL_OPRESPIPE
An operation with [%1\$s] must return a value of type error_status_t	NIDL_STSRETVAl
An [out] conformant array must be a top-level parameter or under a non-[ref] pointer	NIDL_OUTCFMTARR
An [out] parameter or operation result cannot contain [unique] pointers	NIDL_OUTUNIQUE
An [out,ptr] parameter is not valid	NIDL_OUTPTRPRM
An [out,unique] parameter is not valid	NIDL_OUTUNIQPRM
An ROS-association table overflow was detected	GDS_S_Roverflow_ERR
An unexpected abstract syntax identifier was detected	GDS_S_INVABSID_ERR

Message Text	Symbolic Name
An unexpected error occurred to gateway or agent (nnn)	KDDS23140-E
An unexpected receive buffer type or length was detected	GDS_S_INVRCVBUFFER_ERR
An unimplemented feature exception has been raised	cma_s_unimp
An uninitialized exception has been raised	exc_s_uninitexc
An unknown application context was detected	GDS_S_ACONTEXT_ERR
An unrecoverable error occurred in Global Directory Agent.	cds_s_gda_eb
Another replica with the same name or id exists	sec_rgy_rep_doppelganger
Area code of E.163-address missing	GDS_S_NDS_E163AC_ERR
argument to math function didn't have numeric value	tbl_s_expr_arg_math_func_non_numeric
Array attribute variable cannot be used for both [cs_char] and non-[cs_char] arrays	NIDL_ARRATTRSHR
Array elements cannot be conformant arrays or conformant structures	NIDL_ARRELEMCFMT
Array elements cannot be context handles	NIDL_ARRELEMCTX
Array elements cannot be of type handle_t	NIDL_HANARRELEM
Array elements cannot be pipes	NIDL_ARRELEMPIPE
Array function results are not allowed	NIDL_ARRFUNRES
Array size information required for %1\$s	NIDL_ARRSIZEINFO
Arrays can be conformant in the first dimension only	NIDL_ARRCFMTDIM
Arrays can be varying in the first dimension only	NIDL_ARRVARYDIM

Message Text	Symbolic Name
Arrays of [%1\$s] type can only use the [size_is] and [length_is] array attributes	NIDL_ARRTYPATTR
Arrays of [%1\$s] type cannot be multidimensional	NIDL_ARRMULTID
Arrays of nonencapsulated unions are not allowed	NIDL_NEUARRAY
Arrays of strings are not allowed	NIDL_STRARRAY
Arrays with a nonzero lower bound are not yet supported	NIDL_NYSNONZEROLB
Arrays with [transmit_as] cannot be conformant or varying	NIDL_ARRXMITOPEN
Assertion check failed at line %d file %s: B-tree is non null	cds_s_dbcmp_treenotnull_a
Assertion check failed at line %d file %s: (End) Compression context buffer pointer is	cds_s_dbcmp_nullctxend_a
Assertion check failed at line %d file %s: (Finish) Compression context buffer pointer is	cds_s_dbcmp_nullctxfinish_a
Assertion check failed at line %d file %s: Null file pointer.	cds_s_dbcmp_nullfp_a
Assertion check failed at line %d file %s: (Start) Compression context buffer pointer is	cds_s_dbcmp_nullctxstart_a
Assertion check failed at line %d file %s: Unknown level for the compression context	cds_s_dbcmp_levelbad_a
Assertion check failed at line %d file %s: (Write) Compression context buffer pointer is	cds_s_dbcmp_nullctxwrite_a

Message Text	Symbolic Name
Assertion check failed line %d file %s: Last node of level-1 work bucket flushed to disk was non null	cds_s_dbcmp_nonnullptr_a
Assertion check failed line %d file %s: Unable to compress level-1 data.	cds_s_dbcmp_1_a
Assertion check failed line %d file %s: Unable to return free space to bucket	cds_s_dbcmp_toobig_a
Assertion failed!	tcl_s_hist_hist_assert_failed
Assertion "%s" failed in "%s"file> line <%d	svc_s_assertion_failed
Association group maximum exceeded	rpc_s_assoc_grp_max_exceeded
Association group not found	rpc_s_assoc_grp_not_found
Association shutdown	rpc_s_assoc_shutdown
Asynchronous or General cancelability was on.	_____
Asynchronous or General cancelability was off.	_____
at least one control permission bit required on acl	sec_acl_no_owner
At least one of the options '-add' or '-remove' is required.	dcp_s_audfilter_modify_need_option
Attempt to acquire INIT cred by name	gss_s_ac_named_init
Attempt to add current key version detected	sec_rsdb_acct_add_curkey
Attempt to extract creds from no-cred context	gss_s_xcc_no_creds
Attempt to extract PAC from non-PAC-based context	gss_s_xps_no_pac
Attempt to free NULL name in gss_release_name	gss_s_reln_null_name

Message Text	Symbolic Name
Attempt to initialize slave	sec_prop_send_init_slave
Attempt to modify a read-only attribute	dts_s_read_only
Attempt to propagate delete replica %s	sec_prop_send_delete_rep
Attempted to add membership to unknown group.n	pwd_imp_err_unknown_group
Attempted to add membership with unknown principal.n	pwd_imp_err_unknown_princ
Attempting to bind to a registry site using file %s	sec_site_bind_default
Attempting to bind to an arbitrary registry site in cell %s	sec_site_cell_bind_start
Attempting to bind to registry site %s	sec_site_bind_start
Attempting to check slave initialization	sec_prop_chk_prop_slave_init
Attempting to checkpoint registry database	sec_rgy_checkpoint
Attempting to create a replica of registry database for cell %s	sec_crdb_cr_rep_db
Attempting to create master registry database for cell %s	sec_crdb_cr_master_db
Attempting to export bindings to %s	sec_rs_ns_bind_export
Attempting to import next RPC binding from %s	sec_ns_import_next
Attempting to import RPC bindings from %s	sec_ns_import_begin
Attempting to initialize server database	sec_rgy_db_init
Attempting to rebind to an alternate registry site	sec_site_rebind_start
Attempting to rebind to an alternate registry site and retrying operation	sec_rca_site_rebind
Attempting to refresh context (%s)	sec_rs_login_refresh

Message Text	Symbolic Name
Attempting to replay the log file	sec_rs_log_replay
Attempting to start propagation threads in a slave	sec_prop_not_master
Attempting to use credentials belonging to another user	rpc_s_helper_wrong_user
Attribute [%1\$s] cannot be applied to a void * type	NIDL_ATTRPTRVOID
Attribute cannot be used more than once	NIDL_ATTRUSEMULT
Attribute [context_handle] only applies to void * types	NIDL_CTXPTRVOID
attribute instance already exists	sec_attr_inst_exists
attribute instance not found	sec_attr_inst_not_found
attribute name already exists	sec_attr_name_exists
Attribute name contains an illegal character (Registry Edit Kernel)	ek_err_attr_bad_name_chars
Attribute name too long (Registry Edit Kernel)	ek_err_attr_name_too_long
Attribute 'oldpassphrase' and/or 'newpassphrase' not entered.	dcp_s_rgy_pk_missing_eitherpass
Attribute %s missing for %s.	cds_s_server_attributemissing
attribute type id already exists	sec_attr_type_id_exists
Attribute [unique] is not yet supported	NIDL_NYSUNIQUE
attribute value attr_set has bad format	sec_attr_val_attr_set_bad
attribute value bytes/confidential_bytes/i18n_data has bad format	sec_attr_val_bytes_bad
Attribute value is illegal.	dcp_s_cds_ill_attr_val
attribute value is not unique	sec_attr_not_unique
attribute value printstring has bad format	sec_attr_val_printstring_bad
attribute value string array has bad format	sec_attr_val_string_array_bad

Message Text	Symbolic Name
Attribute-value syntax not permitted.	gc_t_om_wrong_value_syntax
Audit action bit set %lx is not within %lx	aud_s_invalid_action_bit_set
Audit Actions: %lx	aud_s_action_bit_set
Audit client's esl mutex initialization failed.	aud_s_client_esl_mutex
Audit commit failed	aud_s_cannot_audit
Audit condition bitset %lx is not within %lx or it contains no bit	aud_s_invalid_condition_bit_set
Audit Conditions: %lx	aud_s_condition_bit_set
Audit daemon serving RPC number %d	aud_s_rpc_count
Audit event class list is empty	aud_s_empty_event_class_list
Audit trail file %s and its companion index file %s are ready to be backed-up.	aud_s_trl_file_size_limit
Audit trail file '%s' is corrupt.	dcp_s_aud_trail_file_corrupt
Audit trail store strategy is invalid	aud_s_trl_invalid_stostrategy
Auditd unable to get current login context.	aud_s_dmn_cannot_get_context
Auditd unable to get machine principal login context.	aud_s_dmn_cannot_get_mp_context
Auditd unable to release current login context.	aud_s_dmn_cannot_release_context
Authentication authorization mismatch	rpc_s_authn_authz_mismatch
Authentication challenge malformed	rpc_s_authn_challenge_malformed
Authentication field too long for implementation	rpc_s_auth_field_toolong
Authentication key version not available	rpc_s_auth_badkeyver
Authentication message out of order	rpc_s_auth_badorder
Authentication message stream modified	rpc_s_auth_modified
Authentication protocol version mismatch	rpc_s_auth_badversion

Message Text	Symbolic Name
Authentication request is a replay	rpc_s_auth_repeat
authentication service invalid	sec_priv_s_invalid_authn_svc
Authentication service key not available	rpc_s_auth_nokey
Authentication ticket expired	rpc_s_auth_tkt_expired
Authentication ticket is not for destination	rpc_s_auth_not_us
Authentication ticket not yet valid	rpc_s_auth_tkt_nyv
Authentication ticket/authenticator do not match	rpc_s_auth_badmatch
authorization protocol unsupported by authentication protocol.	sec_s_authz_unsupp
authorization service invalid	sec_priv_s_invalid_authz_svc
authz service cannot supply the requested credentials	sec_cred_s_authz_cannot_comply
bad acl syntax	sec_acl_bad_acl_syntax
bad argument	sec_rgy_rep_bad_arg
Bad argument for %s option	sec_secd_cl_bad_arg
Bad argument given to -w switch: %s	dts_s_routing_switch
Bad argument type '%d' in '%s'.	dcp_s_bad_arg_type
bad binding	sec_rgy_rep_bad_binding
Bad binding handle	dced_s_bad_binding
bad buffer (either message or token) in gss_sign	gss_s_sign_bad_buffer
Bad buffer in call to gss_verify	gss_s_vfy_bad_buffer
Bad CDS Advertisement received	cds_s_adver_badadver
Bad checksum in process_context_token	gss_s_pct_inv_cksum
bad completion code "%s": must be ok, error, return, break, continue, or an integer	tcl_s_cmdmz_bad_comp_code_ok_err_ret_brk
Bad data in cache version file %s.	cds_s_cache_badversion

Message Text	Symbolic Name
Bad data in shmid file %s, data: %s	cds_s_cache_badheaderid
bad database version	sec_rgy_rep_bad_db_version
bad field specifier "%c"	tcl_s_cmdah_bad_field_spec
bad file identifier "%s"	tcl_s_unixutil_bad_file_id
Bad format in IEEE 802 address file	utils_s_802_addr_format
Bad header size in cache file %s	cds_s_cache_badcacheheader
Bad indefinite-length value.	pkc_s_asn_bad_indefinite
bad index "%s": must be integer or "end"	tcl_s_tclutil_bad_index
bad information in sec_acl_key	sec_acl_bad_key
Bad input. Try again	sec_lksm_bad_input
bad level "%s"	tcl_s_cmdil_bad_level
bad level "%s"	tcl_s_proc_bad_level
Bad manager type parameter to dce_acl_register_object_type()	acl_s_bad_manager_type
Bad mechanism-type in gss_display_status	gss_s_ds_bad_mech
Bad name . %s	sec_rs_login_bad_name
bad operations "%s": should be one or more of rwu	tcl_s_cmdmz_bad_opr_more_rwu
Bad or invalid dce attr binding handle	dce_attr_s_bad_binding
Bad or invalid dce attr cursor	dce_attr_s_bad_cursor
Bad or invalid dce attr name(s)	dce_attr_s_bad_name
Bad or invalid dce attr schema object name(s)	dce_attr_s_bad_schema_name
Bad or wrong argument: %d	pks_s_invalid_arg_1_parm
Bad or wrong arguments	pks_s_invalid_arg
Bad or wrong arguments	dced_s_invalid_arg
Bad Parameter.	pkc_s_asn_bad_param

Message Text	Symbolic Name
Bad Parameter.	pkc_s_bad_param
bad parameter for acl operation	sec_acl_bad_parameter
bad parameter for schema or attribute operation	sec_attr_bad_param
Bad propagation type.	sec_prop_bad_type
bad propagation type after prop operation	sec_rgy_rep_bad_prop_type
Bad 'pwdexpdate' date string supplied.	dcp_s_rgy_bad_expdate
Bad relative time string supplied.	dcp_s_rgy_bad_reftime_string
Bad rgy database state.	sec_rgy_bad_rgy_db
Bad routing specification	svc_s_bad_routespec
Bad routing specification.	dcp_s_log_inv_routing
bad scan conversion character "%c"	tcl_s_cmdmz_bad_scan_conv_char
bad search mode "%s": must be -exact, -glob, or -regexp	tcl_s_cmdil_bad_search_mode
bad security context handle	sec_rgy_bad_handle
Bad signal trap formatting specification '%s', expected one of '%%' or '045S'.	dcp_s_bad_signal_format
Bad size for policy data	sec_rsdb_bad_policy_data
bad software version	sec_rgy_rep_bad_sw_vers
Bad specification %s in DSA configuration file.n	GDS_S_BAD_DSACONF
bad state	sec_rgy_rep_bad_state
Bad time	pkc_s_bad_time
Bad time string supplied.	dcp_s_rgy_bad_time_string
Bad token type (%2.2x %2.2x) in gss_accept_sec_ctx	gss_s_ac_bad_tok_type
Bad token type in gss_verify	gss_s_vfy_bad_tok_type
Bad UUID version	uuid_s_bad_version

Message Text	Symbolic Name
Bad version of log file	sec_rs_log_bad_version
Base propagation sequence in the log header : %s	sec_rs_log_base_prop_seq
BeginThreadGroup failed: error code xxx.	KDDS11007-E
BER of value encoding too long (%d bytes)	gss_s_wrap_ber_long
Bind lookups disabled.	cds_s_gda_nodns
Bindery access error: error code xxx.	KDDS10016-E
binding error on acl operation	sec_acl_bind_error
Binding import from namespace fails: %s	dts_s_binding_import
Binding incomplete (no object ID and no endpoint)	rpc_s_binding_incomplete
Binding type of extended attribute is unknown.	dcp_s_rgy_era_unknown_binding_type
Binding vector full	rpc_s_binding_vector_full
Bindings length wrong (should be %d, was %d)	gss_s_ac_hash_bad_length
bogus interpreter argument!	tcl_s_test_bogus_interpreter
Bogus password pickle	sec_rs_pwd_bogus_pickle
Both the options %s and %s specified.	sec_crdb_cl_dup_option
BSAFE2: Algorithm is not properly initialized	sec_s_bsafe_not_initialized
BSAFE2: Algorithm object has already been set with algorithm info	sec_s_bsafe_algorithm_already_set
BSAFE2: Algorithm object has not been initialized	sec_s_bsafe_algorithm_not_initialized
BSAFE2: Cryptographic hardware error	sec_s_bsafe_hardware
BSAFE2: Data block exceeds 32,767 bytes	sec_s_bsafe_over_32k

Message Text	Symbolic Name
BSAFE2: decryption failure	sec_s_bsafe_decryption_failure
BSAFE2: Generic data error	sec_s_bsafe_data
BSAFE2: Insufficient memory	sec_s_bsafe_alloc
BSAFE2: Invalid algorithm info format	sec_s_bsafe_algorithm_info
BSAFE2: Invalid algorithm object	sec_s_bsafe_algorithm_obj
BSAFE2: Invalid algorithm object for the random algorithm	sec_s_bsafe_random_obj
BSAFE2: Invalid exponent length for public exponent in key pair generation	sec_s_bsafe_exponent_len
BSAFE2: Invalid format for input data	sec_s_bsafe_input_data
BSAFE2: Invalid internal memory object	sec_s_bsafe_memory_obj
BSAFE2: Invalid key info format	sec_s_bsafe_key_info
BSAFE2: Invalid key length	sec_s_bsafe_key_len
BSAFE2: Invalid key object	sec_s_bsafe_key_obj
BSAFE2: Invalid length for input data	sec_s_bsafe_input_len
BSAFE2: Invalid modulus length in public or private key	sec_s_bsafe_modulus_len
BSAFE2: Invalid signature	sec_s_bsafe_signature
BSAFE2: key modulus length should be between 256 - 1024	sec_s_bsafe_mod_size_out_of_range
BSAFE2: Key object has already been set with key info	sec_s_bsafe_key_already_set
BSAFE2: Key object has not been set with key info	sec_s_bsafe_key_not_set
BSAFE2: Operation was canceled by the surrender function	sec_s_bsafe_cancel
BSAFE2: Output data is larger than supplied buffer	sec_s_bsafe_output_len

Message Text	Symbolic Name
BSAFE2: Public exponent in key pair generation is not allowed to be even	sec_s_bsafe_exponent_even
BSAFE2: Random algorithm has not been initialized	sec_s_bsafe_random_not_initialized
BSAFE2: Unknown bsafe error	sec_s_bsafe_unknown_error
BSAFE2: Unknown operation for a key info type	sec_s_bsafe_key_operation_unknown
BSAFE2: Unknown operation for an algorithm or algorithm info type	sec_s_bsafe_alg_operation_unknown
BSAFE2: Unsupported operation requested	sec_s_bsafe_not_supported
BSAFE2: Update called an invalid number of times for inputting data	sec_s_bsafe_input_count
BSAFE2: Update called an invalid number of times for outputting data	sec_s_bsafe_output_count
BSAFE2: Wrong type of algorithm info	sec_s_bsafe_wrong_algorithm_info
BSAFE2: Wrong type of key info	sec_s_bsafe_wrong_key_info
Buffer not usable by IDL Encoding Services	rpc_s_ss_bad_buffer
Buffer too small	CDS_CL_READ
Buffer too small	sec_buf_too_small
Cache corrupt: Bad cache version number or name.	cds_s_cache_version_a
Cache entry not found.n	pwd_imp_err_cache_e_not_found
Cache header corrupt: Bad cache header address.	cds_s_cache_header_a
Cache header corrupt: Bad cache header backward link.	cds_s_cache_blink_a
Cache header corrupt: Bad cache header forward link.	cds_s_cache_flink_a

Message Text	Symbolic Name
Cache header corrupt: Bad cache header in use flag.	cds_s_cache_inuse_a
Cache header corrupt: Bad cache header pattern.	cds_s_cache_pattern_a
Cache header corrupt: Bad cache header type.	cds_s_cache_type_a
Cache of KDC key failed.	dced_s_pkcache_key_write_failure
Cache server '%s' not found.	dcp_s_cds_no_cache_server
Cache size of %d is incorrect - deleting cache files	cds_s_cache_cachesize
Cache snapshot has been written to file %s.	cds_s_cache_snapshot_file
Cache version is not current, deleting cache files.	cds_s_cache_oldversion
Cached Server clearinghouse already exists	CDS_CSCLHEXISTS
Cached Server tag already exists	CDS_CSTAGEXISTS
Cached Server tag is unknown	CDS_CSTAGUNKNOWN
Call canceled	rpc_s_call_cancelled
Call faulted	rpc_s_call_faulted
Call ID in packet unknown	rpc_s_call_id_not_found
Call orphaned	rpc_s_call_orphaned
Call queued	rpc_s_call_queued
Call thread not found	rpc_s_ctypead_not_found
Call timed out	rpc_s_call_timeout
called "%s" with too many arguments	tcl_s_proc_called_with_too_many_args
called Tcl_CreateHashEntry on deleted table	tcl_s_hash_bogus_create

Message Text	Symbolic Name
called Tcl_FindHashEntry on deleted table	tcl_s_hash_bogus_find
Calls too large for well known endpoint	rpc_s_calls_too_large_for_wk_ep
Can not read dtsd bindings file. Check to see if dtsd is running.	dcp_s_dts_bind_file_open_fail
Cancel timeout	rpc_s_cancel_timeout
Cannot accept	rpc_s_cannot_accept
Cannot access endpoint database	ept_s_cant_access
Cannot access file %s.n	gsu_access_right_failed
cannot access local registry	sec_lrgy_s_no_access
Cannot access memory data, shm(%d) has %d users.	cds_s_cache_inuse
Cannot access the DCE login status	KDDS22415-E
Cannot add another instance of this attribute due to lack of multi-value capability.	dcp_s_rgy_era_not_multi_valued
Cannot add any-other obj to ACL: %lx	aud_s_dmn_acl_obj_add_obj_entry
Cannot add audit-admin group to ACL: %lx	aud_s_dmn_acl_obj_add_group_entry
Cannot add host user to ACL: %lx	aud_s_dmn_acl_obj_add_user_entry
Cannot add member: Member "%s", Group UNIX id "%d" - %sn	pwd_imp_err_add_group_member
Cannot add new replica to master registryn%s	sec_crdb_cant_add_replica
Cannot add unauthenticated obj to ACL: %lx	aud_s_dmn_acl_obj_add_unauth_entry
Cannot allocate %d bytes memory	aud_s_cannot_allocate_memory
Cannot allocate memory	pks_s_no_memory
Cannot allocate memory	dced_s_no_memory
Cannot allocate memory	dce_attr_s_no_memory

Message Text	Symbolic Name
Cannot allocate memory for code set info	dce_cs_c_cannot_allocate_memory
Cannot allocate requested amount of memory.n	pwd_imp_err_no_memory
Cannot allocate requested amount of memory.n	pwd_exp_err_no_memory
Cannot allocate the required memory.n	csrc_s_no_memory
Cannot auto-enable CDS server.	cds_s_server_enablefail
Cannot auto-initialize CDS server.	cds_s_server_autofail
Cannot bind socket	rpc_s_cant_bind_socket
Cannot change an attribute which has an encoding type of 'void'.	dcp_s_rgy_era_illegal_change_command
Cannot change or check password	KDDS22210-E
Cannot checkpoint database	sec_rsdb_db_chkpt_err
Cannot checkpoint log file	sec_rsdb_log_chkpt_err
Cannot checkpoint on log filen%s	sec_rgy_chkpt_log_file
Cannot communicate with all slaves	sec_rgy_rep_babel
Cannot communicate with master registryn%s	sec_crdb_cant_com_master
Cannot communicate with NetWare server xxx	KDDS22407-E
Cannot connect	rpc_s_cannot_connect
Cannot contact dts daemon - rpc failure:	dts_s_dtsd_comm
Cannot continue after previous error - import operation terminated.	pwd_imp_err_fatal
Cannot copy the intermediate code set name: %s.n	csrc_s_cannot_copy_intermediate
Cannot create AUD acl database : %lx	aud_s_dmn_db_open_create
cannot create database	sec_rgy_rep_cannot_create_db

Message Text	Symbolic Name
Cannot create endpoint database	ept_s_cant_create
Cannot create global unauth cred handle	sec_rgy_unauth_cred_handle_init
Cannot create key management thread	dced_s_cannot_create_key_mgmt_thr
cannot create local registry	sec_lrgy_s_cannot_create
Cannot create master_key: Error converting	sec_rgy_mky_get_realm_name
Cannot create master_key. Error generating initial keyseedn%s	sec_rgy_mky_init_keyseed
Cannot create master_key: Error generating random master_keyn%s	sec_rgy_mky_gen_random
Cannot create master_key: Error initializing random key generatorn%s	sec_rgy_mky_init_random
Cannot create master_key. Error processing keyseedn%s	sec_rgy_mky_process_keyseed
Cannot create master_key: Error processing master_keyn%s	sec_rgy_mky_process_master_key
Cannot create master_key Error setting up master_key	sec_rgy_mky_setup_mkey_name
Cannot create master_key: Error storing master_key on diskn%s	sec_rgy_mky_store_disk
Cannot create object; already exists	dced_s_already_exists
Cannot create registry journal file	rsdb_journal_create_fail
Cannot create socket	rpc_s_cant_create_socket
Cannot create the listener thread	aud_s_dmn_listener_thread
Cannot create the update thread	aud_s_dmn_create_update_thread
Cannot create to registry journal header	rsdb_journal_hdr_write_failed
Cannot detach key management thread	dced_s_cannot_detach_key_mgmt_thr
Cannot do database checkpointn%s	sec_rgy_rsdb_checkpt
Cannot execute setdfakey command.	KDDS01303-E

Message Text	Symbolic Name
Cannot execute setdfakey command due to unmatched master keys.	KDDS01304-E
Cannot export attribute instancen%s	sec_rgy_rsdb_attr_export
Cannot export bindings to clearinghouse.	cds_s_server_exportfail_eb
Cannot find a matching object.	dced_s_not_found
Cannot find desired attribute in server_t structure	dced_s_server_attr_not_found
Cannot find in-memory replist entry in stable replistn%s	sec_rgy_rep_entry_not_found
cannot find local registry	sec_lrgy_s_not_found
cannot find master	sec_rgy_rep_master_not_found
Cannot fork: Agent cannot take connection requests from gateway.	KDDS02130-E
Cannot fork to start server	dced_s_sc_cant_fork
Cannot free encoding service handle	aud_s_free_encoding_service_handle
Cannot generate a reply message, %x	pks_s_no_gen_reply
Cannot get host identityn%s	sec_rgy_host_identity
Cannot get interface ID	rpc_s_cant_get_if_id
Cannot get local host principal namen%s	sec_rgy_get_local_host_princ
Cannot get login context	aud_s_no_current_login_context
Cannot get override information due to server connection rejected.	pwd_exp_rgy_connect_rejected
Cannot get peer name	rpc_s_cant_getpeername
Cannot get server's bindingsn%s	sec_rgy_ns_svr_get_binding
Cannot get the hash value of the subject uuid: %s ; status: %s	aud_s_uuid_hash_failed
Cannot have more than one level of indirection to a nonencapsulated union	NIDL_PTRNEUNION

Message Text	Symbolic Name
Cannot import from CDS entry, try '-entry' option.	dcp_s_acl_not_rpc_entry
Cannot inherit local host identityn%s	sec_crdb_inherit_hostident_err
Cannot initialize ACL managemn%s	sec_rgy_acl_init
Cannot initialize ACL object : %lx	aud_s_dmn_acl_obj_init
Cannot initialize daemon's ACL	aud_s_dmn_acl
Cannot initialize DTS command parser - reason:	dts_s_cp_init_prs
Cannot initialize master replist	sec_rep_msrepl_not_initied
Cannot initialize RPC servicesn%s	sec_rgy_init_rpc_bind
Cannot initialize server databasen%s	sec_rgy_db_init_err
Cannot initialize server log managersn%s	sec_rgy_log_init_mgr
Cannot initialize server replican%s	sec_rgy_rep_init_replica
Cannot initialize the condition variable for the client	aud_s_client_updt_cond_init_fail
Cannot initialize the mutex for the audit trail.	aud_s_cannot_init_trail_mutex
Cannot initialize the mutex for the client update list.	aud_s_client_updt_mutex_init_fail
Cannot inquire socket	rpc_s_cant_inq_socket
Cannot join with listener task	sec_rgy_thr_join
Cannot locate and bind to master registryn%s	sec_crdb_cant_bind_updsite
Cannot lock esl file %s, retry %d seconds later	aud_s_retry_lock_esl_file
Cannot lock esl update file %s, retry %d seconds later	aud_s_retry_lock_esl_updt_file
Cannot lock file %s	aud_s_lock_esl_file

Message Text	Symbolic Name
Cannot lock the mutex for the client update list.	aud_s_client_updt_mutex_lock_fail
cannot log in with zero-length password	sec_login_s_null_password
Cannot login to DCE	KDDS22002-E
Cannot make %s directory	aud_s_cannot_mkdir
cannot mix "%" and "%n\$" conversion specifiers	tcl_s_cmdah_cannot_mix_conversion_specs
Cannot obtain dced server config data	dced_s_data_unavailable
cannot obtain uuids of name in princ	sec_id_e_no_at_hack
Cannot open AUD ACL database for reading: %lx	aud_s_dmn_db_open
Cannot open audit central trail file %s	aud_s_dmn_cannot_open_central_trail
Cannot open audit daemon's binding file	aud_s_cannot_open_dmn_binding_file
Cannot open Audit daemon's identity file	aud_s_cannot_open_dmn_identity_file
Cannot open audit trail	aud_s_dmn_cannot_open_trail
Cannot open audit trail file '%s'.	dcp_s_aud_cannot_open_trail_file
Cannot open audit trailn%s	sec_rgy_aud_open
Cannot open client binding file	aud_s_cant_open_client_binding_file_rc
Cannot open client binding file %s	aud_s_cant_open_client_binding_file
Cannot open configuration file. %s %s	KDDS02900-E
cannot open database	sec_rgy_rep_cannot_open_db
Cannot open decnet port	dts_s_open_decnet
Cannot open directory <%s>.n	gc_i_cannot_open_dir
Cannot open esl file %s	aud_s_open_esl_file
Cannot open esl update file %s	aud_s_open_esl_update_file
Cannot open ethernet port	dts_s_open_ethernet

Message Text	Symbolic Name
Cannot open event class directory %s to read.	aud_s_cannot_open_event_class_dir
Cannot open event class file %s to read.	aud_s_cannot_open_event_class_file
Cannot open file "%s"	uuidgen_st_cantopen
Cannot open file %sn	CDSCP_CANT_OPEN_PARSE_TABLE
Cannot open message catalog	msg_s_no_cat_open
Cannot open parse table file %s	dts_s_prsfile_open
Cannot open %s: errno = %d	aud_s_updt_opendir_fail
Cannot open specified file	svc_s_cantopen
Cannot open the audit trail file	dts_s_aud_open_file_failed
Cannot open the audit trail file	dts_s_cannot_open_audit_trail
Cannot open the code set registry file	dce_cs_c_cannot_open_file
Cannot open trail file	aud_s_cannot_open_trail_file_rc
Cannot open trail file %s	aud_s_cannot_open_trail_file
Cannot pack replica entryn%s	sec_rgy_rep_pack_entry
Cannot perform endpoint map operation	ept_s_cant_perform_op
Cannot reach the audit daemon	dts_s_aud_open_daemon_failed
Cannot read a field that has no assigned data (Registry Edit Kernel)	ek_field_no_data
cannot read database	sec_rgy_rep_cannot_read_db
Cannot read file %s in buffer	aud_s_cannot_read_file
Cannot read parse table file %s	dts_s_prsfile_read
Cannot read server group name from config info	pks_s_no_group_name
Cannot read the code set registry file	dce_cs_c_cannot_read_file
Cannot recover databasen%s	sec_rgy_rep_recover_db

Message Text	Symbolic Name
Cannot register AUD object type with ACL library: %lx	aud_s_dmn_acl_register_obj_type
Cannot register auth infon%s	sec_rgy_auth_init
Cannot register daemon's ACL Manager interface bindings	aud_s_dmn_acl_mgr_interface
Cannot register daemon's authentication info with RPC runtime	aud_s_dmn_auth_info
Cannot register daemon's control interface bindings to CDS	aud_s_dmn_control_export_interface
Cannot register daemon's control interface bindings with the endpoint mapper.	aud_s_dmn_control_register_bindings
Cannot register daemon's RPC interfaces	aud_s_dmn_interfaces
Cannot register daemon's SVC manager bindings to CDS	aud_s_dmn_svc_mgr_export_interface
Cannot register daemon's svc manager bindings with RPCD	aud_s_dmn_svc_mgr_register_bindings
Cannot register servern%s	sec_rgy_svr_register
Cannot register with nameservicen%s	sec_crdb_cant_register_ns
Cannot remove individual credentials from VM ccache	sec_rs_vmcc_cant_remove
Cannot remove the root directory from clearinghouse %s.	cds_s_server_crucialevent
Cannot rename audit trail file	aud_s_rename_trail_file_rc
Cannot rename audit trail index file	aud_s_rename_trail_index_file_rc
cannot rename database	sec_rgy_rep_cannot_rename_db
Cannot rename files during checkpoint	sec_rldb_file_rename_err
Cannot rename files during checkpointn%s	sec_rgy_checkpt_rename_files
Cannot rename %s to %s	aud_s_rename_trail_file

Message Text	Symbolic Name
Cannot rename %s to %s	aud_s_rename_trail_index_file
Cannot rename %s to %s	aud_s_rename_esl_file
Cannot rename %s to %s	aud_s_rename_esl_update_file
Cannot reopen audit trail file	aud_s_cannot_reopen_trail_file_rc
Cannot reopen audit trail index file	aud_s_cannot_reopen_trail_index_file_rc
Cannot reopen %s	aud_s_cannot_reopen_trail_file
Cannot reopen %s	aud_s_cannot_reopen_trail_index_file
Cannot retrieve cell namen%s	sec_rgy_get_cellname
cannot save database	sec_rgy_rep_cannot_save_db
Cannot save replica state	sec_rsdb_rep_state_not_saved
Cannot save replica state during checkpointn%s	sec_rgy_checkpoint_save_rep_state
Cannot save state init_idn%s	sec_rgy_rep_set_init_id
Cannot save volatile replica staten%s	sec_rgy_rep_set_volatile_state
Cannot set default thread pool queue lengthn%s	sec_rgy_thr_set_pool
Cannot set nodelay	rpc_s_cannot_set_nodelay
Cannot set object's attr_list_idn%s	sec_rgy_rsdb_attr_set_id
Cannot set replica staten%s	sec_rgy_rep_set_state
Cannot set stack size for listener threads	sec_rgy_set_stack_size
Cannot set value	dts_s_set_error
Cannot setup dce_rgy identityn%s	sec_rgy_dce_rgy_identity
Cannot setup locksmith accountn%s	sec_rgy_locksmith_init
Cannot specify a password when 'pkgenprivkey' is also specified.	dcp_s_rgy_pk_gen_and_pass
Cannot specify a public or private keyfile when 'generatekey' is also specified.	dcp_s_rgy_pk_gen_and_key

Message Text	Symbolic Name
Cannot start checkpoint taskn%s	sec_rgy_checkpt_start_task
Cannot start nameservice registration taskn%s	sec_rgy_ns_register
Cannot start propagation tasks	sec_rep_cant_start_prop_tasks
Cannot start signal catch taskn%s	sec_rgy_sigcatch_start_task
Cannot stat esl file %s	aud_s_stat_esl_file
Cannot stat esl update file %s	aud_s_stat_esl_update_file
Cannot unlock the mutex for the client update list.	aud_s_client_updt_mutex_unlock_fail
Cannot update child pointer for directory %s: status = %ld.	cds_s_server_childupdateevent
Cannot update endpoint database	ept_s_update_failed
Cannot update rgy_state filen%s	sec_crdb_cant_upd_rgyst_file
cannot write data to a read-only field (Registry Edit Kernel)	ek_field_readonly
Cannot write to closed log file	sec_rs_log_file_closed
Can't access gda_id file %s : status = %s.	cds_s_gda_uuidfile_eb
Can't acquire Kerberos credential cache in gss_init_sec_ctx	gss_s_ic_no_krb_cred_cache
Cant add alias for this name or principal (e.g. krbtgt)	sec_rgy_alias_not_allowed
Can't allocate %d bytes for channel bindings	gss_s_seca_nomem1
can't allocate memory	sec_priv_s_no_mem
Can't allocate memory for MD5 initializer	gss_s_fmi_md5_nomem
Can't become delegate (%x)	gss_s_ac_no_deleg1
Can't become impersonator (%x)	gss_s_ac_no_deleg2
Can't change to directory %s/%s: errno = %ld.	cds_s_library_cd_eg

Message Text	Symbolic Name
Can't close connection to registry.	pwd_exp_rgy_cannot_close
Can't create child process.	pks_s_fork_error
Can't create mutex	pkc_s_cant_create_mutex
Can't create pipe.	pks_s_pipe_error
Can't decode NSAP-address (error code = %d)	GDS_S_NDS_DNSAP_ERR
Can't delete attribute instancen%s	sec_rgy_rsd_b_attr_delete
Can't delete mutex	pkc_s_cant_delete_mutex
can't delete "%s": command doesn't exist	tcl_s_cmdmz_del_cmd_doesnot_exist
can't delete schema entry with reserved flag set	sec_attr_sch_reserved
Can't determine allowed delegation type (%x)	gss_s_ac_unk_deleg_type
Can't determine delegation type (%x)	gss_s_ic_deleg_type_unk
Can't determine transfer syntax associated to abstract	GDS_S_NOTRSYNTAX_ERR
Can't disable delegation (%x)	gss_s_ic_cant_disable_deleg
Can't enable delegation in gss_init_sec_ctx (%x)	gss_s_ic_cant_delegate
Cant establish authentication to registry (Registry Edit Kernel)	ek_misc_unauth_binding
Cant establish authentication to security server	sec_rgy_cant_authenticate
Can't find a new virtual process-ID	GDS_S_IPCVPID_ERR
can't find appropriate seal for EPAC	sec_authn_s_no_seal
can't find [info library]/init.tcl; perhaps you need to n	tcl_s_basic_interp_init_error
Can't find registration entry (process type = %d,	GDS_S_IPCNOREG_ERR

Message Text	Symbolic Name
Can't get IPC-event description (file descriptor information)	GDS_S_IPCEV_ERR
Can't get login=context for delegation (%x)	gss_s_ac_no_lc
Can't get name from PAC (%x)	gss_s_ac_no_pac_name
Can't get server ticket in gss_init_sec_ctx (%x)	gss_s_ic_no_server_ticket
can't have : operator without ? first	tcl_s_expr_colon_without_question
Can't import attributen%s	sec_rgy_rsdb_attr_import
Can't initialise parent pointer : status = %ld	cds_s_gda_updatepp
Can't initialize clerk managment ACL.	cds_s_adver_aclinit
Can't initialize GENERAL managment ACL.	cds_s_aclinit
Can't initialize shared memory cache.	cds_s_adver_cache_a
Can't initalize ASN.1 subfacility. Code: %x	pkc_s_init_failure_asn
Can't initalize locking subfacility. Code: %x	pkc_s_init_failure_locks
Can't initalize PKC subfacility. Code: %x	pkc_s_init_failure_pkc
Can't lock mutex	pkc_s_cant_lock_mutex
Can't map NSAP-address information	GDS_S_NDS_MAPNSAP_ERR
Can't open connection to registry.	pwd_exp_rgy_cannot_open
Can't open '%s' for input, %s.n	csrc_s_cannot_open_input
Can't open '%s' for logging, %s.n	csrc_s_cannot_open_logfile
Can't open '%s' for output, %s.n	csrc_s_cannot_open_output
Can't perform security initialization.	cds_s_gda_initsec_eb
Can't read attribute description file	GDS_S_ATTRFILE_ERR

Message Text	Symbolic Name
can't read output from command: standard output was redirected	tcl_s_unixaz_cannot_read_output
Can't read stored master key	sec_rgy_mkey_cant_read_stored
Can't receive IPC-request message	GDS_S_CACHE_WAITIN_ERR
Can't register Stub at IPC-level	GDS_S_REG_ERR
Can't register with name servicen%s	sec_rgy_svr_register_ns
can't rename "%s": command doesn't exist	tcl_s_cmdmz_rename_cmd_doesnot_exist
can't rename to "%s": command already exists	tcl_s_cmdmz_rename_cmd_already_exist
Can't resolve profile name: %s	dts_s_get_profile_name
Can't send IPC-result message	GDS_S_CACHE_RESULT_ERR
can't specify "%s" as last word in command	tcl_s_unixutil_cannot_spec_as_last
Can't unlock mutex	pkc_s_cant_unlock_mutex
can't update the multi_instanced flag from unset to set	sec_attr_multi_inst_no_update
can't update the trig_types flag	sec_attr_trig_types_no_update
can't update the unique flag from set to unset	sec_attr_unique_no_update
can't use floating-point value as operand of "%s"	tcl_s_expr_float_non_numeric_as_op
can't use non-numeric string as operand of "%s"	tcl_s_expr_non_numeric_non_numeric_as_op
can't write input to command: standard input was redirected	tcl_s_unixaz_cannot_write_input
Case label must be a constant from the enumeration of the discriminant	NIDL_CASECONENUM
Case label type does not agree with discriminator type	NIDL_CASEDISCTYPE

Message Text	Symbolic Name
Cause: Account invalid or expired.	KDDS11816-I
Cause: Login period expired before renewed.	KDDS11817-I
Cause: Login period too small.	KDDS11813-I
Cause: Password changed while login.	KDDS11814-I
Cause: Security server is not running.	KDDS11812-I
CDS Advertiser Starting.	cds_s_adver_startup
CDS Clerk Starting.	cds_s_child_starting
CDS display internal error.	dcp_s_cds_internal_error
CDS GDA Starting.	cds_s_gda_startup
CDS server principal %s is not a member of group %s.	cds_s_child_servernotmember
CDS server starting.	cds_s_server_startup
Cell name does not start with /.../	sec_authn_bad_cell_name
cell name invalid	dced_s_pkcache_cell_invalid
Cell name %s cannot contain the	sec_crdb_at_char_in_cellname
Cell UUID does not correspond to a valid cell name	sec_id_e_bad_cell_uuid
Chaining is required to perform	DS_E_CHAINING_REQUIRED
Change DCE password.	KDDS11819-I
Channel-bindings mismatch	gss_s_ac_bindings_mismatch
Character sets are not compatible	rpc_s_ss_no_compat_charsets
Checking of syntax in the input failed. No output generated.n	csrc_s_no_output
Checkpoint interval not a positive number.	sec_sec_d_cl_bad_chkpt_interval
Checksum is of wrong type	gss_s_seca_cksum_type_wrong
Checksum length wrong	gss_s_seca_cksum_length_wrong
Checksum too short	gss_s_seca_cksum_too_short

Message Text	Symbolic Name
Checksum type not supported	sec_rgy_bad_chksum_type
child killed: %sn	tcl_s_unixaz_child_killed
child process exited abnormally	tcl_s_unixaz_child_abend_exit
Child process killed, signal = %d.	GDS_S_CHILD_SIGNAL
child suspended: %sn	tcl_s_unixaz_child_suspended
child wait status didn't make sense	tcl_s_unixaz_child_st_no_sense
C-ISAM File could not be closed, iserrno = %d.	GDS_S_ISCLOSE_ERR
C-ISAM File could not be written, iserrno = %d.	GDS_S_ISWRITE_ERR
C-ISAM-File could not be read with mode %d, iserrno = %d.	GDS_S_ISREAD_ERR
C-ISAM-FILE %s could not be opened in mode %d,	GDS_S_ISOPEN_ERR
C-ISAM-FILE %s with record length %d could not be built	GDS_S_ISBUILD_ERR
C-ISAM-record pointer could not be set, iserrno = %d.	GDS_S_ISSTART_ERR
Class not found in the XOM object information schema file.	gc_t_omx_class_not_found_in_schema_file
Cleanup failed within an evaluation routine.	rpc_s_ss_cleanup_failed
Cleanup of propagation queue failed.n%s	sec_prop_propq_clean_fail
Clearinghouse name not provided.	dcp_s_cds_no_clearinghouse_option
Clearinghouse not found.	dcp_s_cds_not_valid_clearinghouse
Clearinghouse :%s - database state assertion failure: observed state	cds_s_server_chstate
Clearinghouse %s created.	cds_s_server_clearinghousecreated
Clearinghouse %s deleted	cds_s_server_clearinghousedeleted

Message Text	Symbolic Name
Clearinghouse %s duplicatedn	CDSCP_DUPCL
Clearinghouse %s exclusion argument missingn	CDSCP_MISEXCL
Client has no permission to execute operation	aud_s_permission_denied
Client out of memory.	KDDS23017-W
Client RPC binding contains invalid authentication information	aud_s_cannot_authenticate
Client's audit log access denied	aud_s_log_access_denied
Clock skew too great to authenticate	rpc_s_auth_skew
clock skewed	sec_rgy_rep_clock_skew
Clock was set: old time = %s, new time = %s	dts_s_clockset
Closing connection to registry.n	pwd_imp_inf_close_rgy
Closing import files.n	pwd_imp_inf_close_import
Code set registry access succeeded.	dce_cs_c_ok
codeset conversion error	rpc_s_ss_codeset_conv_error
Command does not accept a list of names as argument.	dcp_s_bad_arg_list
Command illegal while a time provider is present	dts_s_has_provider
Command illegal while synchronization in progress	dts_s_synching
Command illegal while update time is in progress	dts_s_updating_time
"-command" must be followed by comparison command	tcl_s_cmdil_command_not_with_comparison
Command only valid for servers	dts_s_not_server
Command option -%1\$s %2\$s is not valid	NIDL_INVOPTION

Message Text	Symbolic Name
Command option %1\$s conflicts with %2\$s	NIDL_CONFLICTOPT
Command option %1\$s does not take a value	NIDL_OPTNOVAL
Command option -bug %1\$lu conflicts with -no_bug %2\$lu	NIDL_BUGNOBUG
Command option -bug %1\$lu is not known	NIDL_INVBUG
Command option -no_bug %1\$lu is not known	NIDL_INVNOBUG
Command requires %d byte buffer; parser has %d bytesn	CDSCP_CMD_TOOBIG
command returned bad code: %d	tcl_s_basic_cmd_return_bad_code
Command too big.n	CDSCP_CMD_TOO_BIG
Communication error	KDDS22402-E
Communication error: aaa	KDDS02564-E
Communication error: Logged out from DCE.	KDDS12001-E
Communication error; Logged out from DCE.	KDDS11225-I
Communication error: Logged out from DCE.	KDDS11413-E
Communication failed to %s. Status = %ld.	cds_s_child_nocommunication
Communication failure with time service	dts_s_comm_failure
Communication logging file taken.	KDDS12403-I
Communications failure	rpc_s_comm_failure
comparison command returned non-numeric result	tcl_s_cmdil_com_cmd_ret_non_numeric

Message Text	Symbolic Name
Comparison of a relative and an absolute timestamp is not allowed.	dcp_s_utc_compare_diff_ts
Comparison of the two timestamps failed. Invalid timestamp.	dcp_s_utc_compare_failed
Compatibility log replay entered	sec_rgy_compat_log_replay
Compilation aborted	NIDL_COMPABORT
Compiling stub module %1\$s	NIDL_STUBCOMPILE
Completed importing of RPC bindings from %s	sec_ns_import_done
CONFLICT: (%s %d) -	pwd_imp_msg_conflict
Conflicting arguments specified	CDS_CONFLICTINGARGUMENTS
Conflicting option "%s".	gc_t_conflicting_option
Conformant array or structure is invalid within a union	NIDL_CFMUNION
Connect request refused: unknown gateway. xxx	KDDS02133-I
Connection aborted	rpc_s_connection_aborted
Connection aborted by local host	rpc_s_loc_connect_aborted
Connection closed	rpc_s_connection_closed
Connection closed by remote host	rpc_s_connect_closed_by_rem
Connection error	KDDS23110-E
Connection error occurred between gateway and agent.	KDDS22412-E
Connection request rejected	rpc_s_connect_rejected
Connection request timed out	rpc_s_connect_timed_out
Constant name: %1\$s not found	NIDL_CONSTNOTFND
Constant type does not agree with constant expression	NIDL_CONSTTYPE

Message Text	Symbolic Name
Construct not supported.	pkc_s_asn_not_supported
Context (%s)- wait %d seconds before refreshing	sec_rs_login_refresh_wait
Context handle is not valid as a member of a union	NIDL_CTXUNIMEM
Context handle not valid	sec_login_s_handle_invalid
Context handles are not valid as structure fields	NIDL_CTXSTRFLD
Context has not been validated	sec_login_s_context_invalid
Context id not found	rpc_s_context_id_not_found
Context state is invalid in gss_accept_sec_ctx	gss_s_ac_bad_ctx_state
Control program cannot get rpc binding to DTS daemon - reason:	dts_s_cp_init_rpc
Conversion between codesets not possible	rpc_s_ss_incompatible_codesets
Conversion failed.	pkc_s_conversion_error
Converted path name is too long.	KDDS23012-W
Corrupt database. Bad clearinghouse entry. Status = %ld.	cds_s_gdb_corrupt_db_ch
Corrupt database. No root dir or multiple root dirs	cds_s_gdb_corrupt_db
corrupted opcode	tcl_s_tclregexp_corrupted_opcode
corrupted pointers	tcl_s_tclregexp_corrupted_ptr
corrupted program	tcl_s_tclregexp_corrupted_pgm
Corrupted replica auth handle detected	sec_rep_corrupt_auth_handle
Corruption detection on internal lists.	cds_s_gda_list_a
Could not acquire public key credentials: %s in %s	sec_pk_login_client_fail
Could not add the two timestamps.	dcp_s_utc_add_failed

Message Text	Symbolic Name
Could not allocate memory.	dcp_s_no_memory
Could not allocate memory for error text.n	CDSCP_ASKNOMEM
Could not allocate space in client cache, expected lock is not held.	cds_s_cache_clock_a
Could not allocate space in global cache, expected lock is not held.	cds_s_cache_glock_a
Could not bind to the specified object	dcp_s_acl_could_not_bind
Could not broadcast condition variable	dced_s_cond_bcast_failed
Could not change to directory %s (%s).	pwd_exp_env_fail_change_dir
Could not convert the result back to a string.	dcp_s_utc_conv_fail
Could not employ the services of the network.	gc_t_om_network_error
Could not employ the services of the operating system.	gc_t_om_system_error
Could not fork shell process.	dcp_s_shell_fork_fail
Could not get current key version	sec_rrs_cant_get_next_key
Could not get current time.	dcp_s_clock_get_local_time_fail
Could not get current time using dced services.	dcp_s_clock_get_dced_time_fail
Could not get current time using inetd socket connection.	dcp_s_clock_get_inetd_time_fail
Could not get event classes.	dcp_s_audevents_get_events_fail
Could not get manager type uuid	sec_rsd_b_cant_get_mgr_tpuuid
Could not get pathname of current directory (%s).	pwd_exp_env_fail_getcwd
Could not initialize acl list	sec_rsd_b_cant_init_acl
Could not initialize cache: Cache size is too small to continue.	cds_s_cache_toosmall

Message Text	Symbolic Name
Could not initialize condition variable	dced_s_cond_init_fail
Could not initialize journal list	rsdb_journal_cant_init_list
Could not initialize login list	rsdb_login_cant_init_list
Could not initialize mutex	dced_s_mutex_init_fail
Could not insert cache header into freelist, expected lock is not held.	cds_s_cache_llock_a
Could not insert element into LRU list, element already on LRU list.	cds_s_cache_carefs_a
Could not into a linked list, already in list.	cds_s_cache_inlist_a
Could not invoke the C preprocessor	NIDL_INVOKECPP
Could not lock mutex	dced_s_mutex_lock_failed
Could not move cache block onto freelist, cache header is not in use.	cds_s_cache_notinuse_a
Could not open daemon binding file '%s'.	dcp_s_aud_dmn_binding_file_open_fail
Could not open daemon identity file '%s'.	dcp_s_aud_id_file_open_fail
Could not open file containing ASCII/EBCDIC translation tables	rpc_s_ss_char_trans_open_fail
Could not open file '%s'.	dcp_s_rgy_pk_file_open_fail
Could not open file %sn	CDSCP_CANT_OPEN
Could not open file %s.n	CDSCP_FILE_NOT_OPEN
Could not open or read IEEE 802 address file or device	utils_s_802_cant_read
Could not open '%s' for output.	dcp_s_audtrail_outfile_open_fail
Could not open temporary group file %s for writing (%s).	pwd_exp_f_cannot_open_temp_group
Could not read file %sn	CDSCP_READ_ERROR
Could not read from daemon identity file '%s'.	dcp_s_aud_id_file_read_fail

Message Text	Symbolic Name
Could not read from file '%s'.	dcp_s_rgy_pk_file_read_fail
Could not read internal clearinghouse address: status = %ld.	cds_s_server_readchaddr
Could not remove element from freelist, element is not in list,	cds_s_cache_notinlist_a
Could not rewind the Audit index file	aud_s_rewind_index_file
Could not rewind the Audit trail file	aud_s_rewind_trail_file
Could not %s temporary passwd file %s for writing (%s).	pwd_exp_f_cannot_open_temp_passwd
Could not set the system clock.	dcp_s_clock_set_failed
Could not signal condition variable	dced_s_cond_signal_failed
Could not spawn the postprocessor program	dced_s_postprocessor_spawn_fail
Could not store new item	sec_rsdb_cant_store_new_item
Could not subtract the two timestamps.	dcp_s_utc_sub_failed
Could not unlock mutex	dced_s_mutex_unlock_failed
Could not wait on condition variable	dced_s_cond_wait_failed
Could not write into file %s.n	gsu_inter_write_error
Couldn't add authentication to the Time Provider binding: %s	dts_s_tp_auth_info
Couldn't add Global Time Server entry to right profile: %s	dts_s_add_profile
Couldn't allocate buffer for message data in gss_unseal	gss_s_uns_nomem
Couldn't allocate context in gss_init_sec_ctx	gss_s_ic_ctx_nomem
Couldn't allocate cred in gss_init_sec_ctx	gss_s_ic_cred_nomem
couldn't change working directory to "%s": %s	tcl_s_unixaz_cannot_change_work_dir

Message Text	Symbolic Name
couldn't compile regular expression pattern: %s	tcl_s_tclutil_reg_compile_err
Couldn't continue search for Time Provider Interface in endpoint map: %s	dts_s_tp_ep_next
Couldn't convert client name (%x)	gss_s_ac_cli_name_noconv
Couldn't convert time service interface UUID to string: %s	dts_s_uuid_to_string
Couldn't create context in gss_accept_sec_ctx	gss_s_ac_ctx_nomem
Couldn't create DTS acl database (%s): %s	dts_s_acl_dbopen_create
couldn't create error file for command: %s	tcl_s_unixutil_cannot_creat_err_file
Couldn't create GSSAPI cred-list mutex attributes (%x)	gss_s_cant_create_cred_mutex_attr
Couldn't create GSSAPI cred-list mutex (%x)	gss_s_cant_create_cred_mutex
Couldn't create GSSAPI ctx-list mutex attributes (%x)	gss_s_cant_create_ctx_mutex_attr
Couldn't create GSSAPI ctx-list mutex (%x)	gss_s_cant_create_ctx_mutex
Couldn't create GSSAPI element mutex attributes (%x)	gss_s_cant_create_elem_mutex_attr
Couldn't create GSSAPI mutex attributes (%x)	gss_s_cant_create_gss_mutex_attr
Couldn't create GSSAPI mutex (%x)	gss_s_cant_create_gss_mutex
Couldn't create GSSAPI registry mutex attributes (%x)	gss_s_cant_create_rgy_mutex_attr
Couldn't create GSSAPI registry mutex (%x)	gss_s_cant_create_rgy_mutex
couldn't create input file for command: %s	tcl_s_unixutil_cannot_creat_input_file

Message Text	Symbolic Name
couldn't create output pipe: %s	tcl_s_unixutil_cannot_create_output_pipe
couldn't create pipe: %s	tcl_s_unixutil_cannot_create_pipe
Couldn't create the default DTS ACL: %s	dts_s_acl_create_default
couldn't create the input pipe for command: %s	tcl_s_unixutil_cannot_create_input_pipe
Couldn't delete GSSAPI cred-list mutex attributes (%x)	gss_s_cant_delete_cred_mutex_attr
Couldn't delete GSSAPI ctx-list mutex attributes (%x)	gss_s_cant_delete_ctx_mutex_attr
Couldn't delete GSSAPI mutex attributes (%x)	gss_s_cant_delete_gss_mutex_attr
Couldn't delete GSSAPI registry mutex attributes (%x)	gss_s_cant_delete_rgy_mutex_attr
Couldn't delete server entry from LAN/Cell profile: %s	dts_s_profile_remove
Couldn't export Global Time Server entry to the namespace: %s	dts_s_export_gts
Couldn't export the ACL manager interface: %s	dts_s_export_acl_if
Couldn't extract interface ID from time service interface: %s	dts_s_interface_id
couldn't find "%.300s" to executen	tcl_s_unixutil_not_find_to_exec
couldn't find a matched private key in the file	sec_pvtkey_no_matched_private_key
couldn't find HOME environment variable to expand "%s"	tcl_s_glob_no_home_env
Couldn't find name in default context (%x)	gss_s_ac_noname_default
couldn't find search "%s"	tcl_s_tclvar_illegal_search

Message Text	Symbolic Name
Couldn't fixup registry context in cred_expand_id (%x)	gss_s_cei_frc_failed
couldn't fork child process: %s	tcl_s_unixutil_cannot_fork_chld_proc
Couldn't generate a binding for the Time Provider Interface: %s	dts_s_tp_binding
Couldn't get client PAC in login_context_to_cred (%x)	gss_s_lcc_no_pac
Couldn't get remote server entry name: %s	dts_s_binding_inq_name
Couldn't get remote server's principal name: %s	dts_s_inq_server_princ
Couldn't get the expiration time of server's credentials: %s	dts_s_get_expiration
Couldn't initialize search of node's initial profile: %s	dts_s_profile_begin
Couldn't initialize the dts daemon management ACL: %s	dts_s_init_mgmt_acl
Couldn't initiate search for Time Provider Interface in endpoint map: %s	dts_s_tp_ep_begin
couldn't lstat "%s": %s	tcl_s_unixaz_no_lstat
Couldn't obtain binding to remote time server %s using protocol %s: %s	dts_s_ep_resolve_binding
Couldn't open DTS acl database (%s)for reading: %s	dts_s_acl_dbopen_read
Couldn't open Registry site for security info: %s	dts_s_rgy_site_open
couldn't open "%s": %s	tcl_s_unixaz_cannot_open
Couldn't parse name in gss_init_sec_ctx (%x)	gss_s_ic_bad_name1
Couldn't parse the remote Time Server's principal name: %s	dts_s_sec_id_parse

Message Text	Symbolic Name
couldn't read directory "%s": %s	tcl_s_glob_dir_unreadable
couldn't read file "%s": %s	tcl_s_unixutil_no_read_file
couldn't read file "%s": %s	tcl_s_unixutil_cannot_read_file
couldn't readlink "%s": %s	tcl_s_unixaz_no_readlink
Couldn't register default GSSAPI message table (%x)	gss_s_cant_reg_table
Couldn't register DTS object type with ACL library: %s	dts_s_acl_register_obj_types
Couldn't register Global Time Server interface: %s	dts_s_ep_register_tp
Couldn't register server authentication info: %s	dts_s_server_reg_auth_info
Couldn't register the ACL manager interface: %s	dts_s_register_acl_if
Couldn't register the Version 0 rdacl interface with the endpoint map: %s	dts_s_aclv0_register
Couldn't register the version 0.0 rdacl interface with the RPC runtime: %s	dts_s_aclv0_runtime_register
Couldn't register the Version 1 rdacl interface with the endpoint map: %s	dts_s_aclv1_register
Couldn't register the version 1.0 rdacl interface with the RPC runtime: %s	dts_s_aclv1_runtime_register
couldn't remove error file for command: %s	tcl_s_unixutil_cannot_remove_err_file
couldn't reset or remove input file for command: %s	tcl_s_unixutil_cannot_reset_remove_file
Couldn't resolve context in gss_accept_sec_ctx	gss_s_ac_bad_ctx
Couldn't resolve credential in gss_accept_sec_ctx	gss_s_ac_bad_cred

Message Text	Symbolic Name
Couldn't resolve credential in gss_init_sec_ctx	gss_s_ic_inv_cred
Couldn't retrieve default login context (%x)	gss_s_ic_no_def_ctx
Couldn't retrieve machine principal name: %s	dts_s_prin_host
Couldn't retrieve the ACL for the dtsd: %s	dts_s_fetch_uuid
Couldn't retrieve this host's name from the configuration database: %s	dts_s_cf_hostname
Couldn't retrieve UUID for server %s from the namespace: %s	dts_s_entry_object_inq_next
Couldn't retrieve UUID for server %s from the namespace: %s	dts_s_entry_object_inq_begin
Couldn't return the server principal name for the Time Provider Interface: %s	dts_s_tp_name_search
couldn't save command result in variable	tcl_s_cmdah_could_not_save_cmd_result
Couldn't select a string binding for the Time Provide Interface: %s	dts_s_select_strbind
Couldn't set authorization info for server %s: %s	dts_s_set_auth_info
Couldn't set GSSAPI cred-list mutex attributes (%x)	gss_s_cant_set_cred_attributes
Couldn't set GSSAPI ctx-list mutex attributes (%x)	gss_s_cant_set_ctx_attributes
Couldn't set GSSAPI element mutex attributes (%x)	gss_s_cant_set_elem_attributes
Couldn't set GSSAPI mutex attributes (%x)	gss_s_cant_set_gss_attributes
Couldn't set GSSAPI registry mutex attributes (%x)	gss_s_cant_set_rgy_attributes

Message Text	Symbolic Name
couldn't set loop variable	tcl_s_cmdah_could_not_set_loop_var
couldn't set variable "%s"	tcl_s_cmdmz_could_not_set_var
couldn't stat file "%s": "%s"	tcl_s_unixutil_no_stat_file
couldn't stat "%s": %s	tcl_s_unixaz_no_stat
couldn't store default value in variable "%s"	tcl_s_cmdil_could_not_store_def_val
Couldn't store the auditd ACL in the ACL file : %lx	aud_s_dmn_db_store_uuid
Couldn't store the dtsd ACL in the ACL file: %s	dts_s_db_store_uuid
Couldn't translate name in gss_init_sec_ctx (%x)	gss_s_ic_bad_name
Couldn't unregister the Version 0 rdacl interface from the endpoint map: %s	dts_s_aclv0_unregister
Couldn't unregister the version 1.0 rdacl interface from the endpoint map: %s	dts_s_aclv1_unregister
couldn't write file input for command: %s	tcl_s_unixutil_cannot_write_file_input
couldn't write file "%s": %s	tcl_s_unixutil_cannot_write_file
Country code (CC) of E.163-address missing	GDS_S_NDS_E163CC_ERR
Country code (CC) of E.164-address missing	GDS_S_NDS_E164CC_ERR
Create clearinghouse failed. Skulk failed on root directory: status = %ld.	cds_s_server_crecleskulk
Create clearinghouse failed. Unable to create object: status = %ld.	cds_s_server_crecleobj
Create clearinghouse failed due to a virtual memory allocation error	cds_s_server_creclenomem
Create clearinghouse failed since unable to create clearinghouse object : status = %ld.	cds_s_server_clecrects

Message Text	Symbolic Name
Create clearinghouse failed with error = %ld	cds_s_server_clecrefailed
Create_cred - Couldn't lock cred-list	gss_s_create_cred_nolock
Create_ctx - Couldn't lock ctx-list	gss_s_create_ctx_nolock
Creating group objects from group file.n	pwd_imp_inf_create_groups
Creating include file %1\$s	NIDL_INCLCREATE
Creating principal entries and accounts from passwd file.n	pwd_imp_inf_create_accounts
Creating stub module %1\$s	NIDL_STUBCREATE
Credential is not capable of initiating contexts	gss_s_ic_cred_not_init
Credentials have been fragmented	rpc_s_partial_credentials
Credentials invalid	rpc_s_invalid_credentials
Credentials obtained from local registry.	dcp_s_login_local_creds
Credentials too large for packet	rpc_s_credentials_too_large
Cred_expand_id - Gen_name failed (%x)	gss_s_cei_gn_failed
Cred_expand_id - Parse_name failed (%x)	gss_s_cei_parse_failed
cred_expand_id - Registry server unavailable	gss_s_cei_server_unavailable
Cred_expand_id failed in gss_accept_sec_ctx (%x)	gss_s_ac_cei_failed
Cred_info_to_gss - Couldn't lock cred-list	gss_s_citg_nolock_cred
Critical service extension cannot be provided.	gc_t_unavailable_crit_ext
cthread create failed	rpc_s_cthread_create_failed
cthread invoke disabled	rpc_s_cthread_invoke_disabled
cthread pool exists	rpc_s_cthread_pool_exists
Ctx_info_to_gss - Couldn't lock ctx-list	gss_s_citg_nolock_ctx

Message Text	Symbolic Name
ctx_ptr->client_name non-NULL. Freeing it...	gss_s_ptn_not_null
ctx_ptr->client_name non-NULL. Freeing it...	gss_s_ctn_not_null
Current epoch %d, differs from epoch %d of server %s	dts_s_different_epoch
Cycle detected	rpc_s_cycle_detected
%d byte file %s will not fit in %d byte buffern	CDS SCP_NO_FIT
%d bytes allocated at (%s %d)n	tcl_s_ckalloc_bytes_allocated_at
Daemon cannot open its binding file %s to write	aud_s_dmn_binding_file
Daemon cannot open its identity file %s to write	aud_s_dmn_identity_file
Daemon does not have an identity	aud_s_dmn_identity
Daemon esl mutex initialization failed	aud_s_dmn_esl_mutex
Daemon is ready to listen to its interfaces	aud_s_dmn_ready_to_listen
Daemon registered interfaces with RPC runtime	aud_s_dmn_register_interface
Daemon registered its authentication identity %s with RPC runtime	aud_s_dmn_register_auth_info
Daemon state mutex initialization failed	aud_s_dmn_state_mutex
Daemon thread %s unable to join the listener task	aud_s_dmn_thread_join_listener
Daemon trail mutex initialization failed	aud_s_dmn_trail_mutex
Data attribute is not specified on operation which requires data.	dcp_s_dhd_data_attr_missing
Data attribute specified on entry only operation.	dcp_s_dhd_data_on_entry_ops
Data corruption detected at clearinghouse	CDS_DATA CORRUPTION

Message Text	Symbolic Name
Data country code (DCC)/Data network ID code (DNIC) missing	GDS_S_NDS_X121DCC_ERR
Data integrity error	sec_rgy_bad_integrity
Data is too long for buffer - "%s"n	pwd_imp_err_data_too_long
Data is too long (Registry Edit Kernel)	ek_err_data_too_long
data originated by untrustworthy security/privilege server	sec_s_not_trustworthy
Data string format not valid for the specified field (Registry Edit Kernel)	ek_bad_format
Data type %1\$s must be defined in %2\$s	NIDL_ERRSTATDEF
Data type of [switch_is] variable %1\$s does not agree with [switch_type] %2\$s	NIDL_SWDATATYPE
Data version number not found for directory ID %d.n	GDS_S_NO_DATAVERSION
Database alias chain corrupt	sec_rsdb_corrupt_alias_chain
Database cell name %s is not local cell name or alias	rsdb_cell_mismatch
Database creat failure - data file already exists	db_s_open_already_exists
Database delete operation failure	db_s_del_failed
Database does not use the standard object/record header	db_s_not_std_header
Database fetch failure	db_s_fetch_failed
Database file lock or unlock failed	db_s_file_lock_fail
Database file stat failed	db_s_stat_fail
Database in unrecognized state	sec_rsdb_db_unrecog_state
Database inconsistent	sec_rsdb_db_inconsistent
Database inconsistent, credentials item length incorrect	sec_rsdb_inconsistent_creds

Message Text	Symbolic Name
Database index maintenance routines have detected a corruption.	cds_s_server_dbindex
Database index rebuild has failed: status = %s	cds_s_server_rebuildindex_a
Database is already locked	db_s_already_locked
Database is not locked	db_s_not_locked
Database is opened as 'readonly'	db_s_readonly
database locked	sec_rgy_rep_db_locked
Database name missing	db_s_no_name_specified
Database not open	db_s_not_open
Database open failure	db_s_open_failed
Database open failure - no such file or directory	db_s_open_failed_enoent
Database open failure - permission denied	db_s_open_failed_eaccess
Database replace failed.	sec_rbdb_repl_fail
Database store failed.	sec_rbdb_dbstore_fail
Database store failure	db_s_store_failed
Date out of supported range (Registry Edit Kernel)	ek_err_date_out_of_range
Dates must be in the format [yy]yy/mm/dd (Registry Edit Kernel)	ek_err_bad_date
DCE error %s	dts_s_dce_error
DCE IDL compiler version %1\$s	NIDL_VERSION
DCE login for administrator started.	KDDS11638-I
DCE Logout failed.	KDDS22102-E
DCE mechanism requested in gss_init_sec_ctx, but cred is not DCE-capable	gss_s_ic_cred_nodce

Message Text	Symbolic Name
DCE security server is unavailable.	KDDS11211-E
dce_acl_obj_add_any_other_entry returned status %ld : %s	cds_s_bad_add_any_acl
dce_acl_obj_add_group_entry returned status %ld : %s	cds_s_bad_add_group_acl
dce_acl_obj_add_unauth_entry returned status %ld : %s	cds_s_bad_add_unauth_acl
dce_acl_obj_add_user_entry returned status %ld : %s	cds_s_bad_add_user_acl
dce_acl_obj_init returned status %ld : %s	cds_s_bad_acl_init_obj
dce_acl_register_object_type returned status %ld : %s	cds_s_bad_register_obj
dce_aud_open received invalid option combination	aud_s_trl_invalid_open_flags
dce_aud_print received a server UUID. This was not expected. UUID is %s	aud_s_got_server_uuid
dcecp convenience variable is read-only.	dcp_s_var_set_readonly
'dced' object not specified.	dcp_s_dhd_no_object
Debug option used without DCE_DEBUG defined.	dcp_s_log_no_debug
Declaration of %1\$s cannot contain an anonymous type	NIDL_ANONTYPE
Decode_message_header failed in gss_unseal (%x)	gss_s_uns_dmh_failed
Decode_message_header failed in gss_verify (%x)	gss_s_vfy_dmh_failed
Decrypt integrity check failed	rpc_s_auth_bad_integrity
Decryption failed (%x)	gss_s_uns_decr_failed
(de)encryption type not supported	sec_rgy_crypt_bad_type
default_passwd too long.	sec_crdb_cl_long_passwd

Message Text	Symbolic Name
Definition of tag %1\$s is not yet complete	NIDL_DEFNOTCOMP
delegation chain is corrupt	sec_priv_s_corrupt_deleg_chain
Delegation has not been enabled.	sec_login_s_deleg_not_enabled
Delegation inconsistency	gss_s_ac_inv_deleg
delegation not enabled	sec_priv_s_deleg_not_enabled
delegation token has expired	sec_priv_s_deleg_token_exp
Delete files/directories remaining in volume xxx ? (Y/N)	KDDS11625-Q
Delete pending	pkc_s_delete_pending
Deleting cache file %s due to write errors. Failed to write remaining %d bytes. status: %s	cds_s_cache_writecache
Deleting stub module %1\$s	NIDL_STUBDELETE
DES key has bad parity	sec_s_bad_key_parity
Descriptor not registered	rpc_s_desc_not_registered
Designated aaa(bbb) does not exist in DCE.	KDDS22004-W
Designated agent name does not exist in HOST file. The agent	KDDS10006-W
Designated gateway volume does not exist. The volume	KDDS10002-W
Destroy_ctx - Couldn't lock ctx-list	gss_s_destroy_ctx_nolock
Detected reflected token in decode_message_header	gss_s_dmh_refl_tok
DFA.NLM cannot run on this NetWare version.	KDDS11001-E
DFA.NLM detected self-contradiction.	KDDS11034-E
DFA.NLM has different interface version from %s.	KDDS11002-E

Message Text	Symbolic Name
DFA.NLM requires 3.12g or newer version of CLIB.NLM.	KDDS11008-W
DFA.NLM was unloaded; Logged out from DCE.	KDDS11224-I
DFARAS.NLM has different interface version from DFA.NLM.	KDDS12407-E
DFS client is not ready to run.	KDDS02282-E
DG protocol needs reauthentication.	rpc_s_dg_need_way_auth
didn't specify command to execute	tcl_s_unixutil_no_command_to_exec
Different encryption scheme is used.	KDDS11667-E
different numbers of variable names and field specifiers	tcl_s_cmdmz_diff_num_var_field
Different protocol is used.	KDDS11668-E
Dir id %d already configured as a client/server system and overwrite switch was not set.n	gsu_dirid_server_no_overwrite
directory creation error	dced_s_pkcache_mkdir_error
Directory id %d already configured as a client system and overwrite switch was not set.n	gsu_dirid_client_no_overwrite
Directory move not allowed	sec_rgy_dir_move_illegal
Directory must be empty to be deleted	CDS_NOTEMPTY
Directory not empty	sec_rgy_dir_not_empty
Directory not found	sec_rgy_dir_not_found
Directory replicas are not synchronized	CDS_BADEPOCH
Directory Sync. detected self-contradiction: error code xxx.	KDDS11624-E
Directory Sync. started.	KDDS11646-I

Message Text	Symbolic Name
Directory Sync. terminated: return code %d.	KDDS11647-I
Disconnection occurred in the communication with agent.	KDDS11653-E
Distributed command failed (cmd = %d, destination = %d, reason = %d)	GDS_S_RPC_DISTCMD_ERR
divide by zero	tcl_s_expr_divide_by_zero
Do not specify a username when using the -refresh option.	dcp_s_login_refresh_no_user
Do you wish to associate the existing group name with this id?	pwd_imp_qus_group_conflict
Do you wish to resolve the conflict (y) or skip this entry (n):	pwd_imp_qus_enter_conflict_action
domain error: argument not in valid range	tcl_s_expr_domain_err
DSA of Directory ID: %d has initialized.n	GDS_S_INITDSA
dtsd server still isn't accepting RPC connections after %d seconds	dts_s_mgmt_srvr_listen_timeout
Dump completed.	KDDS11827-I
Dump file taken.	KDDS12405-I
Dump will be started.	KDDS11826-I
Duplicate ACL entries are not allowed.	dcp_s_acl_replace_dup_entries
duplicate acl entry	sec_acl_duplicate_entry
Duplicate Attribute abbreviations.	gc_t_omx_duplicate_attr_abbrev
Duplicate Attribute Object Identifiers.	gc_t_omx_duplicate_attr_obj_id
Duplicate case label value	NIDL_DUPCASEVAL
duplicate masters	sec_rgy_rep_master_dup
Duplicate Object Class Abbreviations.	gc_t_omx_duplicate_obj_abbrev
Duplicate Object Class Identifiers.	gc_t_omx_duplicate_obj_obj_id

Message Text	Symbolic Name
Duplicate OM Class Definition Blocks.	gc_t_omx_duplicate_class_block
Duplicate '%s' field.n	csrc_s_duplicate_field
E.163-address missing	GDS_S_NDS_E163_ERR
E.164-address missing	GDS_S_NDS_E164_ERR
Effective period of DCE password expired. xxx	KDDS02251-E
Effective right for %s is [%s].	KDDS23600-I
ek_err_PAD6	ek_err_PAD6
ek_err_PAD7	ek_err_PAD7
ek_err_PAD8	ek_err_PAD8
ek_err_PAD9	ek_err_PAD9
ek_err_PADa	ek_err_PADa
ek_err_PADb	ek_err_PADb
ek_err_PADc	ek_err_PADc
ek_err_PADd	ek_err_PADd
ek_err_PADe	ek_err_PADe
ek_err_PADf	ek_err_PADf
ek_misc_PAD7	ek_misc_PAD7
ek_misc_PAD8	ek_misc_PAD8
ek_misc_PAD9	ek_misc_PAD9
ek_misc_PADa	ek_misc_PADa
ek_misc_PADb	ek_misc_PADb
ek_misc_PADc	ek_misc_PADc
ek_misc_PADd	ek_misc_PADd
ek_misc_PADe	ek_misc_PADe
ek_misc_PADf	ek_misc_PADf
ek_PAD0	ek_PAD0

Message Text	Symbolic Name
ek_PAD1	ek_PAD1
ek_PAD2	ek_PAD2
ek_PAD3	ek_PAD3
ek_PAD4	ek_PAD4
ek_PAD5	ek_PAD5
ek_PAD6	ek_PAD6
ek_PAD7	ek_PAD7
ek_PAD8	ek_PAD8
ek_PAD9	ek_PAD9
Empty Attribute Definition Block.	gc_t_omx_empty_attr_block
Empty Object Class Definition Block.	gc_t_omx_empty_obj_block
Empty OM Class Definition Block.	gc_t_omx_empty_class_block
Empty set.	CDS_EMPTY
Encoding type 'any' cannot be used when specifying values for attributes.	dcp_s_rgy_era_any_illegal_enc_type
Encoding type is ambiguous.	dcp_s_rgy_ambig_encoding_type
Encoding type is missing.	dcp_s_rgy_missing_encoding_type
Encoding type is unknown.	dcp_s_rgy_unknown_encoding_type
Encoding type of extended attribute is unknown.	dcp_s_rgy_era_unknown_encoding_type
Encoding type specified for the 'any' attribute is ambiguous.	dcp_s_rgy_era_any_ambig_enc_type
Encoding type specified for the 'any' attribute is unknown.	dcp_s_rgy_era_any_unknown_enc_type
End of file detected.	GDS_S_FEOF
End of membership list	sec_rsd_b_end_memb_list
Endpoint database already open by another process	ept_s_database_already_open

Message Text	Symbolic Name
Endpoint does not exist at remote host	rpc_s_no_rem_endpoint
Endpoint not found	rpc_s_endpoint_not_found
Enter new name for %s "%s" "%d":	pwd_imp_msg_enter_new_name
Enter new password for xxx:	KDDS22206-I
Enter new UNIX id:	pwd_imp_prompt_enter_unix_id
Enter old password for xxx:	KDDS22205-I
Enter password for locksmith account:	sec_lksm_passwd_prompt
Enter your username:	pwd_imp_prompt_enter_user_name
Entering sec_pvtkey__lookup_keystore(%s)	sec_psm_i_lookup_keystore
Entry already exists	rpc_s_entry_already_exists
Entry DSA of Directory ID: %d.n	GDS_S_ENTRYDSA
Entry DUA-cache process	GDS_S_ENTRYCACHE
Entry is an alias (Registry Edit Kernel)	ek_misc_is_an_alias
Entry monitor process	GDS_S_ENTRYMONITOR
Entry monitor process (RPC-server for serviceability)	GDS_S_ENTRY_RPCSERVER
Entry not found	rpc_s_entry_not_found
Entry not found.	gc_t_entry_not_found
Entry not found (Registry Edit Kernel)	ek_misc_object_not_found
Entry option used with a string binding.	dcp_s_sbind_entry_option
Entry %s exists and has been modified in X.500	cds_s_addcell_entryexists
Entry Stub of Directory ID: %d	GDS_S_ENTRYSTUB
Environment variable DCEAUDITTRAILSIZE has an invalid value.	aud_s_invalid_audit_trail_size_limit

Message Text	Symbolic Name
EnvTraceProc called with confusing arguments	tcl_s_env_conf_arguments
EnvTraceProc couldn't find interpreter	tcl_s_env_no_interpreter
EPAC missing after authenticator	sec_authn_s_missing_epac
Epoch Change completed, old epoch = %d, new epoch = %d	dts_server_epoch_changed
'-epoch' option not specified.	dcp_s_clock_set_need_epoch
Epoch out of range or not different from current epoch	dts_s_epoch_range
errno text : %s	sec_sys_errno_text_only
Error - Cred_expand_id received foreign_cell_referral	gss_s_cei_referral
Error - gss_init_sec_context couldn't resolve context handle	gss_s_ic_inv_context
Error - gss_init_sec_context was passed a null context-handle	gss_s_ic_null_context
Error - NULL context handle in gss_accept_sec_ctx	gss_s_ac_null_ctx
error accessing %s	tcl_s_ckalloc_error_accessing
Error adding a member	sec_res_mem_add_err
Error adding a person/group/org entry	sec_res_pgo_add_err
Error adding an account	sec_res_acct_add_err
Error adding an entry to the attribute schema	sec_res_attr_sch_add_err
Error adding an entry to the PK attribute schema	sec_res_pk_attr_sch_add_err
Error adding master replica to an uninitialized databasen%s	sec_rgy_rep_add_master_replica
Error adding my replica to an uninitialized databasen%s	sec_rgy_rep_add_my_replica

Message Text	Symbolic Name
Error: Cannot unset %s.	gc_i_cannot_unset_var
Error: Cannot unset '%s': dcep convenience variable is read-only.	dcp_s_var_unset_readonly
Error checkpointing an uninitialized databasen%s	sec_rgy_rsd_b_checkpt_uninit
error closing file "%s": "%s"	tcl_s_unixutil_err_close_file
error closing "%s": %sn	tcl_s_unixaz_error_closing
Error converting cell name to local realm principal	sec_res_princ_cvt_err
Error converting cell uuid to string	sec_res_uuid_cvt_err
Error decoding BER token header. The token is corrupt.	gssdce_s_ber_decoding_error
Error decoding pipe data.	pks_s_pipsvr_decode_error
Error decoding pipe data (%d).	pks_s_pipsvr_decode_errorp
Error decoding token. The token is corrupt.	gssdce_s_authentication_error
Error decrypting data from pipe (%x).	sec_pkss_pipe_decrypt_fail
Error decrypting data in server from pipe (%x).	pks_s_pipe_svr_decrypt_fail
error during seek: %s	tcl_s_unixaz_error_during_seek
Error encrypting data in server for pipe (%x).	pks_s_pipe_svr_encrypt_fail
Error encrypting for pipe (%x)	sec_pkss_pipe_encrypt_fail
Error executing command:	dts_s_cp_error
Error extracting channel bindings from token - Invalid length	gssdce_s_bindings_length_error
error flushing "%s": %s	tcl_s_unixaz_error_flushing
error getting working directory name: %s	tcl_s_unixaz_error_with_cwd_name
Error in communication with agent.	KDDS11216-E

Message Text	Symbolic Name
Error in getting initial login context.	dcp_s_initial_context_fail
error in reading file "%s": "%s"	tcl_s_unixutil_err_read_file
Error in rpc_mgmt_is_server_listing() call: %s	dts_s_mgmt_srvr_listening
Error in watchdog connection.	KDDS11803-E
Error loading clearinghouse from disk. Cannot create a directory that's in the chdirs attribute, %s.	cds_s_insertdirstore
Error loading clearinghouse from disk. Cannot create directory store. Status = %ld	cds_s_pseudo_load
Error loading clearinghouse from disk. Cannot find a directory that's in the chdirs attribute, %s.	cds_s_finddir
Error logging file taken.	KDDS12402-I
Error obtaining auxiliary login-context expiration (%x)	gss_s_gac_err_ctx_exp1
Error obtaining login-context expiration (%x)	gss_s_gac_err_ctx_exp
Error occurred replaying log entry and so skipped	sec_rsdb_logent_replay_err
Error occurred while acquiring group entries.	pwd_exp_rgy_error_group
Error occurred while acquiring passwd entries.	pwd_exp_rgy_error_passwd
Error occurred while fetching data	sec_rsdb_fetch_error
Error opening cache file %s for read: status = %ld.	cds_s_cache_opencache
Error opening cache version file %s for write: status = %ld.	cds_s_cache_createversion

Message Text	Symbolic Name
Error opening cache version file %s for write: status = %ld.	cds_s_cache_createcache
Error opening the keyfile.	sec_pk_e_kf_open_err
Error overflow.	GST_ERR_OVERFLOW
Error purging login-context (%x)	gss_s_ic_error_purging
Error reading cache file %s: status = %ld.	cds_s_cache_readcache
Error reading cache version file %s: status = %ld.	cds_s_cache_readversion
error reading from output pipe: %s	tcl_s_unixaz_error_read_from_out_pipe
error reading "%s": %s	tcl_s_unixaz_error_reading
error reading stderr output file: %s	tcl_s_unixaz_error_read_stderr
Error reading the keyfile.	sec_pk_e_kf_read_err
Error replaying log	sec_rs_log_replay_err
Error retrieving current software version n%s	sec_rep_cant_get_sw_rev_fatal
Error retrieving security configuration information: %s	dts_s_security_init
Error return from gdb_* function.	CDS_GDB_ERROR
Error setting local host's key	sec_res_host_key_set_err
Error storing master_key in databasens	sec_rgy_mky_store_db
Error trying to load a clearinghouse from disk into memory: status = %ld.	cds_s_server_loadfail_eb
Error trying to obtain cell information for X.500: status = %ld.	cds_s_addcell_cellinfo
Error unwrapping per-message token (%x)	gss_s_dmh_unwrap_failed
error waiting for process to exit: %s	tcl_s_unixaz_error_wait_exit
Error when adding principal to org "%s" - %sn	pwd_imp_err_add_org_member

Message Text	Symbolic Name
Error when adding "%s" - %sn	pwd_imp_err_add_pgo
Error while calculating the country bitlist.n	GDS_S_CBL_ERR
error while matching pattern: %s	tcl_s_cmdmz_err_while_match_pat
error while matching regular expression: %s	tcl_s_tclutil_reg_match_err
Error with socket	CDS_SOCKET
error writing "%s": %s	tcl_s_unixaz_error_writing
Error writing the keyfile.	sec_pk_e_kf_write_err
Event Classes:	aud_s_evt_classes
event "%s" hasn't occurred yet	tcl_s_hist_evt_has_not_occurred
event "%s" is too far in the past	tcl_s_hist_evt_too_far_past
Exactly one server principal required	dced_s_need_one_server_prin
Exception in routine at %x, running down context %x of client %x	rpc_m_ctxrundown_exc
Exception name %1\$s referenced in ACF is not defined	NIDL_EXCNOTDEF
Exec failed (%d).	pks_s_exec_fail
Exec failed (E2BIG).	pks_s_exec_e2big
Exec failed (EACCES).	pks_s_exec_eaccess
Exec failed (ELOOP).	pks_s_exec_eloop
Exec failed (ENAMETOOLONG).	pks_s_exec_enametoolong
Exec failed (ENOENT).	pks_s_exec_enoent
Exec failed (ENOEXEC).	pks_s_exec_enoexec
Exec failed (ENOMEM).	pks_s_exec_enomem
Exec failed (ENOTDIR).	pks_s_exec_enotdir
Exit database generation program gdsgendb.n	GDS_S_EXIT_GENDB

Message Text	Symbolic Name
Exit DSA of Directory ID: %d.n	GDS_S_EXITDSA
Exit DUA-cache process	GDS_S_EXITCACHE
Exit due to signal number %d request	cds_s_child_signal_eg
Exit due to signal. sigwait(2) returned system error: %ld.	cds_s_child_sigwait_eb
Exit monitor process	GDS_S_EXITMONITOR
Exiting because thread creation failed.n	sec_rs_thr_exit_creat_fail
Exiting because of error loading the cache.	cds_s_child_cacheload_eb
Expected a floating point argument for '%s' but received '%s'.	dcp_s_expected_float_arg
expected boolean value but got "%s"	tcl_s_get_exp_boolean_but
expected floating-point number but got "%s"	tcl_s_get_exp_float_but
Expected integer argument for '%s' but received '%s'.	dcp_s_expected_int_arg
expected integer but got "%s"	tcl_s_get_exp_integer_but
expected integer or "end" but got "%s"	tcl_s_cmdil_expect_int_or_end
expected integer or "end" but got "%s"	tcl_s_cmdmz_expt_int_or_end
expression didn't have numeric value	tcl_s_expr_non_numeric_exp
Extended attribute internal error.	dcp_s_rgy_era_internal_error
extra characters after close-brace	tcl_s_parse_extra_char_brace
extra characters after close-quote	tcl_s_parse_extra_char_quote
extra switch pattern with no body	tcl_s_cmdmz_extra_switch_pat_no_body
Failed converting clearinghouse uuid from global directory : status = %ld.	cds_s_gda_badchuuid
Failed converting namespace uuid from global directory : status = %ld.	cds_s_gda_badnsuuid

Message Text	Symbolic Name
Failed to access Bindery: error code xxx.	KDDS11215-E
Failed to access master key file.	KDDS02252-E
Failed to access Mount point xxx.	KDDS11665-E
Failed to access semaphore.	KDDS02540-E
Failed to access status logging file. xxx:yyy (zzz)	KDDS02161-E
Failed to access trace file. xxx:yyy (zzz)	KDDS02103-E
Failed to add Time Service entry to LAN profile %s: %s	dts_s_tservicev1_profile_add
Failed to bind an address to the socket.	KDDS02561-E
Failed to bind to registry site %snt%s	sec_site_bind_fail
Failed to change DCE effective login period. aaa:xxx	KDDS02250-E
Failed to connect with agent.	KDDS11607-E
Failed to continue DFALIB handling.	KDDS11807-E
Failed to convert host name to host UUID: %s	dts_s_pgo_name_id
Failed to copy back the file to DFS.	KDDS11401-E
Failed to create databasen%s	sec_rgy_db_create
Failed to create dtsd global data mutex attribute	dts_s_mutexattr_create
Failed to create new databasen%s	sec_crdb_db_not_created
Failed to created thread %s	sec_rs_thr_create_fail
Failed to determine if server is in security group: %s	dts_s_pgo_is_member
Failed to export bindings to %s :status = %ld	cds_s_gda_export
Failed to export Time Control interface to the namespace: %s	dts_s_export_control

Message Text	Symbolic Name
Failed to export Time Control V1 interface to the namespace: %s	dts_s_export_tservicev1
Failed to export Time Control V2 interface to the namespace: %s	dts_s_export_tservicev2
Failed to find file on dced import attempt	dced_s_import_cant_access
Failed to fork.	KDDS02600-E
Failed to generate system communication process. xxx	KDDS02281-E
Failed to generate trace process. xxx	KDDS02280-E
failed to get last attr in seq list	sec_attr_cant_get_instance
Failed to get memory dump.	KDDS11035-E
failed to get next attr instance in seq list	sec_attr_cant_get_attrinst
Failed to initialise server management DACL	cds_s_server_dacl_eb
Failed to initialize administration threads.	KDDS11641-I
Failed to initialize dtsd global data mutex attribute	dts_s_mutex_init
Failed to initialize gateway: error code xxx.	KDDS11012-E
Failed to initialize RPC memory allocation: %s	dts_s_rpc_sm_enable
Failed to initialize server interfaces.	cds_s_server_sec_eb
Failed to initialize the Global Directory Agent ACL : status = %ld	cds_s_gda_acl_init
Failed to initialize the Global Directory Agent ACL from file %s	cds_s_gda_acl_file
Failed to initialize volume %s.	KDDS11633-I
Failed to load DFALIB.NLM.	KDDS11804-E

Message Text	Symbolic Name
Failed to modify effective period of DCE login.	KDDS11810-I
Failed to modify master key.	KDDS11207-E
Failed to obtain lock, semaphore operation structure already locked	cds_s_cache_islocked_a
Failed to open file associated with dced object	dced_s_cant_open_storage_file
Failed to open file associated with pks object	pks_s_cant_open_storage_file
Failed to open file %s	sec_sys_file_open_fail
Failed to open log file	sec_rs_log_open_fail
Failed to open logfile xxx.	KDDS11018-E
Failed to open master key file. File has no access right.	KDDS01300-E
Failed to open socket.	KDDS02560-E
Failed to open status logging file. xxx	KDDS02160-E
Failed to open the hostdata postprocessor list file	dced_s_postprocessor_file_fail
Failed to open trace file. (xxx)	KDDS02102-E
Failed to read agent options.	KDDS11047-E
Failed to read gateway Other options.	KDDS11048-E
Failed to read gateway volume options.	KDDS11046-E
Failed to read string bindings for local dts from file: %s	dts_s_read_bindings
Failed to read volume information of xxx.	KDDS11603-E
Failed to rebind to an alternate registry siten%s	sec_site_rebind_fail
Failed to rebind to an alternate registry to retry operation	sec_rca_site_rebind_fail

Message Text	Symbolic Name
Failed to record communication logging: (hh:mm:ss wcode=x	KDDS12201-E
Failed to refresh server identity: status = %ld.	cds_s_library_refresh
Failed to refresh server identity: status = %ld.	cds_s_library_refresh_eb
Failed to refresh the server's identity: %s	dts_s_refresh_identity
Failed to register DFALIB.	KDDS11805-E
Failed to register Serviceability interface with endpoint map: %s	dts_s_ep_register_serviceability
Failed to register Serviceability interface with runtime: %s	dts_s_srvr_serviceability
Failed to register the rsdb keystore.	sec_pk_e_rsdb_keystore_err
Failed to register Time Control V1 interface with endpoint map: %s	dts_s_tservicev1_ep_register
Failed to register Time Control Version 2.0 interface with endpoint map: %s	dts_s_ep_register_controlv2
Failed to register Time Control Version 2.0 interface with runtime: %s	dts_s_srvr_controlv2
Failed to release lock, semaphore operation structure not locked	cds_s_cache_nolocked_a
Failed to remove file belonging to dced object	dced_s_cant_remove_storage_file
Failed to remove file belonging to pks object	pks_s_cant_remove_storage_file
Failed to remove Service interface from the profile %s: %s	dts_s_tserver_profile_remove
Failed to retrieve cell name: %s	dts_s_cell_name
Failed to retrieve Cell UUID: %s	dts_s_id_parse_name

Message Text	Symbolic Name
Failed to retrieve server binding from the namespace: %s	dts_s_binding_import_next
Failed to retrieve server bindings from RPC runtime: %s	dts_s_inq_bindings
Failed to send a message: xxx yyy	KDDS02330-E
Failed to set locale: C locale is assumed (xxx).	KDDS01107-E
Failed to set mutex attributed kind	dts_s_mutexattr_setkind
Failed to set the expiration age for server binding handle: %s	dts_s_set_exp_age
Failed to start agent.	KDDS02006-E
Failed to start xxx.	KDDS11004-E
Failed to suspend MainThread.	KDDS11011-E
Failed to unexport Control interface from the namespace: %s	dts_s_control_unexport
Failed to unexport dtsd ACL manager interface: %s	dts_s_unexport_acl_mgr
Failed to unexport Service interface from the namespace: %s	dts_s_service_unexport
Failed to unregister Control interface from the endpoint map: %s	dts_s_control_ep_unregister
Failed to unregister dtsd ACL manager interface: %s	dts_s_unregister_acl_mgr
Failed to unregister Service interface from the endpoint map: %s	dts_s_service_ep_unreister
Failed to unregister Serviceability interface from the endpoint map: %s	dts_s_svc_ep_unregister
Failed to validate the servers identity: %s	dts_s_validate_srvr_id
Failed to write local string bindings for dtsd to file: %s	dts_s_write_bindings

Message Text	Symbolic Name
Failed to write to master key file: xxx.	KDDS01305-E
Failure	dts_s_failed
Failure converting name to X.500 object.	cds_s_addcell_nameobj
Failure in retrieving DTS attributes from dced: %s	dts_s_inq_attr
Failure in sec_key_mgmt_manage_key() routine: %s	dts_s_sec_key_mgmt
Failure retrieving profile entry from host: %s	dts_s_cf_profile_name
Fatal command parser error reading table %s	dts_s_prsfile_fatal
Fatal error adopting new software version (%d)nCurrent sw version = (%d): status = %s	sec_rep_adopt_sw_rev_fatal
Fatal error occurred in gateway xxx.	KDDS02134-I
Fatal error parsing command:	dts_s_prsact_fatal
Fatal exception while holding global %s lock	sec_rs_global_lock_fatal_exc
Fatal exception while holding %s %s lock	sec_rs_lock_fatal_exc
Fatal internal error (Registry Edit Kernel)	ek_kernel_failure
Fault address error	rpc_s_fault_addr_error
Fault client stub not linked into application	rpc_s_fault_no_client_stub
Fault codeset conversion error	rpc_s_fault_codeset_conv_error
Fault context mismatch	rpc_s_fault_context_mismatch
Fault floating point divide by zero	rpc_s_fault_fp_div_by_zero
Fault floating point error	rpc_s_fault_fp_error
Fault floating point overflow	rpc_s_fault_fp_overflow
Fault floating point underflow	rpc_s_fault_fp_underflow

Message Text	Symbolic Name
Fault illegal instruction	rpc_s_fault_ill_inst
Fault integer divide by zero	rpc_s_fault_int_div_by_zero
Fault integer overflow	rpc_s_fault_int_overflow
Fault invalid bound	rpc_s_fault_invalid_bound
Fault invalid tag	rpc_s_fault_invalid_tag
Fault pipe closed	rpc_s_fault_pipe_closed
Fault pipe communication error	rpc_s_fault_pipe_comm_error
Fault pipe discipline	rpc_s_fault_pipe_discipline
Fault pipe empty	rpc_s_fault_pipe_empty
Fault pipe memory	rpc_s_fault_pipe_memory
Fault pipe order	rpc_s_fault_pipe_order
Fault remote communication failure	rpc_s_fault_remote_comm_failure
Fault remote no memory	rpc_s_fault_remote_no_memory
Fault unspecified	rpc_s_fault_unspec
fcntl call failed for command %d, errno = %d.	GDS_S_FCNTL_ERR
Feature not supported in kernel	rpc_s_not_in_kernel
field not modifiable	sec_attr_field_no_update
field width may not be specified in %c conversion	tcl_s_cmdmz fld_width_not_be_specified_in_c_conv
File = %s: Line = %d: Error = %s (near String = '%s').n	csrc_s_lex_error
File %1\$s, line %2\$lu	NIDL_LINEFILE
File %1\$s, line %2\$lu: %3\$s	NIDL_FILESOURCE
File %1\$s not found	NIDL_FILENOTFND
File access error.	KDDS10017-E
File already exists on attempt to create dced object	dced_s_import_already_exists

Message Text	Symbolic Name
File containing ASCII/EBCDIC translation tables is damaged	rpc_s_ss_char_trans_short_file
File could not be closed, errno = %d.	GDS_S_FCLOSE_ERR
File could not be closed, errno = %d.	GDS_S_CLOSE_ERR
File could not be flushed, errno = %d.	GDS_S_FFLUSH_ERR
File could not be read, errno = %d.	GDS_S_FREAD_ERR
File could not be read, errno = %d.	GDS_S_READ_ERR
File could not be truncated (file descriptor = %d)	sec_sys_file_ftruncate_fail
File could not be written, errno = %d.	GDS_S_FWRITE_ERR
File could not be written, errno = %d.	GDS_S_WRITE_ERR
File is not a directory: %1\$s	NIDL_FILENOTDIR
File open failed	dce_cf_e_file_open
File read failed (file descriptor = %d)	sec_sys_file_read_error
File %s could not be closed.n	gsu_fclose_error
File %s could not be opened, errno = %d.n	GDS_S_SUP_FOPEN_ERR
File %s could not be opened in mode "%o", errno = %d.	GDS_S_OPEN_ERR
File %s could not be opened in mode '%s', errno = %d.	GDS_S_FOPEN_ERR
File %s could not be opened.n	gsu_fopen_error
File %s does not existn	gsu_existing_error
file "%s" isn't open	tcl_s_unixutil_file_not_open
File <%s> not completely evaluated : %s.n	gc_i_warning_file_eval
File seek failed (file descriptor = %d)	sec_sys_file_lseek_fail
File specification required for %1\$s	NIDL_FILESPECREQ
File system full.	KDDS02580-E

Message Text	Symbolic Name
File write failed (file descriptor = %d)	sec_sys_file_write_error
File-Access administrator failed to log in.	KDDS11605-E
File-access administrator is not registered.	KDDS11604-E
first index must not be greater than second	tcl_s_cmdil_fst_idx_greater_than_second
Fixup_registry_context - Bind failed (%x), retrying	gss_s_frc_bind_retrying
Fixup_registry_context in pac_to_name failed (%x)	gss_s_ptn_frc_failed
Floating point constants not supported	NIDL_FLOATCONSTNOSUP
floating-point value too large to represent	tcl_s_expr_float_val_too_large
floating-point value too small to represent	tcl_s_expr_float_val_too_small
For cellname commands, the CDS_DirectoryVersion attribute is required to be 4.0 or greater.	CDS_LOWDIRVERSION
For delegation support, the CDS_DirectoryVersion attribute is required to be 4.0 or greater.	cds_s_delegdirversion
For high convergence Tue Oct 16 09:43:06 1990	CDS_PROPAGATE_FAIL
Foreign account not specified.	dcp_s_rgy_con_no_faccount
Foreign cell is not registered or has been removed	aud_s_unknown_cell_rc
Foreign cell %s is not registered or has been removed	aud_s_unknown_cell
Foreign group is not registered or has been removed	aud_s_unknown_foreign_group_rc
Foreign group name not specified.	dcp_s_rgy_no_fgroup
Foreign group %s is not registered or has been removed	aud_s_unknown_foreign_group

Message Text	Symbolic Name
Foreign organization name not specified.	dcp_s_rgy_con_no_forg
Foreign principal is not registered or has been removed	aud_s_unknown_foreign_principal_rc
Foreign principal %s is not registered or has been removed	aud_s_unknown_foreign_principal
Foreign quota for realm exhausted	sec_rgy_foreign_quota_exhausted
forked process couldn't set up input/output	tcl_s_unixutil_forked_proc_useless
Format error - %s.	gc_t_format_error
Format error - %s.	gc_t_omx_format_error
Format error in event class file %s.	aud_s_invalid_event_class_file
Format error in the Attribute Definition Block.	gc_t_omx_attr_format_error
Format error in the Object Class Definition Block.	gc_t_omx_obj_format_error
Format error in the OM Class Definition Block.	gc_t_omx_class_format_error
format string ended in middle of field specifier	tcl_s_cmdah_fmt_str_ended_in_middle
Free_creds - sec_cred_free_cred_handle failed (%x)	gss_s_free_cred_handle_fail
Full name text is too long (Registry Edit Kernel)	ek_err_fullname_too_long
Full pointers to context handles are not allowed	NIDL_PTRCTXHAN
Function pointer parameters cannot be of type handle_t	NIDL_FPHANPRM
Function pointers are allowed only in local interfaces	NIDL_FPLOCINT

Message Text	Symbolic Name
Function pointers are not valid as elements of conformant arrays	NIDL_FPCFMTARR
Function pointers are not valid as members of unions	NIDL_FPUNIMEM
Function pointers are not valid as structure fields	NIDL_FPSTRFLD
Function pointers in an operation must be [in] parameters	NIDL_FPINPRM
Function types are allowed only in local interfaces	NIDL_FUNTYPDCL
Gateway and agent have different master keys.	KDDS11210-E
Gateway detected self-contradiction: error code xxx.	KDDS11201-E
Gateway detected unknown error.	KDDS11205-E
Gateway detected unknown error: error code xxx.	KDDS11681-E
Gateway failed to access file 'bindery'	KDDS22410-E
Gateway global resources are being freed.	KDDS11053-I
Gateway initialization completed normally.	KDDS11049-I
Gateway initialization started.	KDDS11003-I
Gateway is not registered with agent.	KDDS11208-E
Gateway is not running on xxx.	KDDS22403-W
Gateway or agent ran out of memory.	KDDS22409-E
Gateway process termination started.	KDDS11051-I
Gateway process will be terminated.	KDDS11052-I
Gateway ran out of memory.	KDDS11214-E

Message Text	Symbolic Name
Gateway user xxx has been logged out from DCE.	KDDS11226-I
Gateway user xxx will be logged out from DCE due to	KDDS12002-E
Gateway user xxx will be logged out from DCE due to	KDDS11414-E
Gateway volume information contains invalid data. The invalid	KDDS10023-W
Gateway volume xxx ran out of disk blocks.	KDDS11672-E
Gateway volume xxx ran out of disk space.	KDDS11671-E
Gateway watchdog connection will be closed.	KDDS11824-I
Gateway watchdog initialization completed.	KDDS11821-I
Gateway watchdog initialization started.	KDDS11820-I
Gateway watchdog will be restarted.	KDDS11823-I
Gateway watchdog will be suspended.	KDDS11822-I
Gateway watchdog will be terminated.	KDDS11825-I
Gateway xxx is not registered with master key file.	KDDS01301-E
gdscp: File %s does not exist.n	gc_i_file_does_not_exist
gdscp: Incorrect usage.n	gc_i_incorrect_usage
gen_name failed in pac_to_name (%x)	gss_s_ptn_gn_failed
get_configuration failure	uuid_s_getconf_failure
Gateway is active on xxx file servers in network.	KDDS22301-I
GetFileServerID failed: error code xxx.	KDDS11040-E

Message Text	Symbolic Name
get_preferred_member: No cell alias detected.	cds_s_server_aliasnoprd
GetServerInformation failed: error code xxx.	KDDS11039-E
GetVolumeNumber failed: error code xxx.	KDDS11009-E
GetVolumeStatistics failed: error code xxx.	KDDS11041-E
Global Directory Agent exiting.	cds_s_gda_eg
Global name yields a principal in foreign cell, use referral	sec_id_e_foreign_cell_referral
Global server %s returned time %s which does not intersect computed time %s	dts_s_global_nointersect
Group already exists (Registry Edit Kernel)	ek_err_group_exists
Group does not exist (Registry Edit Kernel)	ek_err_group_does_not_exist
Group is not registered or has been removed	aud_s_unknown_group_rc
Group member not found	rpc_s_group_member_not_found
Group name contains an illegal character (Registry Edit Kernel)	ek_err_group_bad_name_chars
Group name exists in registry and UNIX ids match.n	pwd_imp_err_gname_exist_match
Group name exists in registry but UNIX ids don't match.n	pwd_imp_err_gname_exist_nmatch
Group name too long (Registry Edit Kernel)	ek_err_group_name_too_long
Group name too long.n	pwd_imp_err_gname_too_long
Group (%s) entry created	sec_rs_ns_grp_ent_create_succ
Group (%s) entry not created	sec_rs_ns_grp_ent_create_fail

Message Text	Symbolic Name
Group %s is not registered or has been removed	aud_s_unknown_group
group_%lun	pwd_imp_msg_temp_group_name
group_obj ACL entries not allowed in this ACL	acl_s_group_not_allowed
Groupset not valid	sec_login_s_groupset_invalid
gss_build_prot_message failed (%x)	gss_s_sign_bpm_failed
gss_cred_get_delegation_type: sec_cred_get_initiator failed (%x)	gss_s_gdt_scgi_failed
gss_cred_get_delegation_type: sec_cred_initialize_cursor failed (%x)	gss_s_gdt_scic_failed
gss_login_get_delegation_type: sec_login_get_initiator failed (%x)	gss_s_gdt_slgi_failed
gss_login_get_delegation_type: sec_login_initialize_cursor failed (%x)	gss_s_gdt_slic_failed
Has all the rights to %s.	KDDS23634-I
Has right to create files and subdirectories.	KDDS23612-I
Has right to create files and subdirectories.	KDDS23614-I
Has right to delete directories.	KDDS23616-I
Has right to delete files.	KDDS23618-I
Has right to modify access control list.	KDDS23626-I
Has right to modify directories.	KDDS23620-I
Has right to modify files.	KDDS23622-I
Has right to modify files.	KDDS23630-I
Has right to modify files and subdirectories.	KDDS23628-I
Has right to read files.	KDDS23606-I
Has right to read files.	KDDS23604-I

Message Text	Symbolic Name
Has right to search files.(F)	KDDS23624-I
Has right to search files.(F)*	KDDS23625-I
Has right to write to files.	KDDS23608-I
Has right to write to files.	KDDS23610-I
Hash table is full for objects of storage class %d	GDS_S_CACHE_HSHFULL_ERR
Header type is incorrectly specified.	db_s_bad_header_type
Helper process aborted	rpc_s_helper_aborted
Helper process catatonic	rpc_s_helper_catatonic
Helper process not running	rpc_s_helper_not_running
Helper process too busy	rpc_s_helper_overflow
hi guard byte %d is 0x%x t%cn	tcl_s_ckalloc_hi_guard_byte
high guard failed at %lx, %s %dn	tcl_s_ckalloc_hi_guard_failed
Home directory pathname is too long after canonicalization	sec_rgy_homedir_too_long
Home directory pathname text is too long (Registry Edit Kernel)	ek_err_homedir_too_long
host configuration info not available	sec_login_s_config
I18N tags structure is not valid	rpc_s_ss_invalid_codeset_tag
iconv failed other than conversion operation	rpc_s_ss_iconv_error
identity to be refreshed is no longer valid	sec_login_s_refresh_ident_bad
IDL inheritance operator ':' is only valid for -lang cxx	NIDL_INHERITNOTVAL
Ignoring name conflict, as instructedn	pwd_imp_inf_ignore_conflict
illegal access mode "%s"	tcl_s_unixaz_illegal_access_mode
Illegal attribute value for cdsbyte style attribute.	dcp_s_cds_illegal_byte_attr

Message Text	Symbolic Name
Illegal cell name : %s	sec_rgy_mky_bad_cellname
Illegal character encountered in principal name.n	pwd_imp_err_pname_bad_char
Illegal combination of attributes specified on command line.	dcp_s_rgy_era_illegal_attribute_list
Illegal combination of modify options specified on command line.	dcp_s_rgy_era_illegal_switches
Illegal directory-ID type parameter (directory-ID = %d)	GDS_S_IPCDIRIDIL_ERR
Illegal 'distributed command parameter size' parameter	GDS_S_IPCPARSZIL_ERR
Illegal dts command:	dts_s_bad_command
Illegal format - parse table file %s	dts_s_prsfile_format
Illegal interpretation %d of a Distinguished Name %b	GDS_S_ILL_DN_INTRPRTN
Illegal IPC-association-ID parameter (association-ID = %d)	GDS_S_IPCASIDIL_ERR
Illegal IPC-buffer reference parameter (buffer reference = %#x)	GDS_S_IPCMREFIL_ERR
Illegal IPC-data fragment parameter (data fragment = %d)	GDS_S_IPCMTYPIL_ERR
Illegal IPC-event mode parameter (event mode = %d)	GDS_S_IPCEVMOIL_ERR
Illegal IPC-invoke information parameter (invoke-ID = %d,	GDS_S_IPCINVIL_ERR
Illegal IPC-invoke-PDU length parameter (PDU-length = %d)	GDS_S_IPCILNIL_ERR
Illegal IPC-operation-ID parameter (operation-ID = %d)	GDS_S_IPCOPIDIL_ERR
Illegal IPC-process type parameter (process type = %d)	GDS_S_IPCPTYPEIL_ERR

Message Text	Symbolic Name
Illegal IPC-result type parameter (result type = %d)	GDS_S_IPCRSTYIL_ERR
Illegal IPC-result-PDU length parameter (PDU-length = %d)	GDS_S_IPCRLNIL_ERR
Illegal IPC-server mode parameter (server mode = %d)	GDS_S_IPCSVMOIL_ERR
Illegal IPC-server-ID parameter (server-ID = %d)	GDS_S_IPCSVIDIL_ERR
Illegal IPC-version number parameter (version = %d)	GDS_S_IPCVERSIL_ERR
Illegal IPC-wait time parameter (wait time type = %d)	GDS_S_IPCWTPIL_ERR
illegal keep count "%s"	tcl_s_hist_illegal_keep_count
Illegal key for policy data	sec_rsdb_bad_policy_key
Illegal 'max. # of distributed command entries' switch value	GDS_S_IPCMXDIST_ERR
Illegal 'max. # of IPC-client entries' switch value	GDS_S_IPCMXCLT_ERR
Illegal 'max. # of IPC-heap buffer entries' switch value	GDS_S_IPCMXHP_ERR
Illegal 'max. # of IPC-registration entries' switch value	GDS_S_IPCMXREG_ERR
Illegal 'max. # of IPC-server entries' switch value	GDS_S_IPCMXSRV_ERR
Illegal 'max. # of IPC-user credential entries' switch value	GDS_S_IPCMXCRD_ERR
Illegal 'max. IPC-communication buffer size' switch value	GDS_S_IPCMXBUFS_ERR
Illegal name %s	sec_crdb_cl_bad_name
Illegal number of timeout values specified.	dcp_s_cds_bad_timeout_value

Message Text	Symbolic Name
Illegal PGO or directory name	sec_rgy_bad_name
Illegal process state detected	GDS_S_ILLSTATE_ERR
Illegal process state parameter (process state = '%s')	GDS_S_IPCSTATEIL_ERR
Illegal process unload factor parameter (unload factor = %d)	GDS_S_IPCUNLDIL_ERR
illegal search identifier "%s"	tcl_s_tclvar_illegal_search_id
Illegal state transition detected in CN client association group state machine [cur_state: %d, cur_event: %d, grp: %x]	rpc_m_cn_ill_state_trans_cg
Illegal state transition detected in CN client association state machine [cur_state: %s, cur_event: %s, assoc: %x]	rpc_m_cn_ill_state_trans_ca
Illegal state transition detected in CN client call state machine [cur_state: %d, cur_event: %d, call_rep: %x]	rpc_m_cn_ill_state_trans_cr
Illegal state transition detected in CN server association group state machine [cur_state: %d, cur_event: %d, grp: %x]	rpc_m_cn_ill_state_trans_sg
Illegal state transition detected in CN server association state machine [cur_state: %s, cur_event: %s, assoc: %x]	rpc_m_cn_ill_state_trans_sa
Illegal state transition detected in CN server call state machine [cur_state: %d, cur_event: %d, call_rep: %x]	rpc_m_cn_ill_state_trans_sr
Illegal state/event combination detected (state = %d,	GDS_S_ILLSTATE_EVENT_ERR
Illegal switch (switch = -%c)nvalid switches are:n	GDS_S_IPCUNKNOWN_ERR
Illegal timeout parameter (timeout = %d sec)	GDS_S_IPCTMOUTIL_ERR
illegal use of or & in command	tcl_s_unixutil_illegal_use_pipeline

Message Text	Symbolic Name
illegal use of default sec login handle	sec_login_s_default_use
Illegal use of '-type' option.	dcp_s_rgy_bad_use_of_types_option
Implementation specific error	CDS_CLERKBUG
Import Group's UNIX id exists in registry.n	pwd_imp_err_guid_exists
Import Principal's UNIX id exists in registry.n	pwd_imp_err_puid_exists
Importing IDL file %1\$s	NIDL_IMPORTIDL
Improper nesting of alert scope	cma_s_alert_nesting
Improper syntax used when attempting to remove an 'any' attribute.	dcp_s_rgy_era_any_illegal_remove
improper value for precision	tcl_s_tclutil_improp_val_prec
in IEEE 802 address file	utils_s_802_uname_failure
Inaccessible or absent configuration file.	pks_s_no_config_file
Inappropriate authentication checksum type	rpc_s_auth_inapp_cksum
Incompatible options (Registry Editor/TTY Interface)	tty_incompatible_options
Incomplete account name (Registry Edit Kernel)	ek_err_incomplete_login_name
Incomplete login name specification	sec_rgy_incomplete_login_name
Incomplete name	rpc_s_incomplete_name
Incomplete operation - Referral returned : %s.n	gc_t_incomplete_referral_returned
Incomplete override entry, cannot proceed.	sec_login_s_incomplete_ovrd_ent
Inconsistent cache data base	GDS_S_CACHE_INCONS_ERR
Inconsistent IPC-message	GDS_S_CACHE_INCONSMSG_ERR

Message Text	Symbolic Name
Inconsistent NSAP-address information (length = %d)	GDS_S_NDS_NSAP_ERR
Inconsistent TSAP-address information (length = %d)	GDS_S_NDS_TSAP_ERR
Inconsistent T-selector information (length = %d)	GDS_S_NDS_TSEL_ERR
Incorrect authentication message direction	rpc_s_auth_baddirection
Incorrect mechanism in mutual response token	gss_s_ic_mutual_bad_mech
Incorrect network address in authentication request	rpc_s_auth_badaddr
Incorrect number of values for attribute type.	dcp_s_rgy_era_wrong_num_values
incorrect response to challenge	sec_s_bad_nonce
Incorrect sequence number in authentication message	rpc_s_auth_badseq
Incorrect syntax for pointer to conformant array	NIDL_PTRCFMTARR
Index out of range	pkc_s_index_out_of_range
Index type in flags parameter does not match type in database	db_s_index_type_mismatch
Index type is not known or incorrectly specified.	db_s_bad_index_type
Information not available	sec_login_s_info_not_avail
Inherited interfaces must be imported: %1\$s	NIDL_INHERITNOTDEF
Initialization completed successfully	sec_rep_init_slave_succ
initialization encryption key not valid	sec_rgy_rep_init_ekey_invalid
Initialization error - Can't create mutex attributes	pkc_s_init_cant_create_mutexattr

Message Text	Symbolic Name
Initialization error - Can't initialize mutex attributes	pkc_s_init_cant_init_mutexattr
Initialization error in watchdog connection.	KDDS11802-E
Initialization failed.	pkc_s_init_error
Initialization failed : %s	sec_rep_init_slave_fail
Initialization failure.	pkc_s_initialization_failure
Initialization of RPC interface has failed.	cds_s_server_rpc_eb
Initialization was interrupted.	dced_s_startup_interrupted
Initializing credentials failed for auth. mech. %d, name of	GDS_S_INIT_SEC_ERR
init_id from slave doesn't match master's init_id for the replica	sec_rgy_rep_bad_init_id
Input arguments too big	rpc_s_in_args_too_big
Input data length exceeds allocated buffer size (Registry Editor/TTY Interface)	tty_err_input_too_long
Input is too long.n	pwd_imp_err_input_too_long
Input not in the expected format (Registry Editor/TTY Interface)	tty_bad_data_format
Input out of range (Registry Editor/TTY Interface)	tty_input_out_of_range
Insufficient information. Variables expected: %d, read: %d.	GDS_S_INSUFF_INFO
Insufficient local resources	CDS_NONSRESOURCES
Insufficient memory.	KDDS10026-E
Insufficient memory.	KDDS11037-E
Insufficient memory.	KDDS11613-E
Insufficient memory for public key operation.	sec_pk_e_no_memory

Message Text	Symbolic Name
Insufficient memory to display tower.n	CDCSCP_NOMEM
Insufficient memory to perform operation.	gc_t_om_memory_insufficient
Insufficient memory to perform operation.	gc_t_omx_memory_insufficient
Insufficient memory to perform operation.n	gc_t_memory_insufficient
Insufficient resources to process request	CDS_RESOURCEERROR
Insufficient rights to perform requested operation	CDS_ACCESSDENIED
Insufficient room in buffer	CDS_NOROOM
Insufficient size limit.	gc_t_size_limit_exceeded
Insufficient time limit.	gc_t_time_limit_exceeded
Insufficient virtual memory	dts_server_no_memory
Insufficient virtual memory for allocation attempt.	gssdce_s_out_of_memory
Integer constant %1\$s is invalid	NIDL_INTCONSTINVAL
Integer division by zero	NIDL_INTDIVBY0
Integer value overflows %1\$s	NIDL_INTOVERFLOW
integer value too large to represent	tcl_s_expr_int_val_too_large
integrity error: EPAC seal mismatch.	sec_authn_s_bad_seal
Internal error - the wrong attribute was returned.	pkc_s_bad_attribute
Interactive read of the password failed.	dcp_s_login_bad_pw_read
Interface attributes [auto_handle] and [implicit_handle] cannot occur together	NIDL_CONFHANATTR
Interface attributes [code] and [nocode] cannot occur together	NIDL_INTCODEATTR
Interface attributes [in_line] and [out_of_line] cannot occur together	NIDL_INTLINEATTR

Message Text	Symbolic Name
Interface id not entered.	dcp_s_rpc_no_interface_id
Interface not found	rpc_s_interface_not_found
Interface reference %1\$s allowed only as target of a * or & pointer	NIDL_INTREFNOTALO
Interface UUID must be specified	NIDL_INTUUIDREQ
Interface version number not recognizable.	dcp_s_resolve_bad_version
Interface's stub/runtime version is unknown	rpc_s_unknown_stub_rtl_if_vers
Interface's version is unknown	rpc_s_unknown_ifspec_vers
Intermediate code sets should not exceed %d.n	csrc_s_too_many_intermediate
Internal cache error -	pwd_imp_err_internal_cache
Internal directory store became corrupt. Exiting server to preserve permanent database. Status = %ld	cds_s_gdb_corrupt_dirstore
internal disaster	tcl_s_tclregexp_int_disaster
Internal error.	pkc_s_asn_internal_error
Internal error.	pkc_s_internal_error
Internal error	uuid_s_internal_error
Internal error - A key usage other than PRIVACY or INTEGRITY was specified	gssdce_s_no_such_key
Internal error - Attempt to shift window backwards.	gss_s_wnd_reverse
Internal error. The credential is corrupt.	gssdce_s_credential_corrupt
internal error: bad linked variable type	tcl_s_link_bad_linked_var_type
Internal error: command function %d not handled.n	CDSCP_CMD_DFL
internal error in sec_login	sec_login_s_internal_error
internal error in Tcl_SplitList	tcl_s_tclutil_internal_err_splitlist

Message Text	Symbolic Name
internal error: linked variable couldn't be read	tcl_s_link_linked_var_unreadable
Internal error (nnn)	KDDS23100-E
Internal error storing unknown type %d.n	csrc_s_internal_unknown_type
Internal error.n	pwd_imp_err_internal_error
internal foulup	tcl_s_tclregexp_internal_foulup
Internal IDL compiler error: Module %1\$s, Line %2\$lu	NIDL_INTERNAL_ERROR
internal inconsistency found	tcl_s_tclregexp_internal_urp
internal local registry error	sec_lrgy_s_internal_error
International prefix of E.163-address missing	GDS_S_NDS_E163IP_ERR
International prefix of E.164-address missing	GDS_S_NDS_E164IP_ERR
International prefix of X.121-address missing	GDS_S_NDS_X121IP_ERR
invalid [] range	tcl_s_tclregexp_invalid_squ_range
Invalid Abbreviation.	gc_t_omx_invalid_abbrev
Invalid absolute DTS style time string.	dcp_s_clock_time_conversion_fail
Invalid access class %d detected.	GDS_S_ILL_ACC_CLASS
invalid access mode "%s": must be RONLY, WRONLY, RDWR, APPEND, CREAT, EXCL, NOCTTY, NONBLOCK, or TRUNC	tcl_s_unixaz_invalid_access_mode
Invalid access right %d detected.	GDS_S_ILL_ACC_RIGHT
Invalid ACL entry.	dcp_s_acl_inv_entry
invalid acl entry class	sec_acl_invalid_entry_class
Invalid ACL entry key.	dcp_s_acl_inv_entry_key
Invalid ACL entry type.	dcp_s_acl_inv_entry_type

Message Text	Symbolic Name
invalid acl handle	sec_acl_invalid_acl_handle
Invalid ACL manager name.	dcp_s_rgy_invalid_acl_mgr_name
Invalid ACL manager syntax.	dcp_s_rgy_invalid_acl_mgr_syntax
invalid acl manager type	sec_attr_bad_acl_mgr_type
Invalid acl manager type specified	dced_s_attr_invalid_manager_type
invalid acl object name	sec_acl_invalid_entry_name
Invalid acl_mgr_set specified	dced_s_attr_bad_acl_mgr_set
invalid acl_mgr_set specified	sec_attr_bad_acl_mgr_set
Invalid acronym %s for object class.n	GDS_S_SRT_NSTR_OC_ERR
Invalid acronym %s for structure rule table.n	GDS_S_SRT_NNAM_AT_ERR
Invalid action '%s', should be one of: default, ignore, error, trap,	dcp_s_signal_invalid_action
Invalid answer - "%s", please answer [yes no].	pwd_imp_err_bad_ask_y_n
Invalid argument	rpc_s_invalid_arg
Invalid argument	CDS_INVALIDARGUMENT
Invalid argument	EINVAL
Invalid argument "%s".	gc_i_invalid_argument
Invalid array bound type	NIDL_INVARRIND
Invalid attribute. Attribute is illegal in this syntax.	dcp_s_rgy_invalid_attribute
Invalid attribute matching rule (rule = %d)	GDS_S_CACHE_INVMATCH_ERR
Invalid attribute name flag.	cds_s_server_namebad_a
Invalid attribute name specified	dced_s_attr_bad_name
invalid attribute name specified	sec_attr_bad_name
Invalid attribute or policy value.	dcp_s_rgy_invalid_pvalue
Invalid attribute schema name specified	dced_s_attr_bad_sch_name

Message Text	Symbolic Name
Invalid attribute specification parameter in IPC-message.	GDS_S_CACHE_INVATTRS_ERR
Invalid attribute trying to start server	dced_s_sc_invalid_attr_type
Invalid attribute type was specified	dced_s_invalid_attr_type
Invalid attribute value - %s.	gc_t_omx_wrong_value
Invalid authentication message type	rpc_s_auth_msg_type
Invalid authentication params	sec_s_invalid_auth_params
Invalid authentication service.	dcp_s_rgy_era_invalid_authentication
Invalid authentication service detected %d.	cds_s_server_badauthn
invalid authentication service specified in binding auth_info	sec_attr_bad_bind_authn_svc
Invalid authorization service.	dcp_s_rgy_era_invalid_authorization
invalid authorization service specified in binding auth_info	sec_attr_bad_bind_authz_svc
Invalid authorization service: status code = %d	cds_s_server_badauthz
Invalid binding	rpc_s_invalid_binding
invalid binding information	sec_attr_bad_bind_info
Invalid binding syntax.	dcp_s_rgy_era_invalid_binding_syntax
Invalid call option	rpc_s_invalid_call_opt
Invalid case label type	NIDL_INVCASETYP
Invalid character input for conversion	rpc_s_ss_invalid_char_input
Invalid character literal	NIDL_INVCHARLIT
Invalid Class Name.	gc_t_omx_invalid_class_name
Invalid combination of unique_flag=true, query trigger,	dced_s_attr_bad_uniq_query_accept

Message Text	Symbolic Name
invalid combination of unique_flag=true, query trigger, and intercell_action=accept	sec_attr_bad_uniq_query_accept
invalid command name: "%s"	tcl_s_basic_invalid_cmd_name
invalid comment text specified	sec_attr_bad_comment
invalid compatibility mode	sec_priv_s_bad_compat_mode
Invalid compatibility mode selection.	sec_login_s_invalid_compat_mode
Invalid confidence level. Must be 'low', 'medium', or 'high'.	dcp_s_cds_invalid_confidence
Invalid configuration attribute %s specifiedn	dts_s_bad_attr
Invalid configuration option. %s : invalid character detected	KDDS02903-E
Invalid configuration option. %s : missing option value	KDDS02902-E
Invalid configuration option. %s : out of range	KDDS02904-E
Invalid configuration option. %s : undefined gateway	KDDS02905-E
Invalid configuration option detected. %s	KDDS02901-E
Invalid configuration type.n	gsu_config_type_failed
Invalid context handle in call to gss_verify	gss_s_vfy_inv_ctx
Invalid context handle in gss_sign	gss_s_sign_inv_ctx
Invalid context state in gss_build_prot_message	gss_s_bp_inv_state
Invalid context state in gss_extract_creds_from_sec_context	gss_s_xcc_inv_ctx_state
Invalid context state in gss_extract_PAC_from_sec_context	gss_s_xps_inv_ctx_state
Invalid context state in gss_sign	gss_s_sign_inv_ctx_state

Message Text	Symbolic Name
Invalid context state in gss_verify	gss_s_vfy_inv_ctx_state
Invalid context state in process_context_token	gss_s_pct_inv_ctx_state
Invalid context-handle (%d) passed to gss_process_context_token	gss_s_pct_inv_ctx
Invalid context-handle in gss_delete_sec_context	gss_s_dsc_inv_ctx
Invalid context-handle passed to gss_extract_creds_from_sec_context	gss_s_xcc_inv_ctx
Invalid context-handle passed to gss_extract_PAC_from_sec_context	gss_s_xps_inv_ctx
Invalid courier role.	dcp_s_dts_modify_invalid_courier_role
invalid credential cursor	sec_cred_s_invalid_cursor
invalid credential handle	sec_cred_s_invalid_auth_handle
Invalid credential handle in pac_to_name	gss_s_ptn_inv_cred
invalid cursor	sec_attr_bad_cursor
Invalid data - record too long (Registry Edit Kernel)	ek_misc_bad_data
Invalid data description length parameter in TP-routine call	GDS_S_INVDATA_ERR
Invalid data description length parameter in TP-routine call	GDS_S_NOTPBUF_ERR
Invalid data record	sec_rgy_bad_data
Invalid database keytype at line %d file %s.	cds_s_server_dbkeytype_a
Invalid database node type at line %d file %s.	cds_s_server_dbnodetype_a
Invalid DBSetMember_t pointers for timestamp check.	cds_s_server_aliasbadptr

Message Text	Symbolic Name
Invalid DCE group name.	KDDS10012-E
Invalid DCE password.	KDDS10010-E
Invalid DCE password	KDDS22005-E
Invalid DCE user name.	KDDS10009-E
Invalid debug level %ld.	GST_INV_DEBUG_LEVEL
Invalid default cell name.	dcp_s_acl_inv_cell_name
invalid delegation type	sec_priv_s_bad_deleg_type
Invalid delegation type selection.	sec_login_s_invalid_deleg_type
Invalid DFS mount point.	KDDS10004-E
Invalid directory identifier (directory-ID = %d)	GDS_S_CACHE_INVDIRID_ERR
Invalid directory identifier "%s".	gc_t_invalid_directory_id
Invalid distinguished name (DN) specification parameter in IPC-message.	GDS_S_CACHE_INVDNS_ERR
Invalid DTS style timestamp.	dcp_s_dts_time_conversion_fail
Invalid E.163-address (size = %d, %d <= size <= %d)	GDS_S_NDS_E163V_ERR
Invalid E.164-address (size = %d, %d <= size <= %d)	GDS_S_NDS_E164V_ERR
Invalid encoded attribute.	gc_t_om_encoding_invalid
Invalid encoding type (Registry Edit Kernel)	ek_err_attr_bad_enc_type
Invalid encoding type specified	dced_s_attr_bad_encoding_type
invalid encoding type specified	sec_attr_bad_encoding_type
Invalid endpoint database	ept_s_database_invalid
Invalid endpoint entry	ept_s_invalid_entry
Invalid endpoint format for remote host	rpc_s_invalid_endpoint_format
Invalid endpoint map or lookup context	ept_s_invalid_context

Message Text	Symbolic Name
Invalid epoch. The value must be in the range of [0..255].	dcp_s_clock_set_invalid_epoch
Invalid file specification: %1\$s	NIDL_INVFILESPEC
Invalid filter syntax (syntax = %d)	GDS_S_CACHE_INVFILT_ERR
Invalid guide supplied	aud_s_invalid_guide
Invalid handle.	pkc_s_invalid_handle
Invalid hostname.	KDDS11017-E
Invalid inquiry context	rpc_s_invalid_inquiry_context
Invalid inquiry type	rpc_s_invalid_inquiry_type
Invalid intercell action.	dcp_s_rgy_invalid_intercell_action
Invalid intercell action specified	dced_s_attr_bad_intercell_action
invalid intercell action specified	sec_attr_bad_intercell_action
Invalid interface version option	rpc_s_invalid_vers_option
Invalid IPC-message tag (tag = %#x, should be %#x)	GDS_S_CACHE_INVMSGTAG_ERR
Invalid IPC-version number (version = %d)	GDS_S_IPCVERS_ERR
Invalid key data has been supplied	dced_s_bad_key_data
Invalid keystore handle	sec_psm_invalid_keystore_handle
Invalid length.	pkc_s_asn_inv_length
Invalid lock type.	pkc_s_inv_lock_type
Invalid log entry module or operation	sec_rgy_log_entry_out_of_range
Invalid MAC-address (ethernet address) (size = %d, should be %d)	GDS_S_NDS_MACV_ERR
Invalid mapping rule parameter (mapping rule = %d)	GDS_S_NDS_MAP_ERR
Invalid '-mask' option value.	dcp_s_acl_inv_mask_option_value
Invalid master key.	KDDS10007-E

Message Text	Symbolic Name
Invalid mechanism in credential in gss_init_sec_ctx	gss_s_ic_inv_cred_mech
Invalid mechanism in token in gss_accept_sec_ctx	gss_s_ac_inv_mech
Invalid mechanism requested in gss_init_sec_ctx	gss_s_ic_inv_req_mech
Invalid message ID	msg_s_bad_id
Invalid name	CDS_INVALIDNAME
Invalid name service handle	rpc_s_invalid_ns_handle
Invalid name syntax	rpc_s_invalid_name_syntax
invalid nameservice entry	sec_s_invalid_nameservice_entry
Invalid nameservice name	sec_rgy_bad_nameservice_name
Invalid NETBIOS-name (size = %d, maximum = %d)	GDS_S_NDS_NBNAMEV_ERR
Invalid network address	rpc_s_inval_net_addr
Invalid network address family ID	rpc_s_invalid_naf_id
Invalid number %d for superior structure rule.n	GDS_S_SRT_SUP_MISSING
Invalid number of NSAP-addresses (no. = %d, maximum = %d)	GDS_S_NDS_NSAP_ERR1
Invalid object	rpc_s_invalid_object
Invalid Object Identifier.	gc_t_omx_invalid_obj_id
Invalid octal digit in %1\$s	NIDL_INVOCTDIGIT
Invalid old password	KDDS22201-W
Invalid OM Syntax.	gc_t_omx_invalid_syntax
Invalid open-ID parameter in TP-routine call (open-ID = %d)	GDS_S_INVOPENID_ERR
Invalid operation mode parameter (operation mode = %d)	GDS_S_NDS_OPMODE_ERR

Message Text	Symbolic Name
Invalid option	KDDS01310-E
Invalid option	KDDS02800-E
Invalid option	KDDS23007-W
Invalid option - %s.	pwd_imp_err_invalid_option
Invalid option value. %s: invalid character detected	KDDS02801-E
Invalid or mismatched inputs or arguments '%s'.	dcp_s_dhd_invalid_args
Invalid or missing directory-ID in GDS-component specification (GDS_S_RPC_GDSINFO_DIR_ERR
Invalid or missing GDS-component specification (spec = %s)	GDS_S_RPC_GDSINFO_ERR
invalid or unsupported attribute type	sec_attr_bad_type
Invalid org name - %s	pwd_imp_rgy_bad_org
Invalid pad byte (%d)	gss_s_uns_inv_pad_byte
Invalid pad check-bytes	gss_s_uns_inv_pad_check
Invalid parameter passed as an argument.	gc_t_invalid_parameter
Invalid parameter passed as an argument.	gc_t_omx_invalid_parameter
Invalid parameters on command line:	NIDL_INVPARAMS
invalid password	sec_pvtkey_invalid_pwd
Invalid password	sec_rgy_passwd_invalid
Invalid password.	sec_login_s_invalid_password
Invalid password (Registry Edit Kernel)	ek_err_passwd_invalid
Invalid permanent virtual call number (number = %d, %d <= number <= %d)	GDS_S_NDS_PVCV_ERR
invalid permission set	sec_attr_bad_permset
Invalid permission set specified	dced_s_attr_acl_bad_permset
Invalid permission string.	dcp_s_rgy_invalid_permset_char

Message Text	Symbolic Name
invalid principal	sec_priv_s_invalid_principal
Invalid priority	rpc_s_invalid_priority
invalid privilege attribute handle	sec_cred_s_invalid_pa_handle
Invalid protection level.	dcp_s_rgy_era_invalid_protection
invalid protection level specified in binding auth_info	sec_attr_bad_bind_prot_level
Invalid psm handle	sec_psm_invalid_handle
Invalid re-entered password	KDDS22202-W
Invalid reference %d to Distinguished Name list detected.	GDS_S_ILL_DN_INDEX
Invalid replica auth handle	sec_rep_invalid_auth_handle
invalid replica entry	sec_rgy_rep_invalid_entry
Invalid rights list	KDDS23008-W
Invalid RPC protocol sequence	rpc_s_invalid_rpc_protseq
Invalid schema entry flag specified	dced_s_attr_bad_entry_flag
invalid scope specified	sec_attr_bad_scope
Invalid seal algorithm	gss_s_bp_inv_seal_alg
invalid sec_pvtkey_handle	sec_pvtkey_invalid_handle
Invalid security method.n	gsu_secur_false
invalid server name specified in binding auth_info	sec_attr_bad_bind_svr_name
Invalid service request (operation-ID = %d)	GDS_S_CACHE_INVRQ_ERR
Invalid set check.	cds_s_server_setbad_a
Invalid signal name: %s.	dcp_s_signal_invalid_name
Invalid signal number: %s.	dcp_s_signal_invalid_num
invalid site name for acl operation	sec_acl_invalid_site_name
Invalid size for key data	sec_rgy_key_bad_size

Message Text	Symbolic Name
Invalid size limit parameter in IPC-message (limit = %d)	GDS_S_CACHE_INVSLIM_ERR
Invalid size limit "%s".	gc_t_invalid_size_limit
Invalid size of an attribute value (length = %d, maximum = %d)	GDS_S_CACHE_INVAVLEN_ERR
Invalid size of object identifier (length = %d, maximum = %d)	GDS_S_CACHE_INVOIDLEN_ERR
Invalid size of serviceability information (size = %d,n	GDS_S_RPC_SVCINFO
Invalid specification of an shared memory extension area	GDS_S_IPCEXTSPEC_ERR
Invalid state machine state	rpc_s_sm_invalid_state
Invalid storage class parameter (storage class = %d)	GDS_S_CACHE_INVSTC_ERR
Invalid string binding	rpc_s_invalid_string_binding
Invalid string UUID	uuid_s_invalid_string_uuid
Invalid structure version.	pkc_s_invalid_version
Invalid switch detectedn	GDS_S_NDS_USAGE_ERR
Invalid syntax in DFS path.	KDDS11016-E
Invalid SYS:\ETC\HOSTS file.	KDDS11202-E
Invalid SYS:\ETC\SERVICES file.	KDDS11203-E
Invalid time limit "%s".	gc_t_invalid_time_limit
Invalid timeout	rpc_s_invalid_timeout
Invalid token-type in gss_build_prot_message	gss_s_bp_inv_tok_type
Invalid tower specification global directory.	cds_s_gda_badtower
Invalid TRANSDATA processor number (processor = %d, %d <= processor < %d)	GDS_S_NDS_PROCV_ERR

Message Text	Symbolic Name
Invalid TRANSDATA region number (region = %d, %d <= region < %d)	GDS_S_NDS_REGIONV_ERR
Invalid transfer type parameter in TP-routine call	GDS_S_INVTRANS_ERR
Invalid trigger binding info specified	dced_s_attr_bad_trig_binding
Invalid trigger type.	dcp_s_rgy_invalid_trigger_type
Invalid trigger type specified	dced_s_attr_bad_trig_types
invalid trigger type specified	sec_attr_bad_trig_type
Invalid TSAP-address buffer size (size = %d, must be > %d)	GDS_S_NDS_BUF_ERR
Invalid type.	pkc_s_asn_inv_type
Invalid type.	pkc_s_asn_wrong_type
Invalid unique/group-ID for NETBIOS-address (id = %d, should be %d or %d)	GDS_S_NDS_NBGUIDV_ERR
Invalid use of tag %1\$s	NIDL_BADTAGREF
Invalid user account. DCE user name: xxx.	KDDS11209-E
Invalid value.	pkc_s_asn_inv_value
Invalid value.	pkc_s_asn_invalid_value
Invalid value for "Local schema is master".n	gsu_local_schema_error
Invalid value for "Use default schema".n	gsu_default_schema_failed
Invalid value position.	gc_t_om_wrong_value_position
Invalid version no. in TP-routine call (version = %d)	GDS_S_INVVERSNO_ERR
Invalid version number (version no. = %d)	GDS_S_CACHE_INVVERS_ERR
Invalid version of NDS-configuration data base (version = %d)	GDS_S_NDS_VERS_ERR

Message Text	Symbolic Name
Invalid X.121-address (size = %d, %d <= size <= %d)	GDS_S_NDS_X121V_ERR
Invalid X.21-address (size = %d, %d <= size <= %d)	GDS_S_NDS_X21V_ERR
Invalid XTI-provider name or index (name = '%s', index = %d)	GDS_S_NDS_PROV_ERR
invoked "break" outside of a loop	tcl_s_basic_break_outside_of_loop
invoked "break" outside of a loop	tcl_s_proc_break_outside_loop
invoked "continue" outside of a loop	tcl_s_basic_continue_outside_of_loop
invoked "continue" outside of a loop	tcl_s_proc_continue_outside_loop
IPC-association limit exceeded (limit = %d)	GDS_S_IPCLIMASS_ERR
IPC-communication buffer too small	GDS_S_CACHE_BUFSZ_ERR
IPC-distributed command entry limit exceeded (limit = %d)	GDS_S_IPCLIMDIST_ERR
IPC-function call not allowed in this state (state = %d)	GDS_S_IPCSTATE_ERR
IPC-heap memory limit exceeded (memory size requested = %d)	GDS_S_IPCLIMHEAP_ERR
IPC-message of invalid size received (size = %d)	GDS_S_IPCMSGSZ_ERR
IPC-registration limit exceeded (limit = %d)	GDS_S_IPCLIMREG_ERR
IPC-resources already in use	GDS_S_IPCINUSE_ERR
IPC-server limit exceeded (limit = %d)	GDS_S_IPCSLIMSVR_ERR
IPC-user credential entry limit exceeded (limit = %d)	GDS_S_IPCLIMCRED_ERR
Journal file already open	rsdb_journal_open
junk on end	tcl_s_tclregexp_junk_end

Message Text	Symbolic Name
Kernel operation invoked on incomplete data set (Registry Edit Kernel)	ek_required_field
Key function not allowed when default authentication service specified	rpc_s_key_func_not_allowed
key generation is not supported	sec_pvtkey_key_generation_not_supported
Key ID in packet unknown	rpc_s_key_id_not_found
Key not found.	pkc_s_key_not_found
Key not found in database	db_s_key_not_found
Key not found; lookup forbidden.	pkc_s_forbidden
key type not supported	sec_rgy_key_bad_type
Key version not supported.	sec_pk_e_key_vers_unsupported
key version number currently in use	sec_rgy_key_version_in_use
key version number out of range	sec_rgy_key_bad_version
Key version requested not found.	sec_pk_e_key_vers_unavailable
Keyfile not recognized.	sec_pk_e_kf_format_err
Keyfile version not supported.	sec_pk_e_kf_version_err
Keyseed too long	sec_rs_mkey_long_keyseed
Keystore already registered.	sec_psm_keystore_already_registered
Keystore entry %d is corrupt	sec_psm_i_bad_keystore_list
Keystore ERA retrieval failed	sec_psm_keystore_attr_read_failed
Keystore list corrupt	sec_psm_keystore_list_corrupt
Keystore not found	sec_psm_keystore_not_found
keytab only supports 'plain' key.	dcp_s_kt_bad_key_type
KRB mechanism requested in gss_init_sec_ctx, but cred is not KRB-capable	gss_s_ic_cred_nokrb
krb5_copy_keyblock failed (%x)	gss_s_seca_copy_kblock_failed

Message Text	Symbolic Name
LAN profile not found	dts_s_no_profile
Legal values are:	NIDL_LEGALVALS
Length of source filename and stub suffix exceed 8 chars	NIDL_SRCFILELEN
Lexical analyser: multiple use of same CC (communication)	GDS_S_NDS_LEX_ERR3
Lexical analyser: multiple use of same CC (communication)	GDS_S_NDS_LEX_ERR4
Lexical analyser: port number range exceeded (port = %d, maximum = %d) %s	GDS_S_NDS_LEX_ERR2
Lexical analyser: same DSP-part number specified twice %s	GDS_S_NDS_LEX_ERR1
Lexical analyser: syntax error %s	GDS_S_NDS_LEX_ERR
Lifespan is not a number or in valid format (Registry Edit Kernel)	ek_err_bad_lifespan
Lifespan out of range (Registry Edit Kernel)	ek_err_lifespan_out_of_range
Line %d of named.ca: class syntax error.	cds_s_gda_class
Line %d of named.ca: data syntax error.	cds_s_gda_data
Line %d of named.ca: DNAME syntax error.	cds_s_gda_dname
Line %d of named.ca: INCLUDE syntax not supported.	cds_s_gda_include
Line %d of named.ca: ORIGIN syntax error.	cds_s_gda_origin
Line %d of named.ca: ttl syntax error.	cds_s_gda_ttl
Line %d of named.ca: type syntax error.	cds_s_gda_type
Line %d of named.ca: Unknown \$ option: %s.	cds_s_gda_option

Message Text	Symbolic Name
Line %d of named.ca: unsupported data type.	cds_s_gda_unsupporteddata
linked variable is read-only	tcl_s_link_linked_var_read_only
list element in braces followed by "%.s" instead of space	tcl_s_tclutil_list_ele_in_braces
list element in quotes followed by "%.s" instead of space	tcl_s_tclutil_list_ele_in_quotes
List was not properly terminated	sec_rsd_b_list_not_terminated
Listener thread is not running	rpc_s_not_listening
Local clock was not intersecting: local time = %s, computed time = %s. It has been reset.	dts_s_resetlocal
Local clock was not intersecting: local time = %s, computed time = %s. It will be adjusted.	dts_s_adjustlocal
Local drive was selected: Should be a Network drive.	KDDS23006-W
Local group not specified.	dcp_s_rgy_con_no_group
Local organization not specified.	dcp_s_rgy_con_no_org
Local server %s returned time %s which does not intersect computed time %s	dts_s_local_nointersect
Local system error %s	dts_s_system_error
Locking error.	pkc_s_locking_violation
Locking violation - Delete not pending	pkc_s_delete_not_pending
Log entry not translated and so skipped	sec_rsd_b_ent_not_xlated
Log entry out of bounds and so skipped	sec_logent_out_of_bounds
Log file is already open	sec_rsd_b_log_file_open
Logfile name is missing.	GST_NO_LOGFILE

Message Text	Symbolic Name
Login context already specifies a delegation chain.	sec_login_s_compound_delegate
login context has already been validated	sec_login_s_already_valid
login context has not been certified	sec_login_s_not_certified
Login context of local host principal not available	sec_rgy_host_context_not_avail
login_context_to_cred failed (%x) in gss_accept_sec_context	gss_s_ac_lcc_failed
Login/logout in progress: No jobs accepted.	KDDS22414-W
low guard byte %d is 0x%x t%cn	tcl_s_ckalloc_low_guard_byte
low guard failed at %lx, %s %dn	tcl_s_ckalloc_low_guard_failed
MAC-address (ethernet address) missing	GDS_S_NDS_MAC_ERR
malformed bucket chain in Tcl_DeleteHashEntry	tcl_s_hash_bad_bucket_chain
malformed delegation token	sec_priv_s_invalid_dlg_token
malformed request	sec_priv_s_invalid_request
Management operation disallowed	rpc_s_mgmt_op_disallowed
Manager not entered	rpc_s_manager_not_entered
Manager type has not been registered with dce_acl_register_object_type()	acl_s_type_not_registered
Mask option used without '-add' or '-change' option.	dcp_s_acl_no_mask_with_option
Master cannot restart prop tasks when become_slave failedn%s	sec_rgy_rep_slv_restart_prop
Master cannot restart prop tasks when change_master failedn%s	sec_rgy_rep_mst_restart_prop
master is running a bad software version	sec_rgy_rep_master_bad_sw_vers

Message Text	Symbolic Name
Master Registry server unavailable (Registry Edit Kernel)	ek_misc_no_update_site
Master sequence number is invalid	sec_rgy_rep_bad_master_seqno
Master_key file I/O operation failed	sec_rgy_mkey_file_io_failed
Master_key in memory doesn't match master_key stored in databasen%s	sec_rgy_mky_not_match
Master's database is probably obsoleten%s	sec_rgy_rep_master_obsolete
master_seqno specified but not duplicate master	sec_rep_mseq_not_dup_master
Max calls (threads) too small	rpc_s_max_calls_too_small
Max descriptors exceeded	rpc_s_max_descs_exceeded
max_entries must be at least as large as num_entries	sec_lrgy_s_max_lt_num_entries
Maximal directory ID number is %d.n	gsu_max_dir_id
Maximal number of clients is %d.n	gsu_max_clients
Maximal number of servers is %d.n	gsu_max_servers
Maximum Distinguished name list index is exceeded.	GDS_S_MAX_DN_INDEX
Maximum identifier length for [%1\$s] type is %2\$lu characters	NIDL_MAXIDTYPE
Maximum identifier length for [context_handle] type is %1\$lu characters	NIDL_MAXIDTYPCH
Maximum identifier length for [handle] type is %1\$lu characters	NIDL_MAXIDTYPHAN
Maximum identifier length for interface name is %1\$lu characters	NIDL_MAXIDINTF
Maximum identifier length for [out_of_line] type is %1\$lu characters	NIDL_MAXIDTYPOOL

Message Text	Symbolic Name
Maximum identifier length for pipe type is %1\$lu characters	NIDL_MAXIDTYPIPE
Maximum identifier length for pointed-to type is %1\$lu characters	NIDL_MAXIDTYPPT
Maximum identifier length for [represent_as] type is %1\$lu characters	NIDL_MAXIDTYPRA
Maximum identifier length for type with [transmit_as] is %1\$lu characters	NIDL_MAXIDTYPTA
Maximum memory for Distinguished name list exceeded.	GDS_S_MAX_DN_MEMORY
Mech-type size (%d) is too large	gss_s_wrap_mech_long
Member name not specified.	dcp_s_cds_no_member
Member picked	rpc_s_mbr_picked
Member (%s) added to group (%s)	sec_rs_ns_grp_mbr_add_succ
Member (%s) not added to group (%s)	sec_rs_ns_grp_mbr_add_fail
Members of unions cannot be of type handle_t	NIDL_HANUNIMEM
Memory allocation failure	dts_s_alloc_virt
memory corruption	tcl_s_tclregexp_mem_corruption
Memory fatal in instrumented allocation routines.	cds_s_library_cdsmalloc_a
Memory validation failure	tcl_s_ckalloc_mem_val_failure
Message catalog does not exist	msg_s_no_catalog
Message logging file taken.	KDDS12401-I
Minimum passwd length specification out of range (Registry Edit Kernel)	ek_err_bad_passwd_len
Miscellaneous info text is too long (Registry Edit Kernel)	ek_err_misc_info_too_long
Mismatched brackets - %s.	gc_t_omx_mismatched_brackets

Message Text	Symbolic Name
Mismatched quotes - %s.	gc_t_mismatched_quotes
Mismatched quotes - %s.	gc_t_omx_mismatched_quotes
Missing "]" on array bound	NIDL_MISSONARR
Missing "]" on attribute list	NIDL_MISSONATTR
Missing "]" on interface declaration	NIDL_MISSONINTER
Missing abbreviation - %s.	gc_t_omx_missing_abbrev
Missing argument for %s option	sec_secd_cl_missing_arg
Missing argument for %s option	sec_crdb_cl_missing_arg
Missing arguments.	gc_t_missing_arguments
Missing attribute information.	gc_t_missing_attribute_info
Missing attribute information - %s.	gc_t_omx_missing_attr_info
Missing attribute value - %s.	gc_t_omx_missing_attr_value
Missing Attribute Value Assertion - %s.	gc_t_omx_missing_ava
Missing authentication type.	gc_t_missing_authentication_type
missing %c	tcl_s_parse_missing_c
Missing class value - %s.	gc_t_omx_missing_class_value
missing close-brace	tcl_s_parse_missing_close_brace
missing close-brace for variable name	tcl_s_parse_missing_close_brace_var
missing close-bracket	tcl_s_parse_missing_close_bracket
Missing component value - %s.	gc_t_omx_missing_comp_value
Missing compound operator - %s.	gc_t_omx_missing_compound_op
Missing convert function	db_s_missing_convert
Missing directory identifier.	gc_t_missing_directory_id
Missing Directory Service Agent name.	gc_t_missing_dsa_name
Missing end of Attribute Definition Block.	gc_t_omx_no_end_attr_block
Missing end of class block operator - %s.	gc_t_omx_missing_class_end_op

Message Text	Symbolic Name
Missing end of Object Class Definition Block.	gc_t_omx_no_end_obj_block
Missing end of OM Class Definition Block.	gc_t_omx_no_end_class_block
Missing equal operator - %s.	gc_t_omx_missing_equal_operator
Missing filter value.	gc_t_missing_filter
Missing hostname.	dcp_s_clock_missing_hostname
Missing information for the new attribute values.	gc_t_missing_new_attribute_info
Missing local DSA name.n	gsu_missing_local_dsa_name
Missing myname	sec_crdb_cl_null_myname
Missing object name.	gc_t_missing_object_name
Missing OM Class Definition Block.	gc_t_omx_class_block_undefined
Missing OM Class Name.	gc_t_omx_no_class_name
Missing operation.	gc_i_missing_operation
Missing operator - %s.	gc_t_omx_missing_operator
Missing password.	gc_t_missing_user_password
Missing Presentation Service Access Point address.	gc_t_missing_psap_address
Missing principal name.n	gsu_missing_principal_name
Missing Relative Distinguished Name delimiter - %s.	gc_t_omx_missing_rdn_delimiter
missing required acl entry	sec_acl_missing_required_entry
Missing result type on operation declaration	NIDL_MISSONOP
Missing '%s' field.n	csrc_s_missing_field
Missing scope of search.	gc_t_missing_scope_of_search
Missing size limit.	gc_t_missing_size_limit

Message Text	Symbolic Name
Missing start of Attribute Definition Block.	gc_t_omx_no_start_attr_block
Missing start of class block operator - %s.	gc_t_omx_missing_class_start_op
Missing start of Object Class Definition Block.	gc_t_omx_no_start_obj_block
Missing start of OM Class Definition Block.	gc_t_omx_no_start_class_block
Missing the PSAP address for %s.n	gsu_missing_psap_name
Missing time limit.	gc_t_missing_time_limit
Missing type on parameter declaration	NIDL_MISSONPARAM
Missing user name.	gc_t_missing_user_name
Missing value.	gc_t_missing_value
Modification affects several DSAs and is prohibited.	DS_E_AFFECTS_MULTIPLE_DSAS
Modification to an interior node of the DIT is prohibited.	DS_E_NOT_ALLOWED_ON_NON_LEAF
modify_cell_alias: Buffer overflow, alias not modified	cds_s_server_aliasoverflow
modify_cell_alias: Not master replica.	cds_s_server_aliasnotmaster
modify_cell_alias: Not root directory.	cds_s_server_aliasnotroot
More than one interface name has been specified.	dcp_s_dhd_too_many_ifnames
More than one master replica specifiedn	CDSCP_TWO_MASTERS
More than one primary alias detected.	cds_s_server_aliasmultiprfd
Mount point xxx does not exist.	KDDS11664-E
Mount point xxx does not have access rights.	KDDS11666-E
multi-byte to wide character conversion failed for "%c"	tcl_s_single_multibyte_conv_failed

Message Text	Symbolic Name
multi-byte to wide character conversion failed for "%s"	tcl_s_multibyte_conv_failed
multi_instanced void attributes are disallowed.	sec_attr_multi_inst_disallowed
Multiple primary aliases have been detected in the CDS_CellAliases attribute.	CDS_MULT_PREFERRED
Must compile stubs with ANSI C compiler to avoid promotion of float to double in operation %1\$s	NIDL_FLOATPROM
Must have read permission for the DTS entity	dts_s_mgt_no_read
Must have write permission for the DTS entity	dts_s_mgt_no_write
Must specify both 'publickeyfile' and 'privatekeyfile'.	dcp_s_rgy_pk_missing_key
Must use either an object UUID or an interface id.	dcp_s_rpc_no_objects
Must use '-interface' or '-default'.	dcp_s_rpc_no_interface_id_def
Mutex initialization failed.	dcp_s_mutex_init_fail
Mutex lock failed.	dcp_s_mutex_lock_fail
Mutex unlock failed.	dcp_s_mutex_unlock_fail
Mutual authentication failed	rpc_s_auth_mut_fail
Mutually exclusive options entered.	dcp_s_mut_excl_opts
"%n\$" argument index out of range	tcl_s_cmdah_arg_index_out_of_range
Name %1\$s is declared in file %2\$s, line %3\$lu	NIDL_NAMEDECLAT
Name %1\$s previously declared in file %2\$s, line %3\$lu	NIDL_NAMEPREVDECLAT
Name already declared: %1\$s	NIDL_NAMEALRDEC
Name already exists	sec_rgy_name_exists

Message Text	Symbolic Name
Name already present in cache, cannot add duplicate entry.n	pwd_imp_err_dup_name
Name field was NULL or empty	dced_s_name_missing
(Name in question - %s.)n	pwd_imp_err_bad_name
Name is either a NULL pointer or a null string.	sec_rs_login_null_name
Name is not a constant: %1\$s	NIDL_NAMENOTCONST
Name is not a field: %1\$s	NIDL_NAMENOTFIELD
Name is not a parameter: %1\$s	NIDL_NAMENOTPARAM
Name is not a type: %1\$s	NIDL_NAMENOTTYPE
Name is referenced in file %1\$s, line %2\$lu	NIDL_NAMEREFAT
Name is too long for current implementation	sec_id_e_name_too_long
Name is underspecified	rpc_s_underspecified_name
Name not found: %1\$s	NIDL_NAMENOTFND
name resolution failed on acl operation	sec_acl_name_resolution_failed
Name service environment variable not defined	rpc_s_no_env_setup
Name service unavailable	rpc_s_name_service_unavailable
Name specified with option %s longer than %d	sec_crdb_cl_long_rgyname
name unavailable	sec_rgy_rep_name_unavailable
Named FIFO %s could not be created in mode "%d", errno = %d.	GDS_S_MKNOD_ERR
National destination code (NDC) of E.164-address missing	GDS_S_NDS_E164NDC_ERR
National prefix of E.163-address missing	GDS_S_NDS_E163NP_ERR

Message Text	Symbolic Name
Neither name nor login-context found in credential	gss_s_gac_cred_inv
nested *?+	tcl_s_tclregexp_nested_ops
NETBIOS-name missing	GDS_S_NDS_NBNAME_ERR
NetWare client ran out of memory.	KDDS22408-W
NetWare server has invalid network environment.	KDDS11651-E
Network error.	KDDS02562-E
Network is down	rpc_s_rem_network_shutdown
Network is unreachable	rpc_s_network_unreachable
New 'mask_obj' entry failed.	dcp_s_acl_new_mask_obj_failed
New namespace cannot be reached: status = %s.	cds_s_server_newread_eb
New passphrase doesn't match other key pairs' passphrase	sec_pvtkey_wrong_passwd
new password is required for updating the password	sec_pvtkey_new_password_required
New time not contained in current time interval	dts_s_no_time_updated
No access right to set rights	KDDS23009-W
No account name.	dcp_s_rgy_no_acct_name
No ACL entries have the control bit set.	acl_s_no_control_entries
No acl file existed - Creating a default ACL	cds_s_adver_noacl
No acl file existed - Creating a default ACL	cds_s_noacl
no acl found	sec_acl_no_acl_found
No action specified by the public key attribute list.	dcp_s_rgy_pk_missing_argument

Message Text	Symbolic Name
No addresses	rpc_s_no_addrs
No appropriate policy could be found.	pkc_s_policy_unavailable
No argument for alt_dir option. Using default path : %s	sec_crdb_cl_alt_dir_no_arg
No binding found for interface.	dcp_s_resolve_not_found
No binding value was specified.	dcp_s_cds_no_binding_specified
No bindings	rpc_s_no_bindings
no body specified for pattern "%s"	tcl_s_cmdmz_no_body_spec_for_pat
No cache name specified.	dcp_s_cds_no_cache_name
No cell alias name.	dcp_s_cds_no_cdsalias_name
No cell name.	dcp_s_rgy_con_no_cell_name
No checksum found in authenticator	gss_s_seca_no_cksum
No clearinghouse name.	dcp_s_cds_no_clearinghouse_name
No clearinghouse or server option specified.	dcp_s_cds_cache_show
No clearinghouse returned by server	CDS_CSNOCLH
No compatible code set found	rpc_s_ss_no_compat_codeset
No currently established network identity for which context exists	sec_login_s_no_current_context
No default available.	pkc_s_asn_no_default_value
No default context in login_context_to_cred	gss_s_lcc_no_def_ctx
No default message found	msg_s_no_default
no default replica	sec_rgy_rep_no_default_replica
No directory name.	dcp_s_cds_no_dir_name
No entries in this ACL	acl_s_no_acl_entries
No entry name	rpc_s_no_entry_name
No event classes were found.	dcp_s_aud_empty_ec_list

Message Text	Symbolic Name
no event matches "%s"	tcl_s_hist_evt_no_matches
No fault	rpc_s_no_fault
no files matched glob pattern "	tcl_s_glob_no_files_match_single
no files matched glob patterns "	tcl_s_glob_no_files_match_plural
No filter defined	svc_s_no_filter
No filter found.	dcp_s_audfilter_no_filter
No filter was found for the subject.	aud_s_no_filter
No gateway is active in network.	KDDS22302-W
No 'gid' specified when attempting to create an alias.	dcp_s_rgy_no_gid
No global servers detected	dts_s_no_global_servers
No group name.	dcp_s_rgy_no_group_name
No group trustee	KDDS23502-I
no identity set yet	sec_s_none_registered
no identity supplied	sec_login_s_no_identity
No IEEE 802 hardware address	uuid_s_no_address
No import cursor	rpc_s_ss_no_import_cursor
No interfaces	rpc_s_no_interfaces
No interfaces exported	rpc_s_no_interfaces_exported
No link name.	dcp_s_cds_no_link_name
No local code set name exists in the code set registry	dce_cs_c_notfound
No manager EPV available	rpc_s_no_mepv
No master in directory replica setn	CDSCP_NOMASTER
No match found	dce_cf_e_no_match
No matching binding information found.	dcp_s_rpc_no_binding_found
no matching local registry account entry	sec_lrgy_s_no_matching_entry

Message Text	Symbolic Name
no matching local registry TGT entry	sec_lrgy_s_no_matching_tgt
No matching override entry found.	sec_login_s_ovrd_ent_not_found
No member name given.	dcp_s_rpc_no_member_name
No member name was specified.	dcp_s_rgy_no_member_name
No membership info exists for the specified PGO object (Registry Edit Kernel)	ek_misc_no_members
No memory available	sec_login_s_no_memory
No memory for building replica set.n	CDS SCP_NOMEM_REPSET
No memory for %d byte file %sn	CDS SCP_NO_FILE_MEM
No memory for endpoint map service	ept_s_no_memory
No memory for mech-OID copy in gss_accept_sec_ctx	gss_s_ac_nomem1
No memory for OID copy in unwrap_token	gss_s_unwrap_nomem
No memory for processing command file %sn	CDS SCP_NOMEM_DOFI LE
No memory for RPC runtime	rpc_s_no_memory
No memory to copy client name	gss_s_ac_nomem2
No memory to copy wrapped token	gss_s_wrap_nomem
No memory to create credential	gss_s_lcc_cred_nomem
No memory to get handle to nameserver.n	CDS SCP_NOGETHAND
No modify operation has been specified.	dcp_s_rgy_no_modify_operation
No more bindings	rpc_s_no_more_bindings
No more data.	pkc_s_asn_no_more_data
No more dced entries available	dced_s_no_more_entries
No more Directory Service operations can be performed.	DS_E_TOO_MANY_OPERATIONS

Message Text	Symbolic Name
No more Directory Service sessions can be started.	DS_E_TOO_MANY_SESSIONS
no more entries (attribute instances or schema entries) found	sec_attr_no_more_entries
no more entries available	sec_cred_s_no_more_entries
no more entries available	sec_lrgy_s_no_more_entries
No more entries to iterate over	db_s_no_more
No more items.	pkc_s_no_more_items
No more matching entries	sec_rgy_no_more_entries
No more matching entries (Registry Edit Kernel)	ek_misc_no_more_entries
No more members	rpc_s_no_more_members
No more profile elements	rpc_s_no_more_elements
No name given to parse.	dcp_s_rgy_no_name_to_parse
No name provided to rename to.	dcp_s_rgy_no_name_to_rename
No new name specified.	dcp_s_rgy_schema_rename_no_newname
No NSAP-address matching rules found	GDS_S_NDS_RULES_ERR
No NSAP-address selection possible	GDS_S_NDS_SEL_ERR
No object name.	dcp_s_cds_no_obj_name
No open slot in list	sec_rldb_no_open_slot
No organization name.	dcp_s_rgy_no_org_name
no override information available	sec_login_s_no_override_info
No permission for name service operation	rpc_s_no_ns_permission
No permission to open message catalog	msg_s_no_cat_perm
No postprocessors have been defined	dced_s_no_postprocessors
No principal name.	dcp_s_rgy_no_princ_name
no privilege attributes available	sec_s_no_pac

Message Text	Symbolic Name
No protocol sequences	rpc_s_no_protseqs
No protocol sequences registered	rpc_s_no_protseqs_registered
no random key seed set yet.	sec_s_no_key_seed
No replica exists at clearinghouse '%s'.	dcp_s_dir_mod_bad_new_entry
No replica of specified directory exists at clearinghouse %sn	CDSCP_NOREP
No response from agent.	KDDS11652-E
No room to place the converted characters	rpc_s_ss_short_conv_buffer
No RPC entry name given.	dcp_s_rpc_no_entry_name
No RPC group name given.	dcp_s_rpc_no_group_name
No RPC profile name given.	dcp_s_rpc_no_profile_name
No sanity check response returned from gateway xxx.	KDDS02220-E
No schema name.	dcp_s_rgy_no_schema_name
No secondary index has been created already on this database	CDS_GDB_NO_SECONDARY
No space for a new keystore	sec_psm_keystore_list_full
No statistics available	svc_s_no_stats
No string binding entered.	dcp_s_rpc_no_binding
No string binding given to acquire host name for.	dcp_s_rgy_no_binding_to_parse
No such cthread pool	rpc_s_ctypead_no_such_pool
no such element in array	tcl_s_tclvar_no_such_ele
No such group	KDDS23004-W
No such path	KDDS23001-W
No such path or file	KDDS23000-W
No such subdirectory	KDDS23002-W
No such thread	ESRCH

Message Text	Symbolic Name
No such user	KDDS23003-W
no such variable	tcl_s_tclvar_no_such_var
No target directory specified.	dcp_s_cds_merge_no_target
No token supplied	gss_s_ic_no_token
No 'uid' specified when attempting to create an alias.	dcp_s_rgy_no_uid
no update sites for this acl operation	sec_acl_no_update_sites
No usable tower entries	sec_rgy_tower_rebind_failed
No user trustee	KDDS23500-I
no value given for parameter "%s" to "%s"	tcl_s_proc_no_val_given_to_par
No values exist in the attribute list.	dcp_s_cds_no_attr_list_value
No XTI-interface support available	GDS_S_NDS_XTI_ERR
Non-integer values are not allowed in expressions	NIDL_NONINTEXP
Non-numeric data encountered where numeric data was expected (Registry Edit Kernel)	ek_err_non_numeric
Non-specific failure.	pkc_s_failure
Normal child exit, status = %d.	GDS_S_CHILD_EXIT
Normal Successful Exit	cds_s_child_exiting_eg
Normal successful exit	cds_s_server_eg
Normal Successful exit due to expected signal.	cds_s_adver_eg
Not a fully qualified schema name.	dcp_s_rgy_bad_schema_name
Not a gateway group	KDDS23022-W
Not a gateway user.	KDDS23014-W
Not a gateway volume	KDDS23020-W
Not a global time server	dts_s_not_global_server

Message Text	Symbolic Name
Not a group	CDS_NOTAGROUP
Not a privileged user	sec_rgy_not_root
Not a supported request	dced_s_no_support
not a valid DFS acl	sec_acl_invalid_dfs_acl
Not a valid UNIX id.n	pwd_imp_err_invalid_uid
Not all objects unexported	rpc_s_not_all_objs_unexported
Not an RPC entry	rpc_s_not_rpc_entry
Not an RPC tower	rpc_s_not_rpc_tower
Not authenticated	rpc_s_binding_has_no_auth
Not authorized to modify group membership (Registry Edit Kernel)	ek_err_g_mbr_unauth
Not authorized to modify org membership (Registry Edit Kernel)	ek_err_o_mbr_unauth
Not authorized to modify the authentication policy (Registry Edit Kernel)	ek_err_auth_plcy_unauth
Not authorized to perform serviceability operation	sec_svc_not_authorized
Not effective in directories or files (denoted by *)	KDDS23632-I
not enough arguments for all format specifiers	tcl_s_cmdah_not_enough_args
Not enough resources for connection at local or remote host	rpc_s_connect_no_resources
Not enough space	ENOMEM
not enough space for this ACL at specified ACL manager	sec_acl_mgr_no_space
Not file owner or root	sec_pvtkey_privileged
Not found	rpc_s_not_found

Message Text	Symbolic Name
not from master	sec_rgy_rep_not_from_master
Not implemented	twr_s_not_implemented
Not logged in to DCE	KDDS22404-W
Not logged in to DCE	KDDS23015-W
Not logged in to NetWare server	KDDS22405-W
not member of any group	sec_priv_s_not_member_any_group
Not registered in endpoint map	ept_s_not_registered
Not supported	rpc_s_not_supported
Not yet implemented operation	dce_attr_s_not_implemented
Nothing to export	rpc_s_nothing_to_export
Nothing to unexport	rpc_s_nothing_to_unexport
NOTICE: NSAP-address description entries decreased to %d (default value = %d)	GDS_S_NDS_NETADDR
NOTICE: Work space decreased to %d byte(s) (default value = %d)	GDS_S_NDS_WORKSPACE
NULL argument	tcl_s_tclregexp_null_arg
Null channel-bindings in sec_krb_gss_decode_message	gss_s_seca_null_bindings
NULL or nil UUID for server instance	dcdd_s_sx_missing_instance
NULL parameter	tcl_s_tclregexp_null_parameter
Null registry login handle.	sec_rs_login_null_handle
Null value of [in] context handle or all [in,out] context handles	rpc_s_ss_in_null_context
Number of connections exceeds the limit: Agent cannot take	KDDS02131-I
Number of entries missing in asn1_attr file.	GDS_S_NUM_ASN1_ATTR_ERR

Message Text	Symbolic Name
Number of subdirectories: %d	KDDS23701-I
NWAddFSMonitorHook failed: error code xxx.	KDDS11005-E
NWRegisterNCPEExtension failed: error code xxx.	KDDS11006-E
Object already exists	sec_rgy_object_exists
object found was not in scope	sec_rgy_object_not_in_scope
Object Manager %s call failed: status = %ld.	cds_s_addcell_om
Object not found	rpc_s_object_not_found
Object replaced.	pkc_s_replaced
Objects/records in this database do not have headers	db_s_no_header
Obsolete command parse table %s	dts_s_prsfile_version
Obsolete feature encountered; Use translator	NIDL_USETRANS
Old name (%s)not removed from nameservice	sec_rs_ns_cant_rm_name
Old name not removed from nameservice, it may not belong to this server	sec_rs_ns_name_not_removed
Old passphrase required for this update	sec_pvtkey_old_pass_required
Old replica cannot be included in new replica set	CDS_NEWVERSIONSKEW
Only DES keys allowed for this account	sec_rsdb_acct_bad_keytype
Only full or simple names are allowed.	dcp_s_rgy_full_or_simple
Only one account per principal allowed (Registry Edit Kernel)	ek_err_unix_acct_exists
Only one CDS client may be specified for this command.	dcp_s_cds_only_one_client

Message Text	Symbolic Name
Only one CDS server may be specified for this command.	dcp_s_cds_only_one_server
Only one directory can be specified.	dcp_s_dir_mod_bad_num_dirs
Only one instance of the same 'void' attribute is allowed.	dcp_s_rgy_era_too_many_voids
Only one master clearinghouse can be specified.	dcp_s_dir_mod_bad_num_masters
Only one registry replica is allowed.	dcp_s_rgy_sa_only_one_replica
Only options or an attribute list are allowed.	dcp_s_rgy_list_and_switches
Opening of NDS-configuration data base file '%s' failed (errno = %d)	GDS_S_NDS_OCONFO_ERR
Operation %1\$s has no binding handle parameter; [auto_handle] assumed	NIDL_DEFAULTOCHAN
Operation attributes [code] and [nocode] cannot occur together	NIDL_OPCODEATTR
Operation cannot be perform within the administrative constraints.	DS_E_ADMIN_LIMIT_EXCEEDED
Operation denied: audit daemon is disabled	aud_s_dmn_disabled_in_selfaudit
Operation in progress.	CDS_PENDING
Operation involving multiple registry updates was only partially successful (Registry Edit Kernel)	ek_misc_acct_partial_op
Operation is not allowed while iterating	db_s_iter_not_allowed
Operation is not supported	ENOTSUP
Operation name %1\$s referenced in ACF is not defined	NIDL_OPNOTDEF
operation not implemented	sec_s_not_implemented
Operation Not Implemented	sec_key_mgmt_e_not_implemented

Message Text	Symbolic Name
Operation not permitted	EPERM
Operation not supported on specified domain	sec_rgy_bad_domain
Operation not supported on specified domain (Registry Edit Kernel)	ek_misc_bad_domain
operation not supported on this object type	sec_attr_bad_object_type
Operation not valid on a reserved name (Registry Edit Kernel)	ek_err_reserved
Operation not valid on local context	sec_login_s_auth_local
Operation not valid on the specified domain (Registry Editor/TTY Interface)	tty_bad_domain
Operation not yet implemented	sec_rgy_not_implemented
Operation not yet implemented	sec_login_s_not_implemented
Operation not yet implemented (Registry Edit Kernel)	ek_misc_not_implemented
operation on acl not authorized	sec_acl_not_authorized
Operation out of range	rpc_s_op_rng_error
Operation with [decode] must have at least one [out] or [in,out] parameter	NIDL_DECNOPARAMS
Operation with [encode] must have at least one [in] or [in,out] parameter	NIDL_ENCNOPARAMS
Operation with [encode] or [decode] may not contain pipe parameters	NIDL_ENCDECIPIE
Operation with [encode] or [decode] must use explicit binding	NIDL_ENCDECBIND
Operation with [encode,decode] must have all [in,out] parameters	NIDL_ENCDECDIR
Operation with [in] [cs_char] data requires [cs_stag] parameter	NIDL_OPINCSCHAR

Message Text	Symbolic Name
Operation with [out] [cs_char] data requires [cs_rtag] parameter	NIDL_OPOUTCCHAR
Operational attribute or object class missing.n	GDS_S_OPAT_MISSING
Option not specified.	dcp_s_cds_no_obj_mod_operation
Option not specified.	dcp_s_cds_no_dir_mod_operation
Option not specified.	dcp_s_cds_no_link_mod_operation
Option %s can only be specified with -locksmith	sec_secd_cl_locksmith_opt
Options table:	NIDL_OPTIONSTABLE
Organization already exists (Registry Edit Kernel)	ek_err_org_exists
Organization does not exist (Registry Edit Kernel)	ek_err_org_does_not_exist
Organization name contains an illegal character (Registry Edit Kernel)	ek_err_org_bad_name_chars
Organization name too long (Registry Edit Kernel)	ek_err_org_name_too_long
Organization name too long.n	pwd_imp_err_ongame_too_long
OS call to open the file for writing	dts_s_binding_file_write_error
Other information contains invalid data. The invalid data will	KDDS10025-W
Out of memory	svc_s_no_memory
Out of memory	dce_cf_e_no_mem
Out of memory.	pkc_s_nomem
Out of memory	msg_s_no_memory
Out of memory	NIDL_OUTOFMEM
Out of memory in gss_build_prot_message	gss_s_bp_nomem1

Message Text	Symbolic Name
Out of memory in gss_display_name	gss_s_disp_nomem
Out of memory in nm_oid_copy	gss_s_oc_nomem
Out of memory in nm_oid_set_add_elem	gss_s_osa_nomem
Out of memory in nm_oid_set_create_empty	gss_s_osc_nomem
Out of memory in pac_to_name	gss_s_ptn_nomem
Out of memory in string_to_irep	gss_s_nomem_1
Out of memory while trying to run down contexts of client %x	rpc_m_ctxrundown_nomem
out of space	tcl_s_tclregexp_out_of_space
Outcome %lx supplied in dce_aud_commit is not consistent with %lx supplied in dce_aud_start().	aud_s_outcomes_inconsistent
Outcome %lx supplied is invalid.	aud_s_invalid_outcome
Output cred-handle is NULL in gssdce_login_context_to_cred	gss_s_lcc_null
Output parameters must be passed by reference	NIDL_OUTPRMREF
Output parameters require an explicit top-level *	NIDL_OUTSTAR
Parameter attributes [in_line] and [out_of_line] cannot occur together	NIDL_PRMLINEATTR
Parameter error: Set one server at a time	KDDS22406-W
parameter must be non-NULL	sec_s_null_param_illegal
Parameter name %1\$s referenced in ACF operation %2\$s is not defined	NIDL_PRMNOTDEF
Parse table load failure (%d)n	CDSCP_LOAD_FAILURE
Parser: Allocating memory for option value failed (size = %d) %s	GDS_S_NDS_OPTMEM_ERR

Message Text	Symbolic Name
Parser: Can't allocate memory for net-address descriptions (%d bytes) %s	GDS_S_NDS_NETSPACE_ERR
Parser: Can't allocate work space memory (%d bytes) %s	GDS_S_NDS_WSPACE_ERR
Parser: Can't encode NSAP-address (error = %d) %s	GDS_S_NDS_ENSAP_ERR
Parser: compiling NSAP-address regular expression failed %s	GDS_S_NDS_CNSAP_ERR
Parser: E.163-information missing (e.g. CC/NP) %s	GDS_S_NDS_MISE163_ERR
Parser: E.164-information missing (e.g. CC/NDC) %s	GDS_S_NDS_MISE164_ERR
Parser: Inconsistent use of interface names (%s != %s) %s	GDS_S_NDS_IFNM_ERR
Parser: Inconsistent use of profile-ID (%d != %d) %s	GDS_S_NDS_PROFID_ERR
Parser: Maximal number of interface descriptions exceeded (maximum = %d) %s	GDS_S_NDS_IFMXDESC_ERR
Parser: Maximum number of net-address descriptions exceeded (maximum = %d) %s	GDS_S_NDS_MXNET_ERR
Parser: Maximum number of NSAP-address address map	GDS_S_NDS_MXOPT_ERR
Parser: Maximum number of profile descriptions exceeded (maximum = %d) %s	GDS_S_NDS_MXPROF_ERR
Parser: No interface description found %s	GDS_S_NDS_IFDESC_ERR
Parser: No NSAP-address found %s	GDS_S_NDS_NONSAP_ERR
Parser: Profile priority already exists (priority = %d) %s	GDS_S_NDS_PRIO_ERR

Message Text	Symbolic Name
Parser: %s %s	GDS_S_NDS_YACC_ERR
Parser: (Sub-)profile information missing %s	GDS_S_NDS_MISPROF_ERR
Parser: Syntax error (profile device missing) %s	GDS_S_NDS_DEVNM_ERR
Parser: Unknown representation for option detected (GDS_S_NDS_UNKNOWNREP_ERR
Parser: Unsufficient work space memory %s	GDS_S_NDS_UWSPACE_ERR
Parser: X.121-information missing (e.g. DCC/DNIC) %s	GDS_S_NDS_MISX121_ERR
Partial results	rpc_s_partial_results
Passphrases for all the public keys must be the same.	dcp_s_rgy_pk_inconsistent_passphrase
Password change is in progress.	KDDS22204-I
password failed password strength server checking policy	sec_pwd_mgmt_str_check_failed
Password for xxx was changed.	KDDS22208-I
Password is too long (Registry Edit Kernel)	ek_err_passwd_too_long
Password is too short	sec_rgy_passwd_too_short
Password is too short (Registry Edit Kernel)	ek_err_passwd_too_short
password management server generic error	sec_pwd_mgmt_svr_error
password management server is unavailable	sec_pwd_mgmt_svr_unavail
Password may not be randomly generated.	dcp_s_rgy_no_random_password
Password must be changed!	dcp_s_login_reset_password

Message Text	Symbolic Name
Password must be generated by password management server (Registry Editor/TTY Interface)	tty_pwd_gen_req
Password validation failure.	dcp_s_login_invalid_pw
Passwords must contain at least one non-alphanumeric character	sec_rgy_passwd_non_alpha
Passwords must contain at least one non-alphanumeric character (Registry Edit Kernel)	ek_err_passwd_non_alpha
Passwords must contain at least one non-blank character	sec_rgy_passwd_spaces
Passwords must contain at least one non-blank character (Registry Edit Kernel)	ek_err_passwd_spaces
Perform bind operation first.	gc_t_bind_not_made
Permanent virtual call (PVC)-number missing	GDS_S_NDS_PVC_ERR
Permission denied	svc_s_no_perm
Permission denied without proper protection level.	dced_s_need_privacy
permission not valid for this acl	sec_acl_invalid_permission
permission set is not valid for this acl manager type	sec_acl_bad_permset
Persistent errors on socket	rpc_s_socket_failure
pe_site file created	sec_crdb_site_file_create_succ
pe_site file not created	sec_crdb_site_file_create_fail
PGO alias entry has an invalid owner	sec_rgy_bad_alias_owner
PGO/account is required and can't be deleted	sec_rgy_s_pgo_is_required
Pipe client can't allocate memory (%d).	pks_s_pipclt_nomem
Pipe data error.	pks_s_pipe_data_error

Message Text	Symbolic Name
Pipe length error.	pks_s_int_length_error
Pipe length error (%d).	pks_s_int_length_errorp
Pipe server can't allocate memory (%d).	pks_s_pipsvr_nomem
Pipes are not valid as members of unions	NIDL_PIPEUNIMEM
Pipes are not valid as structure fields	NIDL_PIPESTRFLD
Pipes must be defined with a typedef	NIDL_ANONPIPE
Playback error: directory/replica %s was not created due to	cds_s_replay_dirmem_a
Playback error: directory/replica %s was not created due to an internal	cds_s_replay_dirinternal_a
Playback error: object %s was not created due to an internal error: %s	cds_s_replay_objinternal_a
Playback error: object %s was not created due to insufficient memory.	cds_s_replay_objmem_a
Please enter a name for imported group (%d):	pwd_imp_msg_enter_group_name
Please verify that no other %s is active on this system.	cds_s_library_alreadyrunning
Pointers to context handles are valid only in parameter declarations	NIDL_INVPTRCTX
Pointers to pipes are valid only in parameter declarations	NIDL_INVPTRPIPE
Pointers to type handle_t are valid only in parameter declarations	NIDL_HANDLEPTR
Pointers to [v1_enum] types are not allowed	NIDL_PTRV1ENUM
Pointers to varying arrays are not allowed	NIDL_PTRVARYARR
Pool of open C-ISAM files is too small.	GDS_S_POOL_OPEN_OVFLW
poorly-formed floating-point value	tcl_s_expr_poor_flat_val_form

Message Text	Symbolic Name
POSIX signals are unavailable on this system.	dcp_s_signal_posix_unavailable
Possible cycle in soft links detected	CDS_POSSIBLECYCLE
Posting a cancel to thread %s	sec_thr_post_cancel
Postprocessor for %s completed successfully	dced_s_postprocessor_ok
Postprocessor for %s exited with status %d	dced_s_postprocessor_bad
Pre-authentication directory bad	dced_s_bad_keydir
Preauthentication failure.	sec_login_s_preauth_failed
Preparing import files.n	pwd_imp_inf_prepare_import
Principal already exists (Registry Edit Kernel)	ek_err_person_exists
Principal does not exist (Registry Edit Kernel)	ek_err_person_does_not_exist
Principal is not a member of specified group and org (Registry Edit Kernel)	ek_err_not_member_go
Principal is not a member of specified group (Registry Edit kernel)	ek_err_not_member_group
Principal is not a member of specified org (Registry Edit Kernel)	ek_err_not_member_org
Principal is not registered or has been removed	aud_s_unknown_principal_rc
Principal name contains an illegal character (Registry Edit Kernel)	ek_err_person_bad_name_chars
Principal name exists in registry and UNIX ids match.n	pwd_imp_err_pname_exist_match
Principal name exists in registry but UNIX ids don't match.n	pwd_imp_err_pname_exist_nmatch

Message Text	Symbolic Name
Principal name too long (Registry Edit Kernel)	ek_err_person_name_too_long
Principal name too long.n	pwd_imp_err_pname_too_long
Principal quota exhausted	sec_rgy_quota_exhausted
Principal "%s", Group "%d" - %sn	pwd_imp_err_add_princ_group
Principal %s is not registered or has been removed	aud_s_unknown_principal
Priority group done	rpc_s_priority_group_done
Priority out of valid range of 0 to 7.	dcp_s_rpc_bad_priority
priv server unavailable	sec_priv_s_server_unavailable
private key deletion functionality is not supported.	sec_pvtkey_key_deletion_not_supported
private key is required fro admin to update user's private key	sec_pvtkey_private_key_is_not_supplied
private key storage mechanism hasn't been initialized	sec_pvtkey_mechanism_not_init
privilege service delegation requests cannot cross cell boundaries	sec_priv_s_intercell_deleg_req
privileged operation invoked in unprivileged process	sec_login_s_privileged
Problem creating cell uuidn%s	sec_crdb_cant_create_celluuid
Problem in emit_line of op_list.c got status %d while trying to write:n%sn on %s.n	CDSCP_BUG_EMIT_LINE
Problem setting up rgy_creatorn%s	sec_crdb_cant_setup_rgycreator
procedure "%s" doesn't have an argument "%s"	tcl_s_cmdil_proc_no_argument
procedure "%s" has argument with no name	tcl_s_proc_no_name_arg
Process has completed normally.	exc_s_normal

Message Text	Symbolic Name
Process_context_token called wirth no token	gss_s_pct_no_token
Processing attribute configuration file %1\$s	NIDL_PROCESSACF
Profile element inquire failed	sec_rs_ns_prof_elt_inq_fail
Profile element not found	rpc_s_profile_element_not_found
Profile element replaced	rpc_s_profile_element_replaced
Profile element (%s) added	sec_rs_ns_prof_elt_add_succ
Profile element (%s) not added	sec_rs_ns_prof_elt_add_fail
Profile name is NULL	sec_rs_ns_null_profile
propagate updates to slaves	sec_prop_updates_to_slaves
Propagation failed : %s	sec_prop_fail
Propagation succeeded	sec_prop_succ
Propagation threads not created	sec_prop_no_prop_thrs
propagation type not init or initing	sec_rep_prop_type_not_init
Protection level changed unexpectedly	rpc_s_protect_level_mismatch
Protocol error	rpc_s_protocol_error
protocol level invalid	sec_priv_s_invalid_protect_lvl
Protocol sequence not supported	rpc_s_protseq_not_supported
PSAP string "%s" not found in %s.n	gsu_readline_dsas_found
psm internal error	sec_psm_internal_error
PSM was not initialized	sec_psm_not_init
Pthread mutex lock or unlock failed	db_s_mutex_lock_fail
pthread_mutex_init() failed	db_s_mutex_init_fail
Public key attribute read failed.	sec_pk_e_key_attr_read_failed
public key cache is fresh	dced_s_pkcache_key_fresh

Message Text	Symbolic Name
Public key domain not supported for this operation.	sec_pk_e_domain_unsupported
Public key usage type not supported.	sec_pk_e_usage_unsupported
Public key usage type unsupported.	dced_s_pkcache_usage_unsupp
pvtkey file cannot be opened.	sec_pvtkey_file_cannot_open_key_file
pvtkey file is locked by other process.	sec_pvtkey_file_locked
pwd_mgmt_binding ERA binding auth type cannot be none	sec_rgy_era_pwd_mgmt_auth_type
Query returned an alias and allow_aliases was not set	sec_rgy_is_an_alias
query trigger not supported for this operation	sec_attr_trig_query_not_sup
Ran out of aliases	sec_rsd_b_acct_noaliases
ran out of memory	sec_pvtkey_no_more_memory
Reached end of database without being able to satisfy request.	CDS_GDB_NOT_FOUND
Reached end of file or argument list	svc_s_at_end
reached malloc break limit (%d)n	tcl_s_ckalloc_reached_malloc_break_limit
Reached maximum of %1\$lu warnings; exiting	NIDL_MAXWARN
Read catalog point: %s from profile: %s	sec_rs_ns_prof_elt_inq_succ
read reach the end of file	sec_pvtkey_no_more_data
Reading PSAP-address from DUA-cache failed because	GDS_S_CREADMSG_ERR
Reading PSAP-address from DUA-cache failed (code = %d,	GDS_S_CREAD_ERR
Ready to listen on interfaces...	pks_s_ready_to_listen
Rebound to site %s	sec_rca_site_rebind_succ

Message Text	Symbolic Name
Received CDS_NOCOMMUNICATION adding attribute %s to %sn	CDSCP_GRATTRS_1
Received FOREIGN_CELL_REFERRAL in pac_to_name	gss_s_ptn_referral
Received packet has an invalid checksum	rpc_s_invalid_checksum
Received packet has an invalid CRC	rpc_s_invalid_crc
Received RGY_SERVER_UNAVAILABLE. Retry count exceeded	gss_s_ptn_retry_exceeded
Received RGY_SERVER_UNAVAILABLE in pac_to_name. Retrying...	gss_s_ptn_server_unavailable
(receive_packet) assoc->%x frag_length %d in header > fragbuf data size %d	rpc_m_frag_toobig
(receive_packet) assoc->%x %s: Protocol version mismatch - major->%x minor->%x	rpc_m_prot_mismatch
Receiver cannot support authentication subtype	rpc_s_unsupported_auth_subtype
Receiving of an attention message failed (fd = %d, errno = %d)	GDS_S_IPCSRATT_ERR
Receiving of an IPC-message failed	GDS_S_IPCRMSG_ERR
Re-connection occurred in gateway xxx.	KDDS02135-I
Redirection of 'stdout' failed (errno = %d)	GDS_S_NDS_REDIR_ERR
Re-enter new password for xxx:	KDDS22207-I
Reenter password to verify:	sec_lksm_passwd_verify
Re-entered master key is unmatched.	KDDS10008-E
Re-entered password is unmatched.	KDDS10011-E
Referral returned - %s.	gc_t_referral_returned
regex too big	tcl_s_tclregex_too_big

Message Text	Symbolic Name
Registry bind retry count exceeded (last error = %x)	gss_s_frc_retry_exceeded
Registry database already exists	sec_crdb_db_exists
Registry is read only - updates are not allowed	sec_rgy_read_only
Registry is read only or operation performed at a slave (Registry Edit Kernel)	ek_misc_read_only
Registry object not found	sec_rgy_object_not_found
registry object not found	sec_attr_rgy_obj_not_found
Registry operation failed (%s): %s	sec_rca_op_status
Registry replica not specified.	dcp_s_rgy_sa_no_replica
Registry replica specified is not the master.	dcp_s_rgy_sa_replica_not_master
Registry replica specified is the master.	dcp_s_rgy_sa_already_master
Registry server is not available	aud_s_rgy_server_unavailable
Registry server '%s' is unavailable.	dcp_s_rgy_server_unavailable
Registry server unavailable	sec_rgy_server_unavailable
Registry server unavailable (Registry Edit Kernel)	ek_misc_no_site
Registry server unavailable (Registry Edit Kernel)	ek_misc_server_unavailable
Registry site name must be absolute	sec_rgy_site_not_absolute
Regular expression compilation error (reason = %s (%d)) %s	GDS_S_NDS_REGCOMP_ERR
Releasing heap memory failed (offset = %#x)	GDS_S_IPCHEAPREL_ERR
Remote host crashed	rpc_s_rem_host_crashed
Remote host is down	rpc_s_rem_host_down

Message Text	Symbolic Name
Remote host is unreachable	rpc_s_host_unreachable
Rename of %1\$s to %2\$s failed	NIDL_RENAMEFAILED
Reopening of NDS-configuration source file '%s' failed (errno = %d)	GDS_S_NDS_OCONF_ERR
replica already marked for initialization	sec_rgy_rep_marked_for_init
Replica cannot be added to old Clearinghouse	CDS_VERSIONSKEW
Replica cannot get local host identityn%s	sec_rgy_rep_host_identity
replica cannot support the specified software version	sec_rgy_rep_sw_rev_nosup
replica deleted	sec_rgy_rep_deleted
Replica is in dupe master state and cannot be started	sec_rep_dupe_cant_start
Replica is in dupe master state but is not the master	sec_rep_dupe_not_master
Replica is in maintenance state but is not the master	sec_rep_maint_not_master
Replica is no longer the master.	sec_rs_rep_not_master
Replica is not the master	sec_rgy_rep_not_master
Replica is the master	sec_rgy_rep_master
Replica not registered with nameservice	sec_crdb_rep_not_registered
Replica '%s' contains more up-to-date information.	dcp_s_rgy_sa_seqno_high
Replica set of specified directory contains more than one replica	CDS_MORETHANONEREPLICA
Replica type in global directory is neither a Master nor Readonly	cds_s_gda_badreplicatype
replication program error	sec_rgy_rep_pgmerr
replist field was NULL or empty	dced_s_empty_replist

Message Text	Symbolic Name
Request for a random key in this operation not allowed	dced_s_random_key_not_allowed
Request for a version zero in this operation not allowed	dced_s_key_v0_not_allowed
Requested attribute does not exist	CDS_UNKNOWNATTRIBUTE
Requested clearinghouse exists but is not available	CDS_CLEARINGHOUSEDOWN
Requested compatibility mode has not been enabled	sec_priv_s_cmode_not_enabled
Requested entry does not exist	CDS_UNKNOWNENTRY
Requested function not supported by this version of architecture.	CDS_NOTSUPPORTED
Requested IPC-server not available (server-ID = %d)	GDS_S_IPCNOSERV_ERR
Requested key is unavailable	sec_key_mgmt_e_key_unavailable
Requested operation would result in lost connectivity to root directory	CDS_ROOTLOST
Requested optional function is not implemented in this release	CDS_NOTIMPLEMENTED
Requested protection level is not supported	rpc_s_unsupported_protect_level
Requesting principal could not be authenticated to the clearinghouse	CDS_CANNOTAUTHENTICATE
Required attribute 'newpassphrase' not entered correctly.	dcp_s_rgy_pk_missing_newpass
Required attribute 'oldpassphrase' not entered correctly.	dcp_s_rgy_pk_missing_oldpass
Required group name attribute not provided.	dcp_s_rgy_acct_no_group
Required input not found (Registry Editor/TTY Interface)	tty_entry_is_required

Message Text	Symbolic Name
Required key version not entered.	dcp_s_kt_missing_key_version
Required option argument is missing (Registry Editor/TTY Interface)	tty_opt_requires_arg
Required option '%s' not entered.	dcp_s_sr_missing_req_opt
Required options not entered.	dcp_s_missing_req_opts
Required organization name attribute not provided.	dcp_s_rgy_acct_no_org
Requires more options.	dcp_s_log_no_modify_op
Requires more options.	dcp_s_acl_no_acl_modify_op
Resolve_cred - Couldn't lock cred-list	gss_s_res_cred_lock_failed
Resolve_cred - Couldn't lock ctx-list	gss_s_resolve_ctx_nolock
Resolve_cred - Cred %ld not found	gss_s_res_cred_not_found
Resource busy	EBUSY
Resource deadlock avoided	EDEADLK
Resource tag cannot be allocated.	KDDS10000-E
Resource temporarily unavailable	EAGAIN
Responding entity in wrong state to process requested operation	CDS_WRONGSTATE
restore_master specified but master not in service	sec_rep_rm_not_in_service
Result too large	ERANGE
ResumeThread failed: error code xxx.	KDDS11036-E
Retrieval of DCE cell name failed: %s	dts_s_get_cell_name
Retrieving RPC string binding handles for %s from file %s	sec_site_lookup_file
Return parameters NULL	sec_pk_e_kf_param_not_alloc
rock key is not valid	sec_cred_s_invalid_key
rock key not found	sec_cred_s_key_not_found

Message Text	Symbolic Name
Routine bind(2) failed on childsocket '%s' : errno = %ld.	cds_s_adver_bind
Routine bind(2) failed on %s: status = %ld.	cds_s_gda_bind_eb
Routine connect(2) failed : status = %ld.	cds_s_gda_connect
Routine dce_cf_get_cell_name failed : status = %ld.	cds_s_cfgetcellname
Routine dce_cf_get_host_name failed : status = %ld.	cds_s_cfgethostname
Routine dce_cf_prin_name_from_host failed : status = %ld.	cds_s_cfprinnamefromhost
Routine fork(2) failed : errno = %ld.	cds_s_library_forkself
Routine gethostname(2) failed: status = %s	cds_s_server_gethostname
Routine listen(2) failed on childsocket '%s' : errno = %ld.	cds_s_adver_listen
Routine mkfifo(2) failed on child fifo '%s' : errno = %ld.	cds_s_adver_mkfifo
Routine open(2) failed for shmid file %s with status %ld.	cds_s_cache_createshmid
Routine open(2) failed for shmid file %s with status %ld.	cds_s_cache_openshmid
Routine open(2) failed on child fifo '%s' : errno = %ld.	cds_s_adver_open
Routine pthread_attr_create failed : status = %ld.	cds_s_pthreadattrcreate
Routine pthread_attr_setstacksize failed : status %ld.	cds_s_pthreadattrsetstacksize
Routine pthread_cond_broadcast(3) failed : status = %ld.	cds_s_pthreadcondbroadcast

Message Text	Symbolic Name
Routine pthread_cond_broadcast(3) failed : status = %ld.	cds_s_pthreadcondbroadcast_a
Routine pthread_cond_destroy failed : status = %ld.	cds_s_pthreadconddestroy
Routine pthread_cond_destroy failed : status = %ld.	cds_s_pthreadconddestroy_a
Routine pthread_cond_init failed : status = %ld.	cds_s_pthreadcondinit
Routine pthread_cond_init failed : status = %ld.	cds_s_pthreadcondinit_a
Routine pthread_cond_signal failed : status = %ld.	cds_s_pthreadcondsignal
Routine pthread_cond_signal failed : status = %ld.	cds_s_pthreadcondsignal_a
Routine pthread_cond_timedwait failed : status = %ld.	cds_s_pthreadcondtimedwait
Routine pthread_cond_timedwait failed : status = %ld.	cds_s_pthreadcondtimedwait_a
Routine pthread_cond_wait failed : status = %ld.	cds_s_pthreadcondwait
Routine pthread_cond_wait failed : status = %ld.	cds_s_pthreadcondwait_a
Routine pthread_create failed : status = %ld.	cds_s_pthreadcreate
Routine pthread_create failed : status = %ld.	cds_s_pthreadcreate_a
Routine pthread_delay_np failed : status = %ld.	cds_s_pthreaddelay_a
Routine pthread_keycreate failed : status = %ld.	cds_s_pthreadkeycreate

Message Text	Symbolic Name
Routine pthread_mutex_destroy failed : status = %ld.	cds_s_pthreadmutexdestroy
Routine pthread_mutex_destroy failed : status = %ld.	cds_s_pthreadmutexdestroy_a
Routine pthread_mutex_init failed : status = %ld.	cds_s_pthreadmutexinit
Routine pthread_mutex_init failed : status = %ld.	cds_s_pthreadmutexinit_a
Routine pthread_mutex_lock failed : status = %ld.	cds_s_pthreadmutexlock
Routine pthread_mutex_lock failed : status = %ld.	cds_s_pthreadmutexlock_a
Routine pthread_mutex_trylock(3) failed : status = %ld.	cds_s_pthreadmutextrylock
Routine pthread_mutex_unlock failed : status = %ld.	cds_s_pthreadmutexunlock
Routine pthread_mutex_unlock failed : status = %ld.	cds_s_pthreadmutexunlock_a
Routine pthread_setspecific failed : status = %ld.	cds_s_pthreadsetspecific
Routine read(2) failed : status = %ld.	cds_s_gda_read
Routine read(2) failed for shmid file %s with status %ld.	cds_s_cache_readshmid
Routine recvfrom(2) failed : status = %ld.	cds_s_gda_recvfrom_eb
Routine rpc_binding_from_string_binding(3rpc) failed : status = %ld.	cds_s_rpcbindingfromstring
Routine rpc_binding_inq_auth_client(3rpc) failed : status = %ld.	cds_s_rpcbindinginqauth

Message Text	Symbolic Name
Routine rpc_binding_reset(3rpc) failed : status = %ld.	cds_s_rpcbindingreset
Routine rpc_binding_set_auth_info(3rpc) failed : status = %ld.	cds_s_rpcsetauthinfo
Routine rpc_binding_set_object(3rpc) failed: status = %ld.	cds_s_rpcsetobject
Routine rpc_binding_to_string_binding(3rpc) failed : status = %ld.	cds_s_rpcstringtobinding
Routine rpc_ep_register(3rpc) failed: status = %ld.	cds_s_rpcregisterep
Routine rpc_ep_resolve_binding(3rpc) failed : status = %ld.	cds_s_rpcresolvebinding
Routine rpc_ep_unregister(3rpc) failed: status = %ld.	cds_s_rpcunregisterep
Routine rpc_ns_binding_export(3rpc) failed: status = %ld.	cds_s_rpcbindingexport
Routine rpc_ns_binding_unexport(3rpc) failed: status = %ld.	cds_s_rpcbindingunexport
Routine rpc_server_init() failed : status = %ld.	cds_s_rpcserverinit
Routine rpc_server_inq_bindings(3rpc) failed : status = %ld.	cds_s_rpcinqbindings
Routine rpc_server_listen(3rpc) failed : status = %ld.	cds_s_rpcserverlisten
Routine rpc_server_register_auth_info(3rpc) failed : status = %ld.	cds_s_rpcregisterauthinfo
Routine rpc_server_register_if(3rpc) failed : status = %ld.	cds_s_rpcregisterif
Routine rpc_server_use_all_protseqs(3rpc) failed: status = %ld.	cds_s_rpcuseallprotseqs

Message Text	Symbolic Name
Routine rpc_string_binding_compose(3rpc) failed : status = %ld.	cds_s_rpcstringbindingcompose
Routine rpc_tower_to_binding(3rpc) failed : status = %ld.	cds_s_rpctowertobinding
Routine rpc_tower_vector_from_binding(3rpc) failed : status = %ld.	cds_s_rpctowervectorfrombind
Routine rpc_tower_vector_from_binding(3rpc) failed : status = %ld.	cds_s_rpctowerfrombinding
Routine sec_id_parse_name(3sec) failed : status = %ld.	cds_s_secidparsename
Routine sec_login_import_context(3sec) failed : status = %ld.	cds_s_secimportctx
Routine sec_rgy_cell_bind(3sec) failed on %s: status = %ld.	cds_s_secrgycellbind
Routine sec_rgy_pgo_is_member(3sec) failed : status = %ld.	cds_s_secrgypgoismember
Routine sec_rgy_pgo_name_to_id(3sec) failed : status = %ld.	cds_s_secrgypgonametoid
Routine sec_rgy_site_bind(3sec) failed on %s: status = %ld.	cds_s_secrgysitebind
Routine sec_rgy_site_open(3sec) failed: status = %ld.	cds_s_secrgysiteopen
Routine semop(2) failed: %s.	cds_s_cache_semop
Routine sendto(2) failed : status = %ld.	cds_s_gda_sendto
Routine setsid(2) failed(%s) trying to set process group id	cds_s_library_setsid
Routine socket(2) failed : status = %ld.	cds_s_gda_socket

Message Text	Symbolic Name
Routine socket(2) failed to create child socket : errno = %ld	cds_s_adver_socket
Routine uuid_from_string(3rpc) failed : status = %ld.	cds_s_uuidfromstr
Routine write(2) failed : status = %ld.	cds_s_gda_write
Routine write(2) failed for shmid file %s with status %ld.	cds_s_cache_writeshmid
Routine writev(2) failed : status = %ld.	cds_s_gda_writev
RPC call ClerkRequistTime() to remote server failed: %s	dts_s_clerk_request
RPC class version mismatch	rpc_s_class_version_mismatch
RPC client used wrong protection level	aud_s_wrong_protection_level
RPC coding error	rpc_s_coding_error
RPC daemon communications failure	rpc_s_rpcd_comm_failure
rpc error on acl operation	sec_acl_rpc_error
RPC interfaces registered.	sec_rs_rpc_if_reg_succ
RPC interfaces unregistered.	sec_rs_rpc_if_unreg_succ
RPC propagation interfaces registered.	sec_rs_rpc_propif_reg_succ
RPC propagation interfaces unregistered.	sec_rs_rpc_propif_unreg_succ
RPC protocol not supported by this authentication protocol	rpc_s_proto_unsupp_by_auth
RPC protocol version mismatch	rpc_s_rpc_prot_version_mismatch
RPC String bindings appended to pe_site file	sec_crdb_site_file_upd_succ
RPC string bindings not appended to pe_site file	sec_crdb_site_file_upd_fail
RPC-server binding info: %s	GDS_S_RPC_BINDINFO
rpc_sm_enable_alloc returned status %ld : %s	cds_s_bad_rpc_alloc

Message Text	Symbolic Name
rs_login_inherit_host_identity must be called before rs_login_become_rgy	sec_rs_login_wrong_call
rs_ns_sec_group_name_v1 is NULL.	sec_rs_ns_null_v1_group
Running C preprocessor %1\$s	NIDL_RUNCPP
Running %s without privileges	aud_s_dmn_privilege
%s	pwd_imp_prompt_print
%s : %s	sec_sys_errno_file_text
(%s) Attempt to free already-freed DG packet	rpc_m_dgpkt_bad_free
%s bytes (%4ld files)	KDDS23800-I
%s: call failed	rpc_m_call_failed_no_status
(%s) Call not implemented	rpc_m_unimp_call
(%s) Can't create UUID	rpc_m_cant_create_uuid
(%s) Can't handle pre-v2 server stubs	rpc_m_pre_v2_ss
(%s) Can't open file %s.	rpc_m_cant_open_file
(%s %d) is the conflicting entry from the registry.n	pwd_imp_msg_conflict_entry
(%s) DG packet free pool is corrupted	rpc_m_dgpkt_pool_corrupt
%s distinguished thread cancelled	aud_s_dmn_distinguished_thread_fault
"%s" doesn't appear in event	tcl_s_hist_evt_does_not_appear
(%s) Error message will not fit in packet	rpc_m_errmsg_toobig
(%s) Event list full	rpc_m_eventlist_full
%s exits normally	aud_s_dmn_normal_exit
%s failed ; errno text : %s	sec_sys_errno_text
%s failed, errno = %d	rpc_m_call_failed_errno
%s failed for unknown reason.	cds_s_addcell_xds_unknown
%s failed: %s	rpc_m_call_failed

Message Text	Symbolic Name
(%s) Illegal or unknown packet type: %x	rpc_m_bad_pkt_type
%s in asn1_attr file cannot be converted.	GDS_S_OBID_ASN1_ATTR_ERR
(%s) Inconsistency in ACC_BYTCNT field	rpc_m_invalid_accbytcent
(%s) Invalid call sequence number	rpc_m_invalid_seqnum
%s is not a known event class.	aud_s_unknown_event_class
"%s" isn't a procedure	tcl_s_cmdil_is_not_a_proc
"%s" isn't an array	tcl_s_tclvar_isnt_array
(%s) Lookaside list is corrupted	rpc_m_lookaside_corrupt
(%s) Memory allocation failed	rpc_m_alloc_fail
(%s) Memory reallocation failed	rpc_m_realloc_fail
(%s) Negotiated transfer syntax not found in presentation context element	rpc_m_nts_not_found
(%s) No stub data to send	rpc_m_no_stub_data
%s non-distinguished thread cancelled	aud_s_dmn_non_distinguished_thread_fault
%s on client failed: %s	rpc_m_call_failed_c
%s on server failed: %s	rpc_m_call_failed_s
%s: Option -d requires argumentn	pwd_exp_cl_bad_opt_d
%s: Option -m requires argumentn	pwd_exp_cl_bad_opt_m
(%s) Pre-v2 interface spec	rpc_m_pre_v2_ifspec
%s Profile element not removed	sec_rs_ns_prof_elt_rm_fail
%s Profile element removed	sec_rs_ns_prof_elt_rm_succ
%s removed NSI and from group entry %s	sec_rs_ns_name_del_succ
%s returned error : status = %ld	cds_s_addcell_xds_error
%s %s has been deleted from the trustees for %s.	KDDS23400-I

Message Text	Symbolic Name
(%s) Socket's maximum receive buffering is less than NCA Connection Protocol minimum requirement	rpc_m_rcvbuf_toosmall
%s thread cancelled. Execution terminated.	sec_thr_exit_cancel
%s thread got exception	aud_s_dmn_distinguished_thread_exit
"%s" thread is going to exit	sec_rs_thr_exiting
"%s" thread started	sec_rs_thr_started
(%s) Unaligned RPC_CN_PKT_AUTH_TRL	rpc_m_unalign_authtrl
(%s) Unexpected exception was raised	rpc_m_unexpected_exc
(%s) Unexpected search attribute seen	rpc_m_invalid_srchattr
(%s) Unhandled call state: %s	rpc_m_unhandled_callstate
%s: Unknown command line option %sn	pwd_exp_cl_bad_arg
(%s) Unknown interface spec version	rpc_m_unk_ifspec
(%s) Unknown socket type	rpc_m_unk_sock_type
(%s) Unsupported stub/RTL IF version	rpc_m_unsupp_stub_rtl_if
%s: User entered an illegal number of requested entries,n	pwd_exp_cl_bad_entries
"%s" wasn't opened for reading	tcl_s_unixutil_file_not_open_reading
"%s" wasn't opened for writing	tcl_s_unixutil_file_not_open_writing
same domain and usage key already exist	sec_pvtkey_same_domain_and_usage_key_already_exist
Saving file %s	sec_rgy_chkpt_save_file
Saving relation %s	sec_rgy_chkpt_save_relation
schema entry not found	sec_attr_sch_entry_not_found
Schema entry '%s' not found.	dcp_s_rgy_sch_entry_not_found

Message Text	Symbolic Name
scope doesn't name existing directory or pgo	sec_rgy_bad_scope
Screens cannot be displayed due to memory shortage.	KDDS10027-E
Screens cannot be generated due to memory shortage.	KDDS10029-E
SEAL algorithm must be NONE for Sign/Delete tokens	gss_s_dmh_seal_sd
Seal algorithm not allowed for SIGN/DELETE token	gss_s_bp_noseal
Search for a security server using profile %s failednt%s	sec_site_profile_search_fail
search identifier "%s" isn't for variable "%s"	tcl_s_tclvar_search_id_var
SEC_ACL_EDIT - bad data format	ae_tty_bad_data_format
SEC_ACL_EDIT - bad domain	ae_tty_bad_domain
SEC_ACL_EDIT - entry required	ae_tty_entry_is_required
SEC_ACL_EDIT - error while reading from file	deif_err_file_read
SEC_ACL_EDIT - incompatible options	ae_tty_incompatible_options
SEC_ACL_EDIT - input out of range	ae_tty_input_out_of_range
SEC_ACL_EDIT - input too long	ae_tty_err_input_too_long
SEC_ACL_EDIT - invalid argument	ae_tty_invalid_argument
SEC_ACL_EDIT - invalid entry specification	deif_err_invalid_entry
SEC_ACL_EDIT - invalid entry type	deif_err_invalid_entry_type
SEC_ACL_EDIT - invalid key	deif_err_invalid_key
SEC_ACL_EDIT - invalid operation on this entry type	deif_err_invalid_entry_op

Message Text	Symbolic Name
SEC_ACL_EDIT - invalid option	ae_tty_invalid_option
SEC_ACL_EDIT - invalid or unknown entry key	deif_err_invalid_entry_key
SEC_ACL_EDIT - invalid permission string	deif_err_invalid_perm
SEC_ACL_EDIT - operation requires argument	ae_tty_opt_requires_arg
SEC_ACL_EDIT - specified entry not found	deif_err_entry_not_found
SEC_ACL_EDIT - too many arguments	ae_tty_too_many_args
SEC_ACL_EDIT - unable to communicate with registry server	deif_err_rgy_not_found
SEC_ACL_EDIT - unable to open file	deif_err_file_open
SEC_ACL_EDIT - unable to parse string	ae_tty_cant_parse
SEC_ACL_EDIT - unknown command	ae_tty_args_not_command
SEC_ACL_EDIT - would unintentionally grant permissions via recalculated mask	ae_tty_would_grant_perms
SEC_ACL_EDIT_PAD1	SEC_ACL_EDIT_PAD1
SEC_ACL_EDIT_PAD2	SEC_ACL_EDIT_PAD2
SEC_ACL_EDIT_PAD3	SEC_ACL_EDIT_PAD3
SEC_ACL_EDIT_PAD4	SEC_ACL_EDIT_PAD4
SEC_ACL_EDIT_PAD5	SEC_ACL_EDIT_PAD5
SEC_ACL_EDIT_PAD6	SEC_ACL_EDIT_PAD6
SEC_ACL_EDIT_PAD7	SEC_ACL_EDIT_PAD7
SEC_ACL_EDIT_PAD8	SEC_ACL_EDIT_PAD8
SEC_ACL_EDIT_PAD9	SEC_ACL_EDIT_PAD9
SEC_ACL_EDIT_PADa	SEC_ACL_EDIT_PADa
SEC_ACL_EDIT_PADb	SEC_ACL_EDIT_PADb

Message Text	Symbolic Name
SEC_ACL_EDIT_PADc	SEC_ACL_EDIT_PADc
SEC_ACL_EDIT_PADd	SEC_ACL_EDIT_PADd
SEC_ACL_EDIT_PADe	SEC_ACL_EDIT_PADe
SEC_ACL_EDIT_PADf	SEC_ACL_EDIT_PADf
sec_cred_get_delegation_type failed (%x)	gss_s_gdt_scgdt_failed
sec_cred_get_initiator failed in pac_to_name (%x)	gss_s_ptn_scg_failed
sec_cred_get_pa_data failed in pac_to_name (%x)	gss_s_ptn_scgp_failed
sec_des_key_sched failed (%x)	gss_s_fmi_ksched_failed
sec_id_parse_name returned status %ld to general : %s	cds_s_parse_name
sec_krb_build_message_common failed (%x)	gss_s_seca_skbmc_failed
sec_krb_decode_msg_common failed (%x: %s)	gss_s_seca_skdmc_failed
sec_krb_gss_build_message failed (%x)	gss_s_ic_skbm_failed
sec_krb_gss_build_rep_message failed (%x)	gss_s_ac_skbr_failed
sec_krb_gss_decode_message failed (%x)	gss_s_ac_skdm_failed
sec_krb_gss_decode_rep_message failed (%x)	gss_s_ic_mutual_dec_failed
sec_login_setup_identity failed (%x)	gss_s_gac_sls_failed
sec_login_valid_from_keytable failed (%x)	gss_s_gac_slv_failed
sec_pvtkey module internal error. Please inform the developer.	sec_pvtkey_internal_error
sec_pvtkey__lookup_keystore(%s) - Bad UUID in keystore %d (%.32s)	sec_psm_i_bad_keystore_id

Message Text	Symbolic Name
sec_pvtkey__lookup_keystore(%s) - Discarded keystore %d (%.32s, uuid %s)	sec_psm_i_discarded_keystore
sec_pvtkey__lookup_keystore(%s) - No default keystore ERA	sec_psm_i_no_def_keystore_era
sec_pvtkey__lookup_keystore(%s) - No principal keystore ERA	sec_psm_i_no_prin_keystore_era
sec_pvtkey__lookup_keystore(%s) - Returning keystore %d (%.32s)	sec_psm_i_chosen_keystore
sec_pvtkey__lookup_keystore(%s) - Returning matchall keystore %d (%.32s)	sec_psm_i_matchall_keystore
sec_pvtkey__lookup_keystore(%s) - Searching for ERA-match keystore %s	sec_psm_i_searching_explicit
sec_pvtkey__lookup_keystore(%s) - Searching for matchall keystore	sec_psm_i_searching_matchall
sec_pvtkey__lookup_keystore(%s) - Using default keystore %d (%.32s)	sec_psm_i_def_keystore
sec_pvtkey__lookup_keystore(%s) failed - Bad domain	sec_psm_i_bad_domain
sec_pvtkey__lookup_keystore(%s) failed - Bad ERA lookup (0x%x)	sec_psm_i_era_lookup_failure
sec_pvtkey__lookup_keystore(%s) failed - No appropriate keystore	sec_psm_i_no_keystore
sec_pvtkey__register_keystore - Bad UUID in keystore %d (%.32s)	sec_psm_i_bad_keystore_id1
sec_rgy_site_bind returned status %ld : %s	cds_s_site_bind
security server program error	sec_s_pgmerr
Security server software version cannot be rolled back dynamically	sec_rgy_rep_sw_rev_no_setback
Security server software version must be set forward one version at a time	sec_rgy_rep_sw_rev_multi

Message Text	Symbolic Name
security service does not support version 1.1 security features	sec_s_v1_1_no_support
secval service already enabled	dced_s_sv_already_enabled
secval service failed to update the pe_site status=0x%8.8lx	dced_s_sv_update_pe_site_fail
secval service is not enabled	dced_s_sv_not_enabled
Seek operation on file failed, errno = %d.	GDS_S_SEEK_ERR
Select one of: (a)lias, (g)enerate, (e)nter, (s)kip entry, (h)elp:	pwd_imp_prompt_select_conflict_action
Selected gateway xxx does not exist in / etc/hosts file.	KDDS01306-E
Semaphore operation failed (operation = %d, errno = %d).	GDS_S_SEMOP_ERR
Sending distributed command failed because of time	GDS_S_IPCTMEX_ERR
Sending of an attention message failed	GDS_S_IPCSSATT_ERR
Sending of an IPC-message failed	GDS_S_IPCSMSG_ERR
Sequence number invalid in decode_message_header	gss_s_dmh_seq_num_inv
Sequence number out of range	gss_s_vrs_seq_invalid
Server clocks are not synchronized	CDS_BADCLOCK
Server exiting	dts_s_exiting
server identity has already been registered	sec_s_multiple_u2u_reg
Server initialization completed	cds_s_server_initcomplete
server is read only	sec_attr_svr_read_only
server is unavailable	sec_attr_svr_unavailable
Server keytab file name not found	dced_s_no_server_keyfile
Server not a member of time servers security group	dts_s_serv_not_in_ts_group

Message Text	Symbolic Name
Server process has insufficient access to clearinghouse	CDS_UNTRUSTEDCH
Server process not specified.	dcp_s_log_no_server
Server %s not in security group %s	dts_s_not_in_group
Server %s not responding, error return is %s	dts_server_not_responding
Server %s returned invalid timestamp.	dts_s_bad_timestamp
Server started	dts_s_starting
Server stub not linked into application	rpc_s_no_server_stub
Server too busy	rpc_s_server_too_busy
Server unable to access %s.	cds_s_server_securityevent
Server value out of range	dts_s_servers_range
Server was not started by dced	dced_s_not_started_by_dced
Server will not accept propagations now because it is serving as initializer ('from_rep') to a new slave	sec_rgy_rep_prop_from_rep
Server xxx is processing DCE logout.	KDDS22105-I
serviceability function call failed (status = %#x)	GDS_S_RPC_SVC_FAILED
Set daemon locale: %s	aud_s_dmn_locale
Setlocale failed, continuing with C locale: xxx	KDDS01309-E
Setting account admin flag to allow %s account to be a clientn	sec_lksm_set_client_valid
Setting account admin flag to allow %s account to be a servern	sec_lksm_set_server_valid
Setting account valid flag for %s accountn	sec_lksm_set_acct_valid
Setting password valid flag for %s accountn	sec_lksm_set_pwd_valid

Message Text	Symbolic Name
Setting policy account lifespan to %d minutes (or %d hours or %d days)n	sec_lksm_set_acct_span
Setting policy password expiration time to %d minutes from nown	sec_lksm_set_polpwd_expire_now
Setting policy password lifetime to %d minutesn	sec_lksm_set_polpwd_expire
Setting %s account good_since_date to nown	sec_lksm_set_date_now
Setting %s account to expire in %d minutesn	sec_lksm_set_expire
Setting up registry information.n	pwd_imp_inf_prepare_rgy
Shared memory already allocated: will be re-allocated.	KDDS02521-I
Shared memory id (%d) invalid : status = %ld.	cds_s_child_badshmem_eb
Shared memory id is required.	cds_s_child_noshmem_eb
Shell text too long (Registry Edit Kernel)	ek_err_shell_too_long
shmid file %s unlinked.	cds_s_cache_shmidremove
shmid(%d) creator process died, clerk processes may still be active	cds_s_cache_usermapped
shmid(%d) creator process pid(%d) is still active.	cds_s_cache_creatormapped
shmid(%d) reassigned to another process.	cds_s_cache_reuseid
shmid(%d) removed.	cds_s_cache_rmid
Short read from kernel helper	rpc_s_helper_short_read
Short token in decode_message_header	gss_s_dmh_short_token
Shutdown complete	dts_s_shutdown_complete
Shutdown completed	sec_rgy_shutdown_done
Signal %d terminates process.	GDS_S_SIGNAL_ERR

Message Text	Symbolic Name
Signal interpreter lost.	dcp_s_signal_lost_interp
simultaneous registration of both keytable and identity not supported	sec_s_svr_type_conflict
Size attributes can only be applied to array types	NIDL_SIZEARRTYPE
Skulk failed for %s in phase %s: reason = %s, status = %ld.	cds_s_server_skulkstat1
Skulk failed for %s in phase %s: status = %ld.	cds_s_server_skulkstat2
Skulk in progress terminated; superseded by more recent skulk.	CDS_OLDSKULK
slave already initialized	sec_rgy_rep_already_initied
Slave initialization done	sec_prop_slave_init_done
slave is running a bad software version	sec_rgy_rep_slave_bad_sw_vers
slave must have missed/lost some update from master	sec_rgy_rep_update_seqno_high
slave received an old update from master	sec_rgy_rep_update_seqno_low
Slave received become master message	sec_rep_rcv_become_master
Slave received i_am_master message	sec_rep_rcv_i_am_master
Slave received initialization request	sec_rep_rcv_init_slave
Slave received stop until software compatible request	sec_rep_rcv_stop_sw_compat
Slave wants init to re-sync with master	sec_rgy_rep_must_init_slave
%sn	pwd_imp_msg_conflict_rgy_st
Socket failure	uuid_s_socket_failure
Software error detected in server	CDS_NAMESERVERBUG
Software version incompatible with master's version. Server is going to exit	sec_rs_rep_incompat_version
Some part of the Directory	DS_E_UNWILLING_TO_PERFORM

Message Text	Symbolic Name
Some part of the Directory is currently not available.	DS_E_UNAVAILABLE
Some permanent difficulty encountered.	gc_t_om_permanent_error
Specified attribute cannot be modified	CDS_INVALIDUPDATE
Specified attribute type is incorrect	CDS_WRONGATTRIBUTETYPE
specified capability name not supported	sec_pvtkey_unsupported_capability_name
specified capability not supported	sec_pvtkey_capability_not_supported
Specified clearinghouse already contains a copy of the directory	CDS_ALREADYREPLICA
Specified clearinghouse does not contain a copy of the directory	CDS_NOTAREPLICA
Specified clearinghouse does not exist	CDS_UNKNOWNCLEARINGHOUSE
Specified directory does not allow clearinghouse name storage	CDS_NOTCHDIRECTORY
Specified directory name too long (%s).	pwd_imp_err_path_too_long
Specified field is not in use in this operation (Registry Edit Kernel)	ek_field_unused
Specified file is not a valid key table	sec_key_mgmt_e_ktfile_err
Specified full name already exists	CDS_ENTRYEXISTS
Specified key already exists in key store	sec_key_mgmt_e_key_version_ex
Specified key table not found	sec_key_mgmt_e_keytab_not_found
Specified name exists but is not a soft link	CDS_NOTLINKED
Specified object already exists (Registry Edit Kernel)	ek_err_object_exists
Specified soft link points to nonexistent entry	CDS_DANGLINGLINK
Start dfaagt with Supervisor mode. (xxx)	KDDS02008-E

Message Text	Symbolic Name
Started administration threads initialization.	KDDS11639-I
Started administration threads termination.	KDDS11642-I
Started agent emergency termination.	KDDS01101-I
Started agent initialization.	KDDS02000-I
Started agent termination.	KDDS01100-I
Started re-connection with agent.	KDDS11636-I
Started volume %s cleanup.	KDDS11634-I
Started volume %s initialization.	KDDS11631-I
Starting search for security server using profile %s	sec_site_profile_search_start
Startup completed	dts_s_startup_done
Startup completed	dts_s_startup_done_set
Startup completed	sec_rgy_startup_done
Status %d returned from parse%sn	CDSCP_MSG_PARSE_STATUS
Stopped outputting trace information of process xxx.	KDDS02101-I
Stopped outputting trace information to file	KDDS02100-I
Stored master key is bad	sec_rgy_mkey_bad_stored
Structure fields cannot be of type handle_t	NIDL_HANSTRFLD
Structures containing conformant arrays must be passed by reference	NIDL_CFMTARREF
Structures with [transmit_as] or [represent_as] cannot be conformant	NIDL_STRUCTXMITCFMT
Stub or runtime protocol error	rpc_s_stub_protocol_error
Subdirectory of %s	KDDS23700-I
Subnetwork-ID missing	GDS_S_NDS_SUBID_ERR

Message Text	Symbolic Name
Subordinates not found.	gc_t_subordinates_not_found
Subtracting an absolute timestamp from a relative timestamp is not allowed.	dcp_s_utc_sub_abs_from_rel
Success, may be stale	CDS_SUCCESS_STALE
Successful completion.	_____
Successful completion	dce_cf_st_ok
Successful completion	svc_s_ok
Successful completion.	CDS_SUCCESS
Successful completion	dts_s_normal
Successful completion	dcp_s_ok
Successful completion	msg_s_ok
Successful completion	msg_s_ok_text
Successfully bound to registry site %s	sec_site_bind_succ
Successfully checkpointed registry database	sec_rgy_checkpoint_succ
Successfully created registry database	sec_crdb_cr_db_succ
Successfully exported bindings to %s	sec_rs_ns_bind_export_succ
Successfully located security server %s using profile %s	sec_site_profile_search_succ
Successfully rebound to registry site %s	sec_site_rebind_succ
Successfully re-connected with agent.	KDDS11637-I
Successfully removed bindings from %s	sec_rs_ns_bind_remove_succ
Successfully replayed the log file	sec_rs_log_replay_succ
Supplied 'acctlife' is a bad date value.	dcp_s_rgy_acct_is_bad
Supplied attribute 'oldpassphrase' is illegal during a create operation.	dcp_s_rgy_pk_illegal_oldpass
Supplied attribute '%s' is illegal.	dcp_s_rgy_illegal_attr
Supplied attribute '%s' is unknown.	dcp_s_rgy_pk_unknown_attr

Message Text	Symbolic Name
Supplied attribute '%s' was specified more than once.	dcp_s_rgy_pk_too_many_attr
Supplied 'gid' must be a positive integer.	dcp_s_rgy_gid_is_wrong
Supplied 'gid' must be less than %d.	dcp_s_rgy_gid_out_of_range
Supplied master key is bad	sec_rgy_mkey_bad
Supplied 'orgid' must be a positive integer.	dcp_s_rgy_orgid_is_wrong
Supplied 'orgid' must be less than %d.	dcp_s_rgy_orgid_out_of_range
Supplied 'pwdlife' is a bad date value.	dcp_s_rgy_pwdlife_is_bad
Supplied 'padminlen' is not a positive integer.	dcp_s_rgy_padminlen_not_int
Supplied 'padminlen' must be a positive integer.	dcp_s_rgy_padminlen_is_negative
Supplied 'padminlen' must be less than %d.	dcp_s_rgy_padminlen_out_of_range
Supplied 'quota' is not a positive integer or 'unlimited'.	dcp_s_rgy_quota_not_int
Supplied 'quota' must be a positive integer.	dcp_s_rgy_quota_is_negative
Supplied 'quota' must be less than %d.	dcp_s_rgy_quota_out_of_range
Supplied 'uid' must be a positive integer.	dcp_s_rgy_uid_is_wrong
Supplied 'uid' must be less than %d.	dcp_s_rgy_uid_out_of_range
Supplied value for attribute of type void must be 'present'.	dcp_s_rgy_era_not_present
Supplied value for extended attribute is not a valid byte sequence.	dcp_s_rgy_era_invalid_byte
Supplied value for extended attribute is not a valid UUID.	dcp_s_rgy_era_not_uuid
Supplied value for extended attribute is not an integer.	dcp_s_rgy_era_not_int

Message Text	Symbolic Name
Supplied value for extended attribute is not less than %d.	dcp_s_rgy_era_out_of_range
Supplied value for key generation attribute must be less than %d.	dcp_s_rgy_pk_genkey_out_of_range
Supplied value for '%s' must be zero, a positive integer or 'default'.	dcp_s_rgy_pk_genkey_not_int
Supplied value for '%s' must not be a negative integer.	dcp_s_rgy_pk_genkey_is_negative
SVR4 TBD	exc_s_ftres
Synchronisation of IPC-shared memory access failed	GDS_S_IPCSYNC_ERR
Synchronization completed, computed time = %s, adjustment = %s	dts_s_sync_complete
Syntax error	NIDL_SYNTAXERR
Syntax error in attribute list	NIDL_ERRINATTR
syntax error in expression "%s"	tcl_s_expr_syntax_err
Syntax error in UUID format	NIDL_SYNTAXUUID
Syntax error near "%2\$.*1\$s"	NIDL_SYNTAXNEAR
Syntax errorn%sn%s^n	CDSCP_PARSE_ERROR
System communication process terminated due to an unexpected	KDDS02031-E
System communication process terminated: xxx	KDDS02301-E
System error	KDDS23120-E
System error message: %1\$s	NIDL_SYSERRMSG
System error occurred in agent	KDDS22417-E
System error occurred in DCE	KDDS22418-E
System error occurred in gateway	KDDS22411-E
system ran out of memory	sec_psm_no_more_memory

Message Text	Symbolic Name
Tag parameters must have type unsigned long int passed by value or reference	NIDL_TAGPRMTYPE
target cell name too long for cache file	sec_pk_e_cell_too_long
Target language supports maximum of %1\$lu array dimensions	NIDL_LANGMAXDIM
Tcl_AppInit failed: %sn	tcl_s_main_appl_init_failed
TclSignalTrap bug occurred.	dcp_s_signal_bug
TCP/IP Port Number xxx is equal or smaller than 5000.	KDDS02283-I
TCPIP.NLM has been unloaded.	KDDS11204-E
Temporary difficulty encountered.	gc_t_om_temporary_error
Temporary internal database became corrupt. Shutting down server to preserve permanent database. Status = %ld	cds_s_gdb_changedirstore
Termination of agent is in progress: Agent cannot take	KDDS02132-I
Text for message code not found	msg_s_not_found
The [%1\$s] attribute cannot be duplicated in the same parameter list	NIDL_DUPPRMATTR
The above gateway shares the same old password as xxx.	KDDS22209-Q
The 'acctlife' attribute requires a single value.	dcp_s_rgy_bad_acctlife_attr_val
The ACL manager set is missing.	dcp_s_rgy_missing_acl_mgr_set
The '-acl' option is required.	dcp_s_acl_no_acl_replace_op
The ACL was not found.	pks_s_no_acl
The administrative limit has been reached.	gc_t_admin_limit_exceeded
The advertiser is exiting due to an unexpected event.	cds_s_adver_eb

Message Text	Symbolic Name
The algorithm has already been registered	pkc_s_alg_already_registered
The algorithm has been deleted	pkc_s_alg_deleted
The 'alias' attribute requires a single value.	dcp_s_rgy_bad_alias_attr_val
The [align] attribute is not yet supported	NIDL_NYSALIGN
The array size attribute variable %1\$s cannot have the [ptr] or [unique] attributes	NIDL_SIZEPRMPTR
The attempt to retrieve legal version information failed.	dcp_s_rgy_no_versions_found
The attribute [%1\$s] can occur at most once per operation	NIDL_STSATTRONCE
The attribute [%1\$s] on a field is not allowed	NIDL_ILLFIELDATTR
The attribute [%1\$s] on a parameter is not allowed	NIDL_ILLPARAMATTR
The attribute [%1\$s] on a type is not allowed	NIDL_ILLTYPEATTR
The attribute [%1\$s] on a union member is not allowed	NIDL_ILLMEMATTR
The attribute [%1\$s] on an interface is not allowed	NIDL_ILLINTATTR
The attribute [%1\$s] on an operation is not allowed	NIDL_ILLOPATTR
The attribute [broadcast] is not valid on an operation with pipes	NIDL_BROADPIPE
The attribute [idempotent] is not valid on an operation with pipes	NIDL_IDEMPIPE
The attribute [ignore] is valid only for pointers	NIDL_IGNATTRPTR
The attribute [ignore] on array elements is not allowed	NIDL_IGNARRELEM

Message Text	Symbolic Name
The attribute [in(shape)] is not yet supported	NIDL_NYSINSHAPE
The attribute is no longer allowed in this context; use translator	NIDL_ATTRTRANS
The attribute list must contain pairs of entries {attribute value}.	dcp_s_dhd_bad_attribute_list
The attribute list syntax is invalid.	dcp_s_cds_bad_attribute_list
The attribute list syntax is invalid.	dcp_s_rgy_bad_attribute_list
The attribute [max_is] cannot be applied to dimension %1\$lu; upper bound is not dynamic	NIDL_MAXCFMTYPE
The attribute [max_is] or [size_is] is required	NIDL_MAXSIZEATTR
The attribute [min_is] cannot be applied to dimension %1\$lu; lower bound is not dynamic	NIDL_MINCFMTYPE
The attribute [min_is] is required	NIDL_MINATTREQ
The attribute name is not a recognized attribute.	dcp_s_cds_bad_attribute_name
The attribute name is not a recognized attribute.	dcp_s_rgy_bad_attribute_name
The '-attribute' option is required.	dcp_s_audfilter_create_need_attr
The attribute or attribute value does not conform to the imposed constraints.	DS_E_CONSTRAINT_VIOLATION
The attribute [out_of_line] is not allowed on parameters	NIDL_INVOOLPRM
The attribute [out(shape)] is not yet supported	NIDL_NYSOUTSHAPE
The attribute [ptr] is invalid on a binding handle parameter	NIDL_PTRATTRHAN

Message Text	Symbolic Name
The attribute [ptr] is not valid on pipe parameters	NIDL_PTRPIPE
The attribute [ptr] is valid only for pointer types or array parameter types	NIDL_PTRATTRPTR
The attribute [ref] is valid only for pointer types or array parameter types	NIDL_REFATTRPTR
The attribute %s is not settable when dtsd is running as a clerkn	dts_s_server_only
The attribute '%s' should be a multi-valued attribute type.	dcp_s_cds_bad_attribute_type
The attribute [size_is] cannot be applied to dimension %1\$lu; upper bound is not dynamic	NIDL_SIZECFMTYPE
The attribute [string] cannot be applied to a [v1_array]	NIDL_STRARRAYV1
The attribute [string] is valid only for one-dimensional array of valid base type	NIDL_STRCHARBYTE
The Attribute Table contains an incorrectly formatted	GDS_S_BADAT_ENTRY
The attribute type is not included in the AVA.	DS_E_MISSING_TYPE
The attribute type is undefined.	DS_E_UNDEFINED_ATTRIBUTE_TYPE
The attribute [unique] is invalid on a binding handle parameter	NIDL_UNIQATTRHAN
The attribute [unique] is valid only for pointer types or array parameter types	NIDL_UNIQATTRPTR
The attribute [uuid] is invalid when the [local] attribute is specified	NIDL_UUIDINV
The attribute [v1_array] cannot occur with the [min_is] or [first_is] attributes	NIDL_SMALLMINFIRST

Message Text	Symbolic Name
The attribute [v1_array] is invalid for an array with more than 65535 elements	NIDL_SMALLINV
The attribute [v1_array] must be in array, not pointer, syntax	NIDL_SMALLARRSYN
The attribute value does	DS_E_INVALID_ATTRIBUTE_SYNTAX
The attribute value does not conform to the syntax.	gc_t_om_wrong_value_makeup
The attribute value in the AVA does not conform to the attribute syntax.	DS_E_INVALID_ATTRIBUTE_VALUE
The attribute value is a single value not a list of values.	dcp_s_rgy_bad_attribute_value
The attribute value is too long.	gc_t_om_wrong_value_length
The attributes [%1\$s] and [%2\$s] cannot occur together	NIDL_CONFLICTATTR
The attributes [in_line] and [out_of_line] cannot occur together	NIDL_CONFLINEATTR
The attributes [last_is] and [length_is] cannot occur together	NIDL_LASTLENCONF
The attributes [max_is] and [size_is] cannot occur together	NIDL_MAXSIZECONF
The audit action '%s' is not valid.	dcp_s_audfilter_invalid_action
The audit condition '%s' is not valid.	dcp_s_audfilter_invalid_condition
The Audit daemon cannot change to working directory %s	aud_s_dmn_work_dir
The audit daemon started	aud_s_dmn_starts
The audit library could not backup a trail file due to failure of utc_gettime call for reading time from the system.	aud_s_cannot_gettime

Message Text	Symbolic Name
The audit library could not backup a trail file due to failure of utc_gmtime call for reading time from the system.	aud_s_cannot_getgmtime
The authentication service is invalid	sec_key_mgmt_e_authn_invalid
The authentication service is unavailable	sec_key_mgmt_e_auth_unavailable
The base type of a pipe cannot be a conformant type	NIDL_CFMTBASETYP
The base type of a pipe cannot be a [context_handle] type	NIDL_CTXBASETYP
The base type of a pipe cannot be a function pointer	NIDL_FPPIPEBASE
The base type of a pipe cannot be a pipe type	NIDL_PIPEBASETYP
The base type of a pipe cannot be a [transmit_as] type	NIDL_XMITPIPEBASE
The base type of a pipe cannot be handle_t	NIDL_HANPIPEBASE
The base type of a pipe cannot be or contain a [%1\$s] type	NIDL_PIPECTYPE
The base type of a pipe cannot be or contain a pointer	NIDL_PTRBASETYP
The cache dump failed in an indeterministic mode.	dcp_s_cadump_fail
The call to the setrlimit(2) routine has failed: error=%s	cds_s_server_setrlimit
The caller has no default login context.	gssdce_s_no_login_context
The caller is unauthorized to perform operation	sec_key_mgmt_e_unauthorized
The CDS name '%s' is too long.	dcp_s_cds_fname_too_long
The cell name '%s' is invalid.	dcp_s_rgy_invalid_cell

Message Text	Symbolic Name
The certificate could not be verified. Key validity mismatch	pkc_s_cert_not_verified_validity
The certificate could not be verified. The signature was wrong.	pkc_s_cert_not_verified_signature
The certificate has been revoked.	pkc_s_certificate_revoked
The certificate has not been revoked.	pkc_s_certificate_not_revoked
The certificate is invalid - signature algorithm mismatch.	pkc_s_cert_invalid_algid
The certificate was not added as it could not be verified.	pkc_s_cert_not_added
The certificate-handle was invalid	pkc_s_bad_certificate_handle
The change epoch options cannot be used when modifying directory attributes.	dcp_s_cds_wrong_options
The '-change' option can not be used with the individual attribute options.	dcp_s_dts_modify_excl_opts
The channel bindings in the token were incorrect	gssdce_s_bindings_value_error
The '-checkpoint' option is required.	dcp_s_cds_no_checkpoint
The class identifier is undefined.	gc_t_om_no_such_class
The class is abstract and not a concrete class.	gc_t_om_not_concrete
The '-clearinghouse' option is invalid without the '-replica' option.	dcp_s_cds_clh_replica_option
The close operation failed.	pkc_s_policy_close_failure
The command didn't supply a key value.	dcp_s_kt_key_value_missing
The command requires at least one argument.	dcp_s_need_arg
The command requires at least one option.	dcp_s_need_opt
The command requires one of the '-state', '-stostrategy' or '-change' options.	dcp_s_aud_modify_need_opt

Message Text	Symbolic Name
The command supplied wrong key value: '%s'.	dcp_s_kt_bad_key_value
The complete IPC-request message exceeds the upper limitn	GDS_S_CACHE_REQSZ_ERR
The context did not contain a PAC.	gssdce_s_no_pac_available
The context does not support confidentiality protection	gssdce_s_no_conf
The context is not available for the attempted operation	gssdce_s_invalid_context_state
The correct private key version not found	sec_pvtkey_version_not_exist
The count of audit record tail information items exceeds the limit	aud_s_evt_tail_info_exceeds_limit
The credential usage parameter is invalid.	gssdce_s_bad_usage
The daemon is disabled for logging	aud_s_dmn_disabled
The DCE registry could not be contacted.	gssdce_s_no_rgy_available
The dced time service failed to get current time.	dcp_s_clock_dced_server_time_fail
The '-default' option cannot be combined with other options.	dcp_s_rpc_default_with_others
The Directory cannot provide a	DS_E_OUT_OF_SCOPE
The directory '%s' was created.	dcp_s_cds_dir_created
The directory '%s' was not created.	dcp_s_cds_dir_not_created
The Directory Service has no	DS_E_NO_SUCH_OPERATION
The Directory Service is	DS_E_PROTECTION_REQUIRED
The Directory Service is temporarily too busy to perform the operation.	DS_E_BUSY
The directory to link to not specified.	dcp_s_cds_no_linkto_value
The distinguished name %s of the schema is illegal.n	GDS_S_ILL_SCHEMA_NAME

Message Text	Symbolic Name
The DSA does not haave the	DS_E_UNABLE_TO_PROCEED
The DSA is unable to perrform the request as directed.	DS_E_INVALID_REF
The DTS control program is not authenticated:	dts_s_mgt_unauthn
The effective and real user ids are not the same	dcp_s_login_euid_not_uid
The empty list is not a valid argument.	dcp_s_null_arg
The esl type %d is invalid	aud_s_invalid_esl_type
The esl type is invalid	aud_s_invalid_esl_type_rc
The event class '%s' is not valid.	dcp_s_audfilter_invalid_ec
The exclusion identifier is undefined.	gc_t_om_no_such_exclusion
The filter type '%s' is not valid.	dcp_s_audfilter_invalid_type
The [first_is] parameter must have the [in] attribute	NIDL_FIRSTINATTR
The fopen() call failed during srvrconf_start, errno = %d	dced_s_sc_open_file_failed
The '-force' option cannot be used with the '-replica' and '-clearinghouse' options.	dcp_s_cds_force_replica_option
The -force option is valid only with the -master option.	dcp_s_rgy_sa_force_set_master
The foreign users password must be supplied.	dcp_s_rgy_con_no_fmypwd
The format of esl file %s is not current version	aud_s_wrong_esl_file_version
The format of esl update file %s is not current version	aud_s_wrong_esl_updt_file_version
The 'fullname' attribute requires a single value.	dcp_s_rgy_bad_fullname_attr_val

Message Text	Symbolic Name
The function does not apply to the object to which it is addressed.	gc_t_om_function_declined
The function was aborted by an external force.	gc_t_om_function_interrupted
The gdsdaemon program for Directory ID %d has finished.n	GDS_S_EXIT_DAEMON
The gdsdaemon program for Directory ID %d has started.n	GDS_S_ENTRY_DAEMON
The gdsdaemon program was called with wrong syntax.n	GDS_S_SUP_USAGE
The gdsdaemon program was started with an illegal directory identifier %d.n	GDS_S_SUP_ILL_DIRID
The gdsdaemon program was started with an illegal operation mode %d.n	GDS_S_SUP_WRONG_OPMODE
The gdsgendb program started.n	GDS_S_ENTRY_GENDB
The gdsmkiss program exited.n	GDS_S_EXIT_MKISS
The gdsmkiss program started.n	GDS_S_ENTRY_MKISS
The gdsmkupd program exited.n	GDS_S_EXIT_MKUPD
The gdsmkupd program started.n	GDS_S_ENTRY_MKUPD
The gdstransfer exited.n	GDS_S_EXIT_TRANSFER
The gdstransfer started.n	GDS_S_ENTRY_TRANSFER
The 'gid' attribute requires a single value.	dcp_s_rgy_bad_gid_attr_val
The [handle] attribute is valid only on transmittable types	NIDL_HANATTRTRAN
The handle did not refer to a valid object.	gssdce_s_invalid_handle
The 'inprojlist' attribute requires a single value.	dcp_s_rgy_bad_inprojlist_attr_val
The interface list must contain pairs of entries	dcp_s_sr_bad_if_attr

Message Text	Symbolic Name
The interface specification does not contain a valid version identifier.	dcp_s_rpc_interface_no_version
The key data should contain principal, keytype, version number	dcp_s_dhd_bad_key_data
The key is not certified	pkc_s_key_not_certified
The key is not trusted	pkc_s_key_not_trusted
The -keytab and -password options are mutually exclusive.	dcp_s_login_no_ktb_and_pass
The [last_is] parameter must have the [in] attribute	NIDL_LASTINATTR
The [length_is] parameter must have the [in] attribute	NIDL_LENINATTR
The level of security	DS_E_INAPPROP_AUTHENTICATION
The list contains too few elements.	dcp_s_too_few_list_elements
The list contains too many elements.	dcp_s_too_many_list_elements
The list {%s} contains too few elements.	dcp_s_list_too_short
The list {%s} contains too many elements.	dcp_s_list_too_long
The '-local' option can only be used when dced and dcecp are in 'local' mode.	dcp_s_bad_use_of_local
The login command requires a username argument.	dcp_s_login_needs_user
The login context could not be validated from a keytable.	gssdce_s_couldnt_validate_context
The lower bound must not be greater than the upper bound	NIDL_LBLESSUB
The major version number is too large; the maximum is %1\$lu	NIDL_MAJORTOOLARGE
The 'maxuid' attribute must be a positive integer.	dcp_s_maxuid_is_negative

Message Text	Symbolic Name
The 'maxuid' attribute must be an integer.	dcp_s_maxuid_not_int
The 'maxuid' attribute must be less than %d.	dcp_s_maxuid_out_of_range
The '-member' can only be used with the '-interface' option.	dcp_s_rpc_member_or_annot
The 'mingid' attribute must be a positive integer.	dcp_s_mingid_is_negative
The 'mingid' attribute must be an integer.	dcp_s_mingid_not_int
The 'mingid' attribute must be less than %d.	dcp_s_mingid_out_of_range
The minor version number is too large; the maximum is %1\$u	NIDL_MINORTOOLARGE
The 'minorgid' attribute must be a positive integer.	dcp_s_minorgid_is_negative
The 'minorgid' attribute must be an integer.	dcp_s_minorgid_not_int
The 'minorgid' attribute must be less than %d.	dcp_s_minorgid_out_of_range
The 'minuid' attribute must be a positive integer.	dcp_s_minuid_is_negative
The 'minuid' attribute must be an integer.	dcp_s_minuid_not_int
The 'minuid' attribute must be less than %d.	dcp_s_minuid_out_of_range
The modification alters an entry's object class attribute.	DS_E_OBJECT_CLASS_MOD_PROHIB
The modification alters an object's RDN.	DS_E_NOT_ALLOWED_ON_RDN
The modification identifier is undefined.	gc_t_om_no_such_modification
The modification leaves a	DS_E_OBJECT_CLASS_VIOLATION

Message Text	Symbolic Name
The modification leaves the DIT structured incorrectly.	DS_E_NAMING_VIOLATION
The mutex is locked; therefore, it is not acquired.	_____
The name of the CDS client to operate on must be specified.	dcp_s_cds_no_cds_client
The name of the CDS server to operate on must be specified.	dcp_s_cds_no_cds_server
The name passed to the add entry operation already exists.	DS_E_ENTRY_EXISTS
The name provided is not a part of the current cell.	CDS_NOTINCELL
The name provided was not an alias or the current cell name.	CDS_NOT_AN_ALIAS
The number of gateway login users exceeds the limit.	KDDS22007-W
The Object Class Table contains an incorrectly formatted	GDS_S_BADOCT_ENTRY
The object is client-generated, rather than service-generated or private.	gc_t_om_not_the_services
The object is nonexistent or the handle is invalid.	gc_t_om_no_such_object
The object is not an instance of the encoding class.	gc_t_om_not_an_encoding
The object is public and not private.	gc_t_om_not_private
The object '%s' does not exist.	dcp_s_sr_obj_not_found
The OM class of an argument is not supported for this operation.	DS_E_BAD_CLASS
the only allowed rock key has been used	sec_cred_s_no_more_key
The open operation failed.	pkc_s_policy_open_failure

Message Text	Symbolic Name
The operation could not be performed within the specified time limit.	DS_E_TIME_LIMIT_EXCEEDED
The operation has already completed,	DS_E_TOO_LATE
The operation is unsupported	pkc_s_unsupported
The operation requires an acceptor context.	gssdce_s_need_acceptor_context
The 'orgid' attribute requires a single value.	dcp_s_rgy_bad_orgid_attr_val
The OS call to open the file for reading failed	dts_s_binding_file_read_error
The PKSS has already initialized.	pkc_s_already_initialized
The policy has already been registered	pkc_s_plcy_already_registered
The policy has been deleted	pkc_s_plcy_deleted
The '-priority' option cannot be combined with other options.	dcp_s_rpc_priority_with_others
The program could not attach to IPC.n	GDS_S_SUP_ATTACH_ERR
The program could not create a link to the file %s, errno = %d.	GDS_S_LINK_ERR
The program could not delete an entry from an error logfile.n	GDS_S_SUP_DELENTN_ ERRLOG_ERR
The program could not execute a command to search an entry in the file %s.n	GDS_S_SUP_SEARCH_ERR
The program could not find the DSA name %s in the database.n	GDS_S_SUP_LOCDSA_ DNLIST_ERR
The program could not find the remote DSA name %s in the	GDS_S_SUP_REMDSA_ DNLIST_ERR
The program could not get file information about %s, errno = %d.n	GDS_S_SUP_NO_FILE_INFO

Message Text	Symbolic Name
The program could not get the state of a found entry.n	GDS_S_SUP_SEARCH_STATE_ERR
The program could not get the status of the file %s, errno = %d.	GDS_S_STAT_ERR
The program could not lock the file %s, errno = %d.n	GDS_S_SUP_LOCK_ERR
The program could not open the directory %s, errno = %d.n	GDS_S_SUP_OPENDIR_ERR
The program could not perform the update operation.n	GDS_S_SUP_UPD_OP_ERR
The program could not read a logmessage, errno = %d.n	GDS_S_SUP_READ_LOG_ERR
The program could not read the complete logmessage.n	GDS_S_SUP_READ_COMPL_LOG_ERR
The program could not read the header information of the file %s.n	GDS_S_SUP_HEADER_ERR
The program could not read the name of the local DSA, errno = %d.n	GDS_S_SUP_LOCDSA_ERR
The program could not remove the unused entries from the file %s.n	GDS_S_SUP_REM_UNUSED_ERR
The program could not resynchronize DSA processes.n	GDS_S_SUP_RESYNC_DSA_ERR
The program could not retrieve the DSA name for the index %d	GDS_S_SUP_DNLIST_REMDSA_ERR
The program could not synchronize DSA processes.n	GDS_S_SUP_SYNC_DSA_ERR
The program could not unlink the file %s, errno = %d.	GDS_S_UNLINK_ERR
The program could not write the header information to file %s,	GDS_S_SUP_WR_HEADER_INFO

Message Text	Symbolic Name
The program could not write the logmessage, errno = %d.n	GDS_S_SUP_WRITE_LOG_ERR
The program has not allocated enough memory for the update information.n	GDS_S_SUP_INSUFF_MEM
The program not could change an entry in an error logfile.n	GDS_S_SUP_CHANGE_ERRLOG_ERR
The proposed parent name is not its cellname or primary alias.	CDS_NOTPREFERREDHIERARCHY
The provided public key is invalid.	pkc_s_invalid_public_key
The PSAP address of DSA %s differs from that of the local DSA.n	gsu_psap_must_same
the public key value is NULL	sec_pk_e_no_key_value
The 'pwdalpha' attribute requires a single value.	dcp_s_rgy_bad_pwdalpha_attr_val
The 'pwdexpdate' attribute requires a single value.	dcp_s_rgy_bad_pwdexpdate_attr_val
The 'pwdlife' attribute requires a single value.	dcp_s_rgy_bad_pwdlife_attr_val
The 'pwdminlen' attribute requires a single value.	dcp_s_rgy_bad_pwdminlen_attr_val
The 'pwdspaces' attribute requires a single value.	dcp_s_rgy_bad_pwdspaces_attr_val
The 'quota' attribute requires a single value.	dcp_s_rgy_bad_quota_attr_val
The record of a C-ISAM File could not be deleted,	GDS_S_ISDELETE_ERR
The registry could could not translate the specified name.	gssdce_s_couldnt_translate_name
The replica at clearinghouse '%s' was not specified.	dcp_s_dir_mod_missing_new_entry

Message Text	Symbolic Name
The '-replica' option is required to use the '-verbose' option.	dcp_s_rgy_verbose_missing_replica
The [represent_as] type %1\$s conflicts with previously defined %2\$s	NIDL_CONFREPRTYPE
The request produced a security error for	DS_E_NO_INFO
The requested critical	DS_E_UNAVAILABLE_CRIT_EXT
The requested feature is not implemented.	gssdce_s_unimplemented_feature
The requested value does not exist	pkc_s_no_value
The requester's credentials are invalid.	DS_E_INVALID_CREDENTIALS
The requestor does not have permission to perform the operation.	DS_E_INSUFFICIENT_ACCESS_RIGHTS
The required modification field is not supported	dced_s_attr_not_supported_for_update
The 'resolve' command requires a binding as an argument.	dcp_s_resolve_need_binding
The resolve command requires the '-interface' option with an interface.	dcp_s_resolve_need_if
The retrieve operation failed.	pkc_s_policy_retrieve_failure
The RPC-server could not be established because of a RPC-	GDS_S_RPC_RUNTIME_ERR
The RPC-server could not be established because of a threads	GDS_S_RPC_THREADS_ERR
The RPC-server has received an unsupported remote procedure	GDS_S_RPC_UNSUPPORTED
The rule identifier is undefined.	gc_t_om_no_such_rules
The %s call failed with the following error:n%sn	uuidgen_st_failure
The '%s' option requires a character string value.	dcp_s_opt_requires_string

Message Text	Symbolic Name
The '%s' option requires a floating point value.	dcp_s_opt_requires_float
The '%s' option requires an integer value.	dcp_s_opt_requires_int
The '%s' option requires more arguments.	dcp_s_opt_requires_more_args
The -s option used without an argument	aud_s_dmn_trail_size
The %s system call failed	dced_s_sc_setup_failed
The same clearinghouse name was found more than once.	dcp_s_dir_mod_duplicate_found
The same file cannot be used for public and private keys.	dcp_s_rgy_pk_same_filename
The same file contents cannot be used for public and private keys.	dcp_s_rgy_pk_same_pk_string
The selected name is not registered with DCE User Group.	KDDS23024-W
The selected name is not trustee.	KDDS23026-W
The server is exiting due to an unexpected event.	cds_s_server_eb
The server that greeted the master is not on the replica list	sec_rgy_rep_not_on_replist
The signal list may not be empty.	dcp_s_signal_list_not_empty
The signature affixed to the request is invalid.	DS_E_INVALID_SIGNATURE
The '-single' option must be used with the '-add' option.	dcp_s_cds_single_no_add
The '-single' option must be used with the '-attribute' option.	dcp_s_cds_single_no_attr
The size attributes do not match the array dimension	NIDL_SIZEMISMATCH
The size of a DUA-cache object entry exceeds the upper limitn	GDS_S_CACHE_INFSZ_ERR

Message Text	Symbolic Name
The source name had insufficient components to complete the operation	pkc_s_insufficient_rdns
The specified ACL type was not recognized.	pks_s_bad_acl_type
The specified attribute or value was not found in the directory entry.	DS_E_NO_SUCH_ATTRIBUTE_OR_VALUE
The specified authorization operation was unrecognized.	pks_s_invalid_op
The specified codeset is invalid.	dcp_s_rgy_era_codeset_not_valid
The specified entry exists in the database	CDS_GDB_EXISTS
The specified extended attribute does not exist.	dcp_s_rgy_era_no_attribute_exists
The specified field is not part of data set of the specified operation (Registry Edit Kernel)	ek_bad_field
The specified filter type '%s' requires a key.	dcp_s_audfilter_need_key
The specified logfile cannot be closed,	GST_LOGCLOSE_ERR
The specified logfile cannot be opened,	GST_LOGOPEN_ERR
The specified name does not match the name of any object in the directory	DS_E_NO_SUCH_OBJECT
The specified name type is not recognized.	gssdce_s_unsupported_name_type
The specified security mechanism is not supported.	gssdce_s_unsupported_mechanism
The status code is invalid.	gssdce_s_bad_status_value
The status type parameter is invalid.	gssdce_s_bad_status_type
The string '%s' is not a legal security software version.	dcp_s_rgy_illegal_version
The string '%s' is not a unique attribute name.	dcp_s_attr_not_unique

Message Text	Symbolic Name
The Structure Rule Table contains an incorrectly formatted	GDS_S_BADSRT_ENTRY
The supplied cellname is required to be < 255 bytes in length.	CDS_ALIASTOOLONG
The supplied cellname is required to have two simple names for an alias and three simple names for a child alias.	CDS_ALIASTOOSHORT
The supplied cellname would result in a hierarchical cycle.	CDS_ALIASCYCLE
The supplied filter type '%s' does not take a key.	dcp_s_audfilter_extra_key
The supplied ownership must either be APPLICATION or GSSAPI.	gssdce_s_invalid_ownership
The supplied principal name has not been registered.	gssdce_s_unknown_principal_name
The supplied principal name is invalid.	gssdce_s_bad_name
The syntax identifier is undefined.	gc_t_om_no_such_syntax
The syntax of the specified i18ndata element is invalid.	dcp_s_rgy_era_invalid_i18ndata_syntax
The system clock has gone backwards.	cds_s_server_timeback
The -t option used without an argument	aud_s_dmn_trail_name
The time service has shut down	dts_s_shut_down
The time string syntax for -at is incorrect.	sec_rgy_checkpt_bad_at_time_str
The timestamp on a new update is older than CDS_AllUpTo. Attribute =%s, CDS_AllUpTo = %s, Update Timestamp = %s.	cds_s_server_timestamp
The '-timestamps' option is required.	dcp_s_cds_no_timestamps
The token is invalid - It is too short	gssdce_s_short_token

Message Text	Symbolic Name
The token is invalid. It specifies an unsupported encryption algorithm.	gssdce_s_unsupported_encryption_algorithm
The token is invalid. It contains invalid padded plaintext.	gssdce_s_bad_plaintext_padding
The token is invalid. It is of an unrecognized type.	gssdce_s_unrecognized_token_type
The token is invalid. It specifies an encryption algorithm but claims not to provide privacy protection.	gssdce_s_seal_algorithm_not_allowed
The token is invalid. It specifies an unsupported integrity algorithm	gssdce_s_unsupported_signature_algorithm
The token is invalid. The routine failed trying to decrypt data.	gssdce_s_couldnt_decrypt_token
The token is not the right type for the attempted use.	gssdce_s_unexpected_token_type
The token sequence number field in the token was invalid.	gssdce_s_bad_sig_seq
The token server principal name does not match the credential principal name.	gssdce_s_incorrect_server_principal
The token signature was incorrect.	gssdce_s_bad_signature
The token signature was incorrect	gss_s_vfy_bad_sig
The token was not created by the remote peer.	gssdce_s_reflected_packet
The token was signed using an unsupported algorithm	gss_s_vfy_sign_unk
The token was valid, but a later token has already been received.	gssdce_s_message_late
The token was valid, but an earlier token has not yet been received	gssdce_s_message_omitted
The token was valid, but is a duplicate of one that has already been received	gssdce_s_message_already_seen

Message Text	Symbolic Name
The token was valid, but is severely out of sequence.	gssdce_s_message_out_of_order
The trail file is full	aud_s_trl_full
The '-tree' option cannot be used with the '-replica' and '-clearinghouse' options.	dcp_s_cds_tree_replica_option
The type identifier is undefined.	gc_t_om_no_such_type
The '-types' option must be used with the '-remove' option.	dcp_s_cds_types_no_remove
The 'uid' attribute requires a single value.	dcp_s_rgy_bad_uid_attr_val
The union switch variable %1\$s cannot be a [ptr] or [unique] pointer	NIDL_NEUSWPTR
The UNIX ID obtained from DCE is larger than supported by this OS.	sec_login_s_unix_id_overflow
The users password must be supplied.	dcp_s_rgy_con_no_mypwd
The 'uuid' attribute requires a single value.	dcp_s_rgy_bad_uuid_attr_val
The UUID is being used more than once.	dcp_s_sr_uuid_mul_used
The '-uuid' option cannot be combined with other options.	dcp_s_rpc_uuid_with_others
The [v1_string] attribute can only be applied to a [v1_array]	NIDL_STRV1ARRAY
The value for 'pkmechanism' must be either 'file' or 'pkss'.	dcp_s_rgy_pk_invalid_storage
The value of the 'pwd_val_type' ERA on the principal is invalid.	dcp_s_rgy_invalid_pwd_val_type
The value '%s' for the 'state' attribute is not valid.	dcp_s_aud_modify_bad_state
The value '%s' for the 'ststrategy' attribute is not valid.	dcp_s_aud_modify_bad_ststrategy

Message Text	Symbolic Name
The value '%s' is not a valid absolute or relative timestamp.	dcp_s_utc_bad_time
The value '%s' is not a valid endpoint map binding.	dcp_s_rpc_bad_endpoint_binding
The value '%s' is not a valid integer error code.	dcp_s_errtext_invalid_code
The value '%s' is not a valid integer or floating point number.	dcp_s_utc_bad_mult
The value '%s' is not a valid relative timestamp.	dcp_s_utc_bad_rel_time
The value '%s' is not a valid version identifier.	dcp_s_rpc_bad_version_opt
The value specified for the '-max' option is illegal.	dcp_s_rpc_bad_max_value
The value was invalid.	pkc_s_bad_value
The '-verbose' option may only be used with the '-replica' option.	dcp_s_rgy_bad_use_of_verbose
The version of esl update file %s is not current	aud_s_wrong_version_esl_updt_file
The '-version' option requires the '-interface' option.	dcp_s_rpc_version_no_interface
The workspace is nonexistent.	gc_t_om_no_such_workspace
The write to the trail file failed.	aud_s_trl_write_failure
There are too many options in command line.	dcp_s_dhd_too_many_opts
There are unremovable users or groups.	KDDS23018-I
There is no existing primary alias for the local cell.	CDS_NOPREFERRED_EXISTS
there is no Tcl library at this installation	tcl_s_cmdil_no_tcl_library

Message Text	Symbolic Name
this attribute type does not support multi-valued updates	sec_attr_not_multi_valued
This command can be executed as user 'root'.	dcp_s_cadump_not_root
This command is not allowed from the command line.	dcp_s_illegal_command
This object requires a verb to form a command.	dcp_s_object_needs_verb
This operation must be performed on the master copy of root directory	CDS_NOTROOT
this operation not implemented	sec_attr_not_implemented
This replica not on replica list	sec_rep_not_on_replist
Thread exiting due to an exception.	sec_thr_exit_exc
Thread is exiting with alert exception	sec_rgy_thr_exit_alert
Thread is exiting with an exception	sec_rgy_thr_exit_exc
Thread received an alert exception	sec_thr_alert
Thread routine error (at line %d) : %ld.	cds_s_library_threads
Threads package has bugchecked.nBugcheck code is ... %dnThreads bug ref# ... %dnErrno String..... %snCurrent thread 0x%xn	cds_s_library_threadsbug
Ticketed server name differs from explicit credential	gss_s_ac_names_differ
Time provider failure detected	dts_s_provider_failed
Time provider timeout detected	dts_s_provider_timeout
Time service already created	dts_s_created
Time service already running on this node	dts_s_another_time_serv
Time service has already been started	dts_s_is_started
Time service has not been created	dts_s_not_created

Message Text	Symbolic Name
Time service has not been enabled	dts_s_not_enabled
Time service in wrong state	dts_s_wrong_state
Timeout occurred in communication with agent.	KDDS11654-E
Timeout occurred; operation may have completed	CDS_TIMEOUTMAYBEDONE
Timeout occurred; operation not performed	CDS_TIMEOUTNOTDONE
Timeout occurred receiving data from gateway xxx.	KDDS02563-E
Timestamp conversion failed. Invalid timestamp.	dcp_s_utc_convert_failed
Timestamp mismatch (received: %x.%x, expected: %x.%x)	gss_s_seca_timestamp
Timestamp multiplication failed. Invalid timestamp or multiplier.	dcp_s_utc_multiply_failed
Token wrapper invalid (Encoded length > actual length)	gss_s_unwrap_inv3
Token wrapper invalid (Framing type != SEQ)	gss_s_unwrap_inv1
Token wrapper invalid (Invalid mech-type length)	gss_s_unwrap_inv5
Token wrapper invalid (Length not 1,2 or 3 bytes)	gss_s_unwrap_inv2
Token wrapper invalid (Mech-type type not OID)	gss_s_unwrap_inv4
Token wrapper was invalid	gss_s_ic_inv_wrapper
Token wrapper was invalid in gss_accept_sec_ctx	gss_s_ac_bad_token_wrapper
too few arguments for math function	tcl_s_expr_few_args_for_math_func

Message Text	Symbolic Name
Too few servers (%ld), need %ld servers	dts_s_too_few_servers
too many ()	tcl_s_tclregexp_too_many_bra
Too many ACL types.	dcp_s_too_many_types
Too many arguments.	gc_t_too_many_arguments
too many arguments for math function	tcl_s_expr_many_args_for_math_func
Too many arguments specified in command.	dcp_s_too_many_args
Too many attribute values.	gc_t_om_too_many_values
Too many attribute values.	gc_t_om_wrong_value_number
Too many cell attributes.	dcp_s_acl_one_cell_attr
Too many connections at remote host	rpc_s_too_many_rem_connects
Too many digits in numeric data (Registry Edit Kernel)	ek_err_int_out_of_range
Too many elements in %1\$s	NIDL_TOOMANYELEM
Too many endpoint specifications; Maximum is %1\$u	NIDL_TOOMANYPORT
too many fields in argument specifier "%s"	tcl_s_proc_too_many_fds_in_arg
too many fields to scan	tcl_s_cmdmz_too_many_fds_to_scan
Too many files specified.n	gsu_input_file_poss
too many key usages supplied	sec_pvtkey_multiple_key_usages
too many nested calls to Tcl_Eval (infinite loop?)	tcl_s_basic_too_many_nested_calls
Too many scoping levels	NIDL_SCOPELVLS
Too many servers (%d), only %d supported	dts_s_toomany_servers
Too many signals supplied in list.	dcp_s_too_many_signals
too many substring variables	tcl_s_cmdmz_too_many_substr_var
Too many values.	gc_t_too_many_values

Message Text	Symbolic Name
Too much cache update requests in the queue.	GDS_S_CUPJOB_QUEUE_FULL
Trace file taken.	KDDS12404-I
Trace process terminated due to an unexpected error. (xxx)	KDDS02030-E
Trace process terminated: xxx	KDDS02300-E
Traced delegation requires explicit acceptor credential	gss_s_ac_trace_no_lc
Trail file %s is corrupted.	aud_s_trail_file_corrupted
trailing backslash	tcl_s_tclregexp_trailing_backslash
Transaction log replay detected an unrecognized buffer state: %d	cds_s_replay_badlog
Transaction log statistics for clearinghouse %s. Creates: %d Directories, %d Objects, %d Do_Updates. Updates: %d Directories, %d Objects %d Clearinghouse.	cds_s_replay_stats
Transaction not started before operation	rpc_s_tx_not_in_transaction
Transaction open failed at server	rpc_s_tx_open_failed
TRANSDATA processor number missing	GDS_S_NDS_PROC_ERR
TRANSDATA region number missing	GDS_S_NDS_REGION_ERR
Transfer syntaxes unsupported	rpc_s_tsyntaxes_unsupported
Transport protocol-ID missing	GDS_S_NDS_TPID_ERR
tReplay: Module=[%s] Op=[%s] Seqno=[%s]	sec_rs_log_replay_entry
tried to decrement num_attrs below zero	sec_attr_num_attr_ltzero
trigger binding info must be specified	sec_attr_trig_bind_info_missing
trigger server is unavailable	sec_attr_trig_svr_unavailable
trust path invalid	sec_priv_s_invalid_trust_path

Message Text	Symbolic Name
Trustee for %ld directories has been changed for %s.	KDDS23304-I
Trustee for %ld files has been changed for %s.	KDDS23302-I
Trustee of the access right is [%s].	KDDS23300-I
Trustee rights cannot be assigned to gateway volume xxx.	KDDS11218-E
Trustee rights cannot be removed from gateway	KDDS11220-I
Trustee rights cannot be removed from gateway volume xxx.	KDDS11219-E
Trustee %s has been deleted from %ld directories.	KDDS23404-I
Trustee %s has been deleted from %ld files.	KDDS23402-I
tty_PAD1	tty_PAD1
tty_PAD2	tty_PAD2
tty_PAD3	tty_PAD3
tty_PAD4	tty_PAD4
tty_PAD5	tty_PAD5
tty_PAD6	tty_PAD6
tty_PAD7	tty_PAD7
tty_PAD8	tty_PAD8
tty_PAD9	tty_PAD9
tty_PADa	tty_PADa
tty_PADb	tty_PADb
tty_PADc	tty_PADc
tty_PADd	tty_PADd

Message Text	Symbolic Name
tty_PADe	tty_PADe
tty_PADf	tty_PADf
Type %1\$s has a represent_as data type %2\$s	NIDL_TYPEREPAS
Type already registered	rpc_s_type_already_registered
Type attributes [in_line] and [out_of_line] cannot occur together	NIDL_TYPLINEATTR
Type name: %1\$s not found	NIDL_TYPENOTFND
Type name %1\$s referenced in ACF is not defined	NIDL_TYPNOTDEF
Type with [%1\$s] cannot be or contain type with [%2\$s]	NIDL_TYPECTYPE
Type with [%1\$s] cannot be used in definition of type with [%2\$s]	NIDL_TYPEATTRUSE
Type with [%1\$s] must resolve to byte or structure containing only byte fields	NIDL_TYPEOFBYTES
Types with [represent_as] cannot be nested	NIDL_REPASNEST
Types with the [%1\$s] attribute cannot be nested	NIDL_TYPENEST
Unable to access file %s: status = %ld.	cds_s_server_lseek
Unable to access group file %s (%s).	pwd_imp_err_no_grp_access
Unable to access passwd file %s (%s).	pwd_imp_err_no_pwd_access
Unable to access private key storage mechanism	sec_psm_unable_to_open_pvtkey
Unable to add principal to group membership	ek_misc_chg_gmem_fail
Unable to add principal to org membership	ek_misc_chg_omem_fail
unable to alloc %d bytes	tcl_s_ckalloc_unable_to_alloc

Message Text	Symbolic Name
unable to alloc %d bytes, %s line %d	tcl_s_ckalloc_unable_to_alloc_bytes_line
Unable to allocate handle (Registry Edit Kernel)	ek_null_handle
unable to allocate memory.	sec_s_no_memory
Unable to allocate memory	sec_rgy_cant_allocate_memory
unable to allocate memory	sec_attr_no_memory
Unable to allocate more memory.	cds_s_alloc
Unable to allocate more memory.	cds_s_alloc_a
unable to authenticate on acl operation	sec_acl_unable_to_authenticate
Unable to begin transaction on server database. Status = %ld.	cds_s_gdb_begin_xtn
Unable to change account admin information	ek_misc_chg_admin_fail
Unable to change account auth-policy	ek_misc_chg_auth_plcy
Unable to change account name	ek_misc_chg_name_fail
Unable to change account user information	ek_misc_chg_uinfo_fail
Unable to change password	ek_misc_chg_passwd_fail
Unable to check local cell name	rsdb_check_cell_failure
Unable to close file %s: status = %ld.	cds_s_server_close
Unable to commit transaction on server database. Status = %ld.	cds_s_gdb_commit_xtn
Unable to communicate with any CDS server	CDS_NOCOMMUNICATION
Unable to construct item name	sec_rsdb_cant_cntr_item_name
Unable to contact the specified dts server.	dcp_s_dts_comm_failure
Unable to convert the clearinghouse name to internal format: status = %ld.	cds_s_server_cvtsimple

Message Text	Symbolic Name
Unable to create default acl. Can't get group uuid. status = %ld.	cds_s_adver_groupfail
Unable to create default acl. Can't get group uuid. status = %ld.	cds_s_groupfail
Unable to create default acl: Can't get host uuid. status = %ld.	cds_s_adver_hostfail
Unable to create default acl: Can't get host uuid. status = %ld.	cds_s_hostfail
Unable to create default acl: status = %ld.	cds_s_adver_aclfail
Unable to create default acl: status = %ld.	cds_s_aclfail
Unable to create directory	sec_rgy_dir_could_not_create
Unable to create file %s: status = %ld.	cds_s_server_create
Unable to delete file %s: status = %ld.	cds_s_server_unlink
Unable to determine if override exists	sec_login_s_override_failure
Unable to establish parent child pipe	sec_rs_pipe_not_created
Unable to establish parent/child pipe: pipe(2) failed: errno = %ld.	cds_s_library_pipe
Unable to establish server bindings	sec_rs_rpc_inq_bind_err
Unable to find appropriate DTS interface at '%s'.	dcp_s_dts_no_more_bindings
Unable to fork child process to execute server: fork(2) failed: errno = %ld.	cds_s_library_fork
Unable to fork clerk process: errno = %ld.	cds_s_adver_fork
Unable to get account by id	sec_rsd_b_acct_cant_getid
Unable to get daemon bindings	aud_s_dmn_bindings
Unable to get information about master	sec_prop_no_master_info
Unable to get item record for sequential id	sec_rsd_b_cant_get_item_seqid
Unable to get key for sequential id	sec_rsd_b_cant_get_key

Message Text	Symbolic Name
Unable to get membership data	sec_rldb_cant_get_member_data
Unable to get message	sec_svc_cant_get_msg
Unable to get server's protocol towers	sec_rs_rpc_prot_twr_err
Unable to get the current context for refresh.	dcp_s_login_get_context_fail
Unable to inform process %s about esl update	aud_s_unable_to_sync_client
Unable to initialize the RPC interface.	cds_s_gda_initrpc_eb
Unable to initialize workspace.	gc_t_cannot_initialize_workspace
Unable to listen on any protocol sequence	sec_rs_rpc_use_protseq_err
Unable to lookup item	sec_rldb_cant_get_item
Unable to lookup schema entry	sec_attr_schema_cant_lookup
Unable to modify the cell aliases because the root directory is missing the AllUpTo attribute.	CDS_MISSING_ALLUPTO
Unable to modify the cell aliases because the root directory is missing the DirectoryVersion attribute.	CDS_MISSING_DIRECTORYVERSION
Unable to obtain credentials for group	sec_rldb_cant_get_group_creds
Unable to obtain credentials for org	sec_rldb_cant_get_org_creds
Unable to obtain credentials for person	sec_rldb_cant_get_person_creds
Unable to obtain credentials for pgo	sec_rldb_cant_get_pgo_creds
Unable to obtain network credentials.	dcp_s_rgy_con_no_cred
Unable to open %1\$s for read access	NIDL_OPENREAD
Unable to open %1\$s for write access	NIDL_OPENWRITE
Unable to open file %s: status = %ld.	cds_s_server_open
Unable to open in-memory database. Status = %ld.	cds_s_gdb_open_dirstore

Message Text	Symbolic Name
Unable to open in-memory database. Status = %ld.	cds_s_server_delete_entries
Unable to open namespace database. Status = %ld.	cds_s_gdb_open_namespace
Unable to open registry journal file	rsdb_journal_cant_open
Unable to parse cell name '%s'.	dcp_s_rgy_con_bad_cell
Unable to parse input (Registry Editor/ TTY Interface)	tty_cant_parse
Unable to properly initialize the diagnostic interface	cds_s_server_diag
Unable to read file %s: status = %ld.	cds_s_server_read
Unable to read the XOM object information schema file "%s".	gc_t_omx_cannot_read_schema
Unable to read version (%d) file	sec_rsdb_readver_fail
Unable to refresh %s identity . Will idle and retry	sec_rs_login_cant_refresh
Unable to refresh the current context.	dcp_s_login_refresh_fail
Unable to register virtual memory kerberos credential cache type	sec_rs_vmcc_cant_register
Unable to remove client update binding directory %s, rc= %d, errno= %d	aud_s_remove_dir_client_update_ binding_failed
Unable to remove client update binding file %s, rc= %d, errno= %d	aud_s_remove_file_client_update_ binding_failed
Unable to remove old name (%s)from group (%s)	sec_rs_ns_cant_rm_member
Unable to remove server's name (%s)from namespace	sec_rep_nm_not_deleted
Unable to repair CHDirectory entry for directory uid %s: error=%s	cds_s_server_fixchdir
Unable to reset previous acct info	sec_rsdb_acct_reset

Message Text	Symbolic Name
Unable to reset schema entry info	sec_attr_schema_cant_reset
unable to retrieve attr_list	sec_attr_cant_get_attrlist
Unable to retrieve cds handle.	dcp_s_cds_no_handle
Unable to retrieve host namen%s	sec_crdb_cant_get_hostname
Unable to retrieve host principal namen%s	sec_crdb_cant_get_host_prname
Unable to rollback transaction on server database. Status = %ld.	cds_s_gdb_rollback_xtn
Unable to save acl.	cds_s_aclwrite
Unable to save acl: status = %ld.	cds_s_adver_aclwrite
Unable to save passwd database to disk, not enough space.n	pwd_exp_no_space
Unable to save server's bindings	sec_rs_rpc_save_bind_err
Unable to select protocol sequence	aud_s_dmn_protseq
Unable to set auth policy	sec_rsdb_cant_set_auth_policy
Unable to set debug routing levels from command line argument : status = %ld.	cds_s_debug_routing_eb
Unable to set message routing for clerk command line argument : status = %ld.	cds_s_adver_routing
Unable to set message routing from command line argument : status = %ld.	cds_s_svc_routing_eb
Unable to set policy	sec_rsdb_cant_set_policy
Unable to set properties	sec_rsdb_cant_set_properties
Unable to set realm	sec_rsdb_cant_set_realm
Unable to set the local account valid on the foreign cell.	dcp_s_rgy_con_no_set_fvalid
Unable to set/unset the foreign account validity on the local cell.	dcp_s_rgy_con_no_set_valid
Unable to setup the in-core message table : status = %ld.	cds_s_define_table

Message Text	Symbolic Name
Unable to start execution of the child: errno = %ld.	cds_s_adver_execve
Unable to start export thread. dthread_create returns : %s	cds_s_export_thread
Unable to stat file (file descriptor = %d)	sec_rsdb_file_stat_fail
Unable to update local address set.	cds_s_server_towerfail_eb
Unable to update same_domain_and_usage_key_already_ exist key because of different pwd	sec_pvtkey_same_domain_and_ usage_key_exist_with_diff_pwd
Unable to upgrade directory %s: status = %ld.	cds_s_server_noupgradeevent
Unable to walk alias chain	sec_rsdb_cant_walk_alias_chain
Unable to write to file %s: status = %ld.	cds_s_server_write
Unauthorized add or modify attempt on user '%s'.	pks_s_acl_not_authorized
unauthorized to call password management server	sec_pwd_mgmt_not_authorized
unauthorized to perform this operation	sec_attr_unauthorized
Unbalanced braces	NIDL_UNBALBRACES
Unbalanced brackets	NIDL_UNBALBRACKETS
Unbalanced parentheses	NIDL_UNBALPARENS
Unchangeable attributes entered.	dcp_s_dhd_mod_invalid_attr
Undefined attribute type for the object.	gc_t_om_wrong_value_type
Undefined service flag has been encountered.	dcp_s_sr_unknown_serv_flag
Undefined stop method flag has been encountered.	dcp_s_sr_wrong_stop_mthd
Undefined timeout code flag has been encountered.	dcp_s_sr_wrong_timeout_code

Message Text	Symbolic Name
Unexpected child termination, status=0x%8.8lx.	pks_s_unexpected_termination
Unexpected command error (xxx).	KDDS01106-E
Unexpected data type value returned for dts attributes: %s	dts_s_attr_encoding
unexpected end of member list	sec_rsdb_acct_end_list
Unexpected end-of-file	NIDL_EOF
Unexpected end-of-file near '%2\$.*1\$s'	NIDL_EOFNEAR
Unexpected error (xxx) occurred to setdfakey command.	KDDS01308-E
Unexpected invocation.	pkc_s_asn_unexpected_call
Unexpected message type returned from pipe helper.	pks_s_bad_msg_type
Unexpected message type returned from pipe helper (%d).	pks_s_pipclt_bad_msg
Unexpected operator - %s.	gc_t_omx_unexpected_operator
Unexpected token type (%2.2x 2.2x)	gss_s_ic_bad_mutual_type
Unidentified communications error in client stub	rpc_s_unknown_error
Unimplemented feature.	pkc_s_unimplemented
Unimplemented output function for attribute id (%d), continuing display.n	CDSCP_UNIMPL_OUT_FNC
Unimplemented syntax.	pkc_s_unimplemented_syntax
Unintended permissions not granted.	dcp_s_acl_would_grant_perms
[unique] pointers to context handles are not allowed	NIDL_UNIQCTXHAN
Unique/group-ID for NETBIOS-address missing	GDS_S_NDS_NBGUID_ERR

Message Text	Symbolic Name
UNIX id already present in cache and entry is not an alias.n	pwd_imp_err_dup_num
Unix id changed on an alias add	sec_rgy_unix_id_changed
Unix id changed or incorrect (Registry Edit Kernel)	ek_err_unix_num_change
Unix id out of range (Registry Edit Kernel)	ek_err_bad_unix_num
Unix id space for domain has been exhausted	sec_rgy_no_more_unix_ids
Unknown ACL manager type	sec_rsd_b_unknown_aclmgr_type
Unknown acronym %s for object class.n	GDS_S_SRT_OC_INVALID
Unknown argument "%s".	gc_t_unknown_argument
Unknown attribute [%1\$s]	NIDL_UNKNOWNATTR
Unknown attribute '%s'.	dcp_s_bad_attribute
Unknown attribute syntax %d detected.	GDS_S_ILL_AT_SYNTAX
Unknown attribute syntax %d.n	GDS_S_ATSYNTAX_UNKNOWN
Unknown attribute type, associated config attribute not set	dts_s_bad_attr_type
Unknown attribute type found in internal table.n	dts_s_invalid_type
Unknown authentication service	rpc_s_unknown_authn_service
Unknown auth_info type.	dce_attr_s_unknown_auth_info_type
Unknown cached clearinghouse attribute id (%d) encountered.n	CDSCP_UNK_CA_CLE_ATT
unknown CDS data type	dcp_s_cds_unknown_data_type
Unknown clearinghouse counter id (%d) encountered.n	CDSCP_UNK_CLE_CTR
Unknown clerk attribute id (%d), continuing display.n	CDSCP_UNK_CLRK_ATT

Message Text	Symbolic Name
Unknown command line option : %s	sec_secd_cl_unknown_opt
Unknown command line option: %1\$s	NIDL_UNKFLAG
Unknown command line option %s	sec_crdb_cl_unknown_option
Unknown component	svc_s_unknown_component
Unknown DCE error.	KDDS11818-I
Unknown dced attribute type	dced_s_unknown_attr_type
Unknown dced list type	dced_s_unknown_list_type
Unknown dced object type	dced_s_unknown_object_type
Unknown dced service	dced_s_unknown_service
Unknown delegation type in context: %d	gss_s_ac_unk_deleg_type1
Unknown encryption algorithm in gss_build_prot_message	gss_s_bp_unk_enc_alg
unknown error	tcl_s_unixstr_unknown_err
Unknown error returned by the XOM convenience library.	gc_t_unknown_conv_lib_error
Unknown error returned by the XOM convenience library.	gc_t_omx_unknown_error
Unknown error returned by XOM.	gc_t_unknown_xom_error
Unknown fatal command parser error	dts_s_prs_unknown
unknown floating-point error, errno = %s	tcl_s_expr_unknown_float_point_err
Unknown gdscp error.	gc_t_unknown_gcp_error
Unknown interface	rpc_s_unknown_if
Unknown keyword encountered - %s.	gc_t_omx_unknown_keyword
Unknown mandatory or optional acronym %s.n	GDS_S_OCT_AT_INVALID
unknown math function "%s"	tcl_s_expr_unknown_math_func
Unknown message received.	KDDS11828-I
Unknown object identifier.	gc_t_omx_unknown_obj_id

Message Text	Symbolic Name
Unknown OM type.	gc_t_omx_unknown_omtype
Unknown operation identifier (Registry Edit Kernel)	ek_bad_op_id
Unknown operation "%s".	gc_i_unknown_operation
unknown operator in expression	tcl_s_expr_unknown_oper_in_expr
Unknown option "%s".	gc_t_unknown_option
Unknown option %s used. Usage: %s [-i identity] [-a] [-t trail_name] [-s size] [-wrap] [-d where] [-w where] [-D]	aud_s_dmn_usage
Unknown option %sn	gsu_unknown_switch
Unknown or invalid auxiliary acronym %s.n	GDS_S_OCT_NAUX_OC_ERR
Unknown or redundant keyword (Registry Editor/TTY Interface)	tty_invalid_option
Unknown or redundant keyword (Registry Editor/TTY Interface)	tty_invalid_argument
Unknown or unsupported manager type	rpc_s_unknown_mgr_type
Unknown reject	rpc_s_unknown_reject
Unknown server attribute id (%d), continuing.n	CDSKP_UNK_SVR_ATT
unknown signal	tcl_s_unixstr_unknown_signal
Unknown signature algorithm in gss_build_prot_message	gss_s_bp_unk_sig_alg
Unknown sockaddr	twr_s_unknown_sa
Unknown superclass acronym %s.n	GDS_S_OCT_SUP_MISSING
Unknown tower	twr_s_unknown_tower
unmatched ()	tcl_s_tclregexp_unmatch_br
unmatched []	tcl_s_tclregexp_unmatch_squ_bra
unmatched open brace in list	tcl_s_tclutil_unmatch_open_brace

Message Text	Symbolic Name
unmatched open quote in list	tcl_s_tclutil_unmatch_open_quote
unmatched open-brace in file name	tcl_s_glob_unmatched_open_brace
unmatched parentheses in expression "%s"	tcl_s_expr_unmatch_parens_in_expr
Unrecognized argument '%s'.	dcp_s_bad_arg
Unrecognized attribute 'gid'.	dcp_s_gid_not_allowed
Unrecognized attribute 'orgid'.	dcp_s_orgid_not_allowed
Unrecognized attribute 'uid'.	dcp_s_uid_not_allowed
Unrecognized authz_proto value	gss_s_ac_unk_authz
Unrecognized encryption algorithm in decode_message_header	gss_s_dmh_unk_enc_alg
Unrecognized master key version decrypting account key	sec_rs_mkey_unknown
Unrecognized option '%s'.	dcp_s_bad_opt
Unrecognized signature algorithm in decode_message_header	gss_s_dmh_unk_sign_alg
Unrecognized token-type in decode_message_header	gss_s_dmh_unk_tok_type
Unsupported algorithm.	pkc_s_unsupported_algorithm
Unsupported attribute.	pkc_s_x500_unsupported_attribute
Unsupported attribute type was given to NSI	rpc_s_mgmt_bad_type
Unsupported authenticator format	gss_s_seca_bad_cksum_type
unsupported crypto algorithm	sec_psm_unsupported_algorithm_id
Unsupported name syntax	rpc_s_unsupported_name_syntax
unsupported password type.	sec_login_s_unsup_passwd_type
Unsupported policy.	pkc_s_unsupported_policy
unsupported session key type	sec_s_keytype_unsupp
Unsupported syntax.	pkc_s_x500_unsupported_syntax

Message Text	Symbolic Name
Unsupported type	rpc_s_unsupported_type
Unsupported version number specified on command line: %s.	cds_s_server_version_eb
Unterminated comment, end-of-file encountered	NIDL_COMMENTEOF
Unterminated string literal	NIDL_STRUNTERM
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_err_PAD0
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_err_PAD1
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_err_PAD2
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_err_PAD3
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_inf_PAD0
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_inf_PAD1
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_inf_PAD2
UNUSED MESSAGE, RESERVED FOR FUTURE IMPLEMENTATIONS _n	pwd_imp_inf_PAD3
update acl operation not valid on a read only site	sec_acl_site_read_only
Update command executed, old time = %s, new time = %s	dts_s_update_complete
updates of query trigger attributes must have encoding type void	sec_attr_qry_trig_bad_enc_type
upvar refers to element in deleted array	tcl_s_tclvar_dangling_upvar
Usage: dtsd -d -c -s -g -k courier noncourier -o -w service	dts_s_usage_error

Message Text	Symbolic Name
Usage: dtsdate [-s] [-q] [-u] hostname [skew-seconds]	dts_s_dtsdate_usage
Usage: idl filename [options]	NIDL_USAGE
Usage: %s [-d dirname][-m maxentries][-s][-n][-x][-v] [-h]nn	pwd_exp_cl_usage
Usage: %s [-h] [-i][-c][-v][-o org][-d dir][-u username] [-p password]nn	pwd_imp_cl_usage
Usage: sec_create_db -master -slave -my[name] my_server_namen	sec_crdb_cl_usage
Usage: secd [-bootstrap] [-restore_master] [-verbose] [-w serviceability]ntt	sec_seccl_usage
Use %1\$s for list of command options	NIDL_CMDERR
Use array syntax to declare multidimensional arrays	NIDL_ARRSYNTAX
User communication process terminated due to an unexpected error.	KDDS02034-E
User defined exception received	rpc_s_fault_user_defined
User identification failure.	dcp_s_login_invalid_user
User is not authorized to update record	sec_rgy_not_authorized
User is not member of specified group	sec_rgy_not_member_group
User is not member of specified group and org	sec_rgy_not_member_group_org
User is not member of specified org	sec_rgy_not_member_org
User not authorized to perform operation (Registry Edit Kernel)	ek_misc_not_authorized
User reset clock using 'clock set'	dts_s_user_reset
user "%s" doesn't exist	tcl_s_glob_no_user
User xxx is not a legitimate File-Access user.	KDDS22003-W

Message Text	Symbolic Name
user_obj ACL entries not allowed in this ACL	acl_s_owner_not_allowed
UUID coding error	uuid_s_coding_error
UUID is badly formatted or out of range (Registry Edit Kernel)	ek_err_bad_id
Uuid version invalid	sec_rgy_uuid_bad_version
V1 attributes are incompatible with this type	NIDL_INCOMPATV1
Validated from local override entry, no network credentials obtained.	dcp_s_login_from_local_override
Value already set.	pkc_s_asn_value_already_set
Value descriptors not adjacent.	gc_t_om_values_not_adjacent
Value not found in the code set registry	dce_cs_c_unknown
Value overflow.	pkc_s_asn_value_overflow
Value unset.	pkc_s_asn_unset
Values of thread1 and thread2 designate the same object.	_____
Values of thread1 and thread2 do not designate the same object.	_____
Variable declarations are not supported; declaration of %1\$s ignored	NIDL_VARDECLNOSUP
variable is array	tcl_s_tclvar_is_array
variable isn't array	tcl_s_tclvar_need_array
variable must have boolean value	tcl_s_link_var_must_be_bool
variable must have integer value	tcl_s_link_var_must_be_integer
variable must have real value	tcl_s_link_var_must_be_real
variable "%s" already exists	tcl_s_tclvar_var_already_exists
Verbose help is only available for objects, not verbs.	dcp_s_help_no_verbose

Message Text	Symbolic Name
Verifying that the necessary Organization exists.n	pwd_imp_inf_check_org
Version mismatch between dced key and password record structures	dced_s_key_version_mismatch
Version mismatch between parse table file %s and parsern	CDSCP_PARSE_VERSION
void * must be used in conjunction with the [context_handle] attribute	NIDL_PTRVOIDCTX
void is valid only in an operation or a context handle pointer declaration	NIDL_VOIDOPPTR
Volume %s initialization started.	KDDS11644-I
Volume %s initialization terminated: return code %d.	KDDS11645-I
Volume %s successfully cleaned up.	KDDS11635-I
Volume %s successfully initialized.	KDDS11632-I
Volume xxx is invalid or not mounted.	KDDS11015-E
Volume xxx is invalid or not mounted.	KDDS11601-E
Warning: A [fault_status] parameter has no utility in this operation	NIDL_NOFLTPARAM
Warning: A size specifier is required; long assumed	NIDL_INTSIZEREQ
Warning: ACF include statement advised for definition of type %1\$s	NIDL_INCLTYPE
Warning: An attribute is defined multiple times	NIDL_MULATTRDEF
Warning: At least one operation must have the [code] attribute	NIDL_NOCODEOPS
Warning: Attribute [%1\$s] not supported for target language	NIDL_LANGATTRNS

Message Text	Symbolic Name
Warning: Character constant cannot be portable across character sets	NIDL_NONPORTCHAR
Warning: Character doesn't map to target language	NIDL_LANGMAPCHAR
Warning: Conformant strings not supported in target language	NIDL_LANGCFMTSTRNG
Warning: Conformant structures not supported in target language	NIDL_LANGCFMTSTRCT
Warning: Duplicate Protocol specification in endpoint list; "%1\$s" ignored	NIDL_DUPPROTOCOL
Warning: error opening %s for priming group file (%s).	pwd_exp_f_cannot_open_prime_group
Warning: Extraneous punctuation character "%1\$s" ignored	NIDL_EXTRAPUNCT
Warning: File %1\$s is a system-defined IDL filename	NIDL_SYSIDLNAME
Warning: Forward tag reference %1\$s in this declaration is not ANSI C compliant	NIDL_FWDTAGREF
Warning: Generated name too long at line %1\$lu.	NIDL_NAMETOOLONG
Warning: Identifier: %1\$s too long; maximum is %2\$lu chars	NIDL_IDTOOLONG
Warning: include filename must not contain a file extension	NIDL_INCLUDEEXT
Warning: Missing pointer class for %1\$s; [ptr], [ref], or [unique] required	NIDL_MISSPTRCLASS
Warning: Name %1\$s differs from a previous name only in case	NIDL_LANGMIXCASE
Warning: No endpoint can be found in the endpoint specification "%1\$s"	NIDL_NOENDPOINT

Message Text	Symbolic Name
Warning: Non-scalar function result converted to trailing [out] parameter	NIDL_LANGUNSFNRS
Warning: Object file for %1\$s placed in current working directory	NIDL_OUTDIRIGN
Warning: Old UUID format must be replaced with new format:	NIDL_OLDUUID
warning: one or more members of the attribute set do not exist on the object	sec_attr_set_member_missing
Warning: Operation with [cs_tag_rtn] contains no codeset tag parameters	NIDL_OPNOTAGS
Warning: Operation with [decode] has [in]-only parameter %1\$s	NIDL_DECINONLY
Warning: Operation with [encode] has [out]-only parameter %1\$s	NIDL_ENCOUTONLY
Warning: Operation with [reflect_deletions] has no [in] or [in,out] full pointers	NIDL_OPREFDELIN
Warning: Pipes not supported for target language	NIDL_LANGPIPESNS
Warning: Pointer attributes are ignored on an interface reference	NIDL_PTRATTBIGN
Warning: Semantic checking prevented by other reported errors	NIDL_NOSEMCHK
warning: some of the requested attributes do not exist on the object	sec_attr_not_all_avail
Warning: Static property or ACF attribute [cxx_static] is ignored except for -lang cxx	NIDL_STATICIGN
Warning: Syntax error in endpoint specification "%1\$s"	NIDL_ENDPOINTSYNTAX
Warning: The attribute [%1\$s] applied on type with [%2\$s] set, [%3\$s] assumed	NIDL_REFUNIQUE

Message Text	Symbolic Name
Warning: The attribute [nocode] does not apply to server stub	NIDL_SRVNOCODE
Warning: The attributes [in_line] and [out_of_line] apply only to non-scalar types	NIDL_LINENONSCAL
Warning: The attributes [max_is,length_is] or [size_is,last_is] used together	NIDL_MIXEDARRATTR
Warning: The [handle] attribute of a parameter in a function pointer declaration is ignored	NIDL_FPHANATTR
Warning: Use of [%1\$s] attribute requires %2\$s	NIDL_NOPORTATTR
Warning: Use of a nonencapsulated union requires %1\$s	NIDL_NOPORTNEU
Warning: Use of anonymous %1\$s may not be portable across C compilers	NIDL_NOPORTANON
Warning: Use of C preprocessor directive requires %1\$s	NIDL_CPPCMDOPT
Warning: Use of conformant minor array dimension requires %1\$s	NIDL_NOPORTCFMT
Warning: Use of nonzero array lower bound requires %1\$s	NIDL_NOPORTNZLB
Warning: Use of [unique] pointers requires %1\$s	NIDL_NOPORTUNIQUE
Warning: Use of user-defined exceptions requires %1\$s	NIDL_NOPORTEXCEP
Warning: Use of varying minor array dimension requires %1\$s	NIDL_NOPORTVARY
Watchdog process terminated due to an unexpected error.	KDDS02033-E
When just setting the epoch, the '-abruptly' option is not allowed.	dcp_s_clock_set_epoch_no_abrupt

Message Text	Symbolic Name
When using '-bypass', other options are not allowed.	dcp_s_clock_set_bypass_and_others
When using '-bypass', specifying a hostname is not allowed.	dcp_s_clock_set_bypass_and_hostname
When using '-dced' or '-inetd', the '-abruptly' option is not allowed.	dcp_s_clock_abrupt_present
Who are you failed	rpc_s_who_are_you_failed
wide character to multi-byte conversion failed	tcl_s_wchar_conv_failed
Wildcards are not allowed in this context (Registry Edit Kernel)	ek_err_no_wildcard
word selector "%s" specified non-existent words	tcl_s_hist_evt_word_sele_non_existent
working directory name is too long	tcl_s_unixaz_cwd_name_too_long
Workspace initialization failed.	cds_s_addcell_workspace
Would need a new name to resolve conflict.n	pwd_imp_inf_need_new_name
Would need new UNIX id to resolve conflict.n	pwd_imp_inf_need_new_uid
Write to database failed	sec_rsdb_db_write_fail
Wrong boot time	rpc_s_wrong_boot_time
Wrong data version number for directory ID %d.	GDS_S_DATAVERSION_ERR
Wrong kind of binding	rpc_s_wrong_kind_of_binding
Wrong number of arguments, exactly %d arguments are required.	dcp_s_wrong_num_args
Wrong priv server name	sec_priv_s_invalid_server_name
wrong public key type. The only supported public key type is RSA_PKCS	sec_psm_wrong_pub_key_type

Message Text	Symbolic Name
Wrong size of description file (size = %d, should be %d)	GDS_S_CACHE_DESCR_SZ_ERR
Wrong size of hash table file (size = %d, should be %d)	GDS_S_CACHE_HASH_SZ_ERR
Wrong size of object data (size = %d, should be %d)	GDS_S_CACHE_INFO_SZ_ERR
Wrong size of reorganization file (size = %d, should be %d)	GDS_S_CACHE_REORG_SZ_ERR
Wrong type of pickle passed to unpickling routine	rpc_s_wrong_pickle_type
Wrong version no. of cache data base (version = %s,	GDS_S_CACHE_VERSION_ERR
Wrong version of IDL Encoding Services	rpc_s_ss_wrong_es_version
X.121-address missing	GDS_S_NDS_X121_ERR
X.21-address missing	GDS_S_NDS_X21_ERR
X.500 lookups disabled.	cds_s_gda_nox500
XOM object information schema file not read.	gc_t_omx_schema_not_read
[y/n]? (n)	sec_lksm_def_no_prompt
[y/n]? (y)	sec_lksm_def_yes_prompt
You are not allowed to logout of an inherited context.	dcp_s_purge_initial_context
You are not logged in to the security service.	dcp_s_not_logged_in
You cannot remove an alias until the primary alias is considered 'safe'.	CDS_REM_NOT_SAFE
You cannot remove the current cellname alias.	CDS_CANNOT_REM_CELLNAME
You cannot remove the current primary cell alias (current cell name).	CDS_CANNOT_REM_PREFERRED

Message Text	Symbolic Name
You cannot supersede a primary cell alias with a normal cell alias of the same name.	CDS_PREFERRED_EXISTS
You must be superuser to adjust the clock	dts_s_superuser
You must have system privileges to start this server.	cds_s_nopriv_eb
You must specify either the '-to' or '-epoch' option.	dcp_s_clock_set_need_time
Zero-length channel bindings	gss_s_seca_zero_channel_binding